



LuxSpace square, recessed

DN572B LED12S/840 PSE-E F WH

LuxSpace2 Square - LED Module, system flux 1200 lm - 840 neutral white - Power supply unit external, DC compatible for central emergency lighting - Facetted reflector - White

Customers are looking to optimize all their resources, and that means not just their running costs (energy, etc.) but also their human resources. Energy savings are therefore a priority, but they must not have an adverse effect on the well-being of employees, who need a pleasant environment in order to be more productive, or on customers, who want to enjoy their shopping experience. LuxSpace provides the perfect combination of efficiency, light comfort and design, without compromising on lighting performance (color rendering and color uniformity). It offers a wide choice of options for creating the desired ambience, no matter the application.

Product data


General Information		
Number of light sources	1 pc	
Lamp family code	LED12S [LED Module, system flux 1200 lm]	
Light source color	840 neutral white	
Cap-Base	- [-]	
Light source replaceable	No	
Number of gear units	1 unit	
Gear	-	
Driver/power unit/transformer	Power supply unit external, DC compatible for central emergency lighting	
Driver included	Yes	
Optic type		Facetted reflector
Optical cover/lens type	-	
Luminaire light beam spread	80°	
Emergency lighting	-	
Connection	Push-in connector and pull relief	
Cable	-	
Protection class IEC	Safety class II	
Glow-wire test	Temperature 850 °C, duration 5 s	
Flammability mark	For mounting on normally flammable surfaces	
CE mark	CE mark	

LuxSpace square, recessed

ENEC mark	ENEC mark	Overall height	119 mm
UL mark	-		
Warranty period	5 years		
Decorative accessories	-		
Remarks	<p>*-Per Lighting Europe guidance paper "Evaluating performance of LED based luminaires - January 2018": statistically there is no relevant difference in lumen maintenance between B50 and for example B10. Therefore the median useful life (B50) value also represents the B10 value.</p>		
Constant light output	No		
Number of products on MCB of 16 A type	32		
B			
RoHS mark	-		
Product family code	DN572B [LuxSpace2 Square]		
Light Technical			
Optical cover/lens type accessory	-		
Operating and Electrical			
Input Voltage	220 to 240 V		
Input Frequency	50 to 60 Hz		
Inrush current	18 A		
Inrush time	0.24 ms		
Power Factor (Min)	0.9		
Controls and Dimming			
Dimmable	No		
Mechanical and Housing			
Housing configuration	-		
Housing Material	Aluminum die-cast		
Reflector material	Polycarbonate aluminum coated		
Optic material	Polycarbonate		
Optical cover/lens material	Glass		
Fixation material	Steel		
Optical cover/lens finish	Frosted		
Overall length	214 mm		
Overall width	214 mm		
Approval and Application			
Ingress protection code	IP20 [Finger-protected]		
Mech. impact protection code	IK02 [0.2 J standard]		
Initial Performance (IEC Compliant)			
Initial luminous flux (system flux)	1250 lm		
Luminous flux tolerance	+/-10%		
Initial LED luminaire efficacy	118 lm/W		
Init. Corr. Color Temperature	4000 K		
Init. Color Rendering Index	>80		
Initial chromaticity	(0.38, 0.37) SDCM <3		
Initial input power	10.6 W		
Power consumption tolerance	+/-10%		
Over Time Performance (IEC Compliant)			
Control gear failure rate at median useful	5 %		
life 50000 h			
Lumen maintenance at median useful	L90		
life* 50000 h			
Application Conditions			
Ambient temperature range	+10 to +25 °C		
Performance ambient temperature Tq	25 °C		
Suitable for random switching	Yes (relates to presence/ movement detection and daylight harvesting)		
Product Data			
Full product code	871829194022700		
Order product name	DN572B LED12S/840 PSE-E F WH		
EAN/UPC - Product	8718291940227		
Order code	910503706586		
Numerator - Quantity Per Pack	1		
Numerator - Packs per outer box	1		
Material Nr. (12NC)	910503706586		
Net Weight (Piece)	1.520 kg		

LuxSpace square, recessed

Dimensional drawing



LuxSpace gen2 DN570B-DN572B

Photometric data

