

**Trade name:** Boardmarker Ink (black) contained in: TZ 111**Current version :** 2.0.1, issued: 27.10.2022**Replaced version:** 2.0.0, issued: 12.01.2016**Region:** GB**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name****Boardmarker Ink (black) contained in: TZ 111****1.2 Relevant identified uses of the substance or mixture and uses advised against****Relevant identified uses of the substance or mixture**

Ink for use in felt pens

**Uses advised against**

No data available.

**1.3 Details of the supplier of the safety data sheet****Address**

Legamaster International B.V.

Kwinkweerd 62

Postbus 111

7240 AC Lochem

The Netherlands

Telephone no. +31 (0) 573-713000

**Information provided by / telephone**

+31 (0) 573-713000

**Advice on Safety Data Sheet**

sdb\_info@umco.de

**1.4 Emergency telephone number**

For medical advice (in German and English):

+49 (0)30 30686 790 (Giftnotruf Berlin)

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification in accordance with Regulation (EC) No 1272/2008 (CLP)**

Eye Irrit. 2; H319

Flam. Liq. 2; H225

STOT SE 3; H336

**Classification information**

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

**2.2 Label elements****Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)****Hazard pictograms**

GHS02



GHS07

**Signal word**

Danger

**Hazardous component(s) to be indicated on label:**

propan-2-ol

**Trade name:** Boardmarker Ink (black) contained in: TZ 111**Current version :** 2.0.1, issued: 27.10.2022**Replaced version:** 2.0.0, issued: 12.01.2016**Region:** GB**Hazard statement(s)**

H225 Highly flammable liquid and vapour.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.

**Precautionary statement(s)**

P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P271 Use only outdoors or in a well-ventilated area.  
 P370+P378 In case of fire: Use water spray, extinguishing powder, foam or CO2 to extinguish.  
 P405 Store locked up.  
 P501 Dispose of contents/container to a facility in accordance with local and national regulations.

**2.3 Other hazards**

No data available.

**SECTION 3: Composition/information on ingredients****3.1 Substances**

Not applicable. The product is not a substance.

**3.2 Mixtures****Chemical characterization**

Mixture (preparation)

**Hazardous ingredients**

No	Substance name	Additional information	
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration %
1	<b>ethanol</b>		
	64-17-5 200-578-6 603-002-00-5 -	Flam. Liq. 2; H225	>= 50.00 - < 70.00 wt%
2	<b>propan-2-ol</b>		
	67-63-0 200-661-7 603-117-00-0 -	Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336	>= 25.00 - < 50.00 wt%
3	<b>CARBON BLACK</b>		
	1333-86-4 215-609-9 - -	-	< 5.00 wt%

Full Text for all H-phrases and EUH-phrases: pls. see section 16

**3.3 Other information**

The data subject of this Material Safety Data sheet refer to the ink contained in this product (marker).

**SECTION 4: First aid measures****4.1 Description of first aid measures****General information**

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

**After inhalation**

Remove affected person from the immediate area. Ensure supply of fresh air.

**After skin contact**

Wash off immediately with soap and water.

**Trade name:** Boardmarker Ink (black) contained in: TZ 111**Current version :** 2.0.1, issued: 27.10.2022**Replaced version:** 2.0.0, issued: 12.01.2016**Region:** GB**After eye contact**

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Seek medical assistance.

**After ingestion**

Rinse the mouth thoroughly with water. Call a doctor immediately. Never give anything by mouth to an unconscious person.

**4.2 Most important symptoms and effects, both acute and delayed**

No data available.

**4.3 Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

Foam; Carbon dioxide; Extinguishing powder

**Unsuitable extinguishing media**

No data available.

**5.2 Special hazards arising from the substance or mixture**

In the event of fire, the following can be released: Carbon dioxide (CO<sub>2</sub>); Carbon monoxide (CO)

**5.3 Advice for firefighters**

Cool endangered containers with water spray jet. Use self-contained breathing apparatus. Wear protective clothing.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures****For non-emergency personnel**

Refer to protective measures listed in sections 7 and 8. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Keep away from ignition sources.

**For emergency responders**

No data available. Personal protective equipment (PPE) - see Section 8.

**6.2 Environmental precautions**

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil.

**6.3 Methods and material for containment and cleaning up**

Take up with absorbent material (e.g., sand, kieselguhr, universal binder). When collected, handle material as described under the section heading "Disposal considerations".

**6.4 Reference to other sections**

No data available.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling****Advice on safe handling**

Provide good ventilation at the work area (local exhaust ventilation, if necessary). If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances.

**General protective and hygiene measures**

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Avoid contact with eyes and skin. Remove soiled or soaked clothing immediately. Do not inhale vapours. Clean skin thoroughly after work; apply skin cream.

**Advice on protection against fire and explosion**

**Trade name:** Boardmarker Ink (black) contained in: TZ 111

**Current version :** 2.0.1, issued: 27.10.2022

**Replaced version:** 2.0.0, issued: 12.01.2016

**Region:** GB

Vapours can form an explosive mixture with air. Take precautionary measures against static charges. Keep away from sources of heat and ignition. Use explosion-proof equipment/fittings and non-sparking tools.

## 7.2 Conditions for safe storage, including any incompatibilities

### Technical measures and storage conditions

Keep container tightly closed and dry in a cool, well-ventilated place.

### Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

### Incompatible products

None known

## 7.3 Specific end use(s)

No data available.

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

### Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
List of approved workplace exposure limits (WELs) / EH40			
	Ethanol		
	WEL long-term (8-hr TWA reference period)	1920 mg/m <sup>3</sup>	1000 ppm
2	propan-2-ol	67-63-0	200-661-7
List of approved workplace exposure limits (WELs) / EH40			
	Propan-2-ol		
	WEL short-term (15 min reference period)	1250 mg/m <sup>3</sup>	500 ppm
	WEL long-term (8-hr TWA reference period)	999 mg/m <sup>3</sup>	400 ppm
3	CARBON BLACK	1333-86-4	215-609-9
List of approved workplace exposure limits (WELs) / EH40			
	Carbon black		
	WEL short-term (15 min reference period)	7 mg/m <sup>3</sup>	
	WEL long-term (8-hr TWA reference period)	3.5 mg/m <sup>3</sup>	

## 8.2 Exposure controls

### Appropriate engineering controls

No data available.

### Personal protective equipment

#### Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

#### Eye / face protection

Safety glasses with side protection shield (EN 166)

#### Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

#### Other

Normal chemical work clothing.

#### Environmental exposure controls

No data available.

**Trade name:** Boardmarker Ink (black) contained in: TZ 111

**Current version :** 2.0.1, issued: 27.10.2022

**Replaced version:** 2.0.0, issued: 12.01.2016

**Region:** GB

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

<b>State of aggregation</b>		
liquid		
<b>Form</b>		
liquid		
<b>Colour</b>		
black		
<b>Odour</b>		
characteristic		
<b>pH value</b>		
No data available		
<b>Boiling point / boiling range</b>		
Value	78.3	°C
Reference substance	CAS 64-17-5	
<b>Melting point/freezing point</b>		
No data available		
<b>Decomposition temperature</b>		
No data available		
<b>Flash point</b>		
Value	13	°C
Reference substance	CAS 64-17-5	
<b>Ignition temperature</b>		
Value	390	°C
<b>Flammability</b>		
No data available		
<b>Lower explosion limit</b>		
Value	2	% vol
<b>Upper explosion limit</b>		
Value	19.0	% vol
<b>Vapour pressure</b>		
No data available		
<b>Relative vapour density</b>		
No data available		
<b>Relative density</b>		
Value	0.823	
<b>Density</b>		
No data available		
<b>Solubility in water</b>		
Comments	insoluble	
<b>Solubility</b>		
No data available		
<b>Partition coefficient n-octanol/water (log value)</b>		
No data available		
<b>Kinematic viscosity</b>		
No data available		

**Trade name:** Boardmarker Ink (black) contained in: TZ 111**Current version :** 2.0.1, issued: 27.10.2022**Replaced version:** 2.0.0, issued: 12.01.2016**Region:** GB**Particle characteristics**

No data available

**9.2 Other information****Other information**

No data available.

**SECTION 10: Stability and reactivity****10.1 Reactivity**

No data available.

**10.2 Chemical stability**

No data available.

**10.3 Possibility of hazardous reactions**

No data available.

**10.4 Conditions to avoid**

Heat, naked flames and other ignition sources. air humidity

**10.5 Incompatible materials**

None known.

**10.6 Hazardous decomposition products**

No hazardous decomposition products known.

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute oral toxicity**

No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
LD50		6200	mg/kg bodyweight
Species	rat		
Source	Manufacturer		
2	propan-2-ol	67-63-0	200-661-7
LD50		5280	mg/kg bodyweight
Species	rat		
Source	Manufacturer		

**Acute dermal toxicity**

No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
LD50		12800	mg/kg bodyweight
Species	rabbit		
Source	Manufacturer		

**Acute inhalational toxicity**

No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
LC50		72.6	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Source	Manufacturer		

**Skin corrosion/irritation**

No data available

**Serious eye damage/irritation**

No data available

**Respiratory or skin sensitisation**

**Trade name:** Boardmarker Ink (black) contained in: TZ 111**Current version :** 2.0.1, issued: 27.10.2022**Replaced version:** 2.0.0, issued: 12.01.2016**Region:** GB

No data available
<b>Germ cell mutagenicity</b>
No data available
<b>Reproduction toxicity</b>
No data available
<b>Carcinogenicity</b>
No data available
<b>STOT - single exposure</b>
No data available
<b>STOT - repeated exposure</b>
No data available
<b>Aspiration hazard</b>
No data available
<b>Delayed and immediate effects as well as chronic effects from short and long-term exposure</b>
Inhalation of solvent vapours in higher concentration may lead to nausea, headache, drowsiness and dizziness. Repeated and prolonged skin contact may cause removal of natural fat from the skin and irritation of the skin. Eye contact with the product may lead to irritation.

**11.2 Information on other hazards****Endocrine disrupting properties**

No data available.

**Other information**

No data available.

**SECTION 12: Ecological information****12.1 Toxicity**

Toxicity to fish (acute)				
No	Substance name	CAS no.		EC no.
1	ethanol	64-17-5		200-578-6
LC50			8150	mg/l
Duration of exposure			96	h
Species		Leuciscus idus		
Source		Manufacturer		
2	propan-2-ol	67-63-0		200-661-7
LC50			9640	mg/l
Duration of exposure			96	h
Species		Pimephales promelas		
Source		Manufacturer		
Toxicity to fish (chronic)				
No data available				
Toxicity to Daphnia (acute)				
No	Substance name	CAS no.		EC no.
1	ethanol	64-17-5		200-578-6
EC50		9268	- 14221	mg/l
Duration of exposure			48	h
Species		Daphnia magna		
Source		Manufacturer		
2	propan-2-ol	67-63-0		200-661-7
EC50			13299	mg/l
Duration of exposure			48	h
Species		Daphnia magna		
Source		Manufacturer		
Toxicity to Daphnia (chronic)				

**Trade name:** Boardmarker Ink (black) contained in: TZ 111**Current version :** 2.0.1, issued: 27.10.2022**Replaced version:** 2.0.0, issued: 12.01.2016**Region:** GB

No data available

**Toxicity to algae (acute)**

No	Substance name	CAS no.	EC no.
1	propan-2-ol	67-63-0	200-661-7
EC50	>	1000	mg/l
Duration of exposure		72	h
Species	Desmodesmus subspicatus		
Source	Manufacturer		

**Toxicity to algae (chronic)**

No data available

**Bacteria toxicity**

No data available

**12.2 Persistence and degradability**

Biodegradability			
No	Substance name	CAS no.	EC no.
1	ethanol	64-17-5	200-578-6
Value			%
Source	Manufacturer		
Evaluation	readily biodegradable		
2	propan-2-ol	67-63-0	200-661-7
Value		95	%
Duration		21	day(s)
Method	OECD 301 E		
Source	Manufacturer		
Evaluation	readily biodegradable		

**12.3 Bioaccumulative potential**

No data available.

**12.4 Mobility in soil**

No data available.

**12.5 Results of PBT and vPvB assessment**

No data available.

**12.6 Endocrine disrupting properties**

No data available.

**12.7 Other adverse effects**

No data available.

**12.8 Other information**

Other information
Do not discharge product unmonitored into the environment.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Product**

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

**Packaging**

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

**SECTION 14: Transport information****14.1 Transport ADR/RID/ADN**

Class

3



**Trade name:** Boardmarker Ink (black) contained in: TZ 111**Current version :** 2.0.1, issued: 27.10.2022**Replaced version:** 2.0.0, issued: 12.01.2016**Region:** GB

Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1263
Proper shipping name	PAINT
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3

**14.2 Transport IMDG**

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	PAINT
EmS	F-E, S-E
Label	3

**14.3 Transport ICAO-TI / IATA**

Class	3
Packing group	II
UN number	UN1263
Proper shipping name	Paint
Label	3

**14.4 Other information**

No data available.

**14.5 Environmental hazards**

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

**14.6 Special precautions for user**

No data available.

**14.7 Maritime transport in bulk according to IMO instruments**

Not relevant

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulations****Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)**

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

**REACH candidate list of substances of very high concern (SVHC) for authorisation**

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

**Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES**

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII.	No	3, 40
--	----	-------

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	CARBON BLACK	1333-86-4	215-609-9	75
2	propan-2-ol	67-63-0	200-661-7	75

**Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances**

This product is subject to Part I of Annex I, risk category:	P5b
--	-----

**15.2 Chemical safety assessment**

---

**Trade name:** Boardmarker Ink (black) contained in: TZ 111

---

**Current version :** 2.0.1, issued: 27.10.2022**Replaced version:** 2.0.0, issued: 12.01.2016**Region:** GB

---

A chemical safety assessment has not been carried out for this mixture.

## SECTION 16: Other information

### Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

### Creation of the safety data sheet

UMCO GmbH

Georg-Wilhelm-Str. 187, D-21107 Hamburg

Tel.: +49 40 / 555 546 300 Fax: +49 40 / 555 546 357 e-mail: [umco@umco.de](mailto:umco@umco.de)

This information is based on our present knowledge and experience.

The safety data sheet describes products with a view to safety requirements.

It does not however, constitute a guarantee for any specific product properties and shall not establish a legally valid contractual relationship.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 630441