### Overview

### HP t530 Thin Client

Front View Image



FRONT

- 1. Power button
- 2. Flash memory activity indicator light
- 3. 1 x USB-A 3.1 Gen 1 port for accessories
- 4. 1 x USB-C 3.1 Gen 1 port for accessories
- 5. 3.5mm headset jack
- 6. System stand



**Rear View Image** 

#### BACK

- 1. DisplayPort™ 1.2 digital video outputs (2)
- 2. 2 x USB-A 2.0 ports for keyboard and mouse
- 3. 2 x USB-A 3.1 Gen 1 ports for accessories
- 4. RJ45 Gigabit Ethernet interface
- 5. 19V DC power input
- 6. Cable lock support

Option port; can be configured as one of the following:

- Blank; no optional port
- Serial port

7.

- VGA video output
  - External Wi-Fi antenna connector



#### Overview

#### **AT A GLANCE**

- AMD GX-215JJ System on Chip; 1.5 2.0 GHz dual-core with a Radeon™ R2E based graphics core
- DDR4 single-channel SDRAM system memory; up to 1,866 MT/s transfer rate; one SODIMM slot; up to 16 GB supported<sup>1</sup>
- 2 x DisplayPort<sup>™</sup> 1.2 video outputs supporting up to Ultra High Definition (UHD)/4K (3840 x 2160) resolutions. Models can be configured with an optional VGA analog video port to support older displays
- Solid-state flash memory storage; single M.2 slot supporting up to a 512 GB flash drive
- Active thermal management technology monitors component operating temperatures, throttles SOC operation if appropriate, and prevents unit thermal shutdown
- Gigabit Ethernet (GbE) network connection supported via an integrated Realtek GbE NIC module
- Optional Wi-Fi/Bluetooth<sup>®</sup> adapters including antennas integrated internally in the chassis. Models can be configured with an optional external Wi-Fi antenna system
- USB ports located on the front and back panels, including a USB-C 3.1 port for supporting accessory devices designed for this newest USB form factor
- Models configured with an optional serial port to support devices requiring the serial interface
- Integrated PC speaker for basic audio playback; 3.5 mm headset audio port on front that can be configured as line in or line out supporting headphones, external speaker systems, or microphone
- TCG certified Trusted Platform Module (TPM) chipset; other security features include a system UEFI designed to address NIST SP 800-147 guidelines, cable lock slot, and power cord retention clip to prevent accidental power cord disconnects
- ENERGY STAR<sup>®</sup> certified and EPEAT<sup>®</sup> Gold registered in the United States. See <a href="http://www.epeat.net">http://www.epeat.net</a> for registration status in other countries
- Post-consumer recycled plastics content greater than 25% total unit plastics (by weight)
- Low halogen<sup>3</sup>material content
- Models can be configured as TAA compliant

<sup>1</sup> If configured with a Windows Embedded 32-bit operating system, memory above 3.2 GB may not be available due to operating system limitations

<sup>2</sup> Wireless access point and Internet access is required; availability of public wireless access points is limited

<sup>3</sup> This product is low halogen except for power cords, cables and peripherals; service parts obtained aftermarket may not be low halogen

#### Warranty

HP Customer Support: limited three-year hardware limited warranty in most regions; HP Care Packs are extended service contracts that go beyond your standard limited warranties; for more details visit http://www.hp.com/go/cpc



### Technical specifications

#### **OPERATING SYSTEMS**

HP Smart Zero Core (Linux®-based) Firmware based SmartZero Core HP ThinPro (Linux®-based) Microsoft Windows Embedded Standard (WES) 7E Microsoft Windows 10 IoT Enterprise

#### PROCESSOR **GPU CUs** GPU Model **CPU Frequency** x86 Cores L2 Cache Memory base/max AMD GX-215JJ 1.5/2.0 GHz 2 2 1 MB AMD Radeon R2E DDR4 1866 NOTE: CPU Maximum frequency is based on AMD Turbo Core Technology

#### GRAPHICS

Number of displays supported:22 x DisplayPort™ (standard)Video outputs:1 x VGA port (optional)NOTE: the optional VGA port does not increase the number of displays supported.

| Displays<br>Content                  | ≤2 x 1080p FHD<br>(1920x1080) 60Hz  | 2 x 4K UHD<br>(3840x2160) 30Hz | 2 x 4K UHD<br>(3840x2160) 30Hz | 1 x 4K UHD (3840x2160)<br>60Hz |
|--------------------------------------|-------------------------------------|--------------------------------|--------------------------------|--------------------------------|
| Static screen (no video)             | √                                   | $\checkmark$                   | V                              | √                              |
| Play 1080p 30fps (or below)<br>video | √                                   | $\checkmark$                   |                                |                                |
| Play 1080p 60fps video               | √                                   |                                |                                |                                |
| Play 4k @ 30fps video                | √<br>(resolution is scaled<br>down) |                                |                                |                                |

#### MEMORY

### Technical specifications

| Туре:                                                                    | Single channel DDR4 SDRAM                                                                                         |
|--------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| Data Transfer Rate:                                                      | up to 1,866 MT/s                                                                                                  |
| Peak Transfer Rate:                                                      | 14,944 MB/s                                                                                                       |
| Number of slots:                                                         | 1 x SODIMM                                                                                                        |
| Capacities offered:                                                      | 4, 8 and 16 GB                                                                                                    |
| Reserved for graphics:                                                   | 256 MB, 512 MB (default) or 1 GB                                                                                  |
| NOTE: WES 7E is a 32-bit operatir                                        | ng system, and only recognizes up to 3.2 GB SDRAM                                                                 |
| <b>NOTE:</b> The system's Graphics Properformance is not available for u | cessing Unit (GPU) uses part of total system memory. System memory dedicated to graphics<br>use by other programs |

#### **UEFI (Unified Extensible Firmware Interface)**

- UEFI Specification Revision: 2.3.1
- Meets requirements for Common Criteria, an independent third-party certification of trustworthiness
- Designed to address NIST SP800-147 guidelines

#### **TRUSTED PLATFORM MODULE (TPM)**

- TPM 1.2 when configured with Microsoft WES 7E
- TPM 2.0 when configured with HP ThinPro / Smart Zero Core, Windows 10 IoT Enterprise or with no operating system

NOTE: TPM 2.0 (Infineon SLB9660) Common Criteria ELA4+ Certified. Convertible to FIPS 140-2 certified mode.

#### STORAGE

| Туре:               | NAND flash memory; non-volatile                       |
|---------------------|-------------------------------------------------------|
| Number of sockets:  | 1 x M.2                                               |
|                     | 0, 8, 16, 32, 64, 128, 256 and 512 GB                 |
| Capacities offered: | WES 7E requires a minimum of 16 GB                    |
|                     | Windows 10 IoT Enterprise requires a minimum of 32 GB |

Solid-state flash-based memory modules are the primary operating system storage media for thin clients supporting highly virtualized operating environments. Thin clients display a hosted session from a data center through standard IP networks which minimizes the required size of local flash-based storage. In a traditional VDI environment, data and application files are stored securely in the remote data center and not on the local storage device.

The HP t530 Thin Client uses three types of flash memory: MLC (2-bits per cell), Ultra MLC (2-bits per cell, but only 1 is utilized) and TLC (3-bits per cell). Because the classic thin client use cases seldom require writing to flash memory storage, a relatively low capacity MLC flash memory module is typically used to provide the best cost and performance. However, when the use case calls for writing to the local flash memory storage module careful consideration should be given to the selection of the proper storage module. A larger capacity and/or the use of Ultra MLC technology could be required to adequately support the usage being planned or expected from the thin client.



### Technical specifications

#### **INPUT/OUTPUT**

| USB ports:     | 1 x USB-C 3.1 (front access)<br>1 x USB-A 3.1 (front access)<br>2 x USB-A 2.0 (rear access); 2 x typically used for keyboard and mouse<br>2 x USB-A 3.1 Gen1 (rear access)            |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video outputs: | 2 x DisplayPort™ 1.2 digital video ports (standard)<br>1 x VGA analog video port (optional)<br><b>NOTE</b> : the optional VGA port does not increase the number of supported displays |
| Other:         | 1 x RJ45 Gigabit Ethernet interface<br>1 x serial port (optional)<br>1 x 3.5mm headset jack (front access)<br>1 x coaxial connectors for external Wi-Fi antenna (optional)            |

**NOTE**: a single position at the back of the system is used for one of three optional I/O features. One of the following can be configured to any system:

- blank; no optional port
- VGA video port
- serial port
- external Wi-Fi antenna connector

#### AUDIO/VIDEO

| Audio:           | Realtek ALC3252 high definition audio Codec; 4-channel DAC supports 16/20/24-bit PCM for two independent<br>stereo or 2.1-channel sound outputs (multiple streaming playback); the 4-channel ADC supports 16/20/24-bit<br>PCM format for two stereo and independent analog sound inputs; incorporating Realtek converter technology<br>achieves a 97dB dynamic range playback quality and a 90dB dynamic range recording quality. It meets WLP<br>(Windows Logo Program) requirements for Windows systems. |
|------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Video:           | MPEG-4 part 2 (DivX, Xvid)<br>MPEG-4 part 10 (H.264), Advanced Video Coding (AVC) (H.264 encode)<br>MPEG-H part 2, High Efficiency Video Coding (HEVC) (H.265. decode)<br>WMV 7/8/9 VC-1 & ASF Demuxer<br>Includes hardware acceleration support                                                                                                                                                                                                                                                           |
| NOTE 1: Playback | x of 2160p videos is not supported                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

**NOTE 2:** Playback of multiple 1080p videos and stretching 1080p videos is supported as long as the resolution in the operating system is set to 2560 x 1600 or lower.

#### HARDWARE SECURITY

- Security lock support (cable lock sold separately)
- Trusted Platform Module (version 1.2 or 2.0 depending on the model's operating system)

#### NETWORKING

Wired networks:

Realtek Gigabit Ethernet (GbE)



### Technical specifications

 Wake on LAN

 PXE

 TCP/IP with DNS DHCP

 Secure Socket Tunneling Protocol (SSTP); supported with a Microsoft operating system

 Wireless networks:

 Intel® Dual Band Wireless-AC 3168 with Bluetooth®

 Intel® Dual Band Wireless-AC 8265 with Bluetooth®

**NOTE**: Wireless access point and Internet access require. Availability of public wireless access point may be limited. Wireless features, performance and support may vary depending on environmental variables such as placement, settings and firmware of the access point. Contact your wireless vendor for support.

NOTE: Tested and compliant with Internet Protocol version 4 (IPv4) and Internet Protocol version 6 (IPv6)

#### SOFTWARE SUPPORT

| Host Environment                     | Protocol                         | HP ThinPro<br>HP Smart Zero Core | MS WES 7E    | MS Win10 loT |
|--------------------------------------|----------------------------------|----------------------------------|--------------|--------------|
| Amazon WorkSpaces                    | Amazon WorkSpace<br>Client/PCoIP |                                  |              |              |
| Microsoft Remote<br>Desktop Services | Remote FX (RFX), RDP             | √                                | V            | V            |
| Citrix®                              | ICA, HDX                         | √                                | $\checkmark$ | √            |
| VMware® Horizon™                     | RDP, PCoIP, Blast<br>Extreme     | √                                | V            | V            |

| Protocol Clients                  | HP ThinPro<br>HP Smart Zero Core | MS WES 7E    | MS Win10 IoT |
|-----------------------------------|----------------------------------|--------------|--------------|
| Amazon WorkSpaces Client/PCoIP    |                                  |              | V            |
| Citrix Receiver™                  | √                                | $\checkmark$ | √            |
| Microsoft Remote Desktop Client   |                                  | $\checkmark$ | V            |
| VMware® Horizon View™ Client      | √                                | $\checkmark$ | √            |
| HP Remote Graphics Software (RGS) | add-on                           | V            | √            |
| HP TeemTalk Terminal Emulator     | √                                | add-on       |              |
| Free RDP                          | √                                |              |              |

| Browser Support  | HP ThinPro<br>HP Smart Zero Core | MS WES 7E | MS Win10 IoT |
|------------------|----------------------------------|-----------|--------------|
| Mozilla Firefox  | 50.0.1                           |           |              |
| nternet Explorer |                                  | 11        | 11           |
| Security         | HP ThinPro                       | MS WES 7E | MS Win10 IoT |

**HP Smart Zero Core** 



### Technical specifications

| SmartCard                     | √ | √         | √   |
|-------------------------------|---|-----------|-----|
| Logon Manager                 | √ | √         | √   |
| Read-only operating system    | √ | √         | √   |
| 802.1x                        | √ | √         | √   |
| Operating system write filter |   | EWF, FBWF | UWF |
| Microsoft Firewall            |   | √         | √   |

| Management Tools              | HP ThinPro<br>HP Smart Zero Core | MS WES 7E    | MS Win10 IoT |
|-------------------------------|----------------------------------|--------------|--------------|
| HP Device Manager             | √                                | $\checkmark$ | √            |
| HP ThinUpdate                 |                                  | $\checkmark$ | √            |
| HP Easy Tools                 | √                                | add-on       |              |
| HP Smart Zero Client Services | √                                |              |              |
| Microsoft SCCM/EDM agent      |                                  | $\checkmark$ | √            |

| Additional Components     | HP ThinPro<br>HP Smart Zero Core | MS WES 7E    | MS Win10 IoT |
|---------------------------|----------------------------------|--------------|--------------|
| HP Velocity               | √                                | V            | √            |
| HP Easy Shell             |                                  | $\checkmark$ | √            |
| HP Universal Print Driver |                                  | √            | √            |
| Windows Media Player      |                                  | 12           | 12           |
| Microsoft Direct Access   |                                  |              | √            |
| Microsoft BranchCache     |                                  |              | √            |
| Microsoft AppLocker       |                                  |              | √            |
| Microsoft Sideloading     |                                  |              | √            |

NOTE: Other add-on software available (see: http://www.hp.com/support for latest list of available add-ons). Software performance and support may vary depending on customer environment and backend.

| Audio/Video CODEC     | HP ThinPro<br>HP Smart Zero Core | MS WES 7E    | MS Win10 IoT |
|-----------------------|----------------------------------|--------------|--------------|
| МРЗ                   | √                                | V            | V            |
| WMA Stereo            | √                                | $\checkmark$ | √            |
| AAC stereo & HE AAC   | √                                | $\checkmark$ | √            |
| Microsoft AC3 encoder |                                  | 12           | 12           |
| MPEG-1                |                                  |              | √            |



### Technical specifications

| MPEG-4 part 2 (DivX, Xvid, H.263) | $\checkmark$ | $\checkmark$ |
|-----------------------------------|--------------|--------------|
| MPEG-4 part 10 (H.264, AVC)       | √            | V            |
| WMV 7/8/9/ VC-1 & ASF Demuxer     | √            | √            |

NOTE: Other add-on software available (see: http://www.hp.com/support for latest list of available add-ons). Software performance and support may vary depending on customer environment and backend.

#### **WEIGHTS & DIMENSIONS**

| W x D x H (without stand) vertical orientation                                                           | 35 x 200 x 200 mm (1.38 x 7.87 x 7.87 in.) |  |  |
|----------------------------------------------------------------------------------------------------------|--------------------------------------------|--|--|
| Volume                                                                                                   | 1.4 liter                                  |  |  |
| System Weight (including stand)                                                                          | 962.8 g (2.12 lb.)                         |  |  |
| Shipping Weight                                                                                          | 1919.7 g (4.23 lb.)                        |  |  |
| <b>NOTE:</b> All measurements are approximate; the addition of optional modules will increase the weight |                                            |  |  |

#### **POWER SUPPLY**

45W external power adapter Worldwide auto-sensing 100-240 VAC, 50-60 Hz Energy saving automatic power-down Surge tolerant

#### **AGENCY COMPLIANCE**

| Accessibility:                    | Section 508 Accessibility. VPAT report available                           |
|-----------------------------------|----------------------------------------------------------------------------|
| Environmental Stewardship:        | Worldwide (ENERGY STAR®, EPEAT, ROHS, ERP, TCO, MEPS, CECP, HP GSE, etc.)  |
| Product Safety:                   | Worldwide (UL, CB, GS, CCC, etc.)                                          |
| Electromagnetic Compliance (EMC): | Worldwide(FCC/CISPR/EN/VCCI/ICES/AS/NZS/CNS/KCC) "Class B" EMI regulations |

#### ENVIRONMENTAL

| Operating Temperature Range:     | 50° to 104° F (10° to 40° C)   |            |  |
|----------------------------------|--------------------------------|------------|--|
| Non-operating Temperature Range: | -22° to 140° F (-30° to 60° C) |            |  |
| Humidity                         | Condensing:                    | 20% to 80% |  |
| Humidity:                        | Non-condensing:                | 10% to 90% |  |

**NOTE**: Specifications are at sea level with altitude derating of 1° C/300m (1.8° F/1000ft) to a maximum of 3 Km (10,000 ft), with no direct, sustained sunlight. Upper limit may be limited by the type and number of options installed.



### Technical specifications

| Eco-Label Certifications & declarations                   | This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |              |                             |              |     |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------------------------|--------------|-----|
|                                                           | <ul> <li>US ENERGY STAR<sup>®</sup></li> <li>EPEAT<sup>®</sup> Gold registered in the United States. See http://www.epeat.net for registration status in your country.</li> <li>IT ECO declaration</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |              |                             |              |     |
| Energy Consumption<br>(in accordance with US ENERGY STAR® |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |              |                             |              |     |
| test method)                                              | 115VAC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | , 60Hz       | 230VAC, 50Hz                | 100VAC, 50H  | z   |
| Normal Operation (Short idle)                             | 7.42                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 2 W          | 7.48 W                      | 7.47 W       |     |
| Normal Operation (Long idle)                              | 5.79                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 9 W          | 6.27 W                      | 5.98 W       |     |
| Sleep                                                     | 0.78                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 3 W          | 0.78 W                      | 0.75 W       |     |
| Off                                                       | 0.69                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | W            | 0.70 W                      | 0.69 W       |     |
| Heat Dissipation*                                         | 115VAC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | , 60Hz       | 230VAC, 50Hz                | 100VAC, 50H; | z   |
| Normal Operation (Short idle)                             | 25 BT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | U/hr         | 26 BTU/hr                   | 26 BTU/hr    |     |
| Normal Operation (Long idle)                              | 20 BT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | U/hr         | 21 BTU/hr                   | 21 BTU/hr    |     |
| Sleep                                                     | 3 BTI                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | J/hr         | 3 BTU/hr                    | 3 BTU/hr     |     |
| Off                                                       | 2 BTI                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | J/hr         | 2 BTU/hr                    | 2 BTU/hr     |     |
|                                                           | *NOTE: Heat dissipation is calculated based on the measured watts, assuming the<br>service level is attained for one hour.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |              |                             | ie           |     |
| Additional Information                                    | <ul> <li>This product is in compliance with the Restrictions of Hazardous Substances (RoHS) directive -2011/65/EC.</li> <li>This HP product is designed to comply with the Waste Electrical and Electronic Equipment (WEEE) Directive – 2002/96/EC.</li> <li>This product is in compliance with California Proposition 65 (State of California; Safe Drinking Water and Toxic Enforcement Act of 1986).</li> <li>This product is in compliance with the IEEE 1680 (EPEAT) standard at the gold level, see www.epeat.net</li> <li>Plastics parts weighing over 25 grams used in the product are marked per ISO 11469 and ISO1043.</li> <li>This product contains 13.9 % post-consumer recycled plastic (by wt.)</li> <li>This product is 93.4 % recycle-able when properly disposed of at end of life.</li> </ul> |              |                             |              |     |
| Packaging Materials                                       | External:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | PAPER/Corru  | gated                       | 45           | 5 g |
|                                                           | Internal:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | PLASTIC/Poly | vethylene Expanded - EPE    | 44           | g   |
|                                                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | PLASTIC/Poly | vethylene low density - LDF | PE 5 g       |     |
| RoHS Compliance                                           | HP Inc. is committed to compliance with all applicable environmental laws and<br>regulations, including the European Union Restriction of Hazardous Substances (RoHS<br>Directive. HP's goal is to exceed compliance obligations by meeting the requirements<br>of the RoHS Directive on a worldwide basis. By July 1, 2006, RoHS substances will be<br>virtually eliminated (virtually = to levels below legal limits) for all HP electronic                                                                                                                                                                                                                                                                                                                                                                    |              |                             | nents        |     |



### Technical specifications

products subject to the RoHS Directive, except where it is widely recognized that there is no technically feasible alternative (as indicated by an exemption under the EU RoHS Directive).

This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at

http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen\_specificat ions.html):

- Asbestos
- Certain Azo Colorants
- Certain Brominated Flame Retardants may not be used as flame retardants in plastics
- Cadmium
- Chlorinated Hydrocarbons
- Chlorinated Paraffins
- Formaldehyde
- Halogenated Diphenyl Methanes
- Lead carbonates and sulfates
- Lead and Lead compounds
- Mercuric Oxide Batteries
- Nickel finishes must not be used on the external surface designed to be frequently handled or carried by the user.
- Ozone Depleting Substances
- Polybrominated Biphenyls (PBBs)
- Polybrominated Biphenyl Ethers (PBBEs)
- Polybrominated Biphenyl Oxides (PBBOs)
- Polychlorinated Biphenyl (PCB)
- Polychlorinated Terphenyls (PCT)
- Polyvinyl Chloride (PVC) except for wires and cables, and certain retail packaging has been voluntarily removed from most applications.
- Radioactive Substances
- Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)



Material Usage

## Technical specifications

| Packaging                                       | <ul> <li>HP follows these guidelines to decrease the environmental impact of product packaging: <ul> <li>Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials.</li> <li>Eliminate the use of ozone-depleting substances (ODS) in packaging materials.</li> <li>Design packaging materials for ease of disassembly.</li> <li>Maximize the use of post-consumer recycled content materials in packaging materials.</li> <li>Use readily recyclable packaging materials such as paper and corrugated materials.</li> <li>Reduce size and weight of packages to improve transportation fuel efficiency.</li> <li>Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.</li> </ul> </li> </ul> |
|-------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| End-of-life Management and Recycling            | HP Inc. offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner.                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|                                                 | The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment<br>information for each product type for use by treatment facilities. This information<br>(product disassembly instructions) is posted on the HP Inc. web site at:<br>http://www.hp.com/go/recyclers. These instructions may be used by recyclers and<br>other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell<br>HP equipment.                                                                                                                                                                                                                                                                                                                            |
| HP, Inc. Corporate Environmental<br>Information | For more information about HP's commitment to the environment:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|                                                 | Global Citizenship Report<br>http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html<br>Eco-label certifications<br>http://www.hp.com/hpinfo/globalcitizenship/environment/productdesign/ecolabels.html<br>ISO 14001 certificates:<br>http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842<br>and<br>http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf                                                                                                                                                                                                                                                                                                                                                                                |



## Summary of Changes

| Date of change:  | Version History: | Type of change | Description of change:                               |
|------------------|------------------|----------------|------------------------------------------------------|
| August 20; 2018  | From v1 to v2    | Changed        | Software support for VMware Horizon                  |
| October 15, 2018 | From v2 to v3    | Changed        | UEFI, TPM, Audio/video and Networking sections       |
| January 11, 2019 | From v3 to v4    | Changed        | Operating Systems and Storage sections               |
| February 8, 2019 | From v4 to v5    | Changed        | At a Glance section                                  |
| May 6, 2019      | From V5 to V6    | Changed        | MS Win10 IoT support unchecked for Amazon WorkSpaces |



© 2015, 2019 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express limited warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. AMD and Radeon are trademarks of Advanced Micro Devices, Inc. DisplayPort<sup>™</sup> and the DisplayPort<sup>™</sup> logo are trademarks owned by the Video Electronics Standards Association (VESA®) in the United States and other countries. Amazon Web Services, the "Powered by Amazon Web Services" logo, and Amazon WorkSpaces are trademarks of Amazon.com, Inc. or its affiliates in the United States and/or other countries. Bluetooth® is a trademark owned by its proprietor and used by HP Inc. under license. ENERGY STAR is a registered trademark owned by the U.S. Environmental Protection Agency. Linux<sup>®</sup> is the registered trademark of Linus Torvalds in the U.S. and other countries. Microsoft and Windows are either registered trademarks or trademarks of Intel Corporation in the U.S and other countries. VMware Horizon and VMware Horizon View are registered trademarks or trademarks or trademarks or other jurisdictions. Citrix and Citrix Receiver are trademarks of Citrix Systems, Inc. and/or one more of its subsidiaries, and may be registered in the United States Patent and Trademark Office and in other countries.

