



## US Power Cable C13 to NEMA 5-15 US, 1.8 m (6 ft.)

AC Power Cord with "Kettle Lead" to North-American Mains 3-pin, 10 A, 250 V, For PC, Monitor, Printer and TV, Black

Part No.: [300179](#)

EAN-13: 0766623300179 | UPC: 766623300179

---

### Powerful connections for computing solutions

Manhattan Power Cables easily connect and extend the reach between a power source and personal computers, monitors, printers, power adapters and other equipment. Ideal for new systems or replacement applications, Manhattan offers an assortment of universal power cables engineered and built from quality materials that meet current safety approvals to deliver and maintain reliable connections. Fully molded boots with strain relief, durable PVC jackets and heavy-duty construction help provide Manhattan Power Cables with the maximum electrical conductivity needed to transmit dependable power where and when it's needed.

#### Features:

- Connects most desktop computers to North American and other similar outlets
- IEC 60320 C13 socket to NEMA 5-15 plug
- Suitable for extreme operating temperatures up to 221°F (105°C)
- Molded connections with strain relief
- Lifetime Warranty

#### Specifications:

IEC 60320 C13 socket, male

- Approvals: UL
- Power: 10 A / 250 V
- Socket count: 3-blade
- Molded plastics

For more information on Manhattan products, consult your local dealer or visit [www.manhattan-products.com](http://www.manhattan-products.com).

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

- Strain-relief connection

NEMA 5-15, male

- Approvals: UL
- Power: 10-13 A / 125 V
- Pin count: 2-blade, 1-pin
- Molded plastics
- Strain-relief connection

Cable

- Number of strands / strand thickness: 41 / 0.16 mm
- Number of cores / core thickness: 3 / 18 AWG
- Insulation thickness: 0.6 mm
- Jacket thickness: 0.38 mm
- Nominal overall diameter: 6.8 mm
- Length: 1.8 m (6 ft.)

Environmental

- Operating temperature: up to 105°C (221°F)

Package Contents

- Power Cable



