

Fujitsu recommends Windows 10 Pro.

# Data Sheet

## FUJITSU Desktop ESPRIMO P558

Flexible and economic desktop PC for standard office applications

The FUJITSU ESPRIMO P558 Desktop PC provides high-quality computing for your daily office tasks. It supports attractive price points and its managed lifecycle ensures the functional stability needed for project continuity. Optional security functions, such as SmartCard reader, the EraseDisk feature and cable cover help secure your valuable business data as well as hardware components. You can easily configure the PC to meet your specific hardware needs as well as customize it to satisfy even more complex project requirements. With the ENERGY STAR® certification, the Low Power Active Mode and up to 94%-efficient power supply, ESPRIMO P558 helps reduce your carbon footprint and energy bill.

### High performance and best price/performance ratio

Powerful and cost-effective microtower

- Up to 9th generation Intel® Core™ processor family

### Best energy efficiency coupled with performance

Low power consumption combined with highest levels of performance

- Latest Intel® processors, an optional switched monitor outlet and a power supply with up to 94% efficiency

### Manageability and Ease of Use

"Plug & work" PC that ensures smooth system administration

- Easy to integrate into existing IT landscapes and reliable DeskView manageability tools

### Robust Security

Designed to protect data and hardware components against manipulation and theft

- Cable cover with lock option at the back to protect ports, cables and components from theft
- Embedded Trusted Platform Module (TPM), Fujitsu Workplace Protect software with full disk encryption and system-level passwords. EraseDisk software and SmartCard are available as options

### Made in Germany

Outstanding quality and stable functions based on German production standards

- The development, production and functionality tests - all under one roof in Germany



# Components

|                                       | ESPRIMO P558/E85+   | ESPRIMO P558/E94+   |
|---------------------------------------|---|---|
| <b>Processor</b>                      | Intel® Celeron® processor G4900 (2 Cores / 2 Threads, 3.10 GHz, 2 MB, Intel® UHD Graphics 610)<br>Intel® Celeron® processor G4930 (2 Cores / 2 Threads, 3.20 GHz, 2 MB, Intel® UHD Graphics 610)<br>Intel® Pentium® Gold G5400 processor (2 Cores / 4 Threads, 3.70 GHz, 4 MB, Intel® UHD Graphics 610)<br>Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630)<br>Intel® Core™ i3-9100 processor (4 Cores / 4 Threads, 3.60 GHz, up to 4.2 GHz, 6 MB, Intel® HD Graphics 630) *<br>Intel® Core™ i5-8400 processor (6 Cores / 6 Threads, 2.80 GHz, up to 4.0 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-8500 processor (6 Cores / 6 Threads, 3.00 GHz, up to 4.1 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-8600 processor (6 Cores / 6 Threads, 3.10 GHz, up to 4.3 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9400 processor (6 Cores / 6 Threads, 2.90 GHz, up to 4.1 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9500 processor (6 Cores / 6 Threads, 3.00 GHz, up to 4.4 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9600 processor (6 Cores / 6 Threads, 3.10 GHz, up to 4.6 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i7-8700 processor (6 Cores / 12 Threads, 3.20 GHz, up to 4.6 GHz, 12 MB, Intel® UHD Graphics 630) * | Intel® Celeron® processor G4900 (2 Cores / 2 Threads, 3.10 GHz, 2 MB, Intel® UHD Graphics 610)<br>Intel® Celeron® processor G4930 (2 Cores / 2 Threads, 3.20 GHz, 2 MB, Intel® UHD Graphics 610)<br>Intel® Pentium® Gold G5400 processor (2 Cores / 4 Threads, 3.70 GHz, 4 MB, Intel® UHD Graphics 610)<br>Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630)<br>Intel® Core™ i3-9100 processor (4 Cores / 4 Threads, 3.60 GHz, up to 4.2 GHz, 6 MB, Intel® HD Graphics 630) *<br>Intel® Core™ i5-8400 processor (6 Cores / 6 Threads, 2.80 GHz, up to 4.0 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-8500 processor (6 Cores / 6 Threads, 3.00 GHz, up to 4.1 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-8600 processor (6 Cores / 6 Threads, 3.10 GHz, up to 4.3 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9400 processor (6 Cores / 6 Threads, 2.90 GHz, up to 4.1 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9500 processor (6 Cores / 6 Threads, 3.00 GHz, up to 4.4 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i5-9600 processor (6 Cores / 6 Threads, 3.10 GHz, up to 4.6 GHz, 9 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i7-8700 processor (6 Cores / 12 Threads, 3.20 GHz, up to 4.6 GHz, 12 MB, Intel® UHD Graphics 630) *<br>Intel® Core™ i7-9700 processor (8 Cores / 8 Threads, 3.00 GHz, up to 4.7 GHz, 12 MB, Intel® HD Graphics 630) * |
|                                       | *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables)   |   |
| <b>Operating systems</b>              |   |   |
| <b>Operating system pre-installed</b> | Windows 10 Pro. Fujitsu recommends Windows 10 Pro.<br>Windows 10 Home   | Windows 10 Pro. Fujitsu recommends Windows 10 Pro.<br>Windows 10 Home   |
| <b>Operating system notes</b>         | Certified for SUSE Enterprise Desktop<br>Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a> .  | Certified for SUSE Enterprise Desktop<br>Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Windows 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at <a href="http://support.ts.fujitsu.com">http://support.ts.fujitsu.com</a> .  |
|                                       | ESPRIMO P558/E85+   | ESPRIMO P558/E94+   |
| <b>Memory modules</b>                 | 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM<br>8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM<br>16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM  | 4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM<br>8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM<br>16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,666 MT/s, UDIMM  |
|                                       | ESPRIMO P558/E85+   | ESPRIMO P558/E94+   |
| <b>Graphics</b>                       | Midrange 3D: NVIDIA® GeForce® GTX 1050 Ti, 4 GB, 3 x DisplayPort, 1 x HDMI, 1 x Dual Link DVI-D<br>Entry 3D: NVIDIA® Quadro® P400, 2 GB, 3 x miniDP<br>Others: VGA Extension Card<br>Others: MiniDP to DP Adapter Cable<br>Others: DP to DVI-D (single link) Adapter Cable  | Midrange 3D: NVIDIA® GeForce® GTX 1050 Ti, 4 GB, 3 x DisplayPort, 1 x HDMI, 1 x Dual Link DVI-D<br>Entry 3D: NVIDIA® Quadro® P400, 2 GB, 3 x miniDP<br>Others: VGA Extension Card<br>Others: MiniDP to DP Adapter Cable<br>Others: DP to DVI-D (single link) Adapter Cable  |

|   | ESPRIMO P558/E85+   | ESPRIMO P558/E94+   |
|---|---|---|
| <b>Hard disk drive</b>                      | HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch<br>HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch<br>HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical<br>HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch<br>HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch<br>SSD PCIe, 1024 GB M.2 NVMe module<br>SSD PCIe, 1024 GB M.2 NVMe module, SED<br>SSD PCIe, 256 GB M.2 NVMe module<br>SSD PCIe, 256 GB M.2 NVMe module, SED<br>SSD PCIe, 512 GB M.2 NVMe module<br>SSD PCIe, 512 GB M.2 NVMe module, SED<br>SSD SATA III, 1024 GB, 2.5-inch<br>SSD SATA III, 128 GB, 2.5-inch<br>SSD SATA III, 256 GB, 2.5-inch<br>SSD SATA III, 512 GB, 2.5-inch | HDD SATA II, 5,400 rpm, 500 GB, 2.5-inch<br>HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch<br>HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical<br>HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch<br>HDD SATA III, 7,200 rpm, 500 GB, 3.5-inch<br>SSD PCIe, 1024 GB M.2 NVMe module<br>SSD PCIe, 1024 GB M.2 NVMe module, SED<br>SSD PCIe, 256 GB M.2 NVMe module<br>SSD PCIe, 256 GB M.2 NVMe module, SED<br>SSD PCIe, 512 GB M.2 NVMe module<br>SSD PCIe, 512 GB M.2 NVMe module, SED<br>SSD SATA III, 1024 GB, 2.5-inch<br>SSD SATA III, 128 GB, 2.5-inch<br>SSD SATA III, 256 GB, 2.5-inch<br>SSD SATA III, 512 GB, 2.5-inch |
| <b>Hard disk notes</b>                      | SSD (Solid State Disk)<br>SED (Self-Encrypting Drive)   |   |
|   | ESPRIMO P558/E85+   | ESPRIMO P558/E94+   |
| <b>Optical drive</b>                        | MultiCard Reader 24in1 USB 2.0 3.5", USB 2.0<br>DVD-ROM<br>DVD Super Multi, SATA<br>DVD Super Multi ultra slim (tray), SATA<br>BD Triple Writer SATA ultra slim (tray), SATA  | MultiCard Reader 24in1 USB 2.0 3.5", USB 2.0<br>DVD-ROM<br>DVD Super Multi, SATA<br>DVD Super Multi ultra slim (tray), SATA<br>BD Triple Writer SATA ultra slim (tray), SATA  |
|   | ESPRIMO P558/E85+   | ESPRIMO P558/E94+   |
| <b>Interfaces add on cards / components</b> | WLAN 802.11ac (2x2) PCIe x1 and BT 5 (dedicated regions only)<br>WLAN 802.11ac (2x2) PCIe x1 (dedicated regions only)<br>Gigabit Ethernet PCIe x1<br>eSATA Interface<br>Dual serial card PCIe x1  | WLAN 802.11ac (2x2) PCIe x1 and BT 5 (dedicated regions only)<br>WLAN 802.11ac (2x2) PCIe x1 (dedicated regions only)<br>Gigabit Ethernet PCIe x1<br>eSATA Interface<br>Dual serial card PCIe x1  |
| <b>Base unit</b>                            | ESPRIMO P558/E85+   | ESPRIMO P558/E94+   |
| <b>Mainboard</b>                            |   |   |
| <b>Mainboard type</b>                       | D3600   |   |
| <b>Formfactor</b>                           | proprietary   |   |
| <b>Chipset</b>                              | Intel® H310   |   |
| <b>Processor socket</b>                     | LGA 1151  |   |
| <b>Processor quantity maximum</b>           | 1   |   |
| <b>Supported capacity RAM (max.)</b>        | 32 GB   |   |
| <b>Memory slots</b>                         | 2 DIMM (DDR4)   |   |
| <b>Memory frequency</b>                     | 2,666 MT/s  |   |
| <b>Memory notes</b>                         | Dual channel support<br>For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same.<br>2666 MHz may be clocked down to 2400 or 2133 depending on used processor   |   |
| <b>LAN</b>                                  | 10/100/1,000 MBit/s Realtek RTL8111G  |   |
| <b>BIOS version</b>                         | AMI Aptio V<br>UEFI Specification 2.6   |   |
| <b>BIOS features</b>                        | BIOS Flash EPROM update by software<br>Recovery BIOS<br>Unified Extensible Firmware Interface (UEFI)<br>Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core™ i technology   |   |
| <b>Audio type</b>                           | On board  |   |
| <b>Audio codec</b>                          | Realtek ALC671  |   |
| <b>Audio features</b>                       | Internal speaker supports audio playback (optional), High Definition audio, 5.1 surround sound  |   |

**I/O controller on board**

|                      |  |
|----------------------|--|
| Serial ATA total     | 3                                      |
| thereof SATA III     | 3                                      |
| thereof eSATA        | 1                                      |
| Controller functions | Serial ATA III (6 Gbit)<br>NCQ<br>AHCI |

**Interfaces**

|                              |  |
|------------------------------|--|
| Audio: line-in               | 1  |
| Audio: line-out              | 1  |
| Front audio: microphone      | 1  |
| Front audio: headphone       | 1  |
| USB 2.0 total                | 6  |
| USB 3.1 Gen1 (USB 3.0) total | 4  |
| USB 3.1 Gen2 total           | 2 optional via add on card   |
| USB front                    | 2x USB 2.0; 2x USB 3.0; optional: 1x USB 3.1 Type-C (Gen2) via add on card and front adapter bay |
| USB rear                     | 2x USB 2.0; 2x USB 3.0; optional: additional 1x USB 3.1 Type C (Gen2) via add on card            |
| USB internal                 | 2x USB 2.0   |
| VGA                          | optional: via adapter card   |
| DisplayPort                  | 1  |
| DVI                          | 1 (DVI-D)  |
| Mouse / Keyboard (PS/2)      | 2  |
| Ethernet (RJ-45)             | 1  |
| eSATA                        | 1 (optional)   |
| Interface Module notes       | Anytime USB charge functionality   |

**Input device / components**

|                          |  |
|--------------------------|--|
| Input devices (optional) | Keyboard<br>Mouse<br>KBPC PX ECO<br>Mouse M440 ECO |
|--------------------------|--|

**Drive bays**

|                         |  |
|-------------------------|--|
| Drive bays total        | 6  |
| 2.5-inch internal bays  | 1  |
| 3.5-inch internal bays  | 2  |
| 3.5-inch external bays  | 1  |
| 5.25-inch external bays | 2  |
| Drive bay notes         | 5,25" bays: one bay in HH format, one bay for slim optical disc drive only |
| M.2-2280                | 1 x on mainboard for SSD NVMe (PCIe 2.0 x2; up to 10Gbit/s)                |

**Slots**

|                                |                                      |
|--------------------------------|--------------------------------------|
| PCI-Express 3.0 x16            | 1 x (240 mm / 9.45 inch) Full height |
| PCI-Express 2.0 x4 (mech. x16) | 1 x (210 mm / 8.27 inch) Full height |
| PCI-Express x1                 | 1 x (174 mm / 6.85 inch) Full height |

**Graphics on board**

|                     |  |
|---------------------|--|
| Graphics brand name | Intel® UHD Graphics 610, Intel® UHD Graphics 630 |
| Shared video memory | Up to half size of total system memory           |

**Graphics on board**

|                                     |   |
|-------------------------------------|---|
| <b>TFT resolution (VGA)</b>         | 1,024 x 768 pixel<br>1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,600 x 1,200 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel  |
| <b>TFT resolution (DVI)</b>         | 1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel<br>1,920 x 1,200 pixel   |
| <b>TFT resolution (DisplayPort)</b> | 1,280 x 1,024 pixel<br>1,360 x 768 pixel<br>1,440 x 900 pixel<br>1,600 x 900 pixel<br>1,680 x 1,050 pixel<br>1,920 x 1,080 pixel<br>1,920 x 1,200 pixel<br>2,560 x 1,440 pixel<br>2,560 x 1,600 pixel<br>3,440 x 1,440 pixel<br>3,840 x 2,160 pixel<br>4,096 x 2,304 pixel  |
| <b>Graphics features</b>            | Dual display support<br>DirectX® 12<br>HDCP support<br>OpenCL™ 2.0 (requires Intel® Core™ i3, i5 or i7 processors)<br>OpenGL® 4.5<br>For multi monitoring mode, graphics card and integrated graphics run in parallel<br>DisplayPort interface supports Ver. 1.2 incl. Multi-Stream<br>DVI-D interface supports audio output and higher resolutions up to 4096 x 2160 pixel (at 30Hz refresh rate) if connected to the HDMI interface of a display via suitable adapter cables (not included) |
| <b>Graphics notes</b>               | up to 1 GB dedicated video memory (main memory owned and locked for graphics use)<br>Tested resolutions, depending on display type additional resolutions and frequencies possible<br>Shared memory depending on main memory size and operating system<br>Resolution (color depth up to 32 Bit/pixel)<br>For TFT we recommend using 60Hz  |

|                  |                   |                   |
|------------------|-------------------|-------------------|
| <b>Base unit</b> | ESPRIMO P558/E85+ | ESPRIMO P558/E94+ |
|------------------|-------------------|-------------------|

**Electrical values**

|   |   |   |
|---|---|---|
| <b>Power efficiency note</b>                | power supply efficiency at 10% / 20% / 50% / 100% load for 230V: 80% / 85% / 88% / 87%; for 115V: 79% / 84% / 87% / 84% | power supply efficiency at 10% / 20% / 50% / 100% load for 230V: 87% / 91% / 94% / 93%; for 115V: 86% / 90% / 92% / 90% |
| <b>Rated voltage range</b>                  | 100 V - 240 V   | 100 V - 240 V   |
| <b>Rated frequency range</b>                | 50 Hz - 60 Hz   | 50 Hz - 60 Hz   |
| <b>Operating voltage range</b>              | 90 V - 264 V  | 90 V - 264 V  |
| <b>Operating line frequency range</b>       | 47 Hz - 63 Hz   | 47 Hz - 63 Hz   |
| <b>Max. output of single power supply</b>   | 210 W   | 280 W   |
| <b>Power factor correction/active power</b> | active  | active  |
| <b>Monitor outlet</b>                       | No  | Switched  |
| <b>Base unit</b>                            | ESPRIMO P558/E85+   | ESPRIMO P558/E94+   |

**Power consumption**

|                                   |   |   |
|-----------------------------------|---|---|
| <b>Power consumption note</b>     | See white paper Energy Consumption  | See white paper Energy Consumption  |
| <b>Link to Energy White Paper</b> | <a href="http://docs.ts.fujitsu.com/dl.aspx?id=ffde962c-ef48-4907-8104-5a6a928f8544">http://docs.ts.fujitsu.com/dl.aspx?id=ffde962c-ef48-4907-8104-5a6a928f8544</a> | <a href="http://docs.ts.fujitsu.com/dl.aspx?id=84621490-fc2f-4845-8cf6-7ae062d7b4f9">http://docs.ts.fujitsu.com/dl.aspx?id=84621490-fc2f-4845-8cf6-7ae062d7b4f9</a> |

**Noise emission**

|   |  |  |
|---|--|--|
| <b>Related Processors for noise</b>                           | Intel® Core™ i7 8700   | Intel® Core™ i7 8700   |
| <b>Standard noise emission</b>                                | 2x4 GB, HDD, ODD, Windows<br>According to ISO 7779:2010, ECMA-74   | 2x4 GB, HDD, ODD, Windows<br>According to ISO 7779:2010, ECMA-74   |
| <b>Standard noise notes / description</b>                     | A-weighted sound power level L <sub>wad</sub> (in B) / Workplace related A-weighted sound pressure level L <sub>pAm</sub> (in dB(A)) | A-weighted sound power level L <sub>wad</sub> (in B) / Workplace related A-weighted sound pressure level L <sub>pAm</sub> (in dB(A)) |
| <b>Standard noise operation mode: CPU 50% load</b>            | 3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position   | 3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position   |
| <b>Standard noise operation mode: HDD load</b>                | 3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position   | 3.4 B / 21 dB(A) Bystander; 23 dB(A) Operator position   |
| <b>Standard noise operation mode: Idle mode</b>               | 3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position   | 3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position   |
| <b>Standard noise operation mode: ODD load</b>                | 4.6 B / 32 dB(A) Bystander; 38 dB(A) Operator position   | 4.6 B / 32 dB(A) Bystander; 38 dB(A) Operator position   |
| <b>Standard noise operation mode: Office applications 2.0</b> | 3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position   | 3.3 B / 20 dB(A) Bystander; 22 dB(A) Operator position   |

**Dimensions / Weight / Environmental**

|                                      |   |
|--------------------------------------|---|
| <b>Dimensions (W x D x H)</b>        | 180 x 304 x 375 mm<br>7.09 x 11.97 x 14.76 inch   |
| <b>Operating position</b>            | Vertical  |
| <b>Weight</b>                        | 7 kg  |
| <b>Weight (lbs)</b>                  | 15.50 lbs   |
| <b>Weight notes</b>                  | Actual weight may vary depending on configuration |
| <b>Operating ambient temperature</b> | 10 - 35 °C (50 - 95 °F)                           |
| <b>Operating relative humidity</b>   | 5 - 85 % (relative humidity)                      |

**Compliance**

|                        |   |                   |
|------------------------|---|-------------------|
| <b>Product</b>         | ESPRIMO P558/E85+   | ESPRIMO P558/E94+ |
| <b>Model</b>           | MI6W  |                   |
| <b>Germany</b>         | TÜV GS  |                   |
| <b>Europe</b>          | CE  |                   |
| <b>USA/Canada</b>      | FCC Class B<br>cTUVus   |                   |
| <b>Global</b>          | RoHS (Restriction of hazardous substances)<br>WEEE (Waste electrical and electronic equipment)<br>Microsoft Operating Systems (HCT / HCL entry / WHQL)<br>ENERGY STAR® 7.1<br>EPEAT® Bronze (dedicated regions) |                   |
| <b>China</b>           | CCC (depending on configuration)<br>CEL (Chinese energy label)<br>TPM 2.0 for China (optional)  |                   |
| <b>Compliance link</b> | <a href="https://sp.ts.fujitsu.com/sites/certificates">https://sp.ts.fujitsu.com/sites/certificates</a>   |                   |

**Additional Software**

|   |   |                   |
|---|---|-------------------|
| <b>Additional software (preinstalled)</b> | Adobe® Reader® (pdf reader)<br>McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed)<br>Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)  |                   |
| <b>Additional software (optional)</b>     | Recovery DVD for Windows®<br>Drivers & Utilities DVD (DUDVD)<br>CyberLink PowerDVD BD (playback software for Blu-ray Disc™)<br>CyberLink PowerDVD DVD (playback software for DVD)<br>Nero Essentials XL<br>Microsoft® Office Professional 2019<br>Microsoft® Office Home and Business 2019<br>(A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.) |                   |
| <b>Base unit</b>                          | ESPRIMO P558/E85+   | ESPRIMO P558/E94+ |

|   |  |  |
|---|--|--|
| <b>Security</b>                         |  |  |
| <b>Physical Security</b>                | Kensington Lock support<br>Eye for padlock<br>Integrated cabinet lock (optional)<br>Cable Cover (optional; covers and secures the ports and cables on rear side)   | Kensington Lock support<br>Eye for padlock<br>Integrated cabinet lock (optional)<br>Cable Cover (optional; covers and secures the ports and cables on rear side)   |
| <b>System and BIOS Security</b>         | Embedded security (TPM 2.0)<br>EraseDisk (optional)<br>Credential Guard Ready and Device Guard Capable (Windows 10, v. 1809; requires 8 GB or more system RAM and SSD PCIe NVME)<br>Boot sector virus protection<br>Write protect option for the Flash EPROM<br>Control of all USB interfaces<br>External USB ports can be disabled separately<br>Control of external interfaces | Embedded security (TPM 2.0)<br>EraseDisk (optional)<br>Credential Guard Ready and Device Guard Capable (Windows 10, v. 1809; requires 8 GB or more system RAM and SSD PCIe NVME)<br>Boot sector virus protection<br>Write protect option for the Flash EPROM<br>Control of all USB interfaces<br>External USB ports can be disabled separately<br>Control of external interfaces |
| <b>User Security</b>                    | User and supervisor BIOS password<br>Hard disk password<br>Access protection via external SmartCard reader (optional)<br>Access protection via internal SmartCard reader (optional)<br>Workplace Protect (secure authentication solution)  | User and supervisor BIOS password<br>Hard disk password<br>Access protection via external SmartCard reader (optional)<br>Access protection via internal SmartCard reader (optional)<br>Workplace Protect (secure authentication solution)  |
| <b>Workplace Embedded Tools</b>         | Auto BIOS Update via Fujitsu Server<br>Auto BIOS Update via customer server<br>Easy PC Protection  | Auto BIOS Update via Fujitsu Server<br>Auto BIOS Update via customer server<br>Easy PC Protection  |
| <b>Manageability</b>                    |  |  |
| <b>Manageability technology</b>         | DeskUpdate Driver management<br>PXE 2.1 Boot code<br>Wake up from S5 (off mode)<br>Intrusion switch (optional)<br>WoL (Wake on LAN)  |  |
| <b>Manageability software</b>           | DeskView Client<br>DeskView Instant BIOS Management  |  |
| <b>DeskView components</b>              | BIOS Management incl. Security<br>Inventory Management<br>Driver Management<br>Alarm Management  |  |
| <b>Supported standards</b>              | DMI (Desktop Management Interface)<br>SMBIOS (System Management BIOS)<br>PXE (Preboot Execution Environment)<br>WMI (Windows Management Instrumentation)<br>WBEM (Web Based Enterprise Management)<br>CIM (Common Information Model)   |  |
| <b>Manageability link</b>               | <a href="http://www.fujitsu.com/fts/manageability">http://www.fujitsu.com/fts/manageability</a>  |  |
| <b>Miscellaneous</b>                    |  |  |
|   | Keyboard on (Special Fujitsu keyboard required)<br>Keyboard on with one key (KBPX Eco, KB521)<br>Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards<br>Keyboard on with any key (USB)<br>Thermal management   | Keyboard on (Special Fujitsu keyboard required)<br>Keyboard on with one key (KBPX Eco, KB521)<br>Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards<br>Keyboard on with any key (USB)<br>Thermal management   |
| <b>Packaging information</b>            |  |  |
| <b>Packaging dimension (mm)</b>         | 439 x 296 x 499 mm   | 439 x 296 x 499 mm   |
| <b>Packaging dimension (inch)</b>       | 17.28 x 11.65 x 19.65 inch   | 17.28 x 11.65 x 19.65 inch   |
| <b>Max. quantity / pallet</b>           | 24   | 24   |
| <b>Material - Weight (g) Carton</b>     | 1040 g   | 1040 g   |
| <b>Material - Weight (lbs) Carton</b>   | 2.29 lbs   | 2.29 lbs   |
| <b>Material - Weight (g) EPS / PS</b>   | 165 g  | 165 g  |
| <b>Material - Weight (lbs) EPS / PS</b> | 0.36 lbs   | 0.36 lbs   |



**Packaging information**

|                            |   |   |
|----------------------------|---|---|
| Material - Weight (g) PE   | 60 g  | 60 g  |
| Material - Weight (lbs) PE | 0.13 lbs  | 0.13 lbs  |
| Packaging notes            | If cable cover is included in packaging: 1.) packaging dimension is increasing to: 505 x 298 x 537mm / (19.88 x 11.73 x 21.14 inch); 2.) material weight of carton will increase to 1400g; 3.) max. quantity/pallet = 18; printed user documentation is bleached in chlorine free process | If cable cover is included in packaging: 1.) packaging dimension is increasing to: 505 x 298 x 537mm / (19.88 x 11.73 x 21.14 inch); 2.) material weight of carton will increase to 1400g; 3.) max. quantity/pallet = 18; printed user documentation is bleached in chlorine free process |

**Warranty**

|                             |  |
|-----------------------------|--|
| Warranty period             | 1 year (for countries in EMEA)   |
| Warranty type               | Bring-In / Onsite Service (for countries within region EMEA, for all other countries depending on local regulations) |
| Warranty Terms & Conditions | <a href="http://www.fujitsu.com/warranty">http://www.fujitsu.com/warranty</a>  |

**Product Support Services - the perfect extension**

|                          |   |
|--------------------------|---|
| Recommended Service      | 9x5, Onsite Response Time: Next Business Day  |
| Spare Parts availability | 5 years after end of product life   |
| Service Weblink          | <a href="http://www.fujitsu.com/emeia/products/product-support-services/">http://www.fujitsu.com/emeia/products/product-support-services/</a> |

## Recommended Accessories

**Display P27-8 TE Pro**

The FUJITSU Display P27-8 TE Pro has a 2560 x 1440 QHD resolution and comes with a thin bezel housing ideal for multi-monitor use scenarios. The monitor has a wide viewing angle that delivers consistent picture quality, a 100% sRGB color space coverage, ECO function, DisplayView™ IT Suite manageability software and a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:  
S26361-K1609-V140

**Display B34-9 UE**

The FUJITSU Display B34-9 UE is an ultrawide curved display with 3440 x 1440 resolution with a thin bezel housing. The monitor has a 1900R curvature and a wide viewing angle that delivers consistent picture quality, DisplayView™ software and a range of connectivity options ideal for medium- and large-sized businesses.

Order Code:  
S26361-K1642-V140

**Wireless Mouse Touch WI910**

The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.

Order Code:  
S26381-K465-L100



# More information

## Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO P558, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

### Computing Products

[www.fujitsu.com/global/products/computing/](http://www.fujitsu.com/global/products/computing/)

### Software

[www.fujitsu.com/software/](http://www.fujitsu.com/software/)

## More information

Learn more about FUJITSU Desktop ESPRIMO P558, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.  
[www.fujitsu.com/fts/ESPRIMO](http://www.fujitsu.com/fts/ESPRIMO)

## Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



## Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 Fujitsu Technology Solutions GmbH

## Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

## Contact

Fujitsu Technology Solutions GmbH  
Website: [www.fujitsu.com/fts](http://www.fujitsu.com/fts)  
2019-07-20 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html>  
Copyright 2019 Fujitsu Technology Solutions GmbH