Fujitsu recommends Windows 10 Pro.



Data Sheet FUJITSU Desktop ESPRIMO K558/24

Ready to use in the blink of an eye

The FUJITSU ESPRIMO K558/24 All-in-One Desktop PC supports the budget-driven, modern workplace: streamlined workspace, reduced complexity, with no compromise in performance. This all-rounder combines up to 9th Gen Intel® Core™ processors and the latest interfaces in a compact, all-in-one design. For ergonomic comfort, it features a 60.5 cm (23.8-inch) anti-glare display, wide viewing angles, height adjustment and front I/Os.

Human-Centric Setup

Tidy and convenient desk with ergonomic working position to help enhance working experience and efficiency

60.5 cm (23.8-inch) anti-glare Full HD display with wide viewing angle screen for exceptional sensory experience. Ergonomic design that includes four-stage height adjustment, a large swivel range and low noise. The keyboard can be placed between the screen and the bottom plate for additional desk space. Wall mounting in accordance with the VESA standard.

Unrivalled Usability

Wide range of features designed to ease your working experience

■ Easy to access and flexible interfaces, microphone and camera option for instant office communication and anytime USB charge functionality

Manageability and Ease of Use

"Plug & work" PC that ensures smooth system administration

■ Easy to integrate into existing IT landscapes and reliable DeskView manageability tools

Excellent Performance and Energy Efficiency

Best-in-class regarding low power consumption combined with new levels of performance

■ Up to 9th generation Intel® Core™ processor family and a highly efficient power supply

Robust Security

Designed to protect data and hardware components against manipulation and theft

- Cable cover with lock option at the back to protect ports, cables and components from theft.
- Embedded Trusted Platform Module (TPM), Fujitsu Workplace Protect software with full disk encryption and system-level passwords. EraseDisk software and SmartCard are available as options











Page 1 / 9 www.fujitsu.com/fts/ESPRIMO

Components

| Operating systems | |
|--------------------------------|---|
| Operating system pre-installed | Windows 10 Pro. Fujitsu recommends Windows 10 Pro. Windows 10 Home |
| Operating system notes | Certified for SUSE Enterprise Desktop (pending) Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support.ts.fujitsu.com. |
| Processor | Intel® Core™ i7-8700T processor (6 Cores / 12 Threads, 2.40 GHz, up to 4.0 GHz, 12 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-9400T processor (6 Cores / 6 Threads, 1.80 GHz, up to 3.4 GHz, 9 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-8500T processor (6 Cores / 6 Threads, 2.10 GHz, up to 3.5 GHz, 9 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-8400T processor (6 Cores / 6 Threads, 1.70 GHz, up to 3.3 GHz, 9 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i3-8100T processor (4 Cores / 4 Threads, 3.10 GHz, 6 MB, Intel® UHD Graphics 630) |
| | Intel® Core™ i5-9500T processor (6 Cores / 6 Threads, 2.20 GHz, up to 3.7 GHz, 9 MB, Intel® UHD Graphics 630) * |
| | Intel® Core™ i5-8500 processor (6 Cores / 6 Threads, 3.00 GHz, 9 MB, Intel® UHD Graphics 630) |
| | Intel® Core™ i5-8400 processor (6 Cores / 6 Threads, 2.80 GHz, 9 MB, Intel® UHD Graphics 630) |
| | Intel® Core™ i3-9100 processor (4 Cores / 4 Threads, 3.60 GHz, up to 4.2 GHz, 6 MB, Intel® HD Graphics 630) * |
| | Intel® Core™ i3-8100 processor (4 Cores / 4 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) |
| | Intel® Pentium® processor G5400T processor (2 Cores / 4 Threads, 3.10 GHz, 4 MB, Intel® UHD Graphics 610) |
| | Intel® Pentium® Gold G5400 processor (2 Cores / 4 Threads, 3.70 GHz, 4 MB, Intel® UHD Graphics 610) |
| | Intel® Celeron® processor G4930 (2 Cores / 2 Threads, 3.20 GHz, 2 MB, Intel® UHD Graphics 610) |
| | Intel® Celeron® processor G4900 (2 Cores / 2 Threads, 3.10 GHz, 2 MB, Intel® UHD Graphics 610) |
| | *with Intel® Turbo Boost Technology (clock speed and performance will vary depending on workload and other variables) |
| Camera | 2.0 megapixel webcam (full HD), optional |
| Microphone | Digital stereo microphone, optional |
| Display | |
| Stand | Stand is removable. If only VESA mounting is required, the stand is just an option. |
| leight adjust range | 110 mm |
| ilt angle | 0° / 20° |
| iwivel angle | +/-170° (340°) |
| Screen Surface Treatment | Anti-glare Anti-glare |
| Contrast - advanced | 1000:1 |
| Response time typical | 14 ms |
| /iewing angle (h/v) - typical | 178°/178° CR10:1 |
| Color performance | 16.7 million colors |
| Brightness - typical | 250 cd/m2 |
| Aspect ratio | 16:9 |
| Diagonal Size | 60.5 cm (23.8-inch) |
| Resolution (native) | 1,920 x 1,080 pixel |
| | 4 GB (1 module(s) 4 GB) DDR4, non-ECC, 2,666 MT/s, SO DIMM |
| Memory modules | 1 db (1 1110ddie(3) 1 db) bbit 1, 11011 Ecc, 2,000 111113, 30 bittitt |
| Memory modules | 8 GB (1 module(s) 8 GB) DDR4, non-ECC, 2,666 MT/s, SO DIMM |

Page 2 / 9 www.fujitsu.com/fts/ESPRIMO

| Hard disk drives (internal) | SSD PCIe, 1024 GB M.2 NVMe module |
|--|---|
| | SSD PCIe, 512 GB M.2 NVMe module |
| | SSD PCIe, 256 GB M.2 NVMe module |
| | SSD PCIe, 1024 GB M.2 NVMe module, SED |
| | SSD PCle, 512 GB M.2 NVMe module, SED |
| | SSD PCIe, 256 GB M.2 NVMe module, SED |
| | SSD SATA III, 1024 GB, 2.5-inch |
| | SSD SATA III, 512 GB, 2.5-inch |
| | SSD SATA III, 256 GB, 2.5-inch |
| | SSD SATA III, 128 GB, 2.5-inch |
| | HDD SATA III, 7,200 rpm, 500 GB, 2.5-inch |
| | HDD SATA II, 5,400 rpm, 1,000 GB, 2.5-inch* |
| | HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch |
| Hard disk notes | SSD (Solid State Disk) |
| | SED (Self-Encrypting Drive) |
| Graphics | DP to DVI-D (single link) Adapter Cable |
| Drives (optional) | BD Triple Writer SATA ultra slim (tray) |
| | DVD Super Multi ultra slim (tray) |
| Interface add on cards/components (optional) | |
| | |

M.2 WLAN 802.11ac (2x2) and BT 5 (dedicated regions only)

Base unit

| Base unit | ESPRIMO K558/24 |
|-------------------------------|--|
| Mainboard | |
| Mainboard type | D3674 |
| Formfactor | proprietary |
| Chipset | Intel® H310 |
| Processor socket | LGA 1151 |
| Supported capacity RAM (max.) | 32 GB |
| Memory slots | 2 DIMM (DDR4) |
| Memory frequency | 2,666 MT/s |
| Memory notes | Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2666 MHz may be clocked down to 2400 or 2133 depending on used processor |
| LAN | 10/100/1,000 MBit/s Realtek RTL8111G |
| Integrated WLAN | 1 (optional with Bluetooth together) |
| BIOS version | AMI Aptio V UEFI Specification 2.5 |
| BIOS features | BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI) Support for Compatibility Support Module (CSM) is no longer possible on systems with 8th Generation Intel® Core™ i technology |
| Audio type | On board |
| Audio codec | Realtek ALC255 |
| Audio features | High Definition audio, Internal stereo speakers, Optional: Internal high quality stereo speakers |

Page 3 / 9 www.fujitsu.com/fts/ESPRIMO

| I/O controller on board | |
|------------------------------|--|
| Serial ATA total | 2 |
| thereof SATA III | 2 2 |
| | |
| Controller functions | Serial ATA III (6 Gbit) NCQ |
| | AHCI |
| Interfaces | |
| Audio: line-out / headphone | 1 |
| Audio: line-in / microphone | 1 |
| Front audio: microphone | 1 |
| Front audio: headphone | 1 |
| Internal microphones | optional with multimedia module (camera and microphone) |
| USB 2.0 total | 3 |
| USB 3.1 Gen1 (USB 3.0) total | 4 |
| USB front | 2x USB 3.0 |
| USB rear | 3x USB 2.0, 2x USB 3.0 |
| DisplayPort | 1 |
| Serial (RS-232) | 1 optional |
| Mouse / Keyboard (PS/2) | 2 |
| Ethernet (RJ-45) | 1 |
| Interface Module notes | Anytime USB charge functionality |
| Input device / components | |
| Input devices (optional) | Keyboard |
| input devices (optional) | Mouse |
| | KBPC PX ECO |
| | Mouse M440 ECO |
| Drive bays | |
| 2.5-inch internal bays | 1 |
| 5.25-inch internal bays | 1 |
| Drive bay notes | 5.25" bay: for slim optical disc drive only |
| M.2-2280 | 1 x on mainboard for SSD NVMe (PCle 2.0 x4; up to 20Gbit/s) |
| Mini PCI slots | |
| M.2-2230 | on mainboard for WLAN module |
| Graphics on board | |
| Graphics brand name | Intel® UHD Graphics 610, Intel® UHD Graphics 630 |
| Shared video memory | Up to half size of total system memory |
| TFT resolution (DisplayPort) | 1,280 x 1,024 pixel |
| | 1,360 x 768 pixel |
| | 1,440 x 900 pixel 1,600 x 900 pixel |
| | 1,600 x 900 pixel 1,680 x 1,050 pixel |
| | 1,920 x 1,080 pixel |
| | 1,920 x 1,200 pixel |
| | 2,560 x 1,440 pixel |
| | 2,560 x 1,600 pixel |
| | 3,440 x 1,440 pixel 3,840 x 2,160 pixel |
| | 4,096 x 2,304 pixel |
| Graphics features | Dual display support |
| r | DirectX [®] 12 |
| | HDCP support |
| | OpenCL [™] 2.0 (requires Intel® Core™ i3, i5 or i7 processors) OpenGL® 4.5 |
| | openut 4.3 |
| | DisplayPort interface supports Ver. 1.2 incl. Multi-Stream |

Page 4 / 9 www.fujitsu.com/fts/ESPRIMO

| Graphics on board | |
|--|--|
| Graphics notes | up to 1 GB dedicated video memory (main memory owned and locked for graphics use) |
| diapines notes | Tested resolutions, depending on display type additional resolutions and frequencies possible |
| | Shared memory depending on main memory size and operating system |
| | Resolution (color depth up to 32 Bit/pixel) |
| | For TFT we recommend using 60Hz |
| Electrical values | |
| Power efficiency note | power supply efficiency (at 230V; 10% / 20% / 50% / 100% load) : 85% / 90% / 93% / 93% |
| Rated voltage range | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz |
| Operating voltage range | 90 V - 264 V |
| Operating line frequency range | 47 Hz - 63 Hz |
| Max. output of single power supply | 170 W |
| Power factor correction/active power | active |
| Power consumption | |
| Power consumption note | See white paper Energy Consumption |
| Link to Energy White Paper | http://docs.ts.fujitsu.com/dl.aspx?id=6e6fdd6b-6b92-48d7-bdac-24a2029b4b65 |
| Heat dissipation | |
| Heat dissipation notes | See white paper Energy Consumption |
| · | See white paper Eliety consumption |
| Noise emission | |
| Related Processors for noise | Intel® Core™ i7 8700T |
| Standard noise emission | 2x4 GB, HDD, ODD, Windows According to ISO 7779:2010, ECMA-74 |
| Standard noise notes / description | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) |
| Standard noise operation mode: CPU | 3.3 B / 19 dB(A) Bystander; 20 dB(A) Operator position |
| 50% load | 5.5 BY 15 dB(V) Bystander, 20 dB(V) Operator position |
| Standard noise operation mode: HDD load | 3.2 B / 17 dB(A) Bystander; 18 dB(A) Operator position |
| Standard noise operation mode: Idle | 3.2 B / 17 dB(A) Bystander; 18 dB(A) Operator position |
| mode | 5.2 BY 17 dB(r) bystander, to dB(r) operator position |
| Standard noise operation mode: ODD | 4.1 B / 27 dB(A) Bystander; 30 dB(A) Operator position |
| load | |
| • | 3.2 B / 17 dB(A) Bystander; 18 dB(A) Operator position |
| applications 2.0 | |
| Dimensions / Weight / Environmental | |
| Dimension with stand $(W \times D \times H)$ | 560 x 258 x 446 mm |
| Dimension with stand $(W \times D \times H)$ inch | 20.1 x 10.2 x 16.2 inch |
| Dimension notes | Height is with display in second position of stand, maximum height is: 516 mm (19 inch), lowest height is: 411 mm (14.9 inch); picture height over desk (min): 85mm, for additional positions: 115/155/190mm, dimensions for display only (without stand) are following |
| Dimensions (W x D x H) | 560 x 93 x 368 mm |
| The state of the s | 22.1 x 3.67 x 14.5 inch |
| Operating position | Vertical with stand or VESA mounted |
| VESA mount | integrated (100 mm) |
| Weight | app. 9.7 kg |
| Weight (lbs) | 14.33 lbs |
| Weight notes | Actual weight may vary depending on configuration |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F) |
| Operating ambient temperature Operating relative humidity | 5 - 85 % (relative humidity) |
| , | S to the lattice from the lattice for the latt |
| Compliance | FCDDIMO (FFG)2/ |
| Product | ESPRIMO K558/24 |
| Model | AI017 |

Page 5 / 9

| Compliance | |
|------------------------------------|--|
| Germany | GS . |
| Еигоре | CE |
| USA/Canada | FCC Class B cCSAus |
| Global | RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 7.1 EPEAT® Bronze (dedicated regions) |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |
| Additional Software | |
| Additional software (preinstalled) | Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.) |
| Additional software (optional) | Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.) |
| Manageability | |
| Manageability technology | DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) |
| Manageability software | DeskView Client DeskView Instant BIOS Management |
| DeskView components | BIOS Management incl. Security Inventory Management Driver Management Alarm Management |
| Supported standards | DMI (Desktop Management Interface) SMBIOS (System Management BIOS) PXE (Preboot Execution Environment) WMI (Windows Management Instrumentation) WBEM (Web Based Enterprise Management) CIM (Common Information Model) |
| Manageability link | http://www.fujitsu.com/fts/manageability |
| Security | |
| Physical Security | Kensington Lock support Eye for padlock |
| System and BIOS Security | Embedded security (TPM 2.0) EraseDisk (optional) Credential Guard Ready and Device Guard Capable (Windows 10, v. 1809; requires 8 GB or more system RAM and SSD PCIe NVME) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces |

Page 6 / 9 www.fujitsu.com/fts/ESPRIMO

| Security | |
|---|---|
| User Security | User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution) |
| Workplace Embedded Tools | Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server Easy PC Protection |
| Miscellaneous | |
| | Keyboard on (Special Fujitsu keyboard required) Keyboard on with one key (KBPX Eco, KB521) Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special USB keyboards Keyboard on with any key (USB) Thermal management |
| Serviceability | |
| | EasyChange for HDD EasyChange for optical drives |
| Packaging information | |
| Packaging dimension (mm) | 705 x 400 x 607 mm |
| Packaging dimension (inch) | 27.76 x 15.75 x 23.9 inch |
| Max. quantity / pallet | 9 |
| Material - Weight (g) Carton | 1750 g |
| Material - Weight (lbs) Carton | 3.86 lbs |
| Material - Weight (g) EPS / PS | 1190 g |
| Material - Weight (lbs) EPS / PS | 2.62 lbs |
| Material - Weight (g) PE | 60 g |
| Material - Weight (lbs) PE | 0.13 lbs |
| Packaging notes | printed user documentation is bleached in chlorine free process |
| Warranty | |
| Warranty type | Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations) |
| Warranty Terms & Conditions Product Support Services - the perfec | http://www.fujitsu.com/warranty at extension |
| Recommended Service | 9x5, Onsite Response Time: Next Business Day |
| Service Weblink | http://www.fujitsu.com/emeia/products/product-support-services/ |

Recommended Accessories

| Display B24-9 TS | The FUJITSU Display B24-9 TS is a widescreen display with 1920 x 1080 Order Code: Full HD resolution with a ultra-thin bezel housing. The monitor has a wide viewing angle that delivers consistent picture quality and DisplayView™ manageability software for further enhancing monitor features with a range of connectivity options ideal for medium- and large-sized businesses. | |
|---------------------|---|---------|
| Display E24-9 TOUCH | The FUJITSU Display E24-9 TOUCH is a 10 point projected capacitive touch (PCT) ergonomic display with 1920 x 1080 Full HD resolution. The monitor screen has anti-glare that helps prevent smudges, spots and blurs owing to touch-intensive tasks. The monitor also has powerful built-in speakers and a range of interfaces for easy connectivity and maximum flexibility. | 44-V160 |

Page 7 / 9 www.fujitsu.com/fts/ESPRIMO

Wireless Mouse Touch WI910



The Fujitsu Wireless Mouse Touch WI910 has a special touch sensitive surface that recognizes when your hand touches the mouse even before you move it. This provides nearly instantaneous wake-up from the intelligent energy saving sleep mode. Unbeatable responsiveness combines with features like switchable resolution, and three programmable buttons for a unique user experience.

Order Code: S26381-K465-L100

Keyboard KB951 PalmM2



The KB951 palm vein keyboard is a modern, slim line USB keyboard featuring Fujitsu PalmSecure™ technology with an integrated palm vein sensor. PalmSecure™ is a cutting-edge authentication system using biometric technology that authenticates users based on vein pattern recognition rather than iris scanners or fingerprint readers. As veins are internal and have a wealth of differentiating features, attempts at identity theft are extremely difficult, enabling a high level of security. This extremely reliable, high-speed input device is the best choice when you don't have a PC or notebook with an integrated palm vein sensor.

S26381-K951-L4** (**: country specific variation)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO K558/24, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO K558/24, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/fts/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/qlobal/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html

Copyright 2019 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com/fts 2019-07-20 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/fts/resources/navigation/terms-of-use.html
Copyright 2019 Fujitsu Technology Solutions GmbH