

Product datasheet

Specifications



APC Netshelter SX, Server Rack Enclosure, 18U, Black, 925H x 600W x 1070D mm

AR3106

EAN Code: 0731304347699

Overview

Presentation	An industry-standard rack with the most standard features for speed of deployment and installation. Ready for low to medium density edge computing. Shorter height allows for deployment underneath cabinets, desks, in remote office branch office spaces for a secure and discrete solution for IT devices.
--------------	---

Main

Product or component type	Rack enclosure
Number of rack unit	18U
Rack width	19"
Permanent permissible load	408.2 kg dynamic 408.2 kg static
Provided equipment	Casters Doors Key(s) Leveling feet Roof Side panels

Complementary

mounting mode	Not rack-mountable
Minimum mounting depth	191 mm
Maximum mounting depth	920.8 mm
Colour	Black
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Height	925 mm
Width	600 mm
Depth	1070 mm
Net weight	72.12 kg

Environmental

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------

Packing Units

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	106 cm
Package 1 Width	116 cm
Package 1 Length	75 cm
Package 1 Weight	93 kg

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	60
----------------------	----

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

 Environmental footprint	
Total lifecycle Carbon footprint	326 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	312 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	8 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	7 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Again

 Repack and remanufacture	
Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

