

ThinkCentre M920 Tiny 10RS0040SP

Product
ThinkCentre M920q Tiny

Region
WE

Country
Spain

Machine Type
10RS

TopSeller
TopSeller

Processor
Core i5-9500T (6C / 6T, 2.2 / 3.7GHz, 9MB)

vPro
vPro

Graphics
Integrated Intel UHD Graphics 630

Monitor Cable
None

Memory
1x 8GB DDR4-2666

Storage
512GB SSD M.2 2280 PCIe x4 NVMe opal

Optical
None

WLAN + Bluetooth
Intel 9560 11ac, 2x2 + BT5.0

Ethernet
Integrated

Optional Rear Ports
1x HDMI + 1x Serial

Chassis Intrusion Switch
Chassis Intrusion Switch

Kensington Cable Lock
None

Adapter Cage
None

Toolless Chassis Screw
Toolless Chassis Screw

Speaker
1.5Wx1

Dust Filter
None

VESA Mount
VESA Mount

Stand
None

Keyboard / Mouse
USB / USB

Power Supply
90W 88% Adapter

TUV Low Noise
None

Operating System
Windows 10 Pro 64

Bundled Software
None

Warranty
3-year, Onsite

End of Support
2025-08-02

Announce Date
2019-07-02



WWW.LENOVO.COM

This publication was developed for products and services offered in the United States and E.M.E.A countries. Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area. Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication “as is” without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



<http://psref.lenovo.com>

Visit psref website for the latest version of Product Specifications Reference.
© Lenovo, 2019. All rights reserved.



ThinkCentre M920 Tiny Platform Specifications

Product Specifications Reference (PSREF)



Processor	Intel® Celeron®, Intel Pentium®, or 8th / 9th Gen Intel Core™ i3 / i5 / i7 / i9 Processor						Bluetooth Ethernet (Opt.) Manageability Security chip Security features Keyboard Mouse Mechanical VESA mount Floor Stand Power supply Limited warranty Preload Environment MIL-SPEC test Accessories	<p><i>Some:</i> Bluetooth 4.2/5.0 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Intel Ethernet Connection I219-LM(Jacksonville), Wake on LAN® <i>Some:</i> Intel Ethernet Server Adapter I350-T4, gigabit ethernet, 4x RJ-45, PCIe x4</p> <p>Intel Active Management Technology 12 (Intel AMT 12); Intel vPro technology on some models (require choosing a vPro-support Wi-Fi adapter to enable vPro function through wireless connection)</p> <p>Discrete TPM 2.0, TCG Certified</p> <ul style="list-style-type: none"> Security slot (in rear for optional Kensington® MicroSaver® cable) Chassis intrusion switch Power-on password Administrator password Hard disk password Boot sequence control Boot without keyboard and mouse Individual USB port disablement Smart USB protection, allows keyboard/mouse only, blocks all storage devices <p><i>Some:</i> Lenovo Calliope Keyboard (USB connector), black <i>Some:</i> Lenovo Traditional Keyboard (USB connector), black <i>Some:</i> Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black <i>Some:</i> Lenovo Calliope Mouse (USB connector), black <i>Some:</i> Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black <i>Some:</i> Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black</p> <p>Tiny (1L), black color; metal case</p> <ul style="list-style-type: none"> Toolless chassis open (need optional toolless chassis screw) Toolless HDD, SSD, memory removal Optional dust filter <p>one 2.5" bay for HDD/SSD, one PCIe 3.0 x8 slot (low-profile), two M.2 slots (one for WLAN, one for M.2 SSD), 2.5" HDD/SSD and PCIe card are mutually exclusive</p> <table border="1"> <thead> <tr> <th></th> <th>Dimensions (WxDxH)</th> <th>Weight (Approx.)</th> </tr> </thead> <tbody> <tr> <td>Tiny only</td> <td>7.05" X 7.20" X 1.36" 179mm X 182.9mm X 34.5mm</td> <td>2.91 lb (1.32 kg), vary by config</td> </tr> <tr> <td>With VESA mount & ODD box</td> <td>7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm</td> <td>3.66 lb (1.66 kg), vary by config</td> </tr> </tbody> </table> <p>Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation</p> <p><i>Some:</i> 65 watts AC/DC adapter, autosensing, 88% PSU <i>Some:</i> 90 watts AC/DC adapter, autosensing, 88% PSU <i>Some:</i> 135 watts AC/DC adapter, autosensing, 88% PSU</p> <p><i>Some:</i> 1-year or 3-year, depot service / service upgrades available <i>Some:</i> 1-year or 3-year, limited onsite service / service upgrades available</p> <p>Preloaded operating system <i>Some:</i> Windows® 10 Pro 64-bit <i>Some:</i> Windows 10 Home 64-bit</p> <p>Preloaded applications (only some listed)</p> <ul style="list-style-type: none"> Lenovo Vantage Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD (only for models with DVD / DVD±RW) Cyberlink Power2GO (only for models with DVD±RW) LinkedIn Intel Unite (Machine Type 10V8 models only) <p>ENERGY STAR® 7.0, EPEAT™ Silver rating (North America), ErP Lot 3, TCO, TUV ultra low noise verified (coming soon, on some models), RoHS-compliant</p> <p>MIL-STD-810G military certification (Low Pressure [Altitude], High Temperature, Low Temperature, Temperature Shock, Humidity, Sand and Dust, Vibration, Shock, Fungus, Solar Radiation)</p> <p>For compatible accessories, please go to http://smartfind.lenovo.com</p>		Dimensions (WxDxH)	Weight (Approx.)	Tiny only	7.05" X 7.20" X 1.36" 179mm X 182.9mm X 34.5mm	2.91 lb (1.32 kg), vary by config	With VESA mount & ODD box	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm	3.66 lb (1.66 kg), vary by config
		Dimensions (WxDxH)	Weight (Approx.)														
	Tiny only	7.05" X 7.20" X 1.36" 179mm X 182.9mm X 34.5mm	2.91 lb (1.32 kg), vary by config														
	With VESA mount & ODD box	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm	3.66 lb (1.66 kg), vary by config														
	Processor	Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)			Integrated Graphics								
		Celeron G4900T	2 / 2	2.9G	2 MB	DDR4-2400			UHD 610								
		Celeron G4930T	2 / 2	3.0G	2 MB	DDR4-2400			UHD 610								
		Pentium Gold G5400T	2 / 4	3.1G	4 MB	DDR4-2400			UHD 610								
		Pentium Gold G5500T	2 / 4	3.2G	4 MB	DDR4-2400			UHD 630								
		Pentium Gold G5600T	2 / 4	3.3G	4 MB	DDR4-2400			UHD 630								
		Pentium Gold G5420T	2 / 4	3.2G	4 MB	DDR4-2400			UHD 610								
		Core i3-8100T	4 / 4	3.1G	6 MB	DDR4-2400			UHD 630								
		Core i3-8300T	4 / 4	3.2G	8 MB	DDR4-2400			UHD 630								
		Core i5-8400T	6 / 6	1.7G / 3.3G	9 MB	DDR4-2666			UHD 630								
		Core i5-8500T	6 / 6	2.1G / 3.5G	9 MB	DDR4-2666			UHD 630								
	Core i5-8600T	6 / 6	2.3G / 3.7G	9 MB	DDR4-2666	UHD 630											
	Core i7-8700T	6 / 12	2.4G / 4.0G	12 MB	DDR4-2666	UHD 630											
	Core i3-9100T	4 / 4	3.1G / 3.7G	6 MB	DDR4-2400	UHD 630											
	Core i3-9300T	4 / 4	3.2G / 3.8G	8 MB	DDR4-2400	UHD 630											
	Core i5-9400T	6 / 6	1.8G / 3.4G	9 MB	DDR4-2666	UHD 630											
	Core i5-9500T	6 / 6	2.2G / 3.7G	9 MB	DDR4-2666	UHD 630											
	Core i5-9600T	6 / 6	2.3G / 3.9G	9 MB	DDR4-2666	UHD 630											
	Core i7-9700T	8 / 8	2.0G / 4.3G	12 MB	DDR4-2666	UHD 630											
	Core i9-9900T	8 / 16	2.1G / 4.4G	16 MB	DDR4-2666	UHD 630											
Memory	32GB max, DDR4-2666*, two 260-pin SO-DIMM sockets, dual-channel capable * System automatically clocks down for the processors with lower memory controller																
Storage	<p><i>Some:</i> Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm</p> <p><i>Some:</i> Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5"</p> <p><i>Some:</i> M.2 SSD / PCIe NVMe, PCIe 3.0 x 4", 32Gb/s</p> <p>* 128GB SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s</p> <p><i>Some:</i> Intel Optane™ Memory (not support Celeron / Pentium Processor), M.2</p> <p><i>Some:</i> DVD-ROM, slim (9.0mm), via USB external ODD box</p> <p><i>Some:</i> DVD Burner (DVD±RW), slim (9.0mm), via USB external ODD box</p>																
Optical	One onboard SATA 6.0Gb/s connector																
Onboard SATA	One onboard SATA 6.0Gb/s connector																
Graphics	<p>Intel HD Graphics 610/630 in processor, uses main memory, DirectX® 12, one DisplayPort™, one HDMI, one optional video port (2nd HDMI, VGA, 2nd DP, or USB 3.1 Type-C Gen1 with DisplayPort function), up to 3 independent displays; <i>Max resolution:</i> 4096x2304 (DP)@60Hz; 4096x2304 (Type-C)@60Hz; 4096x2160 (onboard HDMI)@24Hz; 2048x1536 (VGA)@50Hz</p>																
Monitor cable	Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle (for Collage Display with intel integrated graphics), or DP to HDMI 1.4 dongle																
Chipset	Intel Q370 Chipset																
Front ports (Std.)*	one USB 3.1 Gen1 (Always On and fast charge), one USB 3.1 Type-C Gen 1, one microphone (3.5mm), one headphone / microphone combo jack (3.5mm)																
Rear ports (Std.)*	2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x ethernet (RJ-45), 1x DisplayPort, 1x HDMI																
Rear ports (Opt.)*	Two optional ports (mutually exclusive with PCIe card): Port 1 for VGA / 2nd DP / 2nd HDMI / serial / USB 3.1 Type-C Gen 1 with DP function); Port 2 for serial; Optional ports via PCIe card: 2x USB 3.1 Gen1 via PCIe x1, 4x serial (9-pin) via PCIe x1, 1x Thunderbolt 3 (combo USB3.1 Type-C Gen 2 / DisplayPort) via PCIe x4 * Depending on many factors, actual data transfer speed may be lower than theoretical speed																
Audio support	Realtek ALC233VB2 / optional internal speaker (1.5 watt or 2 watt)																
WLAN	<p><i>Some:</i> 11ac wireless, M.2 Card, Realtek RTL8821CE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 1x1</p> <p><i>Some:</i> 11ac wireless, M.2 Card, Realtek RTL8822BE (dual band), Wi-Fi + Bluetooth 4.2 combo adapter, 2x2</p> <p><i>Some:</i> 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.2 combo adapter, 1x1</p> <p><i>Some:</i> 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.2 combo adapter, 2x2</p> <p><i>Some:</i> 11ac wireless, M.2 Card, Intel Wireless-AC 9560 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, Intel vPro technology support, 2x2</p>																

Note: The specifications above may not be available in all regions.

Lenovo, June 2019

ThinkCentre M920 Tiny

