ThinkCentre M920 Tower Platform Specifications

Product Specifications Reference (PSREF)

Processor					

Intel® Celeron®, Intel Pentium®, or 8th /9th Gen Intel Core™ i3 / i5 / i7 / i9 Processor

Processor	Cores / Threads	Frequency Base/Max(GHz)	Cache	Memory Support (Up to)	Integrated Graphics
Celeron G4900	2 / 2	3.1G	2 MB	DDR4-2400	UHD 610
Celeron G4920	2 / 2	3.2G	2 MB	DDR4-2400	UHD 610
Celeron G4930	2 / 2	3.2G	2 MB	DDR4-2400	UHD 610
Celeron G4950	2 / 2	3.3G	2 MB	DDR4-2400	UHD 610
Pentium Gold G5400	2 / 4	3.7G	4 MB	DDR4-2400	UHD 610
Pentium Gold G5500	2 / 4	3.8G	4 MB	DDR4-2400	UHD 630
Pentium Gold G5600	2 / 4	3.9G	4 MB	DDR4-2400	UHD 630
Pentium Gold G5420	2 / 4	3.8G	4 MB	DDR4-2400	UHD 610
Pentium Gold G5620	2 / 4	4.0G	4 MB	DDR4-2400	UHD 630
Core i3-8100	4 / 4	3.6G	6 MB	DDR4-2400	UHD 630
Core i3-8300	4 / 4	3.7G	8 MB	DDR4-2400	UHD 630
Core i5-8400	6 / 6	2.8G / 4.0G	9 MB	DDR4-2666	UHD 630
Core i5-8500	6 / 6	3.0G / 4.1G	9 MB	DDR4-2666	UHD 630
Core i5-8600	6 / 6	3.1G / 4.3G	9 MB	DDR4-2666	UHD 630
Core i7-8700	6 / 12	3.2G / 4.6G	12 MB	DDR4-2666	UHD 630
Core i3-9100	4 / 4	3.6G / 4.2G	6 MB	DDR4-2400	UHD 630
Core i3-9300	4 / 4	3.7G / 4.3G	8 MB	DDR4-2400	UHD 630
Core i3-9320	4 / 4	3.7G / 4.4G	8 MB	DDR4-2400	UHD 630
Core i5-9400	6 / 6	2.9G / 4.1G	9 MB	DDR4-2666	UHD 630
Core i5-9500	6 / 6	3.0G / 4.4G	9 MB	DDR4-2666	UHD 630
Core i5-9600	6 / 6	3.1G / 4.6G	9 MB	DDR4-2666	UHD 630
Core i7-9700	8 / 8	3.0G / 4.7G	12 MB	DDR4-2666	UHD 630
Core i9-9900	8 / 16	3.1G / 5.0G	16 MB	DDR4-2666	UHD 630

Memory
64GB max, DDR4-2666*, four 288-pin DIMM sockets, dual-channel capable
* System automatically clocks down for the processors with lower memory controller

Storage
Some: Hard Drive / SATA 6.0Gb/s, 2.5" or 3.5", 5400 rpm or 7200 rpm
Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5"
Some: M.2 Solid State Drive (SSD) / PCIe NVMe, PCIe 3.0 x 4*, 32Gb/s
* SSD M.2 (2242) PCIe NVMe only supports PCIe 3.0 x 2, 16Gb/s
Some: Intel Optane™ Memory (not support Celeron / Pentium Processor), M.2

Optical
Optional DVD-ROM or DVD Burner (DVD±RW), SATA 1.5Gb/s Drive, slim (9.0mm)

Onboard SATA
Four onboard SATA 6.0Gb/s connectors, RAID 0/1 support (RAID preset only available via special bid model)

Media reader
Optional 7-in-1 media reader

Graphics
Intel UHD Graphics 610/630 in processor, uses main memory, DirectX® 12, one VGA, two DisplayPort™, supports 3 independent displays, works along with discrete graphics to support more displays;
Max resolution: 4096x2304 (DP)@60Hz; 2048x1536 (VGA)@50Hz
Some: **NVIDIA Geforce® GT 730**, DirectX 12, 2GB, PCIe 2.0 x16 adapter, two DisplayPort, 35 watts;
Max resolution: 3840x2160 (DisplayPort)@60Hz;
Some: **NVIDIA Geforce GTX 1060** (special bid only), DirectX 12, 6GB, PCIe 3.0 x16 adapter, 1x DVI-D, 1x HDMI, 3x DP, 120 watts, occupies two slots;
Max resolution: 2560x1600 (DVI-D)@60Hz; 4096x2160 (HDMI)@60Hz 5120x3200 (DP)@60Hz

Monitor Cable
Optional DP to VGA dongle, DP to DVI-D dongle, DP to dual DP dongle (for Collage Display with intel integrated graphics), or DP to HDMI 1.4 dongle

Chipset
Intel Q370 Chipset

Front ports* (Std.)
2x USB 3.1 Gen2, 2x USB 3.1 Gen1, 1x USB 3.1 Type-C Gen1 (15W charging), 1x microphone (3.5mm), 1x headphone / microphone combo jack (3.5mm)

Front ports* (Opt.)
Optional: 1x media reader

Rear ports* (Std.)
4x USB 3.1 Gen1, 1x serial (9-pin), 1x ethernet (RJ-45), 1x VGA, 2x DisplayPort, 1x line-out (3.5mm)

Rear ports* (Opt.)
Optional: 2x USB 2.0, 2x USB 3.1 Gen1 via PCIe x1, 2x USB 3.1 Type-C Gen2 via PCIe x4 (special bid only), 1x 2nd serial (9-pin), 4x serial (9-pin) via PCIe x1, 1x parallel (25-pin), 2x PS/2 ports (keyboard/mouse), 1x Thunderbolt 3 (combo USB3.1 Type-C Gen 2 / DisplayPort) via PCIe x4 (available on 09/30/2018), additional RJ-45 and video ports available on optional graphics or ethernet card
* Depending on many factors, actual data transfer speed may be lower than theoretical speed

Audio support
High Definition (HD) Audio, Realtek ALC233VB2 / internal speaker (2 watt)

WLAN
Some: 11ac Wi-Fi + BT 4.2, M.2 Card, Realtek RTL8821CE (dual band), 1x1
Some: 11ac Wi-Fi + BT 4.2, M.2 Card, Realtek RTL8822BE (dual band), 2x2
Some: 11ac Wi-Fi + BT 4.2, M.2 Card, Intel Dual Band Wireless-AC 3165, 1x1
Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, 2x2
Some: 11ac Wi-Fi + BT 5.0, M.2 Card, Intel Wireless-AC 9560 (dual band), Intel vPro technology support, 2x2

Bluetooth™
Some: Bluetooth 4.2/5.0 wireless, integrated in Wi-Fi + BT combo adapter

Ethernet
Gigabit ethernet, Intel Ethernet Connection I219-LM(Jacksonville), Wake on LAN®

Ethernet (Opt.)
Some: Intel Ethernet Server Adapter I350-T4, gigabit ethernet, 4x RJ-45, PCIe x4
Some: Bitland BN8E88, gigabit ethernet, 1x RJ-45, PCIe x1 (special bid only)

Manageability
Intel Active Management Technology 12 (Intel AMT 12); Intel vPro technology on some models (require choosing a vPro-support Wi-Fi adapter to enable vPro function through wireless connection)

Security chip
Discrete TPM 2.0, TCG Certified

Security features
- Security slot (in rear for optional Kensington® MicroSaver® cable)
- Padlock loop
- Optional cable lock to physically lock both keyboard and mouse
- Optional chassis intrusion switch
- Optional chassis E-Lock (special bid)
- Power-on password
- Administrator password
- Hard disk password
- Boot sequence control
- Boot without keyboard and mouse
- Individual USB port disablement
- Smart USB protection, allows keyboard/mouse only, blocks all storage devices

Keyboard
Some: Lenovo Calliope Keyboard (USB connector), black
Some: Lenovo Traditional Keyboard (USB connector), black
Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black
Some: Lenovo Keyboard (PS/2 connector), black (only available via special bid)

Mouse
Some: Lenovo Calliope Mouse (USB connector), black
Some: Lenovo Fingerprint Mouse (USB connector), Windows Hello support, black
Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black
Some: Lenovo Mouse (PS/2 connector), black (only available via special bid)

Mechanical
- Tower (18L), black color, metal case
- (WxDxH) 6.5" X 12.65" X 16.15"; 165mm X 321.35mm X 410.25mm
- Approx. 15.45 lb (7 kg), weight may vary by configuration
- Toolless cover, disk, optical, extension card removal
- Optional carry handle, dust filter
Bay 1: Slim external ODD bay
Bay 2: 5.25", 1.6" high, external, ODD / optional front access HDD
Bay 3: 3.5", 1" high, internal, HDD/SSD
Bay 4: 3.5", 1" high, internal, HDD/SSD (optional bay, bay comes with disk)
Bay 5: 2.5", internal, HDD/SSD (optional bay)
Notes: M920 Tower supports up to 3 SATA devices (ODD/HDD/SSD) and 1 eSATA device (front access HDD)
Slot 1: full-length (< 268mm) full-height (< 112mm), PCIe 3.0 x16
Slot 2: full-length (< 268mm) full-height (< 112mm), PCIe 3.0 x1
Slot 3: full-length (< 268mm) full-height (< 112mm), PCIe 3.0 x16 (x4 signal)
Slot 4: no slot, only bracket for optional port extension
M.2 card slots: Two (one for WLAN, one for SSD/Optane)

Power supply
Some: 180 watts, autosensing, 85% PSU
Some: 250 watts, autosensing, 85% PSU
Some: 400 watts, autosensing, 92% PSU (only available via special bid)

Limited warranty
Some: **1-year** or **3-year**, **depot service** / service upgrades available
Some: **1-year** or **3-year**, **limited onsite service** / service upgrades available

Preload
Some: Windows® 10 Pro 64-bit
Some: Windows 10 Home 64-bit

Environment
ENERGY STAR® 6.1, EPEAT™ Silver rating (North America), ErP Lot 3, TCO, TUV low noise verified (coming soon, on some models), RoHS-compliant

Accessories
For compatible accessories, please go to **http://smartfind.lenovo.com**

Note: The specifications above may not be available in all regions.

Lenovo, June 2019