

Product datasheet

Specifications



APC NetShelter SX, Server Rack Enclosure, 18U, Shock Packaging, Black, 925H x 600W x 900D mm

AR3006SP

EAN Code: 0731304347668

Overview

Presentation	An industry-standard server rack with height designed to easily fit through standard doorways. Ready for medium to high-density environments.
--------------	---

Main

Product or component type	Rack enclosure
Number of rack unit	18U
Rack width	19"
Permanent permissible load	408.2 kg dynamic 408.2 kg static
Provided equipment	Casters Doors Key(s) Leveling feet Reusable packaging Roof Side panels Pallet ramps

Complementary

mounting mode	Not rack-mountable
Minimum mounting depth	191 mm
Maximum mounting depth	755.7 mm
Colour	Black
Marking	14 gauge EIA mounting rail 16 gauge front door 16 gauge post 18 gauge rear door 18 gauge roof 18 gauge side panels
Height	925 mm
Width	600 mm
Depth	900 mm
Net weight	67.13 kg

Environmental

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------

Packing Units

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	122 cm
Package 1 Width	107 cm
Package 1 Length	75 cm
Package 1 Weight	120 kg

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	60
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	421 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	402 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	10 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	9 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Again



Repack and remanufacture

Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

