

GEFORCE RTX 2080 SUPER SEA **HAWK X**









SPECIFICATION

Model Name	GeForce® RTX 2080 SUPER™ SEA HAWK X
Graphics Processing Unit	NVIDIA® GeForce RTX 2080 SUPER™
Interface	PCI Express x16 3.0
Cores	3072 Units
Core Clocks	Boost: 1845 MHz
Memory Speed	15.5 Gbps
Memory Size	8GB GDDR6
Memory Bus	256-bit
Output	DisplayPort x 3 (v1.4) / HDMI 2.0b x 1 / USB Type-C x1
HDCP Support	2.2
Power consumption	250 W
Power connectors	8-pin x 1, 6-pin x 1
Recommended PSU	650 W
Card Dimension(mm)	Card: 268 x 114 x 41 mm
	Cooler: 154 x 120 x 52 mm
	Tube: 320 x 10.3 mm
Weight (Card / Package)	1370 g / 2355 g
Afterburner OC	Υ
DirectX Version Support	12 API
OpenGL Version Support	4.5
Multi-GPU Technology	NVIDIA® NVLINK™ (SLI-Ready), 2-way
Maximum Displays	5
VR Ready	Y
G-SYNC® technology	Y
Adaptive Vertical Sync	Υ
Digital Maximum	7680 x 4320
Resolution	

CONNECTIONS



- 1. DisplayPort
- 2. HDMI
- 3. USB Type-C

FEATURE



SUPREME LIQUID COOLING PERFORMANCE

The GPU is kept cool by closed loop liquid cooler while the memory and VRM's are cooled by a radial fan.



MICRO-FIN COPPER BASE

The copper coldplate with internal micro-fin design draws heat directly from the GPU into the circulating coolant.



HARNESS MAGNETIC LEVITATION

PWM fan using magnetic levitation technology and custom engineered rotors provide great performance and low noise.



HIGH PERFORMANCE 120MM RADIATOR

The 120mm TORX fan provides both ample cooling area and wide case compatibility.



SOLID BACKPLATE

Increases toughness of the card to prevent bending while complementing the design.



QUICK AND EASY INSTALLATION

Upgrade to the power of liquid-cooled graphics in one minute or less.



MSI Afterburner

The ultimate overclocking software with advanced control options and real-time hardware monitor.