HP HD Pro 2 Scanner

Produce exceptional, high-quality results with HP's high-production HD colour scanner





Grow - Expand your capabilities and opportunities

- Reproduce everything from technical documents to graphics - even damaged originals - with CCD scanning technology.
- Create large-format colour and monochrome scans/copies up to 1067 mm (42 inches) wide, even on thick¹ media.
- Produce incredibly accurate and high-quality scans with 1200 dpi optical resolution.
- Easily share and collaborate scan to HP SmartStream software,² email, USB, network folders, and HDDs.

Accelerate - Speed up production and drive results

- Accomplish more with incredible speeds scan 33 cm (13 inches/sec) in either colour or monochrome.³
- Experience an uninterrupted workflow with • advanced touchscreen controller that enables ultra-fast processing.
- Save time operating and managing your scanner with an intuitive user interface that requires less clicks to final scan
- Be more productive with improved compression options, unlimited presets, multi-page PDFs, and collating.

Optimise – Integrate and secure your workflow

- Enjoy seamless integration with HP PageWide XL and HP DesignJet printers rely on a single support solution.
- Avoid reprints large touchscreen to preview, enhance images post-scan editing with HP SmartStream software.²
- Protect your data with advanced security set up a password to scan to USB and access advanced settings.
- Build a multifunction system⁴ save space with the adjustable stand and easily control output destinations.⁵

For more information, please visit http://www.hp.com/go/designjethdproscanner

Up to 15 mm (0.6 inches) thickness

 ⁶ HP SmartStream is a professional software solution that supports HP PageWide XL printer series and HP DesignJet Production printers.
 ⁸ Monochrome scanning: A1/D image with black text graphics at 200 dpi; colour scanning: A1/D fully-inked colour image at 200 dpi; 24-bit RGB.
 ⁴ Scanner can be placed above printers from the following HP DesignJet printer series: T730/T790/T795/T830/T1300/T1500/T1500/T1500/T5200/Z5200/Z5200/Z5200/Z5600/Z6200/Z6/29+.
 ⁵ Output destinations when copying – such as folders and stackers – are available for HP PageWide XL 3900/4000/4100/4500/5000/5100/6000/8000 printers, HP DesignJet 5100/T1300/T1500/T1500/T1500/T1200/T2500/T2500/T2500/T2500/T2500/T2500/T2500/T7100/T7200/T795/T830/T920/T930/Z2100/Z3200/Z5200/Z5400/Z5600/Z6610/Z6810 printers, and HP printer series Design let XI 3600 printers

HP SmartStream is a professional software solution that supports HP PageWide XL printer series and HP Design let Production printers

Technical specifications

Scan and copy

Scan and copy	
Scan speed	Colour: up to 33 cm/sec Greyscale: up to 33 cm/sec ¹
Resolution	1200 dpi
Technology	CCD scanning technology and LED-based illumination system
Accuracy	0.1% ±1 pixel
Data capture (color/mono)	48-bit/16-bit
Scan format	PDF, PDF/A, TIFF, JPEG, JPEG2000, DWF, CALS (black and white), multi-page PDF generation
Scan destinations	File, email, USB, HDD, network folder, FTP, print
Settings	Type of original, image crop and align preview, lightness, saturation and RGB controls, white point and black point adjust, sharpen/blur, mirror copy, enlarge/reduce, paneling, tiling, nesting, accounting, batch, multipage PDF generation, invert, collate copy with reprint
Maximum scan width	1067 mm
Applications	Digital fine art; Graphics design; Line drawings; Maps; Orthophotos; Photos; Renderings; Presentations
Media	
Handling	Straight-through scan paper path for sheet and cardboard originals, adjustable paper pressure for very thin media. Face-down, front entry, rear exit, rewind to front, use document return guide for front-return. Automatic high adjustment of scanner bridge for thick originals up to 15 mm (0.6 in) thickness.
Types	Non-abrasive paper, vellum, Mylar, sepia, blueprints, plastic, film, plastic laminate, foam board, cardboard, newspaper, tracing paper. Varying condition documents: old, delicate, folded, creased, crumpled, damaged originals (no plywood, stone plates, metal plates or abrasive, dirty, rough, sharp edged, metal clamped, or burned surfaces or transparencies)
Maximum media width	1118 mm
Maximum media thickness	15 mm
Panel PC	
User interface	396 mm (15.6 inch) large touchscreen to preview and enhance images
Embedded operating system	Windows 10
Processor	Intel Core i7
Memory	4 GB
Hard disk	500 GB
Connectivity	
Interfaces	Dual Gigabit Ethernet (1000Base-T), SuperSpeed USB 3.0
	Nieder de la constant la UD De settier de UD De settement de Désenver
Drivers	Windows drivers for compatible HP PageWide XL and HP DesignJet Printers
Drivers Dimensions (w x d x h)	windows drivers for compatible HP Pagewide XL and HP Designuet Printers
	1530 x 930 x 1660 mm
Dimensions (w x d x h)	
Dimensions (w x d x h) Scanner Shipping	1530 x 930 x 1660 mm
Dimensions (w x d x h) Scanner Shipping Weight	1530 x 930 x 1660 mm 1910 x 680 x 800 mm
Dimensions (w x d x h) Scanner	1530 x 930 x 1660 mm
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster,
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster,
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature Operating humidity	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords 5 to 35°C
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature Operating humidity Storage temperature	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords 5 to 35°C 20 to 80% RH
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature Operating temperature Operating humidity Storage temperature Acoustics	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords 5 to 35°C 20 to 80% RH -25 to 55°C
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature Operating temperature Acoustics Sound pressure	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords 5 to 35°C 20 to 80% RH
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature Operating temperature Operating temperature Acoustics Sound pressure Sound power	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords 5 to 35°C 20 to 80% RH -25 to 55°C 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep)
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature Operating temperature Operating temperature Acoustics Sound pressure Sound power Power	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords 5 to 35%C 20 to 80% RH -25 to 55%C 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep)
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature Operating temperature Operating temperature Acoustics Sound pressure Sound pressure Sound power Power Consumption	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords 5 to 35%C 20 to 80% RH -25 to 55%C 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep) 130 W (scanning), 39 W (ready), < 1 W (sleep)
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature Operating temperature Operating temperature Storage temperature Acoustics Sound pressure Sound pressure Sound power Power Consumption Requirements	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords 5 to 35%C 20 to 80% RH -25 to 55%C 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep)
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature Operating humidity Storage temperature Acoustics Sound pressure Sound pressure Sound power Power Consumption Requirements Certification	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords 5 to 35°C 20 to 80% RH -25 to 55°C 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep)
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature Operating temperature Operating humidity Storage temperature Acoustics Sound pressure Sound pressure Sound power Power Consumption Requirements Certification Safety	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords 5 to 35°C 20 to 80% RH -25 to 55°C 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep) 6.4 B(A) (operating), <3.9 B(A) (idle), <3.9 B(A) (sleep) 130 W (scanning), 39 W (ready), <1 W (sleep) Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz, 5 A max EU: LVD and EN 60950-1 compliant; Russia: EAC
Dimensions (w x d x h) Scanner Shipping Weight Scanner Shipping What's in the box Environmental ranges Operating temperature Operating humidity Storage temperature Acoustics Sound pressure Sound pressure Sound power Power Consumption Requirements Certification	1530 x 930 x 1660 mm 1910 x 680 x 800 mm 71 kg 118 kg HP HD Pro 2 42-in Scanner, stand, touchscreen (panel PC), quick reference guide, media guides, setup poster, copy/scan software, documentation software, Ethernet cable, USB cable, power cords 5 to 35°C 20 to 80% RH -25 to 55°C 48 dB(A) (operating), <22 dB(A) (idle), <22 dB(A) (sleep)

Ordering information

5EK00A	HP HD Pro 2 42-in Scanner
Accessories	
P7V13A	HP Pro Scanner Output Delivery Tray
Service and S	upport
U4PS6E HP 5 U4PS7PE HP 1 U4PS8PE HP 2 U1XV4E HP Pr HP Support Se	ear Next Business Day Onsite Support with Defective Media Retention ear Next Business Day Onsite Support with Defective Media Retention year Post Warranty Onsite Support with Defective Media Retention year Post Warranty Onsite Support with Defective Media Retention eventive Maintenance Service vices offer installation and extended support services (e.g. 2, 3, 4, and 5 years) mation, please visit http://www.hp.com/go/cpc
Supported pr	nters
HP Designet HP Designet	790 Printer series 795 Printer 1300 PostScript® Printer 1500 Printer series 1530 Printer series

ECO highlights

 ENERGY STAR[®] qualified and EPEAT registered.¹
$\label{eq:period} Please recycle large-format printing hardware and printing supplies. Find out how at our website: http://www.hp.com/ecosolutions$
1 EPEAT registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
¹ Colour scanning: A1/D fully-inked colour image at 200 dpi, 24-bit RGB. Monochrome scanning: A1/D image with black text graphics at 200 dpi.



