

Philips Signage Solutions D-Line Display

43" Powered by Android 450cd/m²

SignageSolutions



43BDL4051D

Say more

Smart, fast 24/7 display.

Make it stand out with a faster Philips D-Line Professional display. With Philips superb picture quality and Android SOC more powerful than ever before, capable of delivering complex content to capture your audience's attention. Specificall

Superb picture. Blazing processor speed.

- Android 7. Dedicated Android processor
- Proof of Play for Android content. Know what's playing
- Integrated dual-band WiFi
- Effortless setup. Total control.
- CMND & Control. Operate, monitor, maintain
- CMND & Create. Develop and launch your own content
- · CMND & Deploy. Install and launch apps remotely
- Integrated mPCIe slot for optional 4G/LTE module

Cost-effective system solution

- FailOver. Ensure your display never goes blank
- Integrated HTML5 browser. Play and control online content

PHILIPS

· Energy-saving automatic backlight control

Control your Philips professional display via an internet connection. The integrated Android OS (SoC) lets you install web and native Android apps directly to the display. A built-in scheduler makes it easy to launch apps and content based on time of day, or user. Autoorientation ensures your content displays properly.

CMND & Control



Run your display network over a local (LAN) connection. CMND & Control allows you to perform vital functions like controlling inputs and monitoring display status. Whether you're in charge of one screen or 100.

CMND & Create

Take control of your content with CMND & Create. A drag-and-drop interface makes it simple to publish your own content-whether it's a daily specials board or branded corporate information. Preloaded templates and integrated widgets ensure your stills, text, and video will be up and running in no time.

CMND & Deploy

Quickly install and launch any app-even when you're off-site and working remotely. CMND & Deploy lets you add and update your own apps, as well as apps from the Philips Professional Display App Store. Simply scan the QR code, log in to the store, and click on the app you want to install. The app is automatically downloaded and launched.

Integrated mPCIe slot

Easily connect 4G/LTE modules to your Philips professional display. The integrated mPCle slot

enables your display to communicate with other devices that share the same wireless connectivity. Invaluable if you're installing displays in locations such as banks or government buildings, where you cannot get onto the local network.

FailOver



From waiting room to meeting room, never show a blank screen. FailOver lets your Philips Professional Display switch automatically between primary and secondary inputs ensuring content keeps playing even if the primary source goes down. Simply set a list of alternate inputs to be sure your business is always on.

Specifications

Picture/Display

- Diagonal screen size: 42.5 inch / 108.0 cm
- Panel resolution: 1920x1080p
- Optimum resolution: 1920 x 1080 @ 60Hz
- Brightness: 450 cd/m²
- Contrast ratio (typical): 1100:1
- Dynamic contrast ratio: 500,000:1
- Aspect ratio: 16:9
- Response time (typical): 12 ms
- Pixel pitch: 0.4902 x 0.4902 mm
- Display colors: 16.7 million
- Viewing angle (H / V): 178 / 178 degree • Picture enhancement: 3/2 - 2/2 motion pull down, 3D Combfilter, Motion compens. deinterlacing, 3D MA deinterlacing, Progressive scan
- Operating system: Android 7.1.2
- Panel technology: IPS
- Placement: Landscape, Portrait

Connectivity


- Video input: Display Port1.2x1, DVI-I x 1, HDMI (x2)
- Video output: DisplayPort1.2x1, DVI-I x1
- · Audio input: 3.5 mm jack
- Audio output: 3.5mm jack
- External control: RJ45, RS232C (in/out) 2.5 mm jack, IR (in/out) 3.5 mm jack
- Other connections: micro USB, USB 3.0, USB 2.0, micro SD

Supported Display Resolution

	\sim			c .
•	0.01	ווסמ	ter	torn

Computer formats				
Resolution	Refresh rate			
1920 x 1200	60Hz			
1920 x 1080	60Hz			
1680 x 1050	60Hz			
1600 x 900	60Hz			
1600 x 1200	60Hz			
1400 x 1050	60, 75Hz			
1440 x 1050	60Hz			
1440 x 900	60, 75Hz			
1280 x 768	60Hz, 75Hz			
1360 x 768	60Hz			
1280x1024	60,67,75Hz			
1366 x 768	60Hz			
1152 x 900	66Hz			
1280 x 720	60,70Hz			
1280 x 800	60,75Hz			
1280 x 960	60Hz			

Philips 43BDL4051D Version: 1.0 Release Date: 2018/09/17



5



DHIIDQ

Version: 1.0.1

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V.

12 NC: 8670 001 56725 EAN: 87 12581 75386 3

www.philips.com

or their respective owners.

- Humidity range (operation)[RH]: 10 ~ 80% (without condensation)
- Humidity range (storage) [RH]: 0 ~ 90% (without condensation)

Sound

Built-in speakers: 2 x 10W RMS

Accessories

- Included accessories: Remote Control, Batteries for remote control, Quick start guide, RS232 cable, AC Power Cord
- Stand: Universal Stand-L (BM05922)(Optional)
- Included Accessories: Edge Alignment Kit (1)-2pcs, Edge Alignment Kit (2)-1pcs, M2 Screw x2, M3 screw x 1, Philips logo, RS232 daisy-chain cable, SD card cover x 1, Thumb Screw x8

Multimedia Applications

- USB Playback Audio: AAC, M4A, MP3, WMA
- USB Playback Picture: BMP, JPEG, JPG, PNG
- USB Playback Video: MKV, MP4, MPEG, MPG, TS, VOB, WMV, ASF, AVI, DAT, FLV

Miscellaneous

- On-Screen Display Languages: English, French, German, Spanish, Polish, Turkish, Russian, Italian, Simplified Chinese, Traditional Chinese, Arabic, Japanese, Danish, Dutch, Finnish, Norwegian, Portuguese, Swedish
- Regulatory approvals: CE, BSMI, CB, EAC, EnergyStar 7.0, FCC, Class A, PSB, UL/cUL, CECP, EPA
- Warranty: 3 year warranty

Internal Player

- CPU: Dual-Core Cortex-A72 @2GHz, Quad-Core Cortex-A53 @ 1.5GHz, RK3399
- GPU: ARM Mali-T860 MP4
- Memory: 4GB DDR3
- Storage: 16GB EMMC
- Wifi: 2T2R, 802.11 ac/a/b/g/n, WCT07R2201

Issue date 2019-10-04 © 2019 Koninklijke Philips N.V. All Rights reserved.

 1152×864

1024x768

960x720

848 x 480

832 x 624

800 x 600

720 × 400

640 × 480

640 x 350

Resolution

1080p

1080i

720p

576i 576p

480p

480i

Dimensions

Convenience

DVI, RS232

Power

• Picture in picture: PIP

• Set dimensions (W x H x D):

Set dimensions in inch (W x H x D):

• Bezel width: 9.6 mm (T/L/R), 15.7 mm (B)

Signal Loop Through: IR Loopthrough, DisplayPort,

965.0 x 559.3 x 45.5 mm

37.99 x 22.02 x 1.79 inch

• Product weight (lb): 22.95 lb

• Tiled Matrix: Up to 15 x 15 • Keyboard control: Hidden, Lockable

• VESA Mount: 400 x 400 mm, M6

• Network controllable: RJ45, RS232

· Screen saving functions: Pixel Shift

Standby power consumption: <0.5 W
Mains power: AC (100 ~ 240 V) , 2.5A

• Consumption (On mode): 120W (max)

- Temperature range (operation): 0 ~ 40 $^\circ\text{C}$ • Temperature range (storage): -10 ~ 50 °C

• Consumption (Typical): 70 W

Operating conditions

• Altitude: 0 ~ 3000 m • MTBF: 50,000 hour(s)

• Product weight: 10.41 kg

Video formats

60.70.75Hz

56, 60, 72, 75Hz

60, 67, 72, 75Hz

60.70Hz

75Hz

60Hz

75Hz

70Hz

70Hz

Refresh rate

50, 60Hz

50, 60Hz

50, 60Hz

50Hz

50Hz

60Hz

60Hz

