

4-Port USB3.0 4K DisplayPort Triple Display KVMP™ Switch CS1964

The ATEN CS1964 optimizes your desktop organization to help you effortlessly manage a triple-display multimedia workstation. The CS1964 provides instant, user-friendly access to four computers via a single USB keyboard, USB mouse and three HDMI monitors. By daisy-chaining two CS1964 for six displays, you can multitask smoothly to increase productivity and improve workflow.

The CS1964 is equipped with patented ATEN technology – Video DynaSync[™] – which optimizes display resolution, speeds up switching between systems, and ensures that windows opened on an extended desktop will not revert to their default configurations on the main display when switching between ports, providing a smooth and uninterrupted user experience. What's more, the CS1964 supports the most superior video quality up to 4K DCI (4096 x 2160 @ 60Hz). In addition, the CS1964 delivers data transfer rates up to 5 Gbps with a built-in USB 3.1 Gen 1 hub, allowing you to accelerate multimedia operations with ease, and equipped with N-key Rollover, offering support for up to 15 simultaneous keystrokes that avoids ghosting or jamming.

Integrating all these advanced functionalities, the CS1964 provides a unique advantage for users who need to operate multiple systems and perform multiple tasks across a triple-display extended desktop. The CS1964 especially benefits those doing financial trading, CGI work, graphic design, control center, call center, video post production, gaming applications, and more.



Features

- One USB keyboard/mouse and three HDMI monitors control four DisplayPort computers
- Supports superior video quality up to 4K DCI (4096 x 2160 @ 60Hz)
- DisplayPort 1.2 compliant, HDMI 2.0 compliant, HDCP 2.2 compliant
 Computer selection via pushbuttons, hotkeys, mouse¹, and RS-232 Commands²
- Supports N-key Rollover³ (NKRO) permits collision-free keying
- Video DynaSync[™] an exclusive ATEN technology that optimizes display resolution, speeds up switching between systems, and ensures that windows opened on an extended desktop will not revert to their default configurations on the main display when switching between ports
- Supports six displays by connecting two triple display KVM switches
- Built-in 2-Port USB 3.1 Gen 1 hub with SuperSpeed 5 Gbps data transfer rates
- Supports Console keyboard emulation/bypass feature
 Supports Console meuse emulation/bypass feature
- Supports Console mouse emulation/bypass feature
 Independent switching of KVM, USB peripheral, and audio focus⁴
- Supports HD Audio⁴
- Firmware upgradable
- **Note:** 1. Mouse port switching is only supported under mouse emulation mode and by USB 3-key wheel mice.
 - 2. Slide the DCC switch to the s position to allow the KVM switch to receive RS-232 commands via an RI-45-to-DB9 cable.
 - Please refer to the CS1964 RS-232 Commands document. 3. N-key Rollover supports up to 15 simultaneous keystrokes.
 - Here's nonover supports up to 15 simulatious keystokes.
 HD audio through DisplayPort-HDMI cannot be switched independently.

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com



Specifications

Function	CS1964
Computer Connections	4
Port Selection	Pushbutton, Hotkey, RS-232 Commands, Mouse
Connectors	
Console Ports	2 x USB Type A Female
	3 x HDMI Female (Black)
	2 x 3.5mm Audio Jack Female (Green; 1 x front, 1 x rear)
	2 x 3.5mm Audio Jack Female (Pink; 1 x front, 1 x rear)
KVM (Computer) Ports	4 x USB 3.1 Gen1 Type B Female (Blue)
	12 x DisplayPort Female (Black)
	4 x 3.5mm Audio Jack Female (Green)
	4 x 3.5mm Audio Jack Female (Pink)
Daisy Chain Ports	1 x RJ-45 Female
Power	1 x DC Jack
USB Hub	2 x USB 3.1 Gen1 Type A Female (Blue; 1 x front; 1 x rear)
Switches	
Selected	5 x Pushbutton
Station Selection	1 x Slide Switch
Emulation	
Keyboard / Mouse	USB
Video	4096 x 2160 @ 60Hz
Scan Interval	1-99 seconds (default: 5 seconds)
Power Consumption	DC 12V: 15.49W: 115BTU
Environmental	
Operating Temperature	0–50°C
Storage Temperature	-20-60°C
Humidity	0-80% RH, Non-condensing
Physical Properties	
Housing	Metal
Weight	1.93 kg
Dimensions (L x W x H)	33.50 x 15.60 x 6.55 cm

Product information is subject to change without prior notice.



Publish Date: 10/2020 V2.0

© Copyright 2020 ATEN[®] International Co., Ltd. ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd All rights reserved. All other trademarks are the property of their respective owners.