

Test Certificate

Lenovo (Beijing) Co., Ltd.

According to MIL 810G Test for ThinkPad, the Lenovo product *ThinkPad E495* has been tested based on test items and corresponding conditions of the following table, and the test results met the standard requirements. Hereby Certify!

MIL-810G	Title	Procedure	Item	Test Condition	EUT Condition	Result
500.5	Low Pressure (Altitude)	Procedure I (Storage)	(1)	15,000 feet for 1 hour 57.2kPa or 8.3 psia	Power Off	PASS
		Procedure II (Operation)	(2)	15,000 feet for 1 hour 57.2kPa or 8.3 psia	Power On	PASS
501.5	High Temperature	Procedure I (Storage)	(3)	63C 4 hours (Basic Hot)	Power Off	PASS
		Procedure II (Operation)	(4)	43C 2 hours (Basic Hot)	Power On	PASS
502.5	Low Temperature	Procedure I (Storage)	(5)	-25C 24 hours (Basic Cold)	Power Off	PASS
		Procedure II (Operation)	(6)	-21C 2 hours (Basic Cold)	Power On	PASS
503.5	Temperature Shock	Procedure I-A	(7)	One-way shock -25C to 60C 4hours	Power Off	PASS
		Procedure I-B	(8)	Single cycle shock -25C to 60C to -25C 6hours	Power Off	PASS
505.5	Solar Radiation	Procedure I Cycling	(9)	Three 24-hour cycles of controlled simulated solar radiation	Power Off	PASS (Certificated by 3 rd Party)
		Procedure II Steady State	(10)	Four 24-hour cycles, 505.5-2	Power Off	PASS (Certificated by 3 rd Party)
507.5	Humidity	Procedure II Aggravated Cycle	(11)	95%RH 30C-60C 24hours x 10cycles	Power Off	PASS
508.6	Fungus	Procedure	(12)	28 days exposure	Power Off	PASS (Certificated by 3 rd Party)
510.5	Sand and Dust	Procedure I Blowing Dust	(13)	140 mesh silica, 10 g/m³: 8.9 m/s 12 hours 25C for 6 hours and 35C for 6 hours	Power Off/On	PASS (Certificated by 3 rd Party)
		Procedure II Blowing Sand	(14)	Silica sand (at least 95% by weight SiO2) 0.18 g/m³, 18m/s 90 min x 2 direction	Power Off	PASS (Certificated by 3 rd Party)
511.5	Explosive Atmosphere	Procedure I Explosive Atmosphere	(15)	Operated in a fuel vapor environment	Power On	PASS (Certificated by 3 rd Party)
514.6	Vibration	514.6E-1 Category 24 General	(16)	Fig 514.6E-1 General min integrity exposure 1 hour/axis x 3 axis	Power Off	PASS
		514.6C-1 Category 4 Common carrier	(17)	Table 514.6C-1 Common Carrier 1 hour in all 3 axis	Power On	PASS
516.6	Shock	Procedure I Functional Shock	(18)	Table 516.6-II Terminal peak sawtooth pulse	Power On	PASS
		Procedure IV Transit drop	(19)	122cm Drop on each face, edge and corner	Power Off	PASS
		Procedure V Crash Hazard Shock	(20)	75G/6ms , 12 shocks	Power Off	PASS
		Procedure VI Bench Handling	(21)	100mm height edge drop 4 drops on top and bottom	Power Off	PASS
528	Vibrations of Shipboard	Procedure I (Type I)	(22)	4 to 33 Hz , 2 hours	Power On	PASS

Hefei LCFC Information Technology Co., Ltd.

Nov 29th, 2019

The validity of the certificate is only for the samples tested, and the declaration of conformity of the certificate is based on the test data and results of the reference test report.

The final interpretation right of the certificate belongs to Hefei LCFC Information Technology Co., Ltd., which is used by Lenovo Group in China.