
Samsung SMART Signage QM32R

Highlights

- New symmetrical, slim design simplifies installation and complements any environment
- Affordable digital signage that supports 24/7 operation and 400nit brightness
- All-in-one display solution with embedded MagicINFO Player
 S6 powered by TIZEN™
- Secure, PC-free operation through Knox and rigid threelayer protection




Slim and symmetrical design



The all-new slim and symmetrical design of the QM32R significantly simplifies wall mounting the display and ensures installation is a seamless process. The display's power inlet direction has been redesigned to sit flush against the wall. The new design sets guarantees a long life cycle ensuring the QM32R will stand the test of time.

Attract customers with optimized 24/7 performance



Engage customers and vividly display business messaging with affordable Samsung SMART Signage QM32R, featuring high picture quality with 400nit brightness and reliable 24/7 usage. QM32R displays stunningly present a range of immersive and timely information with captivating picture quality.

Powerful, all-in-one solution



The Samsung SMART Signage Platform (SSSP) is an open-source, all-in-one solution embedded in Samsung SMART signage that simplifies installation and maintenance. With SSSP, there is no need for any external devices to communicate with the server or play digital media enjoying easy development, reinforced capability with multiple web formats, and secured protection.

Samsung Workspace secured by Knox



Samsung Workspace is a powerful new feature fortified by proprietary Knox security technology allowing users to create an enhanced virtual collaboration workspace without needing a PC in the room, or any physical connection. Simply connect a keyboard and mouse to the display and immediately get to work accessing a PC remotely or web-based cloud services such as Microsoft Office 365 and VMWare Horizon.

Wi-Fi and Bluetooth built-in



The QM32R features a nearly endless range of business use-cases thanks to built-in Wi-Fi and Bluetooth. Wireless connectivity allows for personalized and interactive services including enabling integration with beacon technology in store, while also simplifying how businesses showcase content.

Clean cable management



In a corporate or retail environment, the back of a display is often visible to customers. With the QM32R's new cable guide feature retailers can tuck messy cables away from view. This allows for a clean and more visually-appealing customer shopping experience.

Specifications

	Model		QM32R
	Diament C:	Class	32
	Diagonal Size	Measured	31.5
Panel	Туре		Edge LED BLU
	Resolution		FHD (1920 x 1080)
	Pixel Pitch (mm)		0.360(H) x0.360(V)
	Active Display Area		698.4(H) x 392.85(V)
			400
	Brightness(Typ.)		
	Contrast Ratio (Typ.)		5000:1
	Viewing Angle(H/V)		178/178
	Response Time (G to G)		8ms(Typ.)
	Display Colors		16.7M(True Display), 1.07B(Ditherd 10bit)
	Color Gamut		72%
	Operation Hour		24/7
	Haze		2%
Display	Dynamic C/R		MEGA
	H-Scanning Frequency		30 ~ 81kHZ
	V-Scanning Frequency		48 ~ 75HZ
	Maximum Pixel Frequency		594MHz
Sound	Speaker Type		Built in Speaker(10W + 10W)
		RGB	Display Port 1.2 (1)
		VIDEO	HDMI 2.0 (1)
	INPUT	HDCP	HDCP2.2
		AUDIO	Stereo mini Jack, HDMI
		USB	USB 2.0 x 2
		RGB	HDMI 2.0 (Loop-out)
Connectivity		VIDEO	N/A
	OUTPUT	AUDIO	Stereo mini Jack
	EXTERNAL CONTR	Power Out	N/A
		USB	N/A
			RS232C(in/out) thru stereo jack, RJ45
	EXTERNAL CONTROL EXTERNAL SENSOR		IR
	Tuner		N/A
	Type		Internal
	Power Supply	May/W/h3	AC 100 - 240 V~ (+/-10 %), 50/60 Hz
		Max[W/h]	72
Power		Typical[W/h]	44
	Power	Rating[W/h]	65
	Consumption	BTU(Max)	245.5
		Sleep mode	0.5
		Off mode	N/A
	Dimension(mm)	Set	725.1 x 419.6 x 34.6
	Dimension(min)	Package	812 x 513 x 120
	Weight (kg)	Set	5.7
Mechanical Spec	Weight (kg)	Package	8
Mechanical Spec	VESA Mount		200 X 200
	Protection Glass		N/A
	Stand Type		Foot Stand (Optional)
	Bezel Width (Top/Side/Bot) (mm)		8.8mm(U/L/R/B)
	Operating Tempera	ature	0°C~40°C
Operation			
Operation	Humidity		10~80%
Operation			10~80% FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0
Operation	Humidity	H/W	
Operation	Humidity	H/W	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), Video Wall Daisy Chain(HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT
Operation	Humidity Key	S/W	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), Video Wall Daisy Chain(HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)
Operation	Humidity Key	S/W Processor	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug & Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU
Operation	Humidity Key	S/W Processor On-Chip Cache Memory	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), Video Wall Daisy Chain(HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting)
	Humidity Key	S/W Processor On-Chip Cache Memory Clock Speed	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug & Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU
Operation	Humidity Key Special	S/W Processor On-Chip Cache Memory	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor,Pivot Display, Clock Battery(168hrs Clock Keeping), Built in Speaker(10W 2ch), Video Wall Daisy Chain(HDCP2.2:4EA,HDCP1.4:7EA), IPSx Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 3ZKB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit
	Humidity Key Special	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit Graphic resolution : 1920x1080
	Humidity Key Special	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A721.7GHz Quad-Core CPU L1 Instruction Cache: 48KB, L1 Data Cache: 32KB, L2 Cache: 2MB 1.7GHz 2.5GB, LPDDR41.5GHz 64bit Graphic resolution: 1920x1080 Output resolution: 3840x2160 (Scale up from graphic processing result.)
	Humidity Key Special	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM)	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IPSx Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available)
	Humidity Key Special	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IPSx Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG
	Humidity Key Special	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72.1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8BG (3.88GB Occupied by O/S, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG USB 2.0
	Humidity Key Special Internal Player (Embedded H/W)	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux)
	Humidity Key Special Internal Player (Embedded H/W)	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVF, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) 60950-1
Feature	Humidity Key Special Internal Player (Embedded H/W)	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux)
	Humidity Key Special Internal Player (Embedded H/W)	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVF, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) 60950-1
Feature	Humidity Key Special Internal Player (Embedded H/W) Safety EMC	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home Ul, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A721.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR41.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) 60950-1 Class B
Feature	Humidity Key Special Internal Player (Embedded H/W) Safety EMC Environment	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IPSx Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home Ul, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A721.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) 60950-1 Class B N/A
Feature	Humidity Key Special Internal Player (Embedded H/W) Safety EMC Environment Security	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72.1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8BG (3.88GB Occupied by O/5, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AV5+, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) 60950-1 Class B N/A 802.1x(WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP
Feature	Humidity Key Special Internal Player (Embedded H/W) Safety EMC Environment Security Included	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports Operating System	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR41.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) 60950-1 Class B N/A 802.1x(WPA2 Enterprise) : EAP-TLS, EAP-PEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries STN-L3240E
Feature Certification	Humidity Key Special Internal Player (Embedded H/W) Safety EMC Environment Security	S/W Processor On-Chip Cache Memory Clock Speed Main Memory Interface Graphics Storage (FDM) Multimedia IO Ports Operating System	FHD Signage Display, Slim & Light Signage with Built-in MagicInfo S6, SSSP 6.0 Temperature Sensor, Pivot Display, Clock Battery (168hrs Clock Keeping), Built in Speaker (10W 2ch), Video Wall Daisy Chain (HDCP2.2:4EA,HDCP1.4:7EA), IP5x Rating, Wi-Fi/BT Auto Source Switching & Recovery, LFD Home UI, Button Lock, Hot key option, Plug&Play (Initial Setting) Cortex A72 1.7GHz Quad-Core CPU L1 Instruction Cache : 48KB, L1 Data Cache : 32KB, L2 Cache : 2MB 1.7GHz 2.5GB, LPDDR4 1.5GHz 64bit Graphic resolution : 1920x1080 Output resolution : 3840x2160 (Scale up from graphic processing result.) 8GB (3.88GB Occupied by O/S, 4.12GB Available) *Video Decoder : MPEG-1/2/4, H.263, H.264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9, *Audio Decoder : AC3 (DD), MPEG USB 2.0 Tizen 4.0 (VDLinux) 60950-1 Class B N/A 802.1x(WPA2 Enterprise) : EAP-TLS, EAP-TTLS, EAP-PEAP Quick Setup Guide, Warranty Card, Power Cord, Remote Controller, Batteries

About Samsung Electronics Co., Ltd.

Samsung Electronics Co., Ltd. inspires the world and shapes the future with transformative ideas and technologies. The company is redefining the worlds of TVs, smartphones, wearable devices, tablets, cameras, digital appliances, medical equipment, network systems, and semiconductor and LED solutions. For the latest news, please visit the Samsung Newsroom at news.samsung.com.

SMART Signage

 $For more information about Samsung SMART Signage \ QB13R, QB13R-T Series \ Displays, visit www.samsung.com/business \ or www.samsung.com/displaysolutions$

Copyright © 2020 Samsung Electronics Co. Ltd. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co. Ltd. Specifications and designs are subject to change without notice. Non-metric weights and measurements are approximate. All data were deemed correct at time of creation. Samsung is not liable for errors or omissions. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognized and acknowledged.

Samsung Electronics Co., Ltd.

416, Maetan 3-dong, Yeongtong-gu, Suwon-si, Gyeonggi-do 443-772, Korea

