# Product datasheet

Specifications



## APC NetShelter SX, Networking Rack Enclosure, 42U, Black, 1991H x 750W x 1200D mm

AR3340

Discontinued on: 31 Dec 2025

To be discontinued

**EAN Code: 0731304284963**

## Overview

| | |
|---|---|
| **Presentation** | NetShelter SX Networking Enclosure expands Schneider Electric's superior IT enclosure line with improved support for high density networking applications. Integrated high density cable managers and improved cable access roof provide support for large cable bundles. When combined with the Side Airflow Duct Kit, the Networking Enclosure ensures complete isolation of cold intake and hot exhaust air for large switches and SAN directors. |

## Main

| | |
|---|---|
| **Product or component type** | Rack enclosure |
| **Number of rack unit** | 42U |
| **Rack width** | 19" |
| **Permanent permissible load** | 1020.6 kg dynamic<br>1701.0 kg static |
| **Provided equipment** | Baying hardware<br>Key(s)<br>Keyed-alike doors and side panels<br>Leveling feet<br>Mounting hardware<br>Pre-installed casters<br>Side panels<br>Vertical cable managers |

## Complementary

| | |
|---|---|
| **Mounting mode** | Not rack-mountable |
| **Minimum mounting depth** | 279.4 mm |
| **Maximum mounting depth** | 958.9 mm |
| **Colour** | Black |
| **Marking** | 14 gauge EIA mounting rail<br>16 gauge front door<br>16 gauge post<br>16 gauge rear door<br>18 gauge roof<br>18 gauge side panels |
| **Height** | 1991 mm |
| **Width** | 750 mm |
| **Depth** | 1200 mm |
| **Net weight** | 161.36 kg |

## Environmental

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|---|---|
| **Standards** | UL 2416<br>UL 60950-1<br>EIA-310E |

## Packing Units

| | |
|---|---|
| **Unit Type of Package 1** | PCE |
| **Number of Units in Package 1** | 1 |
| **Package 1 Height** | 211.8 cm |
| **Package 1 Width** | 132.08 cm |
| **Package 1 Length** | 85.09 cm |
| **Package 1 Weight** | 183.18 kg |

## Logistical informations

| | |
|---|---|
| **Country of origin** | CN |

## Contractual warranty

| | |
|---|---|
| **Warranty (in months)** | 60 |

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

### Environmental footprint

| | |
|---|---|
| Total lifecycle Carbon footprint | **643 kg CO2 eq.** |
| Carbon footprint of the manufacturing phase [A1 to A3] | **614 kg CO2 eq.** |
| Carbon footprint of the distribution phase [A4] | **16 kg CO2 eq.** |
| Carbon footprint of the installation phase [A5] | **0 kg CO2 eq.** |
| Carbon footprint of the use phase [B2, B3, B4, B6] | **0 kg CO2 eq.** |
| Carbon footprint of the end-of-life phase [C1 to C4] | **14 kg CO2 eq.** |
| Environmental Disclosure | Product Environmental Profile |

## Use Better

### Materials and Substances

| | |
|---|---|
| Packaging made with recycled cardboard | **No** |
| Packaging without single use plastic | **No** |
| EU RoHS Directive | Compliant |
| REACh Regulation | Free of Substances of Very High Concern above the threshold |

## Use Again

### Repack and remanufacture

| | |
|---|---|
| Recyclability potential, in % | **95** |
| End of life manual availability | **No need of specific recycling operations** |
| Take-back | **No** |
| WEEE Label | **The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins** |

Image of product / Alternate images

**Alternative**





























