





- $\sqrt{\mbox{ CircoTherm}^{\mbox{\scriptsize @}}}$ our smart hot-air solution for simultaneous baking and roasting on up to four levels
- $\sqrt{\,}$ Dual cleaning options: Pyrolytic cleaning programmes just let the oven interior clean itself. EasyClean - the quick and easy option for day to day maintenance.
- $\sqrt{\ }$ Shift Control fast navigation through menus and simple operation with the TFT display.
- $\sqrt{}$ Home Connect rediscover your kitchen with our connected home appliances, from wherever you are.
- $\sqrt{}$ Baking and Roasting Assistant your helper in the kitchen for ideal cooking times, temperatures, and modes for many dishes at your fingertips























Features

Technical Data

Color / Material Front : Stainless steel

Construction type: Built-in

Integrated Cleaning system: Hydrolytic, Pyrolytic

Required niche size for installation (HxWxD): 450-455 x 560-568 x

Dimensions of the product (mm): $455 \times 596 \times 548$

Dimensions of the packed product (HxWxD) (mm) : $520 \times 690 \times 650$

Control Panel Material : Stainless steel

Door Material : Glass Net weight (kg): 31.256 Usable volume of cavity (I): 47

Cooking method : Bottom heat, Bread Baking Setting, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air-Eco, Hot air grilling, low temperature cooking, Pizza setting

Oven control: electronic Number of interior lights: 1 Approval certificates: CE, VDE

Length of electrical supply cord (cm): 150

EAN code: 4242004236511 Number of cavities (2010/30/EC): 1 Energy efficiency class (2010/30/EC) : A+

Energy consumption per cycle conventional (2010/30/EC): 0.73 Energy consumption per cycle forced air convection (2010/30/EC) :

Energy efficiency index (2010/30/EC): 81.3

Connection rating (W): 2990

Current (A): 13 Voltage (V): 220-240 Frequency (Hz): 50; 60 Plug type: no plug



Z11AB15A0: Baking tray, non-stick ceramic coated, Z11CR10X0: Baking and roasting grid (standard), Z11GT10X3: Glass roasting dish, 5,4l, Z11GU20X0: Glasspan, Z11SZ00X0: SeamlessCombination mounting kit, Z11SZ60X0 : SeamlessCombination 45 + 14cm , Z11SZ90X0 SeamlessCombination 60 + 45cm , Z11TC10X0 : ComfortFlex Rail (1 level), Z11TC14X0: ComfortFlex Rail (1 level), Z12CB10A0: Baking tray, anthracite enamelled, Z12CM10A0: Moussaka pan, anthracite enamelled, Z12CP10A0: Pizza pan, anthracite enamelled, Z12CQ10A0: Grill tray, anthracite enamelled, Z13CV05S0: Cover Strip, Z13CV06S0: Decor strip, Z18C60X0: Cookbook, Z1913X0: Baking Stone , Z19DD10X0 : Steam set for ovens

N 90, Built-in compact oven, Stainless steel C27CS22H0B

Features

Design

- 4.1" TFT colour and graphics display with ShiftControl
- Enamel anthracite
- Drop down door, SoftClose, soft opening
- Illuminated Shift Control
- Bar handle
- We recommend you to choose complementary products within N90, in order to assure an optimal design combination of your Built-In appliances.

Features

- HomeConnect ready on WLAN
- Control panel lock Automatic safety switch off Residual heat indicator Start button Door contact switch
- Temperature proposal Actual temperature display Heating up indicator Sabbath setting
- Baking and roasting assistant
- Interior halogen light, On/off button
- Cooling fan
- Electronic clock timer
- 3 shelf positions

Cleaning

- Pyrolytic cleaning
- EasyClean
- Full glass inner door

Programmes/functions

- Compact oven with 13 main functions heating methods: CircoTherm®, CircoTherm® Gentle, Top/bottom heat, Conventional heat Gentle, Circo-roasting, Full surface grill, Centre surface grill, CircoTherm® intensive, Bread baking, Bottom heat, Low temperature cooking, Defrost, Dough proving
- Rapid heat

Accessories

• 1 x combination grid, 1 x universal pan

Performance/technical information

• Energy efficiency rating (acc. EU Nr. 65/2014): A+ Energy consumption per cycle in conventional mode: 0.73 kWh Energy consumption per cycle in fan-forced convection mode: 0.61 kWh

Number of cavities: Main cavity Heat source: electrical Cavity volume: 47 litre

- Temperature range 40 °C 200 °C
- Power cord length 150 cm Cable length
- Total connected load electric: 2.99 KW
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 455 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 450 mm 455 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual