

Product data sheet

Specifications



Low temp kit (-35C)

ACAC10047

Overview

Lead time	Special Order - Call for Quoted Lead Times
-----------	--

Main

Main Input Voltage	200...240 V
Provided Equipment	User Manual

Physical

Height	13.82 in (35.1 cm)
Width	9.33 in (23.7 cm)
Depth	10.79 in (27.4 cm)
Product Weight	19.8 lb(US) (9 kg)
Mounting preference	No preference
Mounting Mode	Not rack-mountable

Input

Input Frequency	50 Hz
-----------------	-------

Ordering and shipping details

GTIN	731304408017
------	--------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15.75 in (40 cm)
Package 1 Width	14.96 in (38 cm)
Package 1 Length	15.75 in (40 cm)
Package 1 Weight	21.74 lb(US) (9.86 kg)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Under investigation

Use Again

 Repack and remanufacture	
Take-back	No
WEEE	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.