

Product datasheet

Specifications



APC Easy Rack PDU, Switched, 1U, 1 Phase, 3.7kW, 230V, 16A, 8 x C13 outlets, IEC60320 C20 inlet

EPDU1016S

⚠ To be discontinued

⚠ Discontinued on: 6 Jun 2025

⚠ To be end-of-service on: 31 Dec 2027

EAN Code: 0731304405122

Main

Product or component type	PDU
Main Input Voltage	200 V 208 V 230 V
Input current limits	16 A
Network frequency	50/60 Hz
Main Output Voltage	208 V 230 V
Input Connection Type	IEC 60320 C20
Number of power socket outlets	8 IEC 60320 C13
Load capacity	3680 VA
Max current draw	16 A
PDU type	Switched
Number of rack unit	1U
Cable length	2.49 m
Provided equipment	Horizontal mounting brackets Installation guide Cable

Complementary

Mounting location	Front Rear
mounting mode	Rack-mounted
Mounting position	Horizontal
Height	44.4 mm
Width	482 mm
Depth	200 mm
Net weight	2.8 kg

Environmental

Product certifications	CE EAC TÜV
Relative humidity	5...95 %

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Storage Relative Humidity	5...95 %
Ambient air temperature for storage	-25...65 °C
Storage altitude	0...15240 m
Operating altitude	0...10000 ft
Ambient air temperature for operation	-5...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8 cm
Package 1 Width	26 cm
Package 1 Length	56 cm
Package 1 Weight	3.6 kg

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	12
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	820 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	20 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.1 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.6 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	798 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Again



Repack and remanufacture

End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

