HP DesignJet T830 36-in Multifunction Printer

Communicate more effectively—no learning curve needed—with print plus scan and copy capabilities



CONVENIENT—Fast, agile, intuitive print/scan/copy

- Enjoy easy installation in the office, construction job site with the most compact 36-in largeformat MFP.¹
- Easily print project sets and PDF documents with HP Click printing software.
- Anyone can print smoothly from a smartphone or tablet with HP Mobile Printing.²
- Fit your print volume—choose from 130- and 300-ml HP ink cartridges.

TRUSTED—HP DesignJet quality and reliability

- Get HP DesignJet quality also in small-format sizes—print half-size documents with 50-sheet A4/A3 input tray.
- Smart scanning technology protects originals from damage when scanning and obtains precise colors.
- Reinforced design and strong legs for easy transport and use at the job site.
- Redesigned stand reduces CO2e up to 197 tons/year by units sold.³

COMMUNICATION—Immediately share meeting results

- Use built-in scanner to copy and distribute sketches and hand-annotated drawings to peers/partners right away.
- Easily link your computer, smartphone, or tablet to the printer with Wi-Fi Direct.
- Share drawings immediately—scan/email from front panel, use HP Smart app⁴ to email contacts, post to cloud.
- No learning curve—with the intuitive design of a single touchscreen, you can scan, copy, and share instantly.

For more information, please visit http://www.hp.com/go/designjett830

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

¹ The HP DesignLet T830 24-inch and 36-inch Multifunction Printers are the most compact large-format devices performing print/scan/copy functions based on H x W x L specifications published as of May, 2017.
² Local printing requires mobile device and printer to be on the same network (usual) Wi-Fi access points bridge wireless to wired connections) or have a direct wireless connection. Wireless performance is dependent on physical environment and distance from access point. Wireless one with 2.4 GHz operations only. Remote printing requires an Internet connection of an HP web-connected printer. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See http://www.hp.com/go/designjetmobility for more details.
³ Redesigned stand with reduced material usage and up to 30% weight reduction compared to the previous stand model used in the HP DesignLet T830 Multifunction Printer series. Based on calculations in accordance with PO-14/04/04/Life (used screarcements using Berlie 5 (2018) e 62/18/19.

ISO 14040/14044 Life Cycle Assessments using ReCiPe (H) v. 1.1 (2016) on GaBi 8.5 (2018) software and scaled to reflect expected yearly sales. ⁴ The HP Smart app is available for Apple® iPad, iPhone, and iPod Touch running iOS v7.0 or later and for Android™ mobile devices running Android™ v4.4 or later. The HP Smart app is available for free from the Apple® App Store for Apple® mobile devices and from the Google Play Store for Android™ mobile devices.

Technical specifications

and mac05 printer drivers, printing support for Chrome 05, print from USB pen drive Drivers HP-GL/2, HP-RTL drivers for Windows Raster driver for macOS and Windows Dimensions (W x D x H) Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer 58.2 kg Shipping 80.7 kg What's in the box HP DesignJet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers	Print	
Pint resolution Up to 2400 x 1200 optimized dpi Technology HP Terman Helpt Sheet 5 x 5 x 5 x 5 m Sheet 5 x 5 m HI (L, M, Y): 25 g (m) Diff Herman Line walk Sheet f and the sheet f		25 sec/page on A1, 82 A1 prints per hour ¹
Technology HP Thermal Holpet Margine Rel 15: 45: 5: 5: 5: 5: mm Sheet: 5: 5: 5: 5: 5: 5: mm De-baskell: CA, Yi, P; primer-baskel (mQ) Ink kypas De-baskell: CA, Yi, P; primer-baskel (mQ) Printhead nozzles 1376 Interactions: 10. MV Printhead nozzles 1376 Interactions: 0.0 MV Mariuman line worth 0.0 mm OP-GL2 addressabile Margina: 0.0 MV Martinaction compatibiles 10 MV Scan resolution 0.0 to 00 dpi Up to 1.31 cm/dec (color, 200 dpi) Up to 1.31 cm/dec (color, 200 dpi) Scan resolution Up to 100 dpi 145 Scan resolution Up to 100 dpi 145 Scan destinators Scan to email, scan to cold through HP Smart app), network, USB, compute, mobile Mardine Not to 200 dpi 10 Scan destinators Scan destinators Scan destinators Scan destinators Scan destinators Scan destinators Scan destinators Scan destinators Scan destinators Scan destinators		
Start S x 5 x 5 x 5 x 5 m Start S x 5 x 5 x 5 x 5 m It k dop 6 µ (C, M, Y) 12.6 µ (mA) Pintheads 1, C, M, Y mA) Pintheads 1, C, M, Y mA) Pintheads 1, S, C Une accuracy e0, 1% ² Maimum line width 0.22 mm (HP-GL/2 adiresable) Mathematine width 0.22 mm (HP-GL/2 adiresable) Mathematine width 0.10 a B1 cm/bec (ador, 200 dpl) Start sequed Up to 1.03 a Context (ador, 200 dpl) Start sequed Up to 1.03 context (ador, 200 dpl) Start sequed Up to 1.03 context (ador, 200 dpl) Start sequed Start sequed Start sequed J B65, DPC, TFF Stand start and scan to cloud (Hrough HP Smart app), network, USB, computer, mobile Thackess S am to remal, Scan to cloud (Hrough HP Smart app), network, USB, computer, mobile Start Sequed J B70 freef read, roll Feed, input freed, input freed	Technology	HP Thermal Inkjet
ink types Dye-based (C, M, Y), pigment-based (mk) ink drop G (L, M, Y, 12 S (L MO) Printheads 1 (C, M, Y, No) Printheads 1 (C, M, Y, No) Printheads 0 (L, M, Y, No) Printheads 0 (L, M, Y, No) Printheads 0 (L, M, Y), 12 S (L MO) Printheads 0 (L, M, Y), 12 S (L MO) Printheads 0 (L M, Y), 12 S (L MO) Printheads 0 (L M, Y), 12 S (L MO) Mathurchica problems Sans peed U to 1 38 1 cm/sec (lcolor, 200 dp) Up to 1 (J S cm/sec (lcolor, 200 dp) Sans resolution Up to 5 (S Contact Image Senso), media jam detection sensor, front feed scanning method Sans format JPEC, PD, TFF Sans destrations Sans format S, sans to formal, s, santo cloud (through HP Smart app), network, USB, computer, mobile Thickness 0, 8 mm Media Thickness 0, 8 mm Media State freed, roll feed, input tray, media bin, automatic horizontal cutter Roll Sane (L Y) 9 19 4 mm Stated size 279 19 19 4 mm Stated size 279 19 19 10 mm Amound index 2, 201 x 23 19 330 x 482 to 314 x 1897 mm Manual (acd 2, 201 x 482 to 314 x 1897 mm Manual (acd 2,	Margins	
ink drop 6 pl (C, M, Y); 12.6 pl (mK) Printheads 1.(C, M, Y, rK) Printhead no.21 Printheads 1.(C, M, Y, rK) Printhead no.22 Pr	1-1-4	
Printheads 1 (C, M, Y, mk) Printhead mozales 1376 Brinthead mozales 1376 Minimum line width 0.02 mm (MP-GL/2 addressable) Max optical density 8 (L mm/2, T.O. D) Multifunction capabilities Scan speed Up to 3.81 cm/sec (kode, 200 dpl) (Up to 11.43 cm/sec (kode, 200 dpl) (Up to 11.43 cm/sec (kode, 200 dpl) (Up to 11.43 cm/sec (kode, 200 dpl) Scan resolution Up to 3.81 cm/sec (kode, 200 dpl) Scan resolution Up to 3.81 cm/sec (kode, 200 dpl) Scan format JPEG, PDF, TFF Technology Seederfac, CSI (contact trage Sensor), media jam detection sensor, front feed scanning method Scan format JPEG, PDF, TFF Media Marca detection sensor, Scan to mail, scan to cloud (through HP Smart app), network, USB, computer, mobile Thickness 0.8 mm Media Marca detection sensor, front feed scanning method Standard sheets Input tray, 210 x 279 to 330 x 482 mm Manual feed, ZA, II, AO Manual feed, ZA, II, AO Manual feed, ZA, II, AO Manual feed, ZA, II, AO Gammage 60 to 280 gim! foultmanual feed; 60 to 220 gim? (nput tray) Thickness Up to 3.3 mm Media Manual feed; ZA, II, AO Gammage 60 to 280 gim? foultmanual feed; 60 to 220 gim? (nput tray) Thickness		
Printhead naziles 1376 Line accuracy 10.1% ² Marinum Line with 0.02 mm 0HP-GL/2 addressable) Marinum Line with 8.1 min/2.10 D ³ Multifunction capabilities Sons speed Sons speed Up to 3.81 cm/sec (calor, 200 dp) Scan resolution Up to 600 dpi Scan resolution Up to 600 dpi Scan format JP66, P05, TFF Scan destinations Scan to email, scan to dougl through HP Smart appl, network, USB, compute, mobile Thickness 0.8 mm Maria Stant denail, scan to dougl through HP Smart appl, network, USB, compute, mobile Stand format JP66, P05, TFF Handling Sheet feed, roll feed, input tray, media bin, automatic horizontal cutter Motils 279 to 914 nm Stand ad sheets Input tray, 20 x 270 to 30 x 482 mm Manual (feed, Az, At, AO Stand ad sheets Input tray, 20 x 270 to 30 x 482 mm Manual (feed, Az, At, AO Gammage 60 to 280 g/m ¹ foiL/manual feed, 60 to 220 g/m ² foiput tray) Thickness Up to 0.3 mm Applications Line drawings, Renderings, Presentations		
Line accuracy ±0.1% ² Minimum line width 0.02 mm (RP-GL/2 addressable) Mas optical density 8 L min/2.100 ¹ Mulfinction apabilities 10 to 3.81 cm/sec (color. 200 dpi) Scan speed Up to 1.81 cm/sec (color. 200 dpi) Scan resolution Up to 600 dpi Scan format JPE6, DPC TIFF Scan format JPE6, DPC TIFF Scan format JPE6, DPC TIFF Scan destinations Scan to email, scan to cloud (through HP Smart app), network, USR, computer, mobile Thickness 0.8 mm Media 100 to 100 dpi Handling Sheet feed, coll feed, input tray, media bin, automatic horizontal cutter Roll size 2.79 to 91.4 mm Standard sheets Input tray, A1, A0 Maraual feed, 2.01 xr 20 to 320 x 482 to 91.4 x 1897 mm Standard sheets Up to 10.2 800 gm/r (ultramual feed; 60 to 220 gm ² (input tray) Thickness Up to 10.2 800 gm/r (ultramual feed; 60 to 220 gm ² (input tray) Maraual feed, 2.01 xr 20 to 320 x 482 to 91.4 x 1897 mm Applications Line drawings, Renderings, Presentations Grammage 60 to 280 gm/r (ultramual feed; 60 to 220 gm ² (input tray) Thickness Up to 12.4 x 1.4 A0 Maraual feed, X, 2.1 x A0 Maraual feed; X, 2.1 x A0 Maraual feed, X, 2.1 x A0<		
Manum line width 0.02 mm (HeP-6L/2 addressable) Max optical density B L* min/2 10 D ¹ Multifunction capabilities Up to 3.81 m/scc (color, 200 dpi) San resolution Up to 1.43 m/scc (color, 200 dpi) San resolution Up to 5.00 dpi Technology Sheeffed, CIS (Contact Image Sensor), media jam detection sensor, front feed scanning method San format JPEC, PDE, TIFF San destinations San to email, scan to cloud (through HP Smart app), network, USB, computer, mobile Thickness 0.8 mm Media Manual feed, sign 4.8 gp / 103/3 vd 4.82 mm Manual feed, 30 vd 482 to 914 x 1997 mm Stand dri sheets Input tray, 210 x 271 to 330 vd 4.82 mm Manual feed, 30 vd 482 to 914 x 1997 mm Standard sheets Input tray, 210 x 271 to 330 vd 4.82 mm Manual feed, 30 vd 482 to 914 x 1997 mm Standard sheets Input tray, 210 x 271 to 330 vd 4.82 mm Manual feed, 30 vd 482 to 914 x 1997 mm Standard sheets Input tray, 210 x 271 to 330 vd 4.82 mm Manual feed, Sci to 10 220 g/m ⁵ (input tray) Tickness Up to 0.3 mm Appolications Line drawings; Rendrings; Presentation		
Max optical density 8 L ⁴ min/2.10 D ¹ Multifunction capabilities Scan speed Up to 1.8.3 cm/sec (closc, 200 dpi) Up to 1.1.4.3 cm/sec (closc, 200 dpi) Up to 1.1.4.3 cm/sec (grayscale, 200 dpi) Up to 1.1.4.3 cm/sec (grayscale, 200 dpi) Up to 1.1.4.3 cm/sec (grayscale, 200 dpi) Scan resolution Up to 600 dpi Scan resolution Scan to email, scan to cloud (through HP Smart app), network, USB, computer, mobile Thickness 0.8 mm Media Handling Sheet feed, roll feed, input tray, media bin, automatic horizontal cutter Rel size 279 to 9.14 mm Sheet size Input tray, 210 x 279 to 330 x 482 mm Marual feed: 3.30 x 482 to 91.4 x 1897 mm Sheet size Input tray, 210 x 279 to 330 x 482 mm Marual feed: 3.30 x 482 to 91.4 x 1897 mm Sheet size Up to 280 gm/ foul/manual feed; 60 to 220 gm ² (input tray) Thickness Up to 0.3 mm Applications Line drawings, Renderings, Presentations Memory 1.68 Hand dsk Nore Connectively HP-GL/2, HP-RTL, THF, JPEG, CL, SL G-L, UIF Printer Gigabit Ethermet 110008ase-11, Wi-Fi 802, 11bg/m Nater advises printer divers, printing support for Grimme OS, print from USB pen drive Marual feed for Grimmanus Printed The Close Start for Windows Reserved Windows Numery 1.68 Hand dsk Nore Connectively HP-GL/2, HP-RTL, THF, JPEG, CL, SL G-L, UIF Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Wedia to 114 x 1897 mm Shipping 0.7 JB x 570 x 645 mm HP-GL/2, HP-RTL, THF, JPEG, CL S G-L, UIF Printer 9.2 Lo 20 s 20 s first divers, printing support for Grimme OS, print from USB pen drive Window MHA Tore to enable mobile printing via Up Print, Apple AriPrint and HP Smart app for Android and IOS devices, Window MHA Tore to enable mobile printing via Up Print, Apple AriPrint and HP Smart app for Android and IOS devices, Window MM Tore to enable mobile printing via Up Print, Apple AriPrint and HP Smart app for Android and IOS devices, Window MM Tore to enable on the printing via Up Print, Apple AriPrint and HP Smart app for Android and IOS devices, Window MM Tore to enable the for macOS and Windows ND Printer 140.3 x 6		
Multinction capabilities Scan speed Up to 3.81 cm/sec (color. 200 dpi) Up to 11.4 cm/sec (color. 200 dpi) Scan resolution Up to 600 dpi Technology Sheetfed, CIS (Contact Image Sensor), media jam detection sensor, front feed scanning method Scan format JPEC, DPT, FFF Scan destinations Scan to email, scan to cloud (through HP Smart app), network, USB, computer, mobile Thickness 0.8 mm Media Handing Sheet feed, roll feed, input tray, media bin, automatic horizontal cutter Roll size 279 to 914 mm Sheet size Input tray, 210 x 279 to 330 x 482 mm Manual feed: 2, 214 A.0 Manual feed: 2, 214 A.0 Grammage 60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray) Thickness Up to 0.3 mm Applications Line drawings, Renderings, Presentations Merrory 1 G8 Shard sikk None ConnectMV Interfaces Up to 12, UP-RTL, THF, JPEC, CALS GL, UPF Nature print languages HP-GL2, HP-RTL, THF, JPEC, CALS GL, UPF Nature print languages HP-GL2, IP-RTL, THF, JPEC, CALS GL, UPF <td< td=""><td></td><td></td></td<>		
Scan speed Up to 3.81 cm/sec (color, 200 dpl) Up to 50 dpl Scan resolution Up to 50 dpl Technology Sheetfed, CIS (Contact Image Senson), media jam detection sensor, front feed scanning method Scan format JPEG, PDF, TIFF Scan destinations Scan to email, scan to cloud (through HP Smart app), network, USB, computer, mobile Thickness 0.8 mm Media PSE Bil size 279 to 9 14 mm Schadd sheets Input tray, 210 x 279 to 330 x 482 mm Manual feed, X0 x 482 to 914 x 1897 mm Standard sheets Up to 0.3 mm Applicators Up to 0.3 mm Applicators Line drawings; Renderings; Presentations Memory 1 GB Hand disk None Connectivity Inde Street (SD, ST, IFF, JPEG, CALS GA, UPE Printer paths Wi-Fi JPE, JPE, JPE, PEG, LALS GA, UPE Printer paths None Connectivity 1 GB Hand disk None Connectivity 1 GB Printer paths Wi-Fi JPE, CALS GA, UPE Printer paths Wi-Fi JPE, LALS GA, UPE Printer SS, SQ		8 L* min/2.10 D3
Up to 11.43 cm/sec (grayscale, 200 dpi) Scan resolution Up to 600 dpi Scan resolution JPEG, PDF, FF Scan format JPEG, PDF, FF Scan destinations Scan to email, scan to doud (through HP Smart app), network, USB, computer, mobile Thickness 0.8 mm Media 279 to 914 mm Handling Sheet feed, roll feed, input tray, media bin, automatic horizontal cutter Roll size 279 to 914 mm Stand stenstra Manual Keed, 330 x 482 ro 914 x 1897 mm Standard sheets Input tray, To 4A A3 Manual Keed, 200 Jmr (fullmanual Keed); 60 to 220 g/m² (input tray) Thickness Up to 0.3 mm Applications Line drawings, Renderings, Presentations Marcol None Connectivity Interfaces Gigabit Ethernet (10008ase-T), Wi-Fi 802, 11bg/n Native print trangages HP-GL/2, HP-RTL, THF, JPEG, CALS G4, UFF Printing paths Wi-Fi DOC, LINE-S GM Windows Rater drint trangages HP-GL/2, HP-RTL, THF, JPEG, CALS G4, UFF Printing paths Wi-Fi DOC, ALS G4, UFF Winthing paths So 40 S x 1155 mm	Multifunction capabilities	
Technology SheetFed, CIS (Contact Image Sensor), media jam detection sensor, front feed scanning method Scan format JPEG, PDF, TFF Scan destinations Scan to email, scan to doud (through HP Smart app), network, USB, computer, mobile Thickness 0.8 mm Media Prestinations Handling Sheet feed, roll feed, input tray, media bin, automatic horizontal cutter Roll size 279 to 914 nm Sheet size Input tray, 210 x 279 to 330 x 482 rpm Manual feed, XA, A1, A0 Manual feed, XA, A1, A0 Grammage 60 to 280 g/m² (roll/manual feed; 60 to 220 g/m² (input tray) Thickness Up to 0.3 mm Applications Line drawings, Renderings, Presentations Memory 1 GB Hard disk None Connectivity Interfaces Interfaces Gigabit Ethernet (1000Base-T), W-Fi B02.11b/g/m Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printer 1403 x 605 x 1155 mm Shopping 1578 x 570 x 645 mm Shipping 1578 x 570 x 645 mm Weight Printer Printer 1403 x 605 x 1155 mm Shipping<	Scan speed	
Scan format JPEG, PDF, TIFF Scan definitions Scan to email, scan to cloud (through HP Smart app), network, USB, computer, mobile Thickness 0.8 mm Media Mail Handling Sheet feed, roll feed, input tray, media bin, automatic horizontal cutter Roll size 279 to 914 mm Manual feed, 320 x 482 to 914 x 1897 mm Standard sheets Input tray, 210 x 279 to 330 x 482 to 914 x 1897 mm Standard sheets Input tray, A, A3 Manual feed, A2, A0 Go to 280 g/m² (roll/manual feed); 60 to 220 g/m² (nput tray) Thickness Up to 0.3 mm Applications Line drawings; Renderings; Presentations Memory 1 GB Hard disk None Connectivity Inter the maker mobile printing support for Chrone OS, print and HP Smart app for Android and IOS devices, Window and maxOS printer divers for Windows Drivers Rule Cut, L.P.RTL, DFF, DEC, CALS CA, UBF Printer Printer 1403 x 605 x 1155 mm Shopping 1578 x 570 x 645 mm Weight Printer Printer 582 kg Shopping 160 K MP Shopping 178 x 570 x 645 mm Weig	Scan resolution	Up to 600 dpi
Scan destinations Scan to email, scan to cloud (through HP Smart app), network, USB, computer, mobile Thickness 0.8 mm Media Handling Sheet feed, roll feed, input tray, media bin, automatic horizontal cutter Bell size 279 to 914 mm Sheet size Input tray, 210 x 330 x 482 ron Manual feed: 330 x 482 ro 914 x 1897 mm Standard sheets Input tray, 210 x 330 x 482 ron 14 x 1897 mm Standard sheets Up to 0.3 mm Applications Line drawings; Renderings; Presentations Memory 1 GB Hard disk None Connectivity Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11bg/n Hard disk None Connectivity Interfaces Bigabit Ethernet (1000Base-T), Wi-Fi 802.11bg/n Native print languages HP-GL/2, HP-RLT, IFE, PEE, CALS C4, URF Printing paths Wi-Fi Direct to enable mobile printing support for Chrome 05, print from USB pen drive Drivers HP-GL/2, HP-RLT, Urivers for Windows Raster driver for macOS and Windows Bipping Shipping 1578 x 570 x 645 mm Weight HP Seligulet T830 3	Technology	Sheetfed, CIS (Contact Image Sensor), media jam detection sensor, front feed scanning method
Thickness 0.8 mm Media Filter feed, roll feed, input tray, media bin, automatic horizontal cutter Roll size 279 to 914 mm Sheet size Input tray, 210 x 279 to 330 x 482 to 914 x 1897 mm Standard sheets Input tray, 210 x 279 to 330 x 482 to 914 x 1897 mm Standard sheets Input tray, 210 x 279 to 330 x 482 to 914 x 1897 mm Standard sheets Input tray, 210 x 279 to 330 x 482 to 914 x 1897 mm Grammage 60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray) Thickness Up to 0.3 mm Applications Line drawings; Resentations Memory 168 Hard disk None Connectivity Interfaces Gigabit Ethermet (1000Base-T), Wi-Fi B02.11blg/n Native print Inanuages HP-GL/2, HP-RTI, IFF, JPEG, CALS G4, UBF Printing paths Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and IOS devices, Window and maCOS printer drivers, printing support for Chrome US, print from USB pen drive Drivers HP-GL/2, HP-RTI, IFF, JPEG, CALS G4, UBF Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Proces Printer 58.2 kg Shipping 80.7 kg Borearing temingesture 5 to 40°C Ope	Scan format	JPEG, PDF, TIFF
Media Handling Sheet feed, roll feed, input tray, media bin, automatic horizontal cutter Roll Size 279 to 914 mm Sheet Size Input tray; 210 x 279 to 330 v 482 rnm Manual feed: 320 v 482 to 914 x 1897 rnm Standard sheets Input tray; A4, A3 Manual feed: A2, A1, A0 Grammage 60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (nput tray) Thickness Up to 0.3 mm Applications Line drawings; Renderings; Presentations Memory 1.68 Hard disk None ConnectMity Gigabit Ethernet (1000Base-T), Wi-Fi802, 111/g/n Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths Wi-FiDirect to enable mobile printing vai HP ePrint, Apple AirPrint and HP Smart app for Android and iOS devices, Window and macOS printer drives, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths Wi-FiDirect to enable mobile printing vai HP ePrint, Apple AirPrint and HP Smart app for Android and iOS devices, Window and macOS printer drives, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printer 1403 × 605 × 1155 mm Shipping	Scan destinations	Scan to email, scan to cloud (through HP Smart app), network, USB, computer, mobile
Handling Sheet feed, roll feed, input tray, media bin, automatic horizontal cutter Roll size 279 to 914 mm Sheet size Input tray: 210 x 279 to 330 x 482 mm Manual feed: 330 x 482 mm Manual feed: 330 x 482 mm Standard sheets Input tray: A4, A3 Manual feed: 320 x 482 mm Manual feed: 320 x 482 mm Standard sheets Up to 0.3 mm Applications Line drawings; Renderings; Presentations Memory 1 68 Hard disk None Connectivity Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS GA, URF Printing paths Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and iOS devices, Window and macCS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-RTL drivers for Windows Raster driver for macOS and Windows Drivers HP-GL/2, HP-RTL drivers for Windows Shipping 1578 x 570 x 645 mm Weight Printer 1403 x 605 x 1155 mm Shipping 80.7 kg What in the box HP DesignLet TB30 36-in MFP printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preverters	Thickness	0.8 mm
Roll size 279 to 914 mm Sheet size Input tray, 210 x 279 to 330 x 482 mm Manual feed: 330 x 482 to 914 x 1897 mm Standard sheets Input tray, 210 x 279 to 330 x 482 mm Grammage 60 to 280 g/m² (roll/manual feed; 60 to 220 g/m² (input tray) Thickness Up to 3.0 mm Applications Line drawings; Renderings; Presentations Memory 1 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths wi-Fi Direct to enable mobile printing vab PP ePrint, Apple AirPrint and HP Smart app for Android and IOS devices, Window and macoS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-RTL (TiFF, JPEG, CALS G4, URF Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer Printer 58.2 kg Shipping 80.7 kg What's Int box HP DesignLet T1830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster,	Media	
Roll size 279 to 914 mm Sheet size Input tray, 210 x 279 to 330 x 482 mm Manual feed: 330 x 482 to 914 x 1897 mm Standard sheets Input tray, 210 x 279 to 330 x 482 mm Grammage 60 to 280 g/m² (roll/manual feed; 60 to 220 g/m² (input tray) Thickness Up to 3.0 mm Applications Line drawings; Renderings; Presentations Memory 1 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths wi-Fi Direct to enable mobile printing vab PP ePrint, Apple AirPrint and HP Smart app for Android and IOS devices, Window and macoS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-RTL (TiFF, JPEG, CALS G4, URF Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer Printer 58.2 kg Shipping 80.7 kg What's Int box HP DesignLet T1830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster,	Handling	Sheet feed, roll feed, input tray, media bin, automatic horizontal cutter
Sheet size Input tray: 210 x 279 to 330 x 482 tm m Manual feed: 330 x 482 to 91 a x 1897 mm Standard sheets Input tray: A4, A3 Manual feed: 330 x 482 to 91 a x 1897 mm Grammage 60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray) Thickness Up to 0.3 mm Applications Line drawings; Renderings; Presentations Memory 1 G8 Hard disk None Connectivity Gigabit Ethernet (10008ase-T), Wi-Fi 802.11b/g/n Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths Wi-Fi Inzet to analbe mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and i05 devices, Window and mac0S printer drivers, printing support for Chrome 0S, print from USB pen drive Drivers HP-GL/2, HP-RTL arivers for Windows Raster driver for mac0S and Windows Dimensions (W x D x H) Printer Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer Printer 1403 x 605 x 1155 mm Shipping 80.7 kg What's in the box HP DesignJet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers PH Postyware and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for mac0S and Window En		
Standard sheets Input tray: A4, A3 Manual feed: A2, A1, A0 Grammage 60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray) Thickness Up to 0.3 mm Applications Line drawings; Renderings; Presentations Memory 1 G8 Hard disk None Connectivity Interfaces Gigabit Ethernet (10008ase-T), Wi-Fi 802.11b/g/n Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and iOS devices, Window and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-RTL, driver for Windows Raster driver for macOS and Windows Stanter driver for Windows Dimensions (W x D x H) Printer Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer Printer 58.2 kg Shipping 80.7 kg What's in the box HP DesignLet T80 36-in MFP printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers Printer 58.2 kg Shipping 80.7 kg What's in the box HP DesignLet T80 36-in MFP printhead, ink cartridges, printer stand, spindle, quick reference guide	Sheet size	
Grammage 60 to 280 g/m² (roll/manual feed); 60 to 220 g/m² (input tray) Thickness Up to 0.3 mm Applications Line drawings; Renderings; Presentations Memory 1 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi B02.11b/g/n Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and iOS devices, Window and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-HTL drivers for Windows Raster driver for macOS and Windows Raster driver for macOS and Windows Shipping 1578 x 570 x 645 mm Weight Printer Printer 58.2 kg Shipping 80.7 kg What's in the box HP DesignLet T830 36-in MFP printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignLet T000 and Window Environmental ranges Upcating temperature 5 to 40°C Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating temperature -5 B(A) (operating	Standard sheets	Input tray: A4, A3
Thickness Up to 0.3 mm Applications Line drawings; Renderings; Presentations Memory 1 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), WI-Fi B02.11b/g/n Native print languages HP-GL/2, HP-ATL, TIFF, JPEG, CALS G4, URF Printing paths WI-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and iOS devices, Window and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-ATL drivers for Windows Raster driver for macOS and Windows Raster driver for macOS and Windows Dimensions (W x D xH) V Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight V Printer 58.2 kg Shipping 80.7 kg What's in the box HP Design1et T830 36-in MFP printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP Design1et Utility for macOS and Window Environmental ranges Operating humidity 20 to 80% RH Opa	Grammage	
Applications Line drawings; Renderings; Presentations Memory 1 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802, 11b/g/n Interfaces Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and iOS devices, Window and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-RTL drivers for Windows Raster driver for macOS and Windows Domensions (W x D x H) Printer Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer Printer 58.2 kg Shipping 80.7 kg What's in the box HP DesignJet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers Portoremental ranges Diperating temperature 5 to 40%C Operating temperature 5 to 40%C Operating temperature 25 to 55%C Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)		
Amount 1 GB Memory 1 GB Hard disk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and iOS devices, Window and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Dirvers HP-GL/2, HP-RTL drivers for Windows Raster driver for macOS and Windows Raster driver for macOS and Windows Dimensions (W X D x H) Printer Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer Shipping 80.7 kg What's in the box HP DesignJet TB30 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for macOS and Window Environmental range 20 to 80% RH Storage temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature 5 to 40°		
Hard disk None Connectivity Interfaces Gigabit Ethernet (1000Base-T), Wi-Fi 802.11b/g/n Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and i0S devices, Window and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-RTL drivers for Windows Raster driver for macOS and Windows Dimensions (W x D x H) Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer 58.2 kg Shipping 80.7 kg What's In the box HP Design.Jet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, pover cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP Design.Jet Utility for macOS and Window Environmental ranges Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature 5 to 55°C		
Connectivity Interfaces Gigabit Ethermet (1000Base-T), Wi-Fi 802.11b/g/n Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and I0S devices, Window and macOS printer drivers, printing support for Chrome 0S, print from USB pen drive Drivers HP-GL/2, HP-RTL drivers for Windows Raster driver for macOS and Windows Dimensions (W × D × H) Printer Printer 1403 × 605 × 1155 mm Shipping 1578 × 570 × 645 mm Weight Printer Printer 58.2 kg Shipping 80.7 kg What's in the box HP DesignJet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for macOS and Window Environmental ranges Coperating temperature > 2 to 58°C Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)		
Interfaces Gigabit Ethermet (1000Base-T), Wi-Fi 802.11b/g/n Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and i0S devices, Window and macOS printer drivers, printing support for Chrome 0S, print from USB pen drive Drivers HP-GL/2, HP-RTL drivers for Windows Raster driver for macOS and Windows Dimensions (W × D × H) Printer Printer 1403 × 605 × 1155 mm Shipping 1578 × 570 × 645 mm Weight Printer Printer 58.2 kg Shipping 80.7 kg What's in the box HP DesignJet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for macOS and Window Environmental ranges Coperating temperature > 2 to 58°C Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)		none
Native print languages HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4, URF Printing paths Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and iOS devices, Window and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-RTL drivers for Windows Raster driver for macOS and Windows Dimensions (W x D x H) Printer Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer Printer 58.2 kg Shipping 80.7 kg What's in the box HP DesignJet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and Solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for macOS and Window Environmental ranges Operating temperature 5 to 40% C Operating temperature 5 to 55% C Acoustics 48 dB(A) (operating), <16 dB(A) (idle)		
Printing paths Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and iOS devices, Window and macOS printer drivers, printing support for Chrome OS, print from USB pen drive Drivers HP-GL/2, HP-RTL drivers for Windows Rastern and COS and Windows Dimensions (W x D x H) Printer Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer Printer 58.2 kg Shipping 80.7 kg What's In the box HP DesignJet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for macOS and Window Environmental ranges Operating temperature 5 to 40°C Operating temperature 5 to 40°C Operating temperature Storage temperature 5 to 55°C Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)		
Drivers HP-GL/2, HP-RTL drivers for Windows Raster driver for macOS and Windows Dimensions (W x D x H) Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer 58.2 kg Shipping 80.7 kg What's in the box HP Designlet T830 36-in MFR printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP Designlet Utility for macOS and Window Environmental ranges Operating temperature 5 to 40°C Operating temperature 5 to 55°C Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)		Wi-Fi Direct to enable mobile printing via HP ePrint, Apple AirPrint and HP Smart app for Android and iOS devices, Windows
Dimensions (W x D x H) Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Wight Printer 58.2 kg Shipping 80.7 kg What's in the box HP DesignJet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for macOS and Window Environmental ranges Uperating temperature 5 to 40°C Operating temperature 5 to 55°C Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)	Drivers	HP-GL/2, HP-RTL drivers for Windows
Printer 1403 x 605 x 1155 mm Shipping 1578 x 570 x 645 mm Weight Printer 58.2 kg Shipping 80.7 kg What's in the box HP DesignJet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Cick, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for macOS and Window Environmental ranges 5 to 40°C Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature 5 to 55°C Acoustics Sound pressure Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)	Dimensions (W x D x H)	
Shipping 1578 x 570 x 645 mm Weight Printer Printer 58.2 kg Shipping 80.7 kg What's in the box HP Design1et T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Cick, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP Design1et Utility for macOS and Window Environmental ranges Doperating temperature Storage temperature 5 to 40°C Operating temperature 2 to 55°C Acoustics Sound pressure Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)		1403 x 605 x 1155 mm
Weight Printer 58.2 kg Shipping 80.7 kg What's in the box HP Design Jet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP Design Jet Utility for macOS and Window Environmental ranges Doperating temperature 5 to 40°C Operating temperature 2 to 58% CH Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)		
Printer S8.2 kg Shipping 80.7 kg What's in the box HP DesignJet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for macOS and Window Environmental ranges Derating temperature Operating temperature S to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)		
Shipping 80.7 kg What's In the box HP DesignJet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startur software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for macOS and Window Environmental ranges Departing temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)	5	58.2 ka
What's in the box HP Design.Jet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startu software, power cord, refeed preventers HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP Design.Jet Utility for macOS and Window Environmental ranges Derating temperature S to 40°C Operating temperature 2 to 80% RH Storage temperature -25 to 55°C Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle) Sound power 6.5 B(A) (operating), <3.4 B(A) (idle) Power Consumption 35 watts (printing), 3.5 watts (sleep), 0.2 watts (standby) Standby, Sta		-
HP Software and solutions HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for macOS and Window Environmental ranges		HP Design Jet T830 36-in MFP, printhead, ink cartridges, printer stand, spindle, quick reference guide, setup poster, startup
Operating temperature 5 to 40°C Operating humidity 20 to 80% RH Storage temperature -25 to 55°C Acoustics -25 to 55°C Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)	HP Software and solutions	sortware, power cord, rereed preventers HP Click, HP Smart app, HP Support Assistant, HP Print Preview for Windows, HP DesignJet Utility for macOS and Windows
Operating humidity 20 to 80% RH Storage temperature -25 to 55% Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)	Environmental ranges	
Storage temperature -25 to 55°C Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)	Operating temperature	5 to 40°C
Storage temperature -25 to 55°C Acoustics Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)	Operating humidity	20 to 80% RH
Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)		
Sound pressure 48 dB(A) (operating), <16 dB(A) (idle)	Acoustics	
Sound power 6.5. B(A) (operating), <3.4 B(A) (idle)		48 dB(A) (operatina). <16 dB(A) (idle)
Power Consumption 35 watts (printing), 3.5 watts (sleep), 0.2 watts (standby)		
Consumption 35 watts (printing), 3.5 watts (sleep), 0.2 watts (standby)		אווען אייר ארייאיזאא אייר אייר אייר אייר אייר
		25 watte (printing) 2.5 watte (cloop) 0.2 watte (standbu)
κequirements Input voltage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 A max		
	Requirements	input voitage (auto ranging): 100-240 V (±10%), 50/60 Hz (±3 Hz), 1.2 A max

Certification

Safety	USA and Canada (CSA certified); EU (LVD, EN 60950-1 and EN 62368-1 compliant); Russia (EAC); Singapore (PSB); China (CCC); Mexico (NYCE); Argentina (IRAM); India (BIS)
Electromagnetic	Compliant with Class B requirements, including: USA (FCC rules), Canada (ICES), EU (EMC/R&TTE Directives), Australia (ACMA), New Zealand (RSM), China (CCC), Japan (VCCI); Certified as Class A product: Korea (KCC)
Environmental	ENERGY STAR, EPEAT, CE marking (including RoHS, WEEE, REACH). In compliance with WW RoHS materials restriction requirements in China, Korea, India, Vietnam, Turkey, Serbia, and Ukraine.
Warranty	One-year limited warranty. Warranty and support options vary by product, country and local legal requirements.

Ordering information

Product	
F9A30E	HP DesignJet T830 36-in Multifunction Printer
Accessories	
B3Q37A	HP DesignJet 36-in Spindle
Original HP pri	nting supplies
F9J61A	HP 728 40-ml Yellow DesignJet Ink Cartridge
F9J62A	HP 728 40-ml Magenta DesignJet Ink Cartridge
F9J63A	HP 728 40-ml Cyan DesignJet Ink Cartridge
F9J64A	HP 728 69-ml Matte Black DesignJet Ink Cartridge
F9J65A	HP 728 130-ml Yellow DesignJet Ink Cartridge
F9J66A	HP 728 130-ml Magenta DesignJet Ink Cartridge
F9J67A	HP 728 130-ml Cyan DesignJet Ink Cartridge
F9J68A	HP 728 300-ml Matte Black DesignJet Ink Cartridge
F9K15A	HP 728 300-ml Yellow Design Jet Ink Cartridge
F9K16A	HP 728 300-ml Magenta DesignJet Ink Cartridge
F9K17A	HP 728 300-ml Cyan DesignJet Ink Cartridge
high quality an designed and (to maximize th	Pinks and printheads, and HP large format printing materials, to experience consistent diveliable performance that enable less downtime. These critical components are angineered together as an optimized printing system, and Original HP inks are designed le life of HP printheads. Protect your HP printer investment by using Original HP inks for ty protection. For more information, visit hp.com/ag/OriginalHPInks.

Service and Support

UC744E HP Network Installation Service
U1XV4E HP Preventive Maintenance Service
U8TY8E HP 2 year Next Business Day HW Support
U8PH3E HP 3 year Next Business Day HW Support
U8TY9E HP 4 year Next Business Day HW Support
U8PH4E HP 5 year Next Business Day HW Support
U8PH5PE HP 1 year Post Warranty Next Business Day HW Support
U8TZOPE HP 2 year Post Warranty Next Business Day HW Support
HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit http://www.hp.com/go/cpc

ECO highlights

ENERGY STAR® certified¹ and EPEAT® registered²
 Free, convenient HP ink cartridge recycling³
 FSC®-certified papers⁴ and a range of recyclable HP media with a take-back program⁵

Please recycle printing hardware and eligible printing supplies and prints. Find out how at our website: http://www.hp.com/ecosolutions

¹ ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental

ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. EINITOTIONEINA Protection Agency.
 EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
 EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
 Brogram availability varies. Please check http://www.hp.com/recycle for details.
 BKG trademark license code FSC®-C115319, see http://www.fsc.org. J. Pt trademark license code FSC®-C01753. see http://www.fsc.org. Not all FSC®-centifed products are available in all regions.
 Many HP printing materials are recyclable through commonly available recycling programs. For information about HP large format printing materials, please visit http://www.HPLFMedia.com

Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP inks.
 ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E printing material in Best or Normal mode with HP Heavyweight Coated roll feed and Original HP inks.
 With HP Premium Instant Dry Photo Gloss media with Original HP inks.





© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. in-en March 2023

