# HP LaserJet Pro MFP M428fdn



## Lighten your workload, focus on your business

Winning in business means working smarter. The HP LaserJet Pro MFP M428 is designed to let you focus your time where it's most effective – growing your business and staying ahead of the competition.



## HP LaserJet Pro MFP M428fdn

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block • Print effortlessly from any device, virtually anywhere, to any HP printer – securely through the cloud.<sup>3</sup> cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

## **Highlights**

- 2 sided printing
- **Embedded Security features**
- HP Roam enabled
- Up to 24% energy savings
- High yield toner cartridge







USB drive

## Built to keep you – and your business – moving forward

- Scan files directly to Microsoft® SharePoint, email, USB, and network folders.<sup>1</sup>
- Help save time by automating all the steps in a complicated workflow and use at a touch of a button.<sup>2</sup>

## Best-in-class security – detect and stop attacks<sup>4</sup>

- A suite of embedded security features help protect your MFP from being an entry point for attacks.<sup>4</sup>
- Help ensure the security of confidential information with optional PIN/Pull printing to retrieve print jobs.<sup>5</sup>
- Optional HP JetAdvantage Security Manager lets you set configuration.
- Thwart potential attacks and take immediate action with instant notification of security issues.<sup>6</sup>

#### Simply designed to uncomplicate your day

- Set up this MFP fast, and easily manage device settings to help increase overall printing efficiency.
- Tackle tasks quickly and easily with the simple 6.8 cm colour touchscreen.
- Print Microsoft office formatted files in addition to pdfs right off your USB drive.<sup>7</sup>
- Avoid interruptions with an HP LaserJet MFP designed to be streamlined for maximum productivity.

## Sustainability is smart business

- Avoid frustrating reprints, wasted supplies, and service calls using Original HP toner cartridges.
- Help save paper right out of the box. The duplex print setting is set at default paper savings mode.<sup>8</sup>
- Saves up to 22% over prior products.<sup>9</sup>
- $\bullet \quad$  Help save energy with HP Auto-on/Auto-off technology.  $^{10}$

## Product walkaround

## HP LaserJet Pro M428fdw shown

- 1. Dual-band Wi-Fi with Bluetooth® Low Energy for easy wireless printing and setup
- 2. 6.9 cm customisable colour touchscreen control panel (tilts up for easier viewing)
- 3. Easy-access USB port
- 4. 100 sheet multipurpose tray 1 supports media sizes up to 216 x 356 mm
- 5. Rear door (access to the print path)
- 6. Hi-Speed USB 2.0 port, USB port for job storage and PIN printing, Gigabit Ethernet LAN port, fax port
- 7. 50 sheet automatic document feeder (ADF) with single-pass, two sided scanning
- 8. Flatbed scanner handles media sizes up to 216 x 356 mm
- 9. 150 sheet output bin
- 10. Front door release button
- 11. Front door (access to HP EcoSmart black toner cartridges)
- 12. Automatic two-sided printing
- 13. 250 sheet input tray 2 supports media sizes up to 216 x 356 mm



# Accessories, Supplies and Support

Supplies	CF259XC HP 59X Black Contract LaserJet Toner Cartridge (10,000 pages)
Accessories	D9P29A HP LaserJet Pro 550-sheet Feeder Tray
	UB9R7E HP 3 year Next Business Day LaserJet Pro MFP M428 Service UB9S2PE HP 1 year Post Warranty Next Business Day LaserJet Pro MFP M428 Service

## **Technical specifications**

rechnical speci	incations
Model	HP Laser Jet Pro MFP M428fdn
Product number	W1A29A
Functions	Print, Copy, Scan, Fax, Email
Control panel	6.96 cm (2.7 in) Colour Touchscreen
Print	
Print technology	Laser
Print speed <sup>1</sup> First page out <sup>2</sup>	Black (A4, normal): Up to 38 ppm (default); Up to 40 ppm (HP High Speed); Black (A4, duplex): Up to 31 ipm  Black (A4, ready): As fast as 6.3 sec; Black (A4, sleep): As fast as 8.8 sec
Print resolution	potacy very retailing in the last of 23 sec., potacy very streety, revisities as a consec.  Black (best) revisities of 23 sec., potacy very streety as a consec.  Black (best) revisities (1200 x 1200 opt), "Technology Pre-Streets 1200, HP ProRest 2200, Economode  10 sec. (best) revisities (1200 x 1200 opt), "Technology Pre-Streets 1200, HP ProRest 2200, Economode
Monthly duty cycle <sup>3</sup>	Up to 80,000 pages Aft. Recommended monthly page volume*. 750 to 4,000
Printer smart software features	Apple AirPrint®, Mopria certified, Google Cloud Print 2.0, ROAM capable for easy printing, HP ePrint, and HP Auto-On/Auto-Off Technology, Intuitive 6.86 cm (2.7 in) touchscreen control panel, Scan/Print from Cloud using apps on the control panel, Job Storage with PIN printing, Print
Standard print languages	from USB, N-up printing, collation  HP PCL 6, HP postscript level 3 emulation, PDF, URF, Native Office, PWG Raster
Fonts and typefaces	HP YELD, HP DOSSECTOR UNRER 3 RETURNING PURE, UNER NORTHER MESSAGE ASSECTION OF THE MESSAGE ASSE
Print area	or souther truetype note.  Print margins 10p.5 mm, Bottom: 5 mm, Left: 4 mm, Right: 4 mm; Maximum print area: 207.4 x 347.1 mm
Duplex printing	Automatic (default)
Сору	<u> </u>
Copy speed <sup>5</sup>	Black (A4): Up to 38 cpm
Copier specifications	ID Copy, Number of copies, Resize (including 2-Up); Lighter/Darker; Enhancements; Original Size; Binding Margin; Collation; Tray Selection; Two-Sided; Quality (Draft/Normal/Best); Save Current Settings; Restore Factory Defaults; Maximum number of copies. Up to 999 copies; Reduce/Enlarge: 25 to 400%
Scan	NEULAPEIRI (IV. 2-5 to 41.05)
Scan speed <sup>6</sup>	Normal (A4): Up to 29 ppm/46 ipm; Duplex (A4): Up to 46 ipm
Scan file format	PDF, PG, TIFF
Scanner specifications	Scanner type Flatbed, ADF, Scan technology. Contact Image Sensor (CIS). Scan input modes Front-panel scan, copy, email, or file buttons; HP Scan software, and user application via TWAIN or WA; Twain version: Version 2.3; Duplex ADF scanning: Yes; Optical scan resolution: Up to
_ <del>-</del>	1200 x 1200 dpi  Single-pass 2-sided scanning ADF; Scan to cloud (Google Drive and DropBox); Scan to email with LDAP email address lookup; Scan to network folder; Scan to USB; Scan to Microsoft SharePoint®; Scan to computer with software; Fax archive to network folder; Fax archive to email; Fax
Scanner advanced features	Single-pass 2-stated scanning ALP; Scan to occur and properox; Scan to email with LLM2 email address lookup; Scan to network roloer; Scan to USe; Scan to Microsoft Share-Point*; Scan to computer with software; Fax acrows to email with LLM2 email address lookup; Scan to entwork roloer; Scan to Microsoft Share-Point*; Scan to Computer with software; Fax acrows to email; Fax to computer with software; Fax acrows to email; Fax to computer solutions (Share) and the solution of t
Recommended monthly scan volume	750 to 4000
Scannable area	Maximum media size (flatbed): 216 x 297 mm; Minimum media size (ADF): 102 x 152 mm Maximum media size (ADF): 216 x 356 mm
Bit depth/ Grey scale levels	24-bit / 256
Digital sending	Standard: Scan to email with LDAP email address lookup; Scan to network folder; Scan to USB; Scan to Microsoft SharePoint®: Scan to computer with software; Fax archive to network folder; Fax archive to email; Fax to computer; Enabledisable fax; Quick Sets
Fax Fax <sup>7</sup>	Yes, 33.6 kbps
Fax specifications	Tex, 3.5.0 KUUS  Fax memory: Up to 400 pages; Fax resolution: Standard: 203 x 98 dp; Fine: Up to 203 x 196 dp; Superfine: Up to 300 x 300 dpi (no halftone); Quick dialing: Up to 120 numbers
Fax smart software features	Permanent fax memory backup, Auto fax reduction, Auto redialing; Delays dending; Fax foredarding; TAM interface; Link barrier; Distinctive ring detection; Cover page; Block fax; Billing codes; Save and load; Fax activity reports; Dial prefix setting; Print fax log; HP Digital Fax
Processor speed	1200 MHz
Connectivity	
Standard	1 H-Speed USB 2.0; 1 rear host USB; 1 Front USB port; Gigabit Ethernet 10/100/1000BASE-T network; 802.3az(EEE)
Mobile printing capability <sup>8</sup>	HP Smart App; HP ePrint; Apple AirPrint™, Mobile Apps; Mopris™ Certified; Google Cloud Print™
Supported network protocols	TCP/IP, Pv4, IPv6, Print: TCP-IP port 9100 Direct Mode, IPD (raw queue support only), Web Services Printing, IPP ePrint, Pologie Cloud Print 2:0, Mopria, IPP Print; Discovery, SLP, Bonjour, Web Services Discovery, IP Config: IPv4 (BootR) DHCP, AutoIP, Manual), IPv6 (Stateless List House) and Very Expert Stateful Very Exper
Network capabilities	Yes, via built-in 10/100/10008ase-TX Ethernet, Gigabit; Auto-crossover Ethernet; Authentication via 802.1X
Hard disk	
Haru dibK	No No
Memory Memory	No Standard: 512 MB , Maximum: 512 MB
Memory Media handling	Stendard: 512 MB : Maximum: 512 MB
Memory Media handling Number of paper trays	Standard: 512 MB; Maximum: 512 MB  Standard: 2 Maximum: 3
Memory Media handling Number of paper trays Media types	Standard: 512 MB , Maximum: 512 MB  Standard: 2 , Maximum: 3  Paper (plain, EcoEFFCIENT, light, heavy, bond, coloured, preprinted, prepunched, recycled, rough); Envelopes; Labels
Memory Media handling Number of paper trays	Standard: 512 MB; Maximum: 512 MB  Standard: 2 Maximum: 3
Memory Media handling Number of paper trays Media types	Standard: 512 MB. Maximum: 512 MB  Standard: 2: Maximum: 3  Standard: 3  Standa
Memory Media handling Number of paper trays Media types Media size Media handling Media handling Media weight	Standard: 5:12 MB; Maximum: 5:12 MB  Standard: 2: Maximum: 3  Paper (plain, ExcEFFICENT, light, heavy, bond, coloured, preprinted, prepunched, recycled, rough); Envelopes; Labels  Custom (metric): Tray 1: 762 x 127 to 215.9 x 355.6 mm; Tray 2; 3: 104.9 x 148.59 to 215.9 x 355.6 mm Supported (metric): Tray 1: A4; A5; A6; B5 (JIS); Ohioi (216 x 340 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Envelope #10; Envelope #10; Envelope B5; Envelope C5; Envelope C5; Envelope C5; Envelope C5; Envelope B1; Custom Size; Statement; Tray 2 & Tray 3: A4; A5; A6; B5 (JIS); Ohioi (216 x 340 mm); 16K (197 x 273 mm); Custom Size; A5-R; B6 (JIS) ADP: A4; Custom sizes 102 x 152 to 216 x 356 mm  Standard input: 100 sheet tray 1, 250 sheet input tray 2; 50 sheet Automatic Document Feeder (ADP) Standard output: 150 sheet output bin Optional input: Optional third 550 sheet tray  Tray 1: 60 to 200 g/m²; Tray 2: Optional 550 sheet; Tray 3: 60 to 120 g/m²
Memory Media handling Number of paper trays Media types Media types Media size Media handling Media weight Input capacity	Standard: 512 MB, Maximum: 512 MB  Standard: 2. Maximum: 512 MB  Outcom (Language Color) (Language Colo
Merony Media handling Number of paper trays Media types Media size Media size Media handling Media weight Input capacity Output capacity	Standard: 5:12 MB; Maximum: 5:12 MB  Standard: 2: Maximum: 5:12 MB; Maximum: 5:12 MB  Custom (merit): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.59 x 127.0 mm); 16K (195 x 270 mm); 16K (195 x 270 mm); 16K (195 x 273 mm); 16K (197 x 273 mm
Memory Media handling Number of paper trays Media types Media types Media handling Media handling Media weight Input capacity Output capacity Compatible operating systems	Standard: 5:12 MB. Maximum: 5:12 MB  Standard: 2: Maximum: 5:12 MB. Maximum: 5:12 MB  Standard: 2: Maximum: 3  Paper (plain, EcoEFFICIENT, light, heavy, bond, coloured, preprinted, prepunched, recycled, rough); Envelopes; Labels  Qustom functiv): Tray 1: 76.2 × 127 to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.9 × 148.5 9to 215.9 × 355.6 mm; Tray 2: 3: 104.5 9to 216.1 9
Memory Media handling Number of paper trays Media types Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems	Standard: 5:12 MB; Maximum: 5:12 MB  Standard: 2: Maximum: 5:12 MB; Maximum: 5:12 MB  Standard: 2: Maximum: 5:12 MB; Maximum: 5:12 MB  Standard: 2: Maximum: 5:12 MB; Maximum: 5:12 MB  Custom (merit): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2, 2: 104.59 to 215.9 x 273 mm); TeX (195 x 273 mm); TeX (195 x 273 mm); Lex
Memory Media handling Number of paper trays Media types Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements	Standard: 5:12 MB. Maximum: 5:12 MB. Maximum: 5:12 MB. Standard: 2: Maximum: 5:12 MB. Maximum: 5:12 MB
Memory Media handling Number of paper trays Media types Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems	Standard: 5:12 MB. Maximum: 5:12 MB.  Standard: 2: Maximum: 3  Paper (plain, EcotEPTICIENT, light, heavy, bond, coloured, preprinted, prepunched, recycled, rough): Envelopes; Labels  Custom functify: Tray 1: 76.2 × 127 to 21.5 9 x 35.5 mm; Tray 2: 3: 10.4 9 x 148.5 9 to 21.5 9 x 35.5 mm; Supported (metrid: Tray 1: 1-44.45; A6; B5 (IIS); Oftico (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Envelope #10; Envelope #10; Envelope B5; Envelope C5; Envelope D4; Custom Size: 51 Envelope B1; Envelope B5; Envelope C5; Envelope D4; Custom Size: 51 Envelope B1; Envelope B5; Envelope C5; Envelope D4; Custom Size: 54 Envelope B1; Envelope B6; Envelope B6; Envelope B1; Envelope B2; Envelope C5; Envelope B2; Envelope B3; Envelope B2; Envelope B3; Envelope B2; Envelope B2; Envelope B3; Envelope B2; E
Memory Media handling Number of paper trays Media types Media types Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements	Standard: 2: Maximum: 3  Paper (plain, EcoEFFICIENT, light, heavy, bond, coloured, preprinted, prepunched, recycled, rough): Envelopes Labels  Custom functio: Tray 1: 76.2 x 127 to 21.5 9 x 35.5 mm; Tray 2.3: 104.9 x 148.59 to 21.5 9 x 35.5 mm; Supported (metrid: Tray 1: 1.44.45; A6; B5 (US); Officio (21.6 x 340 mm); 16K (195 x 270 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Envelope #10; Envelope #10; Envelope B5; Envelope C5; Envelope D1; Custom Size; Statement; Tray 2.8 Tray 3: A4; A5; A6; B5 (US); Officio (21.6 x 340 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Custom Size; A5-R; B6 (US) ADF: A4; Custom sizes 102 x 152 to 21.6 x 356 mm  Standard injust: 100 sheet tray 1, 250 sheet injust ray 2, 50 sheet Automatic Document Feeder (ADF) Standard output: 150 sheet output bin Optional Injust:
Memory Media handling Number of paper trays Media types Media types Media types Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management	Standard: 5.12 MB, Maximum: 5.12 MB  Standard: 2. Maximum: 5.12 MB, Maximum: 5.12 MB  Standard: 2. Maximum: 5.12 MB, Maximum: 5.12 MB  Custom (Interfic): Tray 1: 76.2 x 127 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.49 x 148.59 to 21.59 x 35.5.6 mm; Tray 2. 3: 10.40 x 149.50 to 21.50 x 340 mm; 16K (197 x 273 mm); 16K (197 x
Memory Media handling Number of paper trays Media types Media types Media types Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management	Standard: 2: Maximum: 3  Paper (plain, EcoEFFICIENT, light, heavy, bond, coloured, preprinted, prepunched, recycled, rough): Envelopes; Labels  Custom functio; Tray 1: 76.2 x 127 to 21.5 9 x 35.5 fmm; Tray 2: 3: 104.9 x 148.5 91.0 21.5 9 x 35.5 fmm; Supported (metrid): Tray 1: 144.4 St, 146. B5 (US); Officio (21.6 x 340 mm); 16K (195 x 270 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Envelope #10; Envelope #10; Envelope B5; Envelope C5; Envelope D1; Custom Size; Statement; Tray 2: 8 Tray 3: 44; A5; A6; B5 (US); Officio (21.6 x 340 mm); 16K (195 x 270 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Custom Size; A5-R; B6 (US) ADP: A4; Custom size; A5-R; B6 (US) ADP: A4; Custom size; 10.2 x 15.2 to 21.6 x 356 mm  Standard injut: 100 sheet tray 1, 250 sheet input tray 2, 50 sheet Automatic Document Feeder (ADP) Standard output: 150 sheet output bin Optional Injut: Optional
Memory Media handling Number of paper trays Media types Media types Media types Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Dimensions and weight	Standard: 5.12 MB; Maximum: 5.12 MB  Standard: 2. Maximum: 5.12 MB; Maximum: 5.12 MB  Standard: 2. Maximum: 5.12 MB; Maximum: 5.12 MB  Custom (metric): Tray 1: 76.2 x 127 to 215.9 x 355.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.5 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.5 mm; Tray 2, 2: 104.50 to 216.5 x 340 mm); T6K (195 x 270 mm); 16K (1
Memory Media handling Number of paper trays Media handling Media handling Media size Media size Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W×D×H)®	Standard: 5.12 MB; Maximum: 5.12 MB  Standard: 2. Maximum: 3  Standard: 2. Maximum: 3  Standard: 2. Maximum: 3  Standard: 2. Maximum: 3  Custom (Intertic): Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 148.59 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 149.50 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 149.50 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 149.50 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 149.50 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 149.50 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 149.50 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 149.50 to 215.9 x 355.6 mm; Tray 2. 3: 104.9 x 149.50 to 215.9 x 149.50 to
Memory Media handling Number of paper trays Media types Media size Media size Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>®</sup> Printer dimensions (W x D x H) <sup>®</sup>	Standard 2: 12 Maximum: 3  Paper (plain, EcoEFFICIENT, light, theavy, bond, coloured, preprinted, prepurched, recycled, rough); Envelopes; Labels  Custom (metrich: Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 104.9 x 148.59 to 215.9 x 355.6 mm; Supported (metrich) Tray 1: A4. A5. A6, B5 (ISS), Officio (216 x 340 mm); 16K (195 x 270 mm); 1
Mermory Media handling Number of paper trays Media types Media types Media size Media size Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>9</sup> Printer weight Operating environment	Standard 2: 12 MB (Meximum 3)  Paper (plain, EcoEFFICENT, light, heavy, bond, coloured, preprinted, prepunded, recycled, rough); Envelopes; Labels  Custom (methol: Tray 1: 76.2 x 127 to 215.9 x 355.6 mm; Tray 2, 3: 10.4 9 x 146.59 to 215.9 x 355.6 mm Supported (methol: Tray 1: A4, A5, A6, B5 (US), Offico (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 270 mm); 16K (197 x 273 mm); Envelope Biographic (statem Size, Salatement, Tray 2, B Tray 3. AA, A5, A6, B5 (US), Offico (216 x 340 mm); 16K (195 x 270 mm); 16K (195 x 270 mm); 16K (195 x 273 mm); Envelope Biographic (statem Size, Salatement, Tray 2, B Tray 3. AA, A5, A6, B5 (US), Offico (216 x 340 mm); 16K (195 x 273 mm); Envelope Biographic (statem Size, Salatement, Tray 2, B Tray 3. AA, A5, A6, B5 (US), Offico (216 x 340 mm); 16K (195 x 273 mm); Envelope Biographic (statem Size, Salatement, Tray 2, B Tray 3. AA, A5, A6, B5 (US), Offico (216 x 340 mm); 16K (195 x 273 mm); Envelope Biographic (statem Size, Salatement, Tray 3. Biographic (statem Size, Salatement, Salatem
Memory Media handling Number of paper trays Media types Media stypes Media stypes Media stypes Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible entwork operating systems Minimum system requirements Software included Security management  Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>9</sup> Printer weight Operating environment Storage conditions	Standard 2 Navimum 3 Paper (plan, EcoEFFICIBIT, light, heavy, bond, coloured, preprinted, prepunched, recycled, rough); Envelopes; Labels Custom (netted; Tray 1: 76, 2: 72 to 215, 93, 35, 65, mm; Tray 2; 3: 104, 91, 48, 93, 92, 215, 93, 35, 65, mm; Tray 2; 3: 104, 91, 48, 93, 92, 215, 93, 35, 65, mm; Tray 2; 3: 104, 91, 48, 93, 92, 215, 93, 35, 65, mm; Tray 2; 3: 104, 91, 48, 93, 92, 215, 93, 35, 65, mm; Tray 2; 3: 104, 91, 48, 93, 92, 215, 93, 93, 84, 58, 68, 91, 95, 90, 90, 160; 216, 93, 300 mm; 16K (195 x 270 mm); 16K
Mermory Media handling Number of paper trays Media types Media types Media size Media size Media size Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>9</sup> Printer weight Operating environment	Standard: 2 Maximum: 3  Paper (plain, EcoEFFCENT, light, Newsy, bond, coloured, preprinted, prepunched, recycled, rough): Envelopes; Labels  Custom (metric): Toy 1: 7.62 x 127 to 215.9 x 355 s. Fmm; Tray 2, 3: 104 x 148.59 to 215 x 3 355.6 mm; Supported (metric): Tray 1: 7.44; AS, AB, SB SUIS). Officio (216 x 340 mm); 16K (195 x 270 mm); 16K (194 x 260 mm); 16K (195 x 270 mm); 16K (1
Memory Media handling Number of paper trays Media handling Media handling Media size Media size Media size Media handling Media veight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>®</sup> Printer weight Operating environment Storage conditions Acoustics <sup>10</sup>	Standard: 2 Maximum: 3  Paper (plan. EcoEFFCENT, light, heavy, bond, coloured, preprinted, prepunched, recycled, rough): Envelopes; Labels  Custom finethol: Ting 1: 76.9 x 127 to 215.9 x 355.6 mm; Tay 2, 3: 10.8 x 148.5 bit 0: 15.9 x 355.6 mm; Supported finethol: Tay 1.1 x 44, 85, 46; ESI US). Officio 1216 x 340 mm); 16K (194 x 260 mm); 16K (19
Memory Media handling Number of paper trays Media handling Media handling Media size Media size Media size Media handling Media veight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>®</sup> Printer weight Operating environment Storage conditions Acoustics <sup>10</sup>	Standard: 512 Med Medimum: 512 Med  Standard: 2-Medimum: 3  Pipper (blain, EcoEFFICENT, light, heavy, bond, coloured, preprinted, prepanded, recycled, mugh); Envelopes, Labels  Custom (metric) Tay 1: 762 x 127 to 215 x 3356 mm Tay 2: 3 104 39 x 118,59 to 215 y 3355 mm Tay 2: 130 49 x 121 y 32 x 130 x 34 x 355 mm Tay 2: 130 x 34 x
Memory Media handling Number of paper trays Media types Media types Media types Media handling Media weight Input capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>9</sup> Printer weight Operating environment Storage conditions Acoustics <sup>10</sup> Power <sup>11</sup>	Sandard 2: Maximum 512 MB  Sandard 1: Sandard 3: Sandard
Meriony Media handling Number of paper trays Media handling Media handling Media handling Media size Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Dimensions and weight Printer dimensions (W x D x H) <sup>®</sup> Printer weight Operating environment Storage conditions Acoustics <sup>10</sup> Power <sup>11</sup> Energy savings feature technology	Sandard 2: Maximum 3  Piper (stain, EcoEFFCENT, light, heavy, bond, coloured, preprinted, preputitived, recycled, eough); Enveloper; Labels  Gustom (metric), Tray 1: Tra's 2: Tra's 2: Tra's 2: Stain 5: Stain Error (by 2: Stain 5: Stain Error), 2: 3: Other Stain 5: Stain Error (by 2: Stain 5: Stain Error), 2: Stain 5: Stain Error (by 2: Stain 5: Stain Error), 2: Stain 5: Stain Error (by 2: Stain 5: Stain Error), 2: Stain 5: Stain Error (by 2: Stain 5: Stain Error), 2: Stain 5: Stain Error (by 2: Stain 5: Stain Error), 2: Stain 5: Stain Error (by 3: Stain 5: Stain Error), 2: Stain 5: Stain Error (by 3: Stain 5: Stain Error), 2: Stain 5: Stain Error (by 3: Stain 5: Stain Error), 2: Stain 5: Stain Error (by 3: Stain 5: Stain Error), 2: Stain 5: Stain Error (by 3: Stain 6: Stain Error), 2: Stain 6: Stain Error (by 3: Stain 6: Stain Error), 2: Stain 6: Stain Error (by 3: Stain 6: Stain 6
Merinanding Number of paper trays Media handling Number of paper trays Media hypes Media size Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>9</sup> Printer weight Operating environment Storage conditions Acoustics <sup>10</sup> Power <sup>11</sup> Energy savings feature technology Certifications <sup>12</sup>	Standard 512 MB Medimum 512 MB Medimum 512 MB Standard 2 Medimum 512 MB Standard 2 Medimum 3  Pager Estan EccEFFECER Light, Newsy, band, coloured, presented, preparative, mortal, cought, Emotiopes Lisbels Contain Fearly 1, 19 1/24 - 127 e 21.55 a 21.55 cmm, 1 (a), 2.10 cd a 1, 18 0.00 b 2 (1.6 ) 21.55 a 21.55 cmm, Engage #10 Cinetion Medical Estandard Contains Annual Contains Ann
Meriony Media handling Number of paper trays Media types Media types Media types Media size Media size Media size Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Compatible operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>®</sup> Printer weight Operating environment Storage conditions Acoustics To Power 11 Energy savings feature technology Certifications 13 Sustainable impact specifications	Sandard 2 Maximum 3  Paper (San EcoEFFECRIL Spir I, Inst.) Inst. (COSEPTECRIL Spir I, Inst.) 2 St. 25 A SS. Arms (Tay 2.2 1: 10.4 x 14.5 5 to 21.5 3 x 15.5 a FMS Sport (San English Spo
Memory Media handling Number of paper trays Media hypes Media hypes Media hypes Media hypes Media handling Media weight Input capacity Output capacity Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Dimensions and weight Printer dimensions (W x D x H) <sup>9</sup> Printer weight Operating environment Storage conditions Acoustics <sup>10</sup> Power <sup>11</sup> Energy savings feature technology Certifications <sup>13</sup> Sustainable impact specifications Country of origin	Sandard 212-106 Monthum 512-106  Sandard 2 Maximum 3  Paper (pair, EcosFFECH) Egit, Newly, bond, closured, preprinted, preparanted, recycled, rough); Envelopers: Labels  Castern (meetr) For 17-52-12 To 19-52-12 To 19-53-13 Sis form Tips 2, 2-13 ols 3-14 sis 59-21 Sis 3-35 form Separated (meetr) Tips 11-84-85 (Mill SI USC) (files 02-16-3-30 mm); 164 (199 x 27) mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm); Envelopers (Line Special Sis 50-20 mm); 164 (199 x 27) mm);

#### **Footnotes**

- 1 Some scan apps may require an Internet connection to the printer. Services may require registration. App availability varies by country, language, and agreements. For details, see http://www.hpconnected.com
- <sup>2</sup> Connect printer/MFP to the network and complete customisation through the Embedded Web Server.
- <sup>3</sup> To enable HP Roam, some devices may require firmware to be upgraded and an optional accessory to add Bluetooth® Low Energy (BLE) beaconing capabilities. Subscription or accessory may be required. For more information, visit http://hp.com/go/roam.
- <sup>4</sup> Based on HP review of 2019 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a reboot. For a list of printers, visit http://hp.com/go/PrintersThatProtect. For more information: http://hp.com/go/printersecurityclaims.
- Additional solution such as HP Access Control or HP JetAdvantage Private Print is required to use optional proximity card reader. Pin printing enabled via USB installed in rear of device.
- 6 Instant threat notifications can appear on the device control panel when a potential threat occurs from malicious intent or there is a bug or vulnerability in the firmware code of the device. If this error raises concern, please contact your company IT representative or, if unavailable, HP Support, who can investigate the cause through analysis of device syslog data using a standard SIEM tool from McAfee, Splunk, Arcsight or SIEMonster. The control panel error message may show an error code on a blue screen during code signature checks or memory write intrusions.
- 7 Microsoft and PowerPoint are U.S. registered trademarks of the Microsoft group of companies. Feature works with Microsoft Word and PowerPoint 2003 and later. Only Latin language fonts are supported.
- $^{\rm 8}$  Pin printing enabled via USB installed in rear of device.
- <sup>9</sup> Based on HP Internal testing using normalised TEC Value, 2019.
- <sup>10</sup> HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; may require a firmware upgrade.

#### Technical specifications disclaimers

- <sup>1</sup> Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- <sup>2</sup> Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.
- <sup>3</sup> Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.
- <sup>4</sup> HP recommends that the number of pages per month of imaged output be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.
- <sup>5</sup> First Copy Out from Ready and Simplex Copy Speed measured using ISO/IEC 29183, Duplex Copy Speed measured using ISO/IEC 24735, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application and document complexity.
- <sup>6</sup> Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.
- <sup>7</sup> Rates achieved with Fast (V.34), standard resolution and simple images.
- <sup>8</sup> Local printing requires mobile device and printer to be on the same network (usually Wi-Fi access points bridge wireless to wired connections) or have a direct wireless connection. Wireless performance is dependent on physical environment and distance from access point. Remote printing requires an Internet connection to an HP web-connected printer. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. For more information visit http://www.hp.com/go/mobileprinting. To enable HP Roam, some devices may require firmware to be upgraded and an optional accessory to add Bluetooth® Low Energy (BLE) beaconing capabilities. Subscription may be required. For more information, visit http://www.hp.com/go/roam.
- <sup>9</sup> Without trays and covers extended.
- 10 Acoustic values are subject to change. For current information see http://www.hp.com/support. Configuration tested: base model, simplex printing, A4 paper at an average of 38 ppm.
- 11 Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typically based on measurement of 115 V device.
- 12 TEC is equal to Best TEC. Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115 V device.
- 13 EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
- 14 In box cartridge yield: 3,000 black pages based on ISO/IWC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see: http://www.hp.com/go/learnaboutsupplies. Pages may vary based on customer printing conditions and usage.











## http://www.hp.com/uk

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.



