IEC60335_1W – ATTACHMENT					
Clause	Requirement + Test		Result - Remark	Verdict	

ATTACHMENT TO TEST REPORT IEC 60335-1 (AUSTRALIA / NEW ZEALAND) NATIONAL DIFFERENCES (Household and similar electrical appliances – Safety – Part 1: GENERAL REQUIREMENTS)

Differences according to	AS/NZS 60335.1:2011 + A1:2012 + A2:2014 + A3:2015+A4:2017+A5:2019		
Attachment Form No	AU_NZ_ND_IEC60335_1W		
Attachment Originator	NZ Electrotechnical Committee/Standards New Zealand		
Master Attachment:	Date 2016-11		
Copyright © 2016 IEC System for Conformity Testing and Certification of Electrical Equipment			

(IECEE), Geneva, Switzerland. All rights reserved.

IEC60335_1W – ATTACHMENT					
Clause	Requirement + Test		Result - Remark	Verdict	

	National Differences		
5	GENERAL CONDITIONS FOR THE TESTS		
5.8.1	Test at a.c. 50Hz for a.c. only appliance	Р	
	Test at a.c. 50Hz or d.c., whichever is the more unfavourable supply for a.c. and d.c. appliance	N/A	
6	CLASSIFICATION		
6.1	Protection against electric shock: Class I,II,III: Class II	Р	
7	MARKING AND INSTRUCTIONS		
7.1	After the first paragraph of the requirement insert the following variation:		
	Appliances intended for connection to the supply mains, other than class III appliances, shall be marked with:		
	 - a rated voltage of at least: 230 V for single-phase appliances; 400 V for poly-phase appliances; or 	N/A	
	 a rated voltage range that includes: 230 V for single-phase appliances; 400 V for poly-phase appliances. 	Р	
	For appliances outlets and socket outlets accessible to the user that are incorporated in appliances connected to the supply mains; and	N/A	
	- that operate at rated voltage;	N/A	
	the appliances shall be marked with their maximum outlet load in Watts.	N/A	
7.13	Replace the requirement with the following variation:		
	Instructions and other text required by this standard are written in English.	Р	
7.15	After the last paragraph of the requirement insert the following variation:		
	The marking of the maximum outlet load shall be close to the appliance outlet or socket outlet.	N/A	
10	POWER INPUT AND CURRENT		
10.1	After the last paragraph of the test specification insert the following variation:		
	Appliance outlets and socket outlets accessible to the user that are incorporated in appliances connected to the supply mains; and	N/A	
	that operate at rated voltage;	N/A	
	are not loaded during the test, however their contribution to the power input is considered to be the marked outlet load per appliance outlet or socket-outlet.	N/A	

IEC60335_1W – ATTACHMENT					
Clause	Requirement + Test		Result - Remark	Verdict	
			· · · · · · ·		

11	HEATING		
11.7	After the first paragraph of the test specification insert the following variation:		
	Appliance outlets and socket outlets accessible to the user are loaded with a resistive load that gives the marked outlet load in watts.	N/A	
11.8	After the first paragraph of the test specification insert the following variation:		
	The pins of plug connectors inserted into appliance outlets accessible to the user and plugs inserted into socket outlets accessible to the user shall have a temperature rise not exceeding 45 K.	N/A	
19	ABNORMAL OPERATION		
19.13	After the seventh paragraph of the test specification insert the following variation:		
	During and after the tests the no-load output voltage of an accessible safety extra-low voltage outlet or connector or Universal Serial Bus (USB) outlet shall not have increased by more than 3 V or 10% of its no-load output voltage in normal use, which is higher.	N/A	
22	CONSTRUCTION		
22.2	After the first paragraph of the requirement insert the following variation:		
	For stationary appliances permanently connected to the fixed wiring, compliance with this requirement is considered to be met if the instruction concerning disconnection incorporated in the fixed wiring is in accordance with AS/NZS 3000.	N/A	
22.3	Replace the first paragraph of the test specification with the following variation:		
	Compliance is checked by inserting the pins of the appliance into a socket-outlet capable of accepting a plug complying with Figure 2.1(a) of AS/NZS 3112.	N/A	
	The socket-outlet has a horizontal pivot at a distance of 8 mm behind the engagement face of the socket-outlet and in the plane of the lower intersection of the centre lines of the contact apertures.	N/A	
	Replace the third, fourth and fifth paragraphs of the test specification with the following variation:		
	A new sample of the appliance shall be subjected to and shall comply with the tests in 2.13.9.2 of AS/NZS 3112.	N/A	
22.33	Delete the last sentence of the first paragraph of the requirement and introduce it as a new first paragraph of the requirement.	N/A	

	IEC60335_1W – ATTACHMENT	
Clause	Requirement + Test Result - Remark	Verdict
22.201	Appliances having integral pins for insertion into socket outlets shall comply with the appropriate requirements of AS/NZS 3112.	N/A
	Compliance is checked as specified in Annex J of AS/NZS 3112	N/A
22.202	Appliance outlets and socket outlets accessible to the user that are incorporated in appliances connected to the supply mains; and	N/A
	that operate at rated voltage	N/A
	shall be single-phase and have a current rating not exceeding 16 A.	N/A
	The socket outlets shall comply with AS/NZS 3112;	N/A
	accept a 3-pin, flat-pin plug as described in figure 2.1(a1) of AS/NZS 3112.	N/A
	The appliance outlets and socket outlets shall be protected by one of the following protection devices that has a current rating not exceeding the current rating of the appliance outlet or socket-outlet:	
	- a circuit breaker for equipment complying with IEC 60934;	N/A
	- a manually resettable trip-free or cycling trip-free overcurrent protection device;	N/A
	- a non-user replaceable fuse-link.	N/A
	The protection device shall be placed behind a non-detachable cover. The actuating member of the circuit breaker and the manually resettable protection device may be accessible.	N/A
	The current rating of the appliance outlets and socket outlets is obtained from the marked outlet load in watts divided by the rated voltage.	N/A
	Compliance is checked by inspection and for a manually resettable trip-free or cycling trip-free overcurrent protection device by the following tests:	
	The device shall be operated at rated voltage at 136% of its current rating, in an ambient temperature of $23^{\circ}C \pm 2^{\circ}C$ in a draught-free environment.	N/A
	The device shall operate to interrupt the current within 2 h.	N/A
	The device shall be operated at rated voltage at 600% of its current rating in an ambient temperature of $23^{\circ}C \pm 2^{\circ}C$ in a draught-free environment	N/A
	The device shall operate to interrupt the current within 5 s.	N/A

	IEC60335_1W – ATTACHM	ENT	
Clause	Requirement + Test	Result - Remark	Verdict
	Immediately following the overcurrent tests, the test of clause 16.3 shall be applied, and the device shall comply with the specified requirements of the test.		N/A
	The device shall comply with the ball pressure test of 30.1 carried out at 160 °C.		N/A
	The device shall comply with the glow-wire test of 30.2.3.1 with a test severity of 960 °C.		N/A
25	SUPPLY CONNECTION AND EXTERNAL FLEXIBLE CORDS		
25.1	Supply cords for single-phase portable appliances intended for direct connection to the supply mains, shall be fitted with an appropriate plug complying with AS/NZS 3112.		Р
	SPECIAL NATIONAL CONDITIONS		Р
	Australian		Р
5.201	For appliances, other than class III appliances, that are intended for connections to the supply mains and that are not marked with:		
	- a rated voltage of at least 240 V for single-phase appliances and at least 415 V for three-phase appliances, or		N/A
	- a rated voltage range that includes 240 V for single-phase appliances and 415 V for three-phase appliances,		N/A
	the rated voltage is equal to 240 V for single-phase appliances and 415 V for three phase appliances,		N/A
	and the upper limit of the rated voltage range is equal to 240 V for single-phase appliances and 415V for three-phase appliances.		N/A
	In addition, the rated current or rated power input is equal to the calculated value corresponding to 240 V for single-phase appliances and 415 V for three- phase appliances as appropriate		N/A
24.1.7	Telecommunication interface circuitry must comply with the Telecom Labeling Notice issued under the Telecommunications Act instead of IEC 62151		N/A

-END-