# HP Laser MFP 130 series



## Full-featured laser printing. Entry-level pricing.

Get productive MFP performance at an affordable price. Print, scan, copy, and fax,<sup>1</sup> produce high-quality results, and print and scan from your phone.<sup>2,3</sup>



HP Laser MFP 135a

## Highlights

- Ideal size for any workspace •
- Sharp black text, crisp graphics •
- Print, scan, copy and fax (fax in 'f' model only)
- Speeds up to 20 ppm in A4<sup>2</sup>
- 40-sheet automatic document feeder (137fwg)
- Wireless-network printing (135wg, 137fwg) •
- In box 500 pages initial toner
- Easy mobile printing and scanning with the HP Smart app (135wg, 137fwg)
- Apple AirPrint™, Mopria-certified, Google Cloud Print™ certified





Compact size



Mobile printing



HP Laser MFP 135w

### Legendary quality at an affordable price

- This surprisingly small laser delivers exceptional quality, page after page. •
- Produce sharp text, bold blacks, and crisp graphics. •
- Rely on a high-performance laser MFP at an affordable price. •

#### Designed to fit your space

•

•

- You can fit this MFP almost anywhere – it's that small and compact.
- Get print speeds up to 20 ppm.<sup>4</sup>
  - Get hands-free printing, scanning, copying, and faxing, using the 40-page ADF.<sup>1</sup>
- Get quick and easy printing and faxing directly at the control panel.

#### Easy mobile printing and scanning with HP Smart app

- Get simple setup, and print and scan from your phone, with the HP Smart app.<sup>2,3</sup>
- Easily print from a variety of smartphones and tablets.<sup>3,5</sup> •
- Easily share resources access and print with wireless and Ethernet networking.<sup>3,6,7</sup> ٠
- Connect your smartphone or tablet directly to your printer easily print without accessing • a network.<sup>3,8</sup>

Data sheet | HP Laser MFP 130 series

## **Product walkaround**

#### HP Laser 137fnw shown

- 1. 20 ppm A4
- 2. Flatbed scanner handles up to A4
- 3. 40 page ADF (f models)
- 4. 2-line LCD and keypad (f models) 5. 100 sheet output bin
- 6. Hi-Speed USB 2.0; Fast Ethernet (n models); Fax (f model) ports
- 7. Built-in wireless networking; Wi-Fi Direct printing (w model) 8. 150 sheet input tray
- 9. Pre-installed Original HP Toner cartridge delivers up to 500 pages

## Series at a glance





Model	HP Laser MFP 135a	HP Laser MFP 135w	HP Laser MFP 137fnw
Product number	4ZB82A	4ZB83A	4ZB84A
Memory/processor	128MB/600MHz		
Control panel	2-line LCD and keypad		
Mobile printing	HP's best-in-class mobile printing app - HP Smart App; AirPrint 1.8 enabled; Mopria; Google Cloud Print™		
Connectivity (USB, wireless, Wi-Fi Direct, Ethernet)	USB 2.0 high-speed, no, no, no	USB 2.0 high-speed, yes, yes, no	USB 2.0 high-speed, yes, yes, yes
Recommended Monthly Page Volume	Up to 2,000 pages		
Print speed (A4)	Up to 20 ppm		

# Configurable Items, Accessories, Supplies and Support

Supplies	W1106A HP 106A Black Original Laser Toner Cartridge (~1,000 pages)
	UB4W1E HP 3 year Standard Exchange Service for Laser 135 and 137 series UB4V8E HP 3 year Next Business Day Exchange Service for Laser 135 and 137 series UB4W3E HP 2 year Return to Depot Service for Laser 135 and 137 series UB4W4E HP 3 year Return to Depot Service for Laser 135 and 137 series (UB4W1E + All EMEA countries except ME, Africa, South Africa, Israel, Turkey, Rusia, CIS, UB4V8E - Austria, Belgium, Denmark, Finland, France, Germany, Ireland, Italy, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, UK, Czech Republic, Greece, Hungary, Poland, Slovakia, UB4W3E - ME, Africa, South Africa, Israel, Turkey, UB4W4E - Adriatic, Africa, CIS, EEM, Israel, Slovenia, South Africa, Turkey)

# Technical specifications

Model	HP Laser MFP 135a	HP Laser MFP 135w	HP Laser MFP 137fnw	
Product number	4ZB82A	4ZB83A	4ZB84A	
Functions	Print, copy, scan	•	Print, copy, scan, fax	
Control panel	2-Line LCD; 12 Buttons (Power, Cancel, Start, Navigation(Menu, OK, Back, Left, Right), ID Copy, Contrast, Scale, Info); LED indicator lights (Power, Status)	2-Line LCD; 12 Buttons (Power, Cancel, Start, Navigation (Menu, OK, Back, Left, Right), ID Copy, Contrast, Scan to, Wireless); LED indicator lights (Power, Status, Wireless)	2-Line LCD; 30 Buttons (Power, Cancel, Start, Navigation (Menu, OK, Back, Left, Right), ID Copy, Contrast, Scale, Wireless, Numeric & Tel(1 to 9, 0, *, #, Address Book, Redial, On hook), Mode (Fax, Copy, Scan to); LED indicator lights (Power, Status, Wireless, Mode)	
Print	ŧ	+	ł	
Print technology	Laser			
Print speed <sup>1</sup>	Black (A4, normal) Up to 20 ppm			
First page out <sup>2</sup>	Black (A4, ready): As fast as 8.3 sec ; Black (A4, sleep): As fast as 18 sec			
Print resolution	Black (best): Up to 1,200 × 1,200 dpi ; Technology: ReCP			
Monthly duty cycle <sup>3</sup>	Up to 10,000 pages A4; Recommended monthly page volume <sup>4</sup> : 100 to 2,000			
Printer smart software features	Manual duplex and booklet print, N-up printing, skip blank pages, poster print, watermarks			
Standard print languages	SPL			
Print area	Print margins Top: 5 mm, Bottom: 5 mm, Left: 5 mm, Rig	ht: 5 mm; Maximum print area: 216 x 356 mm		
Duplex printing	Manual (driver support provided)			
Сору				
Copy speed <sup>5</sup>	Black (A4): Up to 20 cpm			
Copier specifications	Copies; Original Size; Reduce/Enlarge; Darkness; Original copies; <b>Reduce/Enlarge</b> : 25 to 400%	Type; Collation; 2-Up; 4-Up; ID Copy; Adjust Background; A	uto Fit Copy; ; <b>Maximum number of copies</b> : Up to 99	
First copy out	A4: As fast as 8.9 sec			
Scan				
Scan speed			Normal (A4): Up to 20 ipm (b&w), up to 7 ipm (color)	
Scan file format	Windows Scan SW supports file format: PDF, JPG, TIFF, PN	IG, BMP	Γ	
Scanner specifications	Scanner type: Flatbed; Scan technology: Contact Image Sensor (CIS); Scan input modes: Front-panel copy, HP MFP scan software, user application via TWAIN or WIA; Twain version: Version 1.9; Optical scan resolution: Up to 600 × 600 dpi		Scanner type: Flatbed, ADF; Scan technology: Contact Image Sensor (CIS); Scan input modes: Front-panel copy HP MFP scan software, user application via TWAIN or WIA; Twain version: Version 1.9; Optical scan resolution: Up to 600 × 600 dpi	
Scanner advanced features	Scan to WSD (network support only); Book Scanning; Pos	ter stitching for multiple scan; Text converting; Scan to E-t	Book; Existing file to E-Book	
Scannable area	Maximum media size (flatbed): 216 x 297 mm;		Maximum media size (flatbed): 216 x 297 mm; Minimur media size (ADF): 145 x 145 mm Maximum media size (ADF): 216 x 356 mm	
Bit depth/ Grey scale levels	8-bit (monochrome) 32-bit (color) / 256		Į · · · ·	
Digital sending	Standard: PC Scan	Standard: Scan to WSD; WSD Scan; PC Scan		
Fax	•	•		
Fax	No,		Yes, black & white and color (send only), 33.6 kbps	
Fax specifications			Fax memory: Up to 400 pages; Fax resolution: Standarc 203 x 98 dpi; Fine: Up to 203 x 196 dpi; 256 levels of grey; Superfine: Up to 300 x 300 dpi; Quick dialing: Up to 200 numbers	
Fax smart software features			Permanent fax memory backup, colour faxing, auto fax reduction, auto redialing, delayed sending, fax forwarding, PC fax, secure receive	
Processor speed	600 MHz			
Connectivity				
Standard	Hi-Speed USB 2.0	Hi-Speed USB 2.0; Wireless 802.11 b/g/n	Hi-Speed USB 2.0; Fast Ethernet 10/100Base-Tx network port; Wireless 802.11 b/g/n	
Optional	None			
Wireless	No	Yes, built-in Wi-Fi 802.11b/g/n		
Mobile printing capability		Apple AirPrint™; Google Cloud Print™; Mobile Apps; Mopr	ia™ Certified; Wi-Fi <sup>®</sup> Direct Printing	
Supported network protocols	No	Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), WSD; Discovery: SLP, Bonjour, WS-Discovery; IP Config: IPv4 (BootP, DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Stateful via DHCPv6); Management: SNMPv1/v2/v3, HTTP		
Network capabilities	No Via built-in 10/100 Base-TX networking		Via built-in 10/100 Base-TX networking	
Memory	Standard: 128 MB; Maximum <sup>6</sup> : 128 MB			

# Technical specifications

Model	HP Laser MFP 135a	HP Laser MFP 135w	HP Laser MFP 137fnw		
Product number	4ZB82A	4ZB83A	4ZB84A		
Media handling	*	•	•		
Number of paper trays	Standard: 1 ; Maximum: 1				
Media types	Plain, Thick, Thin, Cotton, Colour, Preprinted, Recycled, Labels, CardStock, Bond, Archive, Envelope				
Media size	<b>Custom (metric)</b> : 76 × 127 to 216 × 356 mm <b>; Supported (metric)</b> : A4; A5; A5 (LEF); B5 (JIS); Oficio; Envelope (DL, C5)		Custom (metric): 76 x 127 to 216 x 356 mm ; Supported (metric): A4; A5; A5 (LEF); B5 (JIS); Oficio; Envelope (DL, C5) ; ADF: A4, A5, B5, Executive, Letter		
Media handling	Standard input: 150 sheet input tray Standard output: 100 sheet output bin		Standard input: 150 sheet input tray Standard output: 100 sheet output bin ADF: Standard, 40 sheets		
Media weight	60 to 163 g/m <sup>2</sup> ;		60 to 163 g/m <sup>2</sup> ; ADF: 60 to 105 g/m <sup>2</sup>		
Input capacity	Tray 1: Sheets (75 g/m <sup>2</sup> ): 150; Envelopes: 10 Maximum: Up to 150 sheets		Tray 1: Sheets (75 g/m <sup>2</sup> ): 150; Envelopes: 10 Maximum: Up to 150 sheets ADF: Standard, 40 sheets		
Output capacity	Standard: Up to 100 sheets Envelopes: Up to 10 envelopes Maximum: Up to 100 sheets				
Compatible operating systems <sup>7</sup>	Windows 8; Windows 8.1; Windows 10; macOS 10.14 Mojave; macOS 10.13 High Sierra; macOS 10.12 Sierra; macOS 10.11 El Capitan				
Compatible network operating systems	Windows 10; Windows 8; Windows 8.1; macOS 10.11 El Capitan; macOS 10.12 Sierra; macOS 10.13 High Sierra; macOS 10.14 Mojave				
Minimum system requirements	Windows: Windows 10 or newer, Intel <sup>®</sup> Pentium <sup>®</sup> IV 1 GHz 32-bit or 64-bit processor or higher, 1 GB RAM, 16 GB HDD; Mac: OS X v10.11 or newer, AirPrint 1.8 compatible with MacOS 10.11, 1.5 GB available hard disk space, Internet, USB	Windows: PC: Windows <sup>®</sup> 10, 8.1, 8, 2 GB available hard disk space, CD-ROM/DVD drive or Internet connection, USB port, Internet Explorer.; Mac Apple <sup>®</sup> OS X El Capitan (v10.11), macOS Sierra (v10.12), macOS High Sierra (v10.13), 1.5 GB available hard dis space, Internet required, USB			
Software included	Common Installer, V3 Print Driver with Lite SM, TWAIN/WI	A Driver, HP MFP Scan, OCR program	Common Installer, V3 Print Driver with Lite SM, TWAIN/WIA Driver, HP MFP Scan, HP LJ Network PC-FAX, OCR program		
Security management	No	Password-protected network embedded Web server; En change; SNMPV2/V3; IPSec; Filtering: MAC, IPv4, IPv6	able/disable Network ports; SNMPv1 community passworc		
Printer management	None	•			
Dimensions and weight					
Printer dimensions (W × D × H) <sup>8</sup>	<b>Minimum</b> 406 x 359.6 x 253 mm; <b>Maximum</b> : 406 x 424 x	x 253 mm	<b>Minimum</b> 406 x 359.6 x 308.7 mm; <b>Maximum</b> : 421.9 x 424 x 308.7 mm		
Printer weight <sup>9</sup>	7.46 kg 8.58 kg				
	7.40 Ky		8.58 kg		
	Temperature: 10 to 30°C; Humidity: 20 to 70% RH (non-c	condensing)	8.58 kg		
Operating environment	5	condensing)	8.58 kg		
Operating environment Storage conditions Acoustics	Temperature: 10 to 30°C; Humidity: 20 to 70% RH (non-c	condensing)			
Operating environment Storage conditions	Temperature: 10 to 30°C; Humidity: 20 to 70% RH (non-o Temperature: -20 to 40°C		8.58 kg Requirements: 110-volt input voltage: 110 to 127 VAC, 50/60Hz and 220-volt input voltage: 220 to 240 VAC, 50/60Hz. Not dual voltage, power supply varies by part number with # Option code identifier. ; Consumption: 300 watts (Active Printing), 38 watts (Ready), 1.9 watts (Sleep), 0.2 watts (Manual off) ; Power supply type: Internal (Built-in) power supply		
Operating environment Storage conditions Acoustics	Temperature: 10 to 30°C; Humidity: 20 to 70% RH (non-o Temperature: -20 to 40°C Acoustic power emissions: 6.5 B(A) (printing at 20 ppm); Requirements: 220 to 240 VAC, 50/60Hz ; Consumption: 300 watts (Active Printing), 38 watts (Read (Auto Off/Manual On) ;		Requirements: 110-volt input voltage: 110 to 127 VAC, 50/60Hz and 220-volt input voltage: 220 to 240 VAC, 50/60Hz. Not dual voltage, power supply varies by part number with # Option code identifier. ; Consumption: 300 watts (Active Printing), 38 watts (Ready), 1.9 watts (Sleep), 0.2 watts (Manual Off) ;		
Operating environment Storage conditions Acoustics Power <sup>10</sup> Energy savings feature	Temperature: 10 to 30°C; Humidity: 20 to 70% RH (non-o Temperature: -20 to 40°C Acoustic power emissions: 6.5 B(A) (printing at 20 ppm); Requirements: 220 to 240 VAC, 50/60Hz ; Consumption: 300 watts (Active Printing), 38 watts (Read (Auto Off/Manual On) ; Power supply type: Internal (Built-in) power supply	Jy), 1.9 watts (Sleep), 0.2 watts (Manual Off), 0.2 watts UL listed; CE Marking; Nemko; Fimko; Demko; Semko; Eastern European Electromagnetic emission standard: EN 61000-3- 2:2014, EN 61000-3-3:2013, EN55024:2010, EN 55032:2012/AC:2013, 47 CFR Part 15, Subpart B1ANSI	Requirements: 110-volt input voltage: 110 to 127 VAC, 50/60Hz and 220-volt input voltage: 220 to 240 VAC, 50/60Hz. Not dual voltage, power supply varies by part number with # Option code identifier.; Consumption: 300 watts (Active Printing), 38 watts (Ready), 1.9 watts (Sleep), 0.2 watts (Manual Off); Power supply type: Internal (Built-in) power supply		
Operating environment Storage conditions Acoustics Power <sup>10</sup> Energy savings feature technology Certifications Sustainable impact	Temperature: 10 to 30°C; Humidity: 20 to 70% RH (non-or Temperature: -20 to 40°C         Acoustic power emissions: 6.5 B(A) (printing at 20 ppm);         Requirements: 220 to 240 VAC, 50/60Hz ;         Consumption: 300 watts (Active Printing), 38 watts (Read (Auto Off/Manual On);         Power supply type: Internal (Built-in) power supply         HP Auto-Off Technology; Power save         UL listed; CE Marking; Nemko; Fimko; Demko; Semko;         Eastern European         Electromagnetic emission standard: EN 61000-3-         2:2014, EN 61000-3-3:2013, EN55024:2010, EN         55032:2012/AC:2013, 47 CFR Part 15, Subpart B1ANSI (63.4-2009, ICES-003 Issue S, KN32, KN35, GB/T 9254-2008, GB17625-1-2012, CISPR22:2008, CISPR22:2010, CN         CISPR32:2012,CNS 13438, other EMC approvals as	Jul Listed; CE Marking; Nemko; Fimko; Demko; Semko; Eastern European Electromagnetic emission standard: EN 61000-3- 2:2014, EN 61000-3-3:2013, EN55024:2010, EN 55032:2012/AC:2013, 47 CFR Part 15, Subpart B1ANSI C63:4-2009, ICES-003 Issue 5, KN32, KN35, GB/T 9254- 2008, GB17625.1-2012, CISPR22:2008, CISPR32:2012, CNS 13438, other EMC approvals as required by	Requirements: 110-volt input voltage: 110 to 127 VAC, 50/60Hz and 220-volt input voltage: 220 to 240 VAC, 50/60Hz. Not dual voltage, power supply varies by part number with # Option code identifier.; Consumption: 300 watts (Active Printing), 38 watts (Ready), 1.9 watts (Sleep), 0.2 watts (Manual Off); Power supply type: Internal (Built-in) power supply Power save UL listed; CE Marking; Nemko; Fimko; Demko; Semko; Eastern European Electromagnetic emission standard: EN 61000-3- 2:2014, EN 61000-3-3:2013, EN55024:2010, EN 55032:2012/AC:2013, 47 CFR Part 15, Subpart B1 ANSI C63.4-2009, ICES-003 Issue 5, KN32, KN35, GB/T 9254- 2008, GB17625.1-2012, CISPR22:2008, CISPR32:2012, CNS 13438, other EMC approvals as required by individual countries		
Operating environment Storage conditions Acoustics Power <sup>10</sup> Energy savings feature technology	Temperature: 10 to 30°C; Humidity: 20 to 70% RH (non-ofference)         Temperature: -20 to 40°C         Acoustic power emissions: 6.5 B(A) (printing at 20 ppm);         Requirements: 220 to 240 VAC, 50/60Hz;         Consumption: 300 watts (Active Printing), 38 watts (Reactive)         (Auto Off/Manual On);         Power supply type: Internal (Built-in) power supply         HP Auto-Off Technology; Power save         UL listed; CE Marking; Nemko; Fimko; Demko; Semko; Eastern European         Electromagnetic emission standard: EN 61000-3- 2:2014, EN 61000-3-3:2013, EN55024:2010, EN 55032:2012/AC:2013, 47 CFR Part 15, Subpart B1 ANSI C63.4-2009, ICES-003 Issue 5, KN32, KN35, GB/T 9254- 2008, GB17625.1-2012, CISPR22:2008, CISPR32:2012,CNS 13438, other EMC approvals as required by individual countries	Jul Listed; CE Marking; Nemko; Fimko; Demko; Semko; Eastern European Electromagnetic emission standard: EN 61000-3- 2:2014, EN 61000-3-3:2013, EN55024:2010, EN 55032:2012/AC:2013, 47 CFR Part 15, Subpart B1ANSI C63:4-2009, ICES-003 Issue 5, KN32, KN35, GB/T 9254- 2008, GB17625.1-2012, CISPR22:2008, CISPR32:2012, CNS 13438, other EMC approvals as required by	Requirements: 110-volt input voltage: 110 to 127 VAC, 50/60Hz and 220-volt input voltage: 220 to 240 VAC, 50/60Hz. Not dual voltage, power supply varies by part number with # Option code identifier.; Consumption: 300 watts (Active Printing), 38 watts (Ready), 1.9 watts (Sleep), 0.2 watts (Manual Off); Power supply type: Internal (Built-in) power supply Power save UL listed; CE Marking; Nemko; Fimko; Demko; Semko; Eastern European Electromagnetic emission standard: EN 61000-3- 2:2014, EN 61000-3-3:2013, EN55024:2010, EN 55032:2012/AC:2013, 47 CFR Part 15, Subpart B1 ANSI C63.4-2009, ICES-003 Issue 5, KN32, KN35, GB/T 9254- 2008, GB17625.1-2012, CISPR22:2008, CISPR32:2012, CNS 13438, other EMC approvals as required by individual countries		
Operating environment Storage conditions Acoustics Power <sup>10</sup> Energy savings feature technology Certifications Sustainable impact specifications	Temperature: 10 to 30°C; Humidity: 20 to 70% RH (non-ormatic construction)         Temperature: -20 to 40°C         Acoustic power emissions: 6.5 B(A) (printing at 20 ppm);         Requirements: 220 to 240 VAC, 50/60Hz;         Consumption: 300 watts (Active Printing), 38 watts (Read (Auto Off/Manual On);         Power supply type: Internal (Built-in) power supply         HP Auto-Off Technology; Power save         UL listed; CE Marking; Nemko; Fimko; Demko; Semko;         Eastern European         Electromagnetic emission standard: EN 61000-3-         2:2014, EN 61000-3-3:2013, EN55024:2010, EN         55032:2012/AC:2013, 47 CFR Part 15, Subpart B I ANSI         CiSPR32:2012,(CNS 13438, other EMC approvals as required by individual countries         Mercury free	Jul Listed; CE Marking; Nemko; Fimko; Demko; Semko; Eastern European Electromagnetic emission standard: EN 61000-3- 2:2014, EN 61000-3-3:2013, EN55024:2010, EN 55032:2012/AC:2013, 47 CFR Part 15, Subpart B1ANSI C63:4-2009, ICES-003 Issue 5, KN32, KN35, GB/T 9254- 2008, GB17625.1-2012, CISPR22:2008, CISPR32:2012, CNS 13438, other EMC approvals as required by	Requirements: 110-volt input voltage: 110 to 127 VAC, 50/60Hz and 220-volt input voltage: 220 to 240 VAC, 50/60Hz. Not dual voltage, power supply varies by part number with # Option code identifier.; Consumption: 300 watts (Active Printing), 38 watts (Ready), 1.9 watts (Sleep), 0.2 watts (Manual Off); Power supply type: Internal (Built-in) power supply Power save UL listed; CE Marking; Nemko; Fimko; Demko; Semko; Eastern European Electromagnetic emission standard: EN 61000-3- 2:2014, EN 61000-3-3:2013, EN55024:2010, EN 55032:2012/AC:2013, 47 CFR Part 15, Subpart B1ANSI C63.4-2009, ICES-003 Issue 5, KN32, KN35, GB/T 9254- 2008, GB17625.1-2012, CISPR22:2008, CISPR32:2012, CNS 13438, other EMC approvals as required by individual countries		

#### Footnotes

<sup>1</sup> Fax capabilities and ADF only available on p, pn, pnw, and fnw models.

<sup>2</sup> Requires the HP Smart app download. For details on local printing requirements see http://www.hp.com/go/mobileprinting.

<sup>3</sup> Wireless and mobile printing available only on w, nw, pnw, or fnw models.

<sup>4</sup> Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

<sup>5</sup> For details on local printing requirements see http://www.hp.com/go/mobileprinting.

<sup>6</sup> Wireless operations are compatible with 2.4 GHz operations only. Learn more at http://www.hp.com/go/mobileprinting. Wi-Fi is a registered trademark of Wi-Fi Alliance®.

<sup>7</sup> Ethernet networking available only on nw, pn, pnw, or fnw models.

<sup>8</sup> Mobile device needs to be connected to Wi-Fi Direct<sup>®</sup> signal of a Wi-Fi Direct-supported AiO or printer prior to printing. Details at http://www.hp.com/go/mobileprinting. Wi-Fi Direct<sup>®</sup> is a registered trademark of Wi-Fi Alliance<sup>®</sup>.

#### Technical specifications disclaimers

<sup>1</sup> Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

<sup>2</sup> Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

<sup>3</sup> Duty cycle is defined as the maximum number of pages per month of imaged output. <sup>4</sup> HP recommends that the number of pages per month of imaged output be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended

warranty period. <sup>5</sup> First Copy Out and Copy Speed measured using ISO/IEC 29183, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

<sup>6</sup> 128 MB (DDR3-1333).

<sup>7</sup> Windows 7 or higher.

<sup>8</sup> Dimensions vary as per configuration.

<sup>9</sup> Weight varies as per configuration.

<sup>10</sup> Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typically based on measurement of 115V device.

<sup>11</sup> Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device and 230V for Blue Angel.

<sup>12</sup> Introductory cartridges included; Yield: 500 black pages. Replacement cartridge average declared yield 1,000 based on ISO/IEC 19752. Actual yield varies considerably based on content of printed pages and other factors. For details see http://www.hp.com/go/learnaboutsupplies.



© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.