HP DesignJet XL 3600 Multifunction Printer series



Experience a new standard with the most immediate and robust MFP in the market²



IMMEDIATE RESULTS—Fastest first page out²

- Don't wait in front of your printer with the fastest first page out, in just 29 seconds.²
- Free up your time with radically simple and fast batch PDF printing using HP Click software.
- Quickly access your personal and group folders from the touchscreen, so you can print and share right away.³
- Easily digitize your projects with automated scanning, user-centric quicksets, and postediting capabilities.

A NEW STANDARD—Experience extreme reliability

- Built with the most robust design for demanding environments.²
- Best fit for your office with up to 30% smaller footprint and the most quiet operation.⁴
- Flawless user experience thanks to automatic media loading and print stacking up to 100 pages
- Get the lowest running costs, with mono and color prints at the same price and using up to 10X less energy.²

SECURE—World's most secure large-format printer¹

- Rely on the best network protection with features like HP Secure Boot and whitelisting.¹
- Control who accesses the printer and its confidential documents with secure user authentication.
- Keep your fleet secure at any time with HP JetAdvantage Security Manager.

For more information, please visit http://www.hp.com/go/designjetxl3600

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: http://www.hp.com/go/learnaboutsupplies

¹ Advanced embedded security features are based on HP review of 2019 published embedded security features of competitive printers, as of February 2019

² Based on comparable printers using LED technology and capable of printing 4-6 D/A1 pages per minute and which represent more than 70% of the share of low-volume LED printers in the US and Europe according to IDC as of November, 2018. Fastest first page out and up to 10 times less energy consumption based on internal HP testing for specific use scenarios. Operational costs based on low-volume LED technology under \$17,000 USD in the market as of November, 2018. Operational costs consist of supplies and service costs. For testing criteria, see http://www.hp.com/go/designjetxlclaims.

³ Using Linbtweight Directory Access Protocol (10AD)

 ³ Using Lightweight Directory Access Protocol (LDAP).
 4 30% smaller footprint based on comparable printers using LED technology and capable of printing 4-6 D/A1 pages per minute and which represent more than 40% of the share of low-volume LED printers in the US and Europe according to IDC as of November, 2018. Measure done considering operational footprint (with the media drawer open). Most quiet operation based on comparable printers using LED technology and capable of printing 4-6 D/A1 pages per minute and which represent more than 70% of the share of low-volume LED printers in the US and Europe according to IDC as of November, 2018. Most quiet according to internal HP testing of operation mode and ready/sound mode sound pressure (plain paper, line drawing, normal mode) compared to published specifications of competitive printers. For testing criteria, see http://www.hp.com/go/designjetxlclaims.

Technical specifications

HP Thermal Inkjet Line drawings; Maps; Orthophotos; Presentations; Renderings Dye-based (C, G, M, pK, Y); pigment-based (mK) 6 (cyan, gray, magenta, matte black, photo black, yellow) 1 (C, M, Y, G, mK, pK) Up to 2400 x 1200 optimized dpi 0.0008 in (0.02 mm) (HP-GL/2 addressable) 0.07 mm (ISO/IEC 13660:2001(E)) ³ ±0.1% ² 29 sec; Wake-up time less than 10 sec (no warm-up time)
Dye-based (C, G, M, pK, Y); pigment-based (mK) 6 (cyan, gray, magenta, matte black, photo black, yellow) 1 (C, M, Y, G, mK, pK) Up to 2400 x 1200 optimized dpi 0.0008 in (0.02 mm) (HP-GL/2 addressable) 0.07 mm (ISO/IEC 13660:2001 (E)) ³ ±0.1% ² 29 sec; Wake-up time less than 10 sec (no warm-up time)
6 (cyan, gray, magenta, matte black, photo black, yellow) 1 (C, M, Y, G, mK, pK) Up to 2400 x 1200 optimized dpi 0.0008 in (0.02 mm) (HP-GL/2 addressable) 0.07 mm (ISO/IEC 13660:2001(E)) ³ ±0.1% ² 29 sec; Wake-up time less than 10 sec (no warm-up time)
1 (C, M, Y, G, mK, pK) Up to 2400 x 1200 optimized dpi 0.0008 in (0.02 mm) (HP-GL/2 addressable) 0.07 mm (ISO/IEC 13660:2001(E)) ³ ±0.1% ² 29 sec; Wake-up time less than 10 sec (no warm-up time)
Up to 2400 x 1200 optimized dpi 0.0008 in (0.02 mm) (HP-GL/2 addressable) 0.07 mm (ISO/IEC 13660:2001(E)) ³ ±0.1% ² 29 sec; Wake-up time less than 10 sec (no warm-up time)
0.0008 in (0.02 mm) (HP-GL/2 addressable) 0.07 mm (ISO/IEC 13660:2001(E)) ³ ±0.1% ² 29 sec; Wake-up time less than 10 sec (no warm-up time)
0.07 mm (ISO/IEC 13660:2001(E)) ³ ±0.1% ² 29 sec; Wake-up time less than 10 sec (no warm-up time)
±0.1% ² 29 sec; Wake-up time less than 10 sec (no warm-up time)
29 sec; Wake-up time less than 10 sec (no warm-up time)
2
2
11to36-in(279to914-mm) width, 656-ft (200-m) length, 3-in core (default) or 2-in core (optional)
7 in (180 mm)
Up to 19.7 mil Up to 0.5 mm
Bond and coated paper (bond, coated, heavyweight coated, super heavyweight plus matte, colored), technical paper (natural tracing, translucent bond, vellum), film (matte, polyester), photographic paper (satin, gloss, semi-gloss, matte, high-gloss), backlit, self-adhesive (two view cling, indoor paper, polypropylene, vinyl), banner and sign materials (polypropylene, scrim banner)
Sheetfed, CIS (Contact Image Sensor)
Scan: Up to 3 in/sec (7.62 cm/sec) color, 200 dpi, up to 10 in/sec (25.4 cm/sec) grayscale, 200 dpi; Copy: Up to 6 in/sec (15.24 cm/sec) color, 200 dpi, up to 10 in/sec (25.4 cm/sec) grayscale, 200 dpi
Up to 600 dpi
36×315 in (914 $\times8000$ mm) JPEG; 24 $\times590.5$ in (610 $\times15,000$ mm) TIFF; 36×315 in (914 $\times8000$ mm) PDF
0.03 in (0.8 mm)
JPEG, TIFF, PDF (for PostScript Printer)
USB, shared network folder, printer HDD, email
128 GB (file processing) ⁴
Standard, 500 GB (AES-256 encrypted)
Standard: PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7, HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4; Non-PostScript Printer: HP-GL/2, HP-RTL, TIFF, JPEG, CALS G4 Optional: Non-PostScript Printer: Adobe PostScript 3, Adobe PDF 1.7
Gigabit Ethernet (1000Base-T), supporting the following standards: TCP/IP, BootP/DHCP (IPv4 only), DHCPv6, TFTP (IPv4 only), SNMP (v1, v2c, v3), Apple Bonjour Compatible, WS Discovery, Embedded Web Server (HTTP, HTTPS), IPsec, SMTP (email), Raw IP printing (9100), LPD, IPP, WS print, NTLM v2, SMBv3, SSL/TLS, 802.1X authentication (LEAP, PEAP, EAP-TLS), DFS
Direct printing from USB flash drive, print from network shared folder, email printing, HP driver for Windows, HP Print Service for Android, Apple AirPrint driver for macOS and iOS, HF Print for Chrome OS, HP Click, HP Smart App for iOS and Android, HP SmartStream (optional
59 x 26 x 52 in (1500 x 660 x 1310 mm)
64 x 30 x 50 in (1620 x 770 x 1260 mm)
Single-roll: 340 lb (154 kg), Dual-roll: 375 lb (170 kg)
g

Environmental

Operating temperature	41 to 95°F (5 to 35°C)	
Operating humidity	20 to 80% RH	
Acoustics		
Sound pressure	Printing: 42 dB(A); Ready: 32 dB(A); Sleep: < 19 dB(A)	
Sound power	Printing: 5.9 B(A); Ready: 4.9 B(A); Sleep: < 3.7 B(A)	
Power		
Consumption	< 120 W (printing + scanning); 40 W (ready); < 1.0 W (< 14 W with embedded Digital Front End) (sleep); 0.3 W (off)	
Requirements	Input voltage (auto ranging) 100-240 V (±10%), 50/60 Hz (±3 Hz), 2 A	
Certification		
Safety	USA and Canada (CSA certified)	
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES	
Environmental	ENERGY STAR; WEEE; REACH; EPEAT	
Warranty	6KD24A, 6KD26A 90 days; 6KD24H, 6KD26H 3 years	

Ordering information

Product

6KD26G	SKD26G HP DesignJet XL 3600dr 36-in Multifunction Printer with PostScript/PDF	
Accessories		
6CC86A	HP SmartTracker USB for HP XL 3000 Printer series	
6CC86AAE	HP SmartTracker for HP XL 3000 Printer series	
6SE88A	HP SmartStream Print Controller USB for HP XL 3000 Printer series	
6SE88AAE	HP SmartStream Print Controller for HP XL 3000 Printer series HP	
C0C66C	DesignJet PostScript/PDF Upgrade Kit	Ξ
L3J69A	HP SmartStream USB Preflight Manager	Τ

Original HP ink cartridges and maintenance supplies

B3P06A	HP 727 DesignJet Printhead	
P2V89A	HP 766 300-ml Cyan DesignJet Ink Cartridge	
P2V90A	HP 766 300-ml Magenta DesignJet Ink Cartridge	
P2V91A	HP 766 300-ml Yellow DesignJet Ink Cartridge	
P2V92A	HP 766 300-ml Matte Black DesignJet Ink Cartridge	
P2V93A	HP 766 300-ml Gray DesignJet Ink Cartridge	
P2V94A	HP 766 300-ml Photo Black DesignJet Ink Cartridge	

ECO highlights

- Save paper with automatic print settings and image nesting
 ENERGY STAR® certified¹ and EPEAT® registered²
 Free, convenient HP ink cartridge recycling³
 FSC®-certified papers⁴, recyclable HP media; some HP media eligible for take-back program⁵ $^{\rm 1}$ ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental

¹ ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency.

² EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.

³ Program availability varies. Please check http://www.hp.com/recycle for details.

⁴ BMG trademark license code FSC®-C115319, see http://www.fsc.org. HP trademark license code FSC®-C017543, see http://www.fsc.org. HP trademark license code FSC®-C017543, see http://www.fsc.org. HP trademark license code FSC®-C017543, see http://www.fsc.org. HP LFMedia.com. For information about HP large format printing materials, please visit http://www.HPLFMedia.com. S Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific practices. Some HP media are eligible for return through the HP Large Format Media takeback program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.

Please recycle large-format printing hardware and printing supplies. Find out how at our website: http://www.hp.com/ecosolutions

¹ Mechanical printing time. Printed in Fast mode with Economode on, using HP Bright White Inkjet Paper (bond) and Original HP inks.

² ±0.1% of the specified vector length or ±0.2 mm (whichever greater) at 23°C (73°F), 50-60% relative humidity, on A0/E HP Matte Film in Best or Normal mode with Original HP inks.

³ Measured on HP Matte Film.

**Based on 8 GB RAM.

**Based on 8 GB RAM.

PBased on 8 GB RAM.

5 BMG trademark license code FSC®-C115319, see http://www.fsc.org, HP trademark license code FSC®-C017543, see http://www.fsc.org. BMG trademark license code PEFC™/29-31-261, see http://www.pefc.org. HP trademark license code PEFC™/29-31-198, see http://www.pefc.org. Not all FSC®- or PEFC™-certified products are available in all regions.

6 Can be recycled through commonly available recycling programs.

7 Applicable for dual-roll printers only.













