# HP LaserJet Enterprise MFP M430f



HP's entry-level Enterprise-class MFP with speeds up to 40 ppm<sup>9</sup> and strongest security.<sup>1</sup>





## Easy to use, simple to manage

- HP FutureSmart firmware can be updated with the latest features<sup>2</sup> to optimize your investment for years to come.
- Centralize control of your printing environment with HP Web Jetadmin—and help build business efficiency.<sup>3</sup>
- Easily enable workflows across your fleet with a consistent user experience and intuitive, tablet-like icons.
- Set up this MFP fast, and easily manage device settings to help increase efficiency.



## The world's most secure printing<sup>1</sup>

- The operating code (BIOS) is automatically checked during startup and repairs itself if compromised.
- Common Criteria certified<sup>4</sup> to continually monitor memory activity to detect and stop attacks in real time.
- Firmware is automatically checked during startup to determine if it's authentic code—digitally signed by HP.
- The printer's outgoing network connections are inspected to stop suspicious requests and thwart malware.



### Enhanced productivity to empower work teams

- Give workgroups what they need to succeed with hundreds of HP and third-party solutions and card reader support.
- Optimize workflows, reduce steps and errors, and support mobile workers with optional MFP apps that meet your specific business needs.
- Help ensure the security of confidential information with PIN/Pull printing to retrieve print jobs.
- Stay connected with an optional accessory for wireless, <sup>6</sup> Bluetooth <sup>®</sup> Low Energy, and NFC touch-to-print.



#### Sustainability is smart business

- Help save paper right out of the box. Two-sided (duplex) printing is set at default for automatic savings.<sup>7</sup>
- Help reduce wasted paper and toner by only printing jobs that are truly needed, using HP Roam for Business.<sup>8</sup>
- Save energy without sacrificing performance—this MFP is ENERGY STAR® and Blue Angel certified.
- Leverage HP End of Life Solutions to ensure your Hardware and Supplies are sustainably retired.

# **Technical specifications**

The contribution of the Co		
Processor  According to the Company of the Company		<u>'</u>
And well Assembly  And Assembly		
New York Constraints  Annual Constraints  Annu		Print, copy, scan, lax
See 1. May 1. See 1. Se		Automatic (default)
reference of the control of the cont		
The interactions of the Control of t	Print speed <sup>8</sup>	
Per contraction  Find Medical or 1 (2017) 12 (or 100) 15 (or 100)	First page out <sup>9</sup>	Black (A4, ready): As fast as 6.5 sec; Black (A4, sleep): As fast as 8.8 sec
Note authors because of Tables 1 (1962). The process of Tables 1 (1962) is a process of Tables	Print technology	Laser
The carnet description of This Card general causes of The PCC (CPT PCC). If PCC CARD bend I amount of the Card general causes of	Print resolution	
Started primary immunities  IPPE LEAR PACE, SEPPE LEAR PROCESSOR DE Primary Pace (Pace 1997) Primary Pace 1997) Primary Pace (Pace 1997) Primary P	Print resolution technology	300 dpi, 600 dpi, HP FastRes 1200, HP ProRes 1200
Hoter measured  IPP for for counter, 1979 to published or forms. 19 Instructions of counter, 1979 to published and 1979 to published or		
Administration followers all miles were consistent on the Description and product Cells and the Description (College of the Description (Colle	Standard print languages	
Seminated Services of Control (Control	Printer management	
Some statement for the control of th		Naveral (Ad), U. v. 20 and (45 for 160 Å), as to 20 and (25 for 160 Å), as to 25 for 160 Å.
Substitution of the control of the c	Scan speed.	
Substitution (Statistics)  Substitution (Statist	Scanner specifications	(flatbed): $216 \times 297$ mm; Optical scan resolution: Up to 600 dpi; Enhanced Scan Resolution: Up to 600 dpi; Hardware resolution: Up to $600 \times 600$ dpi
Septiment Septim	Scanner advanced features	
Find captivals  Bask RM, mady & find an 27 acro. Bask (PM, mady) & find an 5 2 acro. Bask (PM, mady) &	Сору	
Ties years and the second processor of the among of available bits again for resembling to 100 at 200 gs. Auto framework to second processor on the among of available bits again for resembling to 100 at 200 gs. Auto framework to second processor on the among of available bits again for resembling to 100 at 200 gs. Auto framework to the 100 at 200 gs. Auto framework to the 100 at 200 gs. Auto framework to the 100 at 200 at 200 gs. Auto framework to the 100 at 200 at 200 gs. Auto framework to the 100 at 200 at	Copy speed	Black (A4, normal): Up to 38 cpm; Black (letter, normal): Up to 40 cpm; Black (A4, duplex): Up to 31 cpm; Black (letter, duplex): Up to 33 cpm
Source of Sub-Steps Innoverture in the Author (Service) per page  Face specifications  Face s	First copy out	Black (A4, ready): As fast as 7.2 sec; Black (A4, sleep): As fast as 9.5 sec; Black (letter, ready): As fast as 6.8 sec
Farmenry Deportule on the annual of seatable data Space. Revenue departure of the present of seatable data Space. Revenue departure of the present of space of the present of the prese	Fax <sup>6</sup>	
risk conclusions in globerolation supported five. Surface and conclusions supported five. Surface and conclusions supported five. Surface and conclusions supported five. Surface and conclusions. Surface Surface. The surface and conclusions supported five. Surface and conclusions. Surface Surface. The surface supported five surface S	Fax speed	
Connectivity  2-14-Spared USB 2-2 House 1 Hi-Spared USB 2-0 Device 1 Gigated Ethornel 1 (01100)-0006T retroeck; 1 Fax  White prompting coachilary  4-9 Afferts, Apple Afferting,	Fax specifications	ring detection supported: No; Fax forwarding supported: Yes; Junk barrier supported: Yes, as blocked fax numbers; Maximum speed dialing numbers: Up to 1000 numbers; PC interface
Streets promise products of the Septe of USE 2 Privace   Septe Of Septe 2 Privace   Septe Of	Fax smart software features	Stored faxes; Fax archiving; Fax forwarding; Scale to fit; Fax address book; LAN/Internet fax; Fax number confirmation; Holiday fax schedule
Notice crossbilly  IP ePrints Apple Amen's Apple Amen's March Control (MET) Direct Printing (ET) Couche op your displayment, Recompany (Meteor Apple Amen's Apple	Connectivity	
Octoord, enabled with purchase of a writeries bedwere accessory. Jan band Werkers Station and Will Fillers Entertainting would be with Hill Address of 100 MB EAPPC Werkers Accessory 3 1800 MB EAPPC Werkers Accessory 4 New York Published Entertainting would be with Hill Address of 100 MB EAPPC Werkers Accessory 4 New York Published Entertainting would be with Hill Address of 100 MB EAPPC Werkers Accessory 3 New York Published Entertainting would be with Hill Address of 100 MB EAPPC Werkers Accessory 3 New York Published Entertainting Werkers Accessory 3 New	Standard connectivity	
Sales of Sales (Sales Sales Sa	Mobile printing capability <sup>5</sup>	
Security management  BOLT 1 a highly inventels; sectorizing (Diptional). Security Element (port (Diptional))  Broaded Score appearably  Broaded Score (Processor appearably)  Broaded Score (Processor appearably)  Broaded Score (Processor appearably)  Duty cycle (monthly, AR) (pp to 100.000 pages, Recommended monthly page volume 900 to 4,800 Pages  Broaded Score (Processor appearably)  Duty cycle (monthly, AR) (pp to 100.000 pages, Recommended monthly page volume 900 to 4,800 Pages  Broaded Score (Processor appearably)  Duty cycle (monthly, AR) (pp to 100.000 pages, Recommended monthly page volume 900 to 4,800 Pages  Broaded Score (Processor appearably)  Duty cycle (monthly, AR) (pp to 100.000 pages, Recommended monthly page volume 900 to 4,800 Pages  Broaded Score (Processor Appearably)  Duty cycle (monthly, AR) (pp to 100.000 pages, Recommended monthly page volume 900 to 4,800 Pages  Broaded Score (Processor Appearably)  Duty cycle (monthly, AR) (pp to 100.000 pages, Recommended monthly page volume 900 to 4,800 Pages  Broaded Score (Processor Appearably)  Duty cycle (monthly, AR) (pp to 100.000 pages, Recommended monthly page volume 900 to 4,800 Pages  Duty cycle (monthly, AR) (pp to 100.000 pages, Recommended monthly page volume 900 to 4,800 Pages  Duty cycle (monthly, AR) (pp to 100.000 pages, Recommended monthly pages volume 900 to 4,800 Pages  Duty cycle (monthly, AR) (pp to 100.000 pages, Recommended monthly pages volume 900 to 4,800 Pages (pp to 4,800 Pages ) (pp to 4,8	Wireless capability	3,069A
Strenger Gandard V Processor Streed  800 Miles  Warm-so time  180 Joseph Street	Network capabilities	802.11a/b/g/n wireless networking (Optional); second Ethernet port (Optional).
Nem up time 189 sec Processor speed 180 live:		·
Processor gened  ### Story Cycle (Frontifly)  ### Discretion		
Normary Dime  180 sec  Pages handing  Duty cycle immorthy  Duty cycle immorthy  Duty cycle immorthy  Duty cycle immorthy  150 sheet tray 1,250 sheet may 1,250 sheet and 1,250 sheet may 1,250		
Power function in process of the control of the con	<u>.</u>	
Duty cycle (minorthy) Duty (1904) Duty (19		Tou Sec
Input capacity  100-sheet tray) 1.250-sheet Input tray 2, 50-sheet Automatic Document Feeder (ADF), Optional third 550-sheet tray  Would be of paper trays  Sandrair 2, Marinum 3  Number of paper trays  Sandrair 2, Marinum 3  Media spees  Paper (Dan), Confidential Injut heavy, bond, colored, letterhead, pre-pained, pre-pauched, recycled, rough), envelopes, labels  Tray 1, 50 to 175 gm², tray 2, colored 550-sheet tray 3, 60 to 120 gfore  Nedia seegit  179 1, 50 to 175 gm², tray 2, colored 550-sheet tray 3, 60 to 120 gfore  180 x 15 cm, Ag. 164, envelopes 855, 55 to 1, 65 to 1, 60 to 100 gfore  180 x 15 cm, Ag. 164, envelopes 855, 55 to 1, 65 to 1, 60 to		Duty cycle (monthly Ad): Up to 100,000 pages: Peronmended monthly page volume: 900 to 4,900 Pages
Output capacity  150 -Sheet cutput bin  Number of pages trys:  Pager (plan, coefficient, light, heavy, bond, colored, elettehad, pre-punched, recycled, rough), envelopes, labels  Toy 1, 500 to 17 Signt, troop, and the state of		
Number of paper trays  Media types  Paper [blain, excertificit, light, heavy, bond, colored, letterhead, pre-printed, pre-punched, recycled, roughly, envelopes; babels  Tray 1: 60 to 175 g/m²- tray 2, captional 550-sheet ray 3: 60 to 120 g/m²-  Count fewtor? In 17-17 17		
Media segist  Tray 1: 6.0 to 175 g/m²: tray 2, optional 550-5-line tray 3: 6.0 to 120 g/m²  Louton (metric) 7: 774 x 127 to 216 x 356 m/m; Cap 216	Number of paper trays	Standard: 2; Maximum: 3
Custom (merric). Troy 1: 76 x 127 to 21 ft x 35 fmm; Troy 2: 105 x 14 ft to 21 ft x 35 fmm; Troy 2: 144, 84, 85 ft Sills, 96 ft Sills, 45 to 16 x 34 ft to 21 ft x 35 fmm; Approach (metric). Troy 1: 748, 124 to 16 x 35 fmm; Approach (metric). Troy 1: 748, 124 to 14 to 14 x 34 to 1	Media types	Paper (plain, ecoefficient, light, heavy, bond, colored, letterhead, pre-printed, pre-punched, recycled, rough); envelopes; labels
Media size  10 x 15 cm, A6, 16x, Envelopes (BS, C5 SD, C6, DL SO)t, Custom? 76x 127 to 216 x 356 mm; Tay 2: A4; RA4, A5, B5 (US); B6 (US) A5, 16x (105 x 146 to 216 x 356 mm; ADF letter; legicly clificity, executive, statement; A4; RA4, A5, B5 (US); B6 (US) A5, 16x (105 x 146 to 216 x 356 mm; ADF letter; legicly clificity, executive, statement; A4; RA4, A5, B5 (US); B6 (US) A5, 16x (105 x 146 to 216 x 356 mm; ADF letter; legicly clificity, executive, statement; A4; RA4, A5, B5 (US); B6 (US) A5, 16x (105 x 146 to 216 x 356 mm; ADF letter; legicly clificity, executive, statement; A4; RA4, A5, B5 (US); B6 (US); A5, 16x (105 x 146 to 216 x 356 mm; ADF letter; legicly clificity, executive, statement; A4; RA4, A5, B5 (US); B6 (US); A5, 16x (105 x 146 to 216 x 356 mm; ADF letter; legicly clificity, executive, statement; A4; RA4, A5, B5 (US); B6 (US); A5, 16x (105 x 146 to 216 x 356 mm; ADF); ADF letter; legicly clificity, executive, statement; A4; RA4, A5, B5 (US); B6 (US); A5, 16x (105 x 146 to 216 x 356 mm; ADF); ADF letter; legicly clificity, executive, statement; A4; RA4, A5, B5 (US); B6 (US); A5, 16x (105 x 146 to 216 x 356 mm; ADF); ADF letter; legicly clificity, executive, statement; A4; RA4, A5, B5 (US); B6 (US); A5, 16x (105 x 146 to 216 x 246 t	Media weight	
Printer weight  13.01 kg  Software included  No software solutions are included in the Box only on http://hp.com or http://h23.hp.com  What's in the box'  HP Laser/let Enterprise MFP M430f printer; HP Black Original Laser/let Florer Cartridge (~3,000 pages); Getting started Guide; 1 Power cord  Warranty  One-year, On-site Repair 24-hour / 7 day a week phone support  Systems  Windows Client OS (32/64 bit)—Win 10, Win8 1, Win 7 Ultimate, Mobile OS-, ri05, Android, Mac-, Apple® MacOS High Sierra v10.13, Apple® MacOS Mojave v10.14, Apple® MacOS Catalina v10.15, Discrete PLES Printer Drivers, For more information on the supported operating systems go to the hybrid Systems, For more information on the supported operating systems go to the Systems, For more information on the supported operating systems go to the Systems, For more information on the supported operating systems go to the Systems, For more information on the supported operating systems seem seem seems on the Systems, For more information on the supported operating systems seem seems on the Systems, For more information on the supported operating systems seem seems on the supported operating systems seem seems on the supported operating systems on the supported operating sy	Media size	10 x 15 cm, A6, 16K, envelopes (B5, C5 ISO, C6, DL ISO); Custom: 76 x 127 to 216 x 356 mm; Tray 2: A4; RA4; A5; B5 (JIS); B6 (JIS); A6; 16K; 105 x 148 to 216 x 356 mm; Optional Tray 3: A4;
Software solutions are included  No software solutions are included in the Box only on http://pp.com or http://l.23.hp.com What's in the box  HP Laser Jet Enterprise MFP M430f printer; HP Black Original Laser Jet Tone Cartridge (~3,000 pages); Getting started Guide; 1 Power cord  Warranty  One-year, On-ster Repair 24-hour / 7 day a Week Prone support  Systems  Windows Client OS (32/64 bit)-, Win10, Win8.1, Win7 Ultimate, Mobile OS-, IOS, Android, Mac., Apple** MacOS High Sierra v10.13, Apple** MacOS Mojave v10.14, Apple** MacOS Catalina v10.15, Discrete PLG. Printer Driver., For more information on the supported operating systems on the supported operating systems and search for the Supported potenting systems see seeing of the Supported operating systems see which the Supported operating systems see increased in the Supported operating systems see which the Supported operating systems seed in the Supported operating systems seed in the Supported operating systems seed in the Supported operating systems seed with the Supported operating systems seed in the Supported operating systems seed in the Supported operating systems seed with the Supported operating systems seed under the Supported operating systems seed space seed systems seed to support supported operating syst	Printer dimensions (W x D x H)	420 x 390 x 323 mm
What's in the box    #PL Laser Jet Enterprise MPF M30f printer, IPB Black Oniginal Laser Jet Toner Cartridge (~3,000 pages); Getting started Guide; I Power cord   Warranty   One-year, On-site Repair 24-hour, I7 day a week phone support   Windows Client OS (32/64 bit)-, Win JU Win B., Win T Ultimate, Mobile OS-, iOS, Android, Mac., Apple* MacOS High Sierra v10.13, Apple* MacOS Mighave v10.14, Apple* MacOS Catalina v10.15,  Discrete PCLE Printer Drivers, For more information on the supported operating systems on the http://support.hp.com. Enter your product name and search, Click on User Guides and enter your product name and search for User Guide Search for your Product Name) - User Guide, Search for the Supported Operating Systems see see www.hp.com/get.pdf. Search for the Supported Operating Systems see www.hp.com/get.pdf. Search for the Supported Operating Systems see www.hp.com/get.pdf. Search Search Guide Search for the Supported Operating Systems see www.hp.com/get.pdf. Search Search Guide Search for the Supported Operating Systems see www.hp.com/get.pdf. Search Search Guide Search for the Supported Operating Systems see www.hp.com/get.pdf. Search Search Guide Search for the Supported Operating Systems see www.hp.com/get.pdf. Search Search Search Guide Search for your Product Name) - User Guide, Search for the Supported Operating Systems see www.hp.com/get.pdf. Search Search Search Guide Search for your Product Name) - User Guide, Search for the Supported Operating Systems (Search Search Guide Search for Your Product Name) - User Guide Search for the Supported Operating Systems (Search Search Guide Search for Your Product Name) - User Guide Search for the Search	Printer weight	13.01 kg
Systems  Windows Client OS (32/64 bit)-, Win10, Win8.1, Win7 Ultimate, Mobile OS-, iOS, Android, Mac-, Apple® MacOS High Sierra v10.13, Apple® MacOS Mojave v10.14, Apple® MacOS Catalina v10.15, Discrete PCL6 Printer Driver-, For more information on the supported operating systems go to http://support.bp.com, Enter your product name and search for 10 to your Product on Amen and Search for 10 to your Product on Amen and Search for 10 to your Product Amen and Search for 10 to your Product on Provide Common and Search for 10 to your Product on Provide Common and Search for 10 to your Product on Provide Common and Search for 10 to your Product on Provide Common and Search for 10 to your Product on Provide Common and Search for 10 to your Product on Provide Common and Search for 10 to your Product on Provide Common and Search for 10 to your Product on Provide Common and Search for 10 to your Product on Provide Common and Search for 10 to your Product Operating Systems section, UPD PCL6 / PS Printer Drivers, Supported Operating Systems Section, UPD PCL6 / PS Printer Drivers, Supported Operating Systems Section, UPD PCL6 / PS Printer Drivers, Supported Operating Systems Section, UPD PCL6 / PS Printer Drivers, Supported Operating Systems Section, UPD PCL6 / PS Printer Drivers, Supported Operating Systems Section, UPD PCL6 / PS Printer Drivers, Supported Operating Systems Section (PS PCR6 / PS Associated Operating System	Software included	No software solutions are included in the Box only on http://hp.com or http://123.hp.com
Systems  Windows Client OS (32/64 bit)-, Win10, Win8.1, Win7 Ultimate, Mobile OS-, iOS, Android, Mac., Apple® MacOS High Sierra v10.13, Apple® MacOS Mojave v10.14, Apple® MacOS Catalina v10.15, Discrete PCL6 Printer Driver, For more information on the supported operating systems go to http://support.hp.com, Enter your product name and search, Click on User Guide, Search for User Guide, Search for User Guide, Search for User Guide, Search for Syour (Product Name) – User Guide, Search for the Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Operating Systems section, UPD PCL6 /PS Printer Drivers, Supported Drivers, PCC6 /PS Printer Drivers, Supported Drivers, PCC6 /PS Pri	What's in the box <sup>1</sup>	HP Laser Jet Enterprise MFP M430f printer; HP Black Original Laser Jet Toner Cartridge (~3,000 pages); Getting started Guide; 1 Power cord
Compatible operating systems  Control space oper	Warranty	One-year, On-site Repair 24-hour / 7 day a week phone support
Compatible operating systems  Discrete PCLG Printer Drivers, For more information on the supported operating systems go to http://support.hp.com, Enter your product name and search for your (Product Name) - User Guide, Search for the Supported Operating Systems section, UPD PCLG / PS Printer Drivers, Supported Operating Systems section, UPD PCLG / PS Printer Drivers, Supported Operating Systems see www.hp.com/go/upd  Minimum system requirements  Minimum system requirements  Minimum system requirements  A construction of USB port Internet connection or USB port Internet connection or USB port Internet connection or USB port Internet proveser. For additional OS hardware requirements see microsoft.com; Mac 2 GB available hard drive space Internet connection or USB port Internet connection or USB port Internet requirements see apple.com  Identity management: Kerberos authentication. LDAP authentication. 1000 uses PIS 100 beld door of USB port Internet Systems see apple.com  Identity management: Kerberos authentication. LDAP authentication. Systems see apple.com  Identity management (Expression Systems See apple.com)  Identity management: Kerberos authentication. LDAP authentication. Systems see apple.com  Identity management (Expression See apple.com)  Identity	Systems	
Internet connection or USB port Internet browser. For additional OS hardware requirements see apple.com  Identity management. Kerberos authentication, LDAP authentication, 1000 user PIN codes, Optional HP and 3rd party advanced authentication (EAP-PEAP-EAP-TLS), SNMPV3, HTTPS, Certificates, Access Control List, Data: Storage Encryption, Encrypted PDF & Email (uses FIPS 104 volidated cryptographic libraries from Microsoft), SSL/TLS (HTTPS), Encrypted Credentials, Device: HP Sure Security United Platform Module, HP Connection Inspector, Security lock slot, USB port disablement; Security management: Compatible with HP JetAdvantage Security Manager, Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMS  Fonts and typefaces  105 internal Truel ype fonts scalable in HP PCL, 92 internal scalable fonts in HP PostScript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono World Type); 2 internal Wilndows Vista B Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP Laser Jet Fonts and IPDS Emulation available at Http://www.hp.com/go/laserietfonts  Control panel  4.3° Color Capacitive Touch Control Panel  Display  4.3° diagonal Color TFT-LCD back-list 480 RGB (H) x 272 (V)  Requirements 110-volt input voltage: 110 to 127 VAC (+7-10%), 60 Hz (+7-3 Hz); 220-volt input voltage: 220 to 240 VAC (+7-10%), 50/60Hz (+7-3 Hz) (Not dual voltage, power supply varies by byart number with #B Option code identifier); Consumption: 525 watts to printing), 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical Electricity Consumption (TEC) <sup>1</sup> : 1.222 kWh/week (Blue Angel); 0.463 kWh/week (Energy); 54ar 3.0); Power supply type Internal (Built-in) power supply  Operating temperature range: 15 to 32.5°C; Recommended operating humidity range: 30 to 70% RH  Ecolabels  EPEAT® Silver; CECP; ENERGY STAR® certified <sup>4</sup> Sustainable impact specifications  Accustics  Accustics  Accustics  Accustic	Compatible operating systems	Discrete PCL6 Printer Driver-, For more information on the supported operating systems go to http://support.hp.com, Enter your product name and search, Click on User Guides and enter your product name and search for User Guide, Search for your (Product Name) - User Guide, Search for the Supported Operating Systems section, UPD PCL6 / PS Printer Drivers, Supported Operating
Identity management: Kerberos authentication, LDAP authentication, 1000 user PIN codes, Optional HP and 3rd party advanced authentication solutions (e.g., badge readers); Network: IPsec/firewall with Certificate, Pre-shared Key, Kerberos authentication, Supports Wila-10 IPsec configuration Plug-in, 802.1X authentication (EAP-PEAP; EAP-TLS), SMMPv3, HTTPS, Certificates, Access Control List; Data: Storage fencryptopion, Encrypted DP 8. Email (uses FIPS 140 validated cryptographic libraires from Microsoft), SSL/TLS, (HTTPS), Encrypted Credentials; Device: HP start Secure Boot (BIOS Integrity Checking with self-healing capability), Intrusion Detection (Constant in-device monitoring for attacks), Whitelisting (loads only known good code), Embedded Trusted Platform Module, HP Connection Inspector, Security lock slot, USB port disablement; Security management: Compatible with HP JetAdvantage Security Manager, Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMs  To Sinternal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP PostScript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono World Type); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP Laser Jet Fonts and IPDS Emulation available at Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP Laser Jet Fonts and IPDS Emulation available at Hittp://www.hp.com/golaserjetfonts  Control panel  1.3 "Color Capacitive Touch Control Panel  Display  4.3" diagonal Color TFT-LCD back-lit 480 RGB (H) x 272 (V)  Requirements: 110-volt input voltage; 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage; 220 to 240 VAC (+/- 10%), 50/60Hz (+/- 3 Hz) (Not dual voltage, power supply varies by part number with # Option code identifier); Consumption: 525 wasts (active printing), 1.01 wasts (seep), 0.08 wasts (auto-off-manual-on), 0.08 wasts (au	Minimum system requirements	
Pisec/fireadi with Certificate, Pre-shared Key, Kerberos authentication, Supports WiA-10 IPsec configuration Plug-in, 802.1X authentication (EAP-PEAP; EAP-TEA); SNMPA3, HTTPS, Certificates, Access Control List: Data: Storage Encryption, Encrypted OF & Ermild place of PS 14 Page 14 Pa	>	
105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP PostScript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono World Type); 2 Internal Windows Vista 8 Fonts (Galibri, Cambria); additional font solutions available via third-party flash memory cards; HP Laser Jet Fonts and IPDS Emulation available at Http://www.hp.com/go/laser/jetfonts  Control panel  4.3" Color Capacitive Touch Control Panel  Display  4.3" diagonal Color TFT-LCD back-lit 480 RGB (H) x 272 (V)  Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60Hz (+/- 3 Hz) (Not dual voltage, power supply varies by part number with # 0ption code identifier); Consumption: 525 watts (active printing), 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical Electricity Consumption (TEC) <sup>11</sup> : 1.222 kWh/week (Blue Angel); 0.463 kWh/week (Energy Star 3.0); Power supply type: Internal (Built-in) power supply  Operating temperature range: 15 to 32.5"C; Recommended operating temperature range: 15 to 27°C Operating humidity range: 10 to 90% RH; Recommended operating humidity range: 30 to 70% RH  Ecolabels  EPEAT® Silver; CECP; ENERGY STAR® certified <sup>4</sup> Sustainable impact specifications  Acoustics  Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): inaudible  EC 60950-1:2005 +A1:2009 +A2:2013 (international); EN60950-1:2006 +A11:2009 +A1:2011 +A2:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010 [IEC 62471:2006 ; IEC 62368-1:2014; EN 62368-1:2014 Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS certificate (Germany, Europe); UJ/Cull Listed and UC Coc (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2 Tad Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except	Security management	IPsec/firewall with Certificate, Pre-shared Key, Kerberos authentication, Supports WJA-10 IPsec configuration Plug-in, 802.1X authentication (EAP-PEAP; EAF-TLS), SMMPv3, HTTPS, Certificates, Access Control List; Data: Storage Encryption, Encrypted Drob & Email (uses FIPS 140 validated cryptographic libraries from Microsoft), SSL/TLS (HTTPS), Encrypted Credentials; Device: HP Sure Start Secure Boot (BIOS Integrity Checking with self-healing capability), Intrusion Detection (Constant in-device monitoring for attacks), Whitelisting (loads only known good code), Embedded Trusted Platform Module, HP Connection Inspector, Security lock slot, USB port disablement; Security management: Compatible with HP JetAdvantage Security Manager, Device Security Vision
Acoustics  Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): Inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): Inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): Inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): Inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): Inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acous	Fonts and typefaces	105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP PostScript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono World Type); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria);additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at
Requirements: 110-volt input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 3 Hz); 220-volt input voltage: 220 to 240 VAC (+/- 10%), 50/60Hz (+/- 3 Hz) (Not dual voltage, power supply varies by part number with # 0ption code identifier); Consumption: 525 wasts (active printing), 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical Electricity Consumption (TEC) <sup>11</sup> : 1.222 kWh/week (Blue rape); 0.463 kWh/week (Energy Star 3.0); Power supply type: Internal (Built-in) power supply  Operating temperature range: 15 to 32.5°C; Recommended operating temperature range: 15 to 27°C Operating humidity range: 10 to 90% RH; Recommended operating humidity range: 30 to 70% RH  Ecolabels  EPEAT® Silver; CECP; ENERGY STAR® certified <sup>4</sup> Sustainable impact specifications  Mercury-free  Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): Inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): Inaudible  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2011 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/EC 60825-1:2014 (Class 1 Laser Product); EN 62479:22010/IEC 62479:2010; IEC 62471:2006 / EN 62471:2006; IEC 62486-1:2014; EN 62368-1:2014 (EN 62085-1:2014/EC 60825-1:2014 (Class 1 Laser Product); EN 62479:22010/IEC 62479:2010; IEC 62471:2006 / EN 62471:2	Control panel	4.3" Color Capacitive Touch Control Panel
by part number with # Option code identifier): Consumption: \$25 watts (active printing), 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical Electricity Consumption (TEQ) <sup>11</sup> : 1.222 kWh/week (Blue Angel); 0.463 kWh/week (Energy Star 3.0); Power supply type: Internal (Built-in) power supply  Operating temperature range: 15 to 32.5°C. Recommended operating temperature range: 15 to 27°C Operating humidity range: 10 to 90% RH; Recommended operating humidity range: 30 to 70% RH  Ecolabels EPEAT® Silver; (ECP; ENERGY STAR® certified <sup>4</sup> Sustainable impact specifications Mercury-free  Acoustics Mercury-free  Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): inaudible  IEC 60950-1:2005 +A1:2009 +A2:2013 (International): EN60950-1:2006 +A11:2009 +A1:2011 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010/IEC 62471:2006 / EN 62471:2006 / EN 62471:2006 +A11:2009 +A12:2011 +A12:2011 +A12:2011 +A12:2011 +A12:2011 / EN 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010/IEC 62471:2001 / EN 62471:2006 / EN 62471:2	Display	
Operating environment  Operating temperature range: 15 to 32.5°C; Recommended operating temperature range: 15 to 27°C Operating humidity range: 10 to 90% RH; Recommended operating humidity range: 30 to 70% RH  Ecolabels  EPEAT® Sliver; CECP; ENERGY STAR® certified⁴  Sustainable impact specifications  Mercury-free  Acoustics  Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): Inaudible; Acoustic pressure emissions: 54 dB(A) @ 38 ipm; Acoustic pressure emissions: 64 dB(A) @ 38 ip	Power	by part number with # Option code identifier); Consumption: 525 watts (active printing), 10.1 watts (ready), 1.2 watts (sleep), 0.08 watts (auto-off/manual-on), 0.08 watts (manual off); Typical
Ecolabels EPEAT® Silver; CECP; ENERGY STAR® certified <sup>4</sup> Sustainable impact specifications Mercury-free  Acoustics Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): inaudible; Acoustic pressure emissions: 5.4 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): inaudible  EC 60950-1:2005 +A1:2009 +A2:2013 (international); EN60950-1:2006 +A11:2009 +A1:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010; IEC 62479:2010; IEC 62471:2006; IEC 623588-1:2014; EN 62368-1:2014 (Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, erquirements  Europe); Ul/Cull Listed and UC Coc (US/Ganada); CAN/CSA C2:2 No. 60950-1-07 2 nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD, Web Services Printing, IPP 2.0, Apple AirPrint™, HP ePrint; Discovery; EN Config: IPv4 (Boott) DHCP, AutolP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/Na, HTTP/HTTPS, Syslog; Security: SNMPv3, SSL	Operating environment	Operating temperature range: 15 to 32.5°C; Recommended operating temperature range: 15 to 27°C
Acoustics Acoustic power emissions: 6.4 B(A) @ 38 ipm; Acoustic power emissions (ready): inaudible; Acoustic pressure emissions: 5.4 dB(A) @ 38 ipm; Acoustic pressure emissions bystander (ready): Inaudible  Safety approvals and 62479:2010   IEC 60950-1:2005 +A1:2009 +A2:2013 (international); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62369-1:2014   EN 62368-1:2014	Ecolabels	
Inaudible  IEC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2011 +A2:2011 +A2:2013 (EU); EN 60825-1:2014/IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010/IEC 62479:2010/IEC 62479:2010/IEC 62471:2008 (EC 62368-1:2014; EN 62368-1:2014 Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD, Web Services Printing, IPP 2.0, Apple AirPrint™, HP ePrint; Discovery; SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (Boottp, DHCP, Autol), Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/N3, HTTP/HTTPS, Syslog; Security: SNMPv3, SSL	Sustainable impact specifications	
Safety approvals and requirements 62479:2010/IEC 62479:2010, IEC 62471:2006 / EN 62471:2008; IEC 62368-1:2014; EN 62368-1:2014Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UI/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations pursuant to Laser notice No. 50, Dated June 24, 2007; Other safety approvals as required by individual countries.  Supported network protocols  Supported network protocols  Supported network protocols	Acoustics	Inaudible
Supported network protocols Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/v3, HTTP/HTTPS, Syslog; Security: SNMPv3, SSL	Safety approvals and	62479:2010/IEC 62479:2010; IEC 62471:2006 / EN 62471:2008; IEC 62368-1:2014; EN 62368-1:2014Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 2nd Ed. 2011-12; Compliance with Laser safety standards 21 CFR 1040.10 and 1040.11 except for deviations

## Ordering information

#### Accessories

Number	Description	
3JN69A	HP Jetdirect 3100w BLE/NFC/Wireless Accessory	
4QL32A	HP Legic Secure USB Reader	
8FP31A	HP Jetdirect LAN Accessory	
8ZN00A	HP HIP2 Card Reader Accessory Kit	
B5L31A	HP Foreign Interface Harness	
D9P29A	HP LaserJet Pro 550-sheet Feeder Tray	
X3D03A	HP Universal USB Proximity Card Reader	
Y7C05A	HP HIP2 Keystroke Reader	

### **HP Care Packs**

Number	Description
U11D7E	HP 3 year Next Business Day Service for LaserJet Enterprise MFP M43x
U11D8E	HP 4 year Next Business Day Service for LaserJet Enterprise MFP M43x
U11D9E	HP 5 year Next Business Day Service for LaserJet Enterprise MFP M43x
U11DBE	HP 3 year 4 hour 9x5 Service for LaserJet Enterprise MFP M43x
U11DCE	HP 4 year 4 hour 9x5 Service for LaserJet Enterprise MFP M43x
U11DDE	HP 5 year 4 hour 9x5 Service for LaserJet Enterprise MFP M43x
U11DME	$\mbox{HP}$ 3 year Parts Exchange Service for Laser Jet Enterprise MFP M43x (Managed Component Only)
U11DNE	HP 4 year Parts Exchange Service for LaserJet Enterprise MFP M43x (Managed Component Only)
U11DQE	HP 5 year Parts Exchange Service for Laser Jet Enterprise MFP M43x (Managed Component Only) $$
U11DRPE	HP 1 year Post Warranty Next Business Day Service for LaserJet Enterprise MFP M43x
U11DSPE	HP 2 year Post Warranty Next Business Day Service for LaserJet Enterprise MFP M43x
U11DTPE	HP 1 year Post Warranty 4 hour 9x5 Service for LaserJet Enterprise MFP M43x
U11DVPE	HP 2 year Post Warranty 4 hour 9x5 Service for LaserJet Enterprise MFP M43x
U11DZPE	HP 1 year Post Wty Parts Exchange Service for LaserJet Enterprise MFP M43x (Managed Component Only)
U11E0PE	HP 2 year Post Wty Parts Exchange Service for LaserJet Enterprise MFP M43x (Managed

Protect your investment with HP Care Pack. Let HP certified engineers resolve your technical issues. For more details on HP Care Pack, go to hp.com/go/cpc















#### Supplies and Media

Number	Description
4WN07A	HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/Tabloid/11 x 17 in
4WN08A	HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/Letter 8.5 x 11 in
7MV81A	HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/A3/297 x 420 mm
7MV82A	HP Everyday Laser Glossy FSC Paper 120 gsm-150 sht/A4/210 x 297 mm
CF276A	HP 76A Black Original LaserJet Toner Cartridge (~3,000 pages)
CF276X	HP 76X High Yield Black Original LaserJet Toner Cartridge (~10,000 pages)

Contact HP via phone: Asia: 65 6253 8500

## HP Inc. offices

Australia 13 10 47 hp.com.au China (010) 6564 3888 hp.com.cn Hong Kong (852) 3077 2688 hp.com.hk India (80) 2612 9000 hp.com/in Indonesia (62-21) 579 1088 hp.com/idw Korea (02) 2199 0114 hp.co.kr Malaysia (603) 2332 3333 hp.com.my New Zealand (09) 0800 449 553 hp.con.z Philippines (632) 888 5900 hp.com/ph Singapore (65) 6275 3888 hp.com.sg Taiwan (02) 3789 9900 hp.com/tw Thailand (662) 353 9500 hp.com/th Vietnam (848) 3823 4151 hp.com/vn

#### Solutions

For more solutions information, please visit hp.com/go/gsc

#### **Footnotes**

- <sup>1</sup> HP's most advanced embedded security features are available on HP Managed and Enterprise devices with HP FutureSmart firmware 4.5 or above. Claim based on HP review of 2019 published features of competitive in-class printers. Only HP offers a combination of security features to automatically detect, stop, and recover from attacks with a self-healing reboot, in alignment with NIST SP 800-193 quidelines for device cyber resiliency. For a list of compatible products, visit
- hp.com/go/PrintersThatProtect. For more information, visit hp.com/go/PrinterSecurityClaims

  Some features enabled by future HP FutureSmart firmware upgrades may not be available on older devices, if for example, physical product characteristics limit the functionality of the new feature.
- <sup>3</sup> HP Web Jetadmin is free and available for download at hp.com/go/webjetadmin

  <sup>4</sup> Third-party certification based on Common Criteria Information Technology Security Evaluation ISO/IEC 15408 Standard requirements as of May 2019. Certification applicable to HP Managed and Enterprise devices running HP FutureSmart Firmware version 4.5.1 and later. For more information: https://www.commoncriteriaportal.org/files/epfiles/Certification%20Report%20-%20HP%20Intrusion%20Detection.pdf
- Suse of the HP Trusted Platform Module may require a firmware upgrade.

  Wireless performance is dependent on physical environment and distance from access point and may be limited during active VPN connections.
- Dependent upon country setup specifications.
- <sup>8</sup> To enable HP Roam, some devices may require firmware to be upgraded and an optional accessory to add Bluetooth® Low Energy (BLE) beaconing capabilities. Subscription may be required. For more information, visit hp.com/go/roam
- 9 Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document

#### Technical specifications disclaimers

- 1 For vield information on the cartridge included with your printer, see http://www.hp.com/go/tonervield. Yield values measured in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors.

  <sup>2</sup> Declared yields based on ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/toneryield
- 3 Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit: http://www.hp.com/go/learnaboutsupplies 4 EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.
- <sup>5</sup> To enable HP Roam, some devices may require firmware to be upgraded and an optional accessory to add Bluetooth® Low Energy (BLE) beaconing capabilities. Customer can purchase the HP Jetdirect 3100w BLE/NFC/Wireless accessory or the RadBeacon USB. Subscription may be required. For more information, visit http://www.hp.com/go/roam

  <sup>6</sup> Based on standard ITU-T test image #1 at standard resolution. More complicated pages or higher resolution will take longer and use more memory.
- <sup>7</sup> Measured using ISO/IEC 24734 Feature Performance Test, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity. <sup>8</sup> Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document
- First Copy Out from Ready and Simplex Copy Speed measured using ISO/IEC 29183, Duplex Copy Speed measured using ISO/IEC 24735, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims.
- Exact speed varies depending on the system configuration, software application, document complexity, media size, media orientation and media type.

  10 Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device and 230V for Blue Angel.
- 11 Sample Data: Typical Electricity Consumption (TEC) rating represents the typical electricity consumed by a product during 1 week, measured in kilowatt-hours (kWh).
- 12 Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.

#### To learn more, visit hp.com