ThinkStation P340 Tower **30DH00HFUK**

Product

ThinkStation P340 Tower

Region WE

Country/Region

Machine Type 30DH

TopSeller TopSeller

Processor Intel Xeon W-1270P (8C / 16T, 3.8 / 5.1GHz, 16MB)

Integrated Graphics Intel UHD Graphics P630

Discrete Graphics None

Chipset Intel W480

HDD Controller Onboard Intel RST SATA RAID

M.2 SSD RAID Controller Onboard Intel RSTe PCIe

Memory 2x 8GB UDIMM DDR4-2933 ECC

Internal Disk Drive None

M.2 SSD Drive 1x 512GB SSD M.2 PCIe NVMe Opal

Optane Memory None

Optical 9.0mm DVD±RW

Media Reader SD Reader

Onboard Ethernet 1x GbE RJ-45

Additional Ethernet None

WLAN + Bluetooth None

Optional Rear Ports None

Chassis Intrusion Switch Chassis Intrusion Switch

Cover Lock

Cable Lock

Keyboard

USB Traditional Keyboard, English (UK)

Mouse USB Calliope Mouse

Power Supply 500W 92%

System Management Intel vPro with AMT 14

Operating System Windows 10 Pro 64 for Workstations, English

Bundled Software

Base Warranty 3-year, Onsite

Bundled Service

EAN/UPC/JAN 0195235616888

End of Support 2028-07-30

Announce Date 2020-07-17

Recommended Services

Best 5Y Premier Support Upgrade from 3Y Onsite (5WS0T36135)

Better 4Y Premier Support Upgrade from 3Y Onsite (5WS0T36136) Good

3Y Premier Support Upgrade from 3Y Onsite (5WS0U26646)

L WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.

https://psref.lenovo.com

Visit psref website for the latest version of

Product specifications Reference. © Lenovo, 2020. All rights reserved.





ThinkStation P340 Tower Platform Specifications

Lenovo

Components	Specification						Components	Specification
Form factor	17L Tower							Disk Type Interface RPM Offering Max Qty
Dimensions	Height: 376 mm (14.8 in). Width: 170 mm (6.7 in). Depth: 315.35 mm (12.4 in)						Storage Support	3.5" SATA HDD SATA 6Gb/s 7.2K 1TB/2TB/4TB/6TB 2
								2.5" SATA HDD SATA 6Gb/s 7.2K 1TB FIPS 4
Weight	Maximum configuration: 20.7 lb (9.4 kg)						-	2.5" SATA SSD SATA 6Gb/s - 512GB/1TB 4
Processor Sockets								M.2 PCIe SSD PCIe NVMe - 256GB/512GB/1TB/2TB 4
Processor Support	Support Up to one Xeon, Core i9, i7, i5, or i3 processor							Bay 1 First 3.5" disk bay
Processor	Processor Number Cores Threads Base Frequency Cache TDP Memory Types ECC Processor Graphics vPro					vPro		Bay 2 First 2.5" SATA bay
	Xeon W-1290P 10		Hz 20MB 125W Hz 20MB 80W Hz 16MB 125W	/ DDR4-2933 Yes DDR4-2933 Yes / DDR4-2933 Yes	UHD P630 UHD P630 UHD P630	Yes	Storage Bays	Bay 3 Secondary 3.5" disk bay
	Xeon W-1290 10							Bay 4 Secondary 2.5" disk bay
	Xeon W-1270P 8							Bay 5 9mm Slim ODD bay
	Xeon W-1270 8			DDR4-2933 Yes				Bay 6 Media reader
	Xeon W-1250P 6 Xeon W-1250 6	12 4.1GHz 12 3.3GHz		DDR4-2666 Yes				
	Core i9-10900K 10			DDR4-2000 105				M.2 4x M.2 SSD (2 onboard. 2 via PCIe to M.2 adapter)
	Core i9-10900 10			DDR4-2933 No			Media reader	Optional SD reader on most models
	Core i7-10700K 8			/ DDR4-2933 No		Yes	Network	One onboard GbE port via integrated gigabit ethernet Intel i219LM, supports Wake-on-LAN. Optional PCIe ethernet adapters are available
	Core i7-10700 8	16 2.9GHz		DDR4-2933 No		Yes	interfaces	· · · · · ·
	Core i5-10600K 6			/ DDR4-2666 No			WLAN + Bluetooth	Optional Intel Wi-Fi 6 AX201, 2x2, 2.4GHz/5GHz (160MHz channels), WiFi 6, Bluetooth 5
	Core i5-10600 6			DDR4-2666 No		-		Power-on and admin password. Trusted Platform Module, TCG 2.0 compliant.
	Core i5-10500 6 Core i5-10400 6			DDR4-2666 No DDR4-2666 No		Yes No	Security features	Optional chassis intrusion switch, E-lock, cable lock, Kensington lock, and pad
	Core i3-10320 4			DDR4-2666 No		-		lock
	Core i3-10300 4			DDR4-2666 No			Intel vPro	Supports Intel vPro on Xeon and selected Core i7 or i5 models.
	Core i3-10100 4 8 3.6GHz 6MB 65W DDR4-2666 No UHD 630 No							vPro also requires AX201 if Wi-Fi function is needed
Chipset	Intel W480 Chipset						Intel AMT	Intel Active Management Technology 14 on vPro models, Intel Standard Manageability on other models
Memory Sockets	4 DIMM sockets with 2 channels							Most models comes with 3-year limited onsite service with 9x5/NBD.
Memory Types	/pes 8GB/16GB/32GB DDR4-2933 UDIMM ECC, or 4GB/8GB/16GB/32GB DDR4-2933 UDIMM non-ECC						Base warranty	Other models may have 1 or 2-year limited onsite service with 9x5/NBD.
Memory Capacity							HD Audio	Intel HD Audio interface with Realtek ALC623 Codec
	ection ECC. ECC memory and ECC-enable CPU are needed							2x USB-A 3.2 Gen 1. 2x USB-A 3.2 Gen 2. 1x USB-C 3.2 Gen 1. 1x Mic-in. 1x
,	Three PCIe 3.0 slots as following:						Front ports	
Expansion slots	Slot 1 PCle 3.0 x16, full height, full length, links to CPU						Rear ports	2x USB-A 3.2 Gen 1. 2x USB-A 2.0. 1x RJ-45. 1x COM. 2x DP. 1x Audio line-out
	Slot 2 PCle 3.0 x1, full height, full length, links to PCH							Supports the following via cable:
	Slot 3 PCIe 3.0 x16 (negotiable link width x4), full height, full length, links to PCH							1x COM. 1x Parallel. 2x PS/2. 1x video (DP. HDMI, or USB-C). 2x USB 2.0.
								Supports the following via PCIe adapter:
	Integrated Intel UHD Graphics P630 in Xeon processors, or Intel UHD Graphics 630							4x COM*. 1x USB-C 3.2 Gen 2. 2x USB-A 3.2 Gen 1*. 1x Thunderbolt
Processor graphics	in Core processors. Works along with discrete graphics to support multi-display, enables three rear							Notes: 4x COM and 2x USB-A 3.2 Gen 1 are special bids only.
	display connectors (2 DP standard, 1 video port optional (Video port can be DP, HDMI, or USB-C)						Temperature	Operating: 50 °F to 95 °F (10 °C to 35 °C) Non operating (no package): 14 °F to 140 °F (-10 °C to 60 °C)
								Non operating (with package): -40 °F to 140 °F (-40 °C to 60 °C)
Discrete Graphics Offering	Graphics	Memory	Power	Connector		Max		Operating: -15.2 m (-50 ft) to 3048 m (10 000 ft).
	Quedre D400		00)4/	Ou minipp		Qty	Altitude	Storage: -15.2 m (-50 ft) to 10, 668 m (35 000 ft)
	Quadro P400	2GB GDDR5 2GB GDDR5	30W 40W	3x miniDP 4x miniDP		2	Humidity	Operating: 30%~90%, non-condensing
	Quadro P620 Quadro P1000	4GB GDDR5	40W 50W	4x miniDP 4x miniDP		2	· · · · · · · · · · · · · · · · · · ·	Storage (with package): 20%~90%, non-condensing
	Quadro P1000 Quadro P2200	5GB GDDR5X		4x miniDP 4x DP		2	Environmental	RoHS-compliant, EPEAT Silver rating, and ENERGY STAR 8 qualified
	Quadro RTX 4000	8GB GDDR5	-	3x DP, 1x Virtua	all ink	1	certification	
	Quadro RTX 5000 16GB GDDR6 265W 4x DP, 1x VirtualLink 1					1	Power supply	Supports one of the following: • 300W, 90% PSU, 100V - 240V, 80 PLUS Gold gualified
	Notes: RTX 4000/RTX 5000/2x P2200 needs 500W PSU.							 500W, 90% PS0, 100V - 240V, 80 PLUS Gold qualified 500W, 92% PSU, 100V - 240V, 80 PLUS Platinum gualified
	Storage Controller Type Interface Disk Type RAID						ISV certifications	Please visit www.thinkworkstations.com/isv-certifications/
Storage Controller	Onboard Intel RST SATA RAID Std SATA 6Gb/s HDD or SSD 0/1/10/5						Note:	
	Onboard Intel RST PCIe RAID Std PCIe NVMe M.2 PCIe SSD 0/1						1. Depending on many factors, actual data transfer speed mentioned on this page may be lower than theoretical speed. 2. Any questions or advice on ThinkStation PSREF, please contact Lenovo workstation PSREF developer	
	Notes: RAID 5 and 10 are available on 2.5" HDD/SSD.							
L	Notes. HAID 5 and 10 ale							

ThinkStation P340 Tower











