PROFESSIONAL MACHINES FOR ADVANCED USERS



ThinkStation P3 Series workstations provide affordable power-computing with a choice of processor technologies, expansion bays and support for multiple storage drives.

ThinkStation P340 Tower

For a modest budget advanced users can get this compact workstation and scale performance capabilities as they need. Although 5% smaller than the previous generation, it supports the latest 125W multi-core processors, up to NVIDIA Quadro RTX5000 graphics, 4 internal SATA drives plus up to 4x M.2 SSD. Users can quickly screen and identify potential system errors with the ThinkStation Diagnostics tool.



REASONS TO BUY

Lenovo Performance Tuner enables users to fine-tune power management, BIOS, processor priority, graphics features and more. Save settings in softwarespecific profiles or use the predefined profiles created by our experts for popular applications like ANSYS, AutoDesk and Solidworks.

Smarter

for all

technology

Lenovo

Select Intel Xeon W processors and error-free ECC memory configurations to support data analysis workloads.

For graphic design, configure with multiple PCIe SSD drives, up to a 125W Intel Xeon processor and advanced NVIDIA Quadro graphics.

ThinkStation P340 Tower

KEY SPECIFICATIONS

REF ST ECHTCATIONS			
Processor	up to Intel Xeon W-1290P or 10th Gen Intel Core i9 processor		
Operating System	Powered by Windows 10 Pro for Workstations		
Max Graphics	up to 1x NVIDIA Quadro RTX 5000		
Memory	up to 128GB DDR4-2933 ECC or 128GB DDR4-2933 non-ECC		
Max Storage Drives	Internal storage: 14TB (2x 6TB 3.5"" SATA HDD + 2x 1TB 2.5"" SATA HDD/SSD) or 4TB (4x 2.5"" 1TB SATA SSD/HDD) M.2 SSD: 8TB (4x 2TB M.2 PCIe NVMe SSD - 2 onboard & 2 via PCIe to M.2 adapter) Overall storage capacity depends on mix of Internal, M.2, PCIe cards ar other options installed		
Storage Types Supported	3.5"" SATA HDD 6Gb/s 7.2k RPM up to 6TB 2.5"" SATA HDD 6GB/s 7.2k RPM up to 1TB FIPS 2.5"" SATA SSD 6GB/s up to 1TB Optane Memory PCIe NVMe 32GB M.2 PCIe NVMe SSD up to 2TB RAID 0/1/10/5 supported		
Storage Controllers	Onboard Intel RST SATA RAID Onboard Intel RSTe PCIe		
Optical	optional DVD Burner		
Power Supply	One of the following 300W 90% 500W 92%		
Dimensions	Width: 170mm (6.7"") Depth: 315.35mm (12.4"") Height: 376mm (14.8"")		
Weight	Max configuration: 9.4kg (20.7lb)		
Weight	Max configuration: 9.4kg (20.7lb)		

GREEN CERTIFICATIONS

GREENGUARD. EPEAT Silver rating. ENERG

CONNECTIVITY

on W-1290P or 10th Gen Intel Core i9 processor	Front I/O	2x USB 3.2 Gen 1, 2x USB 3.2 Gen 2, 1x USB-C 3.2 Gen 1, mic-in,	
Vindows 10 Pro for Workstations		audio combo jack	
DIA Quadro RTX 5000	Rear I/O	2x USB 3.2 Gen 1, 2x USB 2.0, ethernet (RJ-45), 1x COM, 2x DisplayPort, audio line-out	
DDR4-2933 ECC or 128GB DDR4-2933 non-ECC	Optional Rear Ports	$ \begin{array}{l} One \ of \ the \ following \\ 1x \ PS/2 \ \ 1x \ PS/2 \ + \ 1x \ Thunderbolt \ \ 1x \ PS/2 \ + \ 1x \ Video \ port, \ DP \ \\ 1x \ PS/2 \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ PS/2 \ + \ 1x \ Video \ port, \ USB-C \ \\ 1x \ Parallel \ \ 1x \ Parallel \ + \ 1x \ VSB-C \ \ 1x \ Parallel \ + \ 1x \ Video \ port, \ USB-C \ \\ 1x \ Parallel \ \ 1x \ Serial \ + \ 1x \ Serial \ + \ 1x \ Parallel \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ Serial \ + \ 1x \ Parallel \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ Serial \ + \ 1x \ Parallel \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ Serial \ + \ 1x \ Parallel \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ Serial \ + \ 1x \ Parallel \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ Serial \ + \ 1x \ Parallel \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ Serial \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ Serial \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ USB-C \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ USB-C \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ USB-C \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ USB-C \ + \ 1x \ Video \ port, \ HDMI \ + \ 1x \ Serial \ + \ 1x \ Video \ port, \ HDMI \ \ 1x \ USB-C \ + \ 1x \ Video \ port, \ HDMI \ + \ 1x \ Serial \ + \ 1x \ Video \ port, \ HDMI \ + \ 1x \ Serial \ + \ 1x \ Video \ port, \ HDMI \ + \ 1x \ Serial \ + \ 1x \ Serial \ + \ 1x \ Video \ port, \ HDMI \ + \ 1x \ Serial \ + \ 1x \ Serial \ + \ 1x \ Video \ port, \ HDMI \ + \ 1x \ Serial \ + \ 1x \ Serial \ + \ 1x \ Video \ port, \ HDMI \ + \ 1x \ Video \ port, \ HDMI \ + \ 1x \ Serial \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB-C \ + \ 1x \ Video \ port, \ USB \ 2.0 \$	
ge: 14TB (2x 6TB 3.5"" SATA HDD + 2x 1TB 2.5"" D) or 4TB (4x 2.5"" 1TB SATA SSD/HDD) (4x 2TB M.2 PCIe NVMe SSD - 2 onboard & 2 via dapter) capacity depends on mix of Internal, M.2, PCIe cards and istalled			
DD 6Gb/s 7.2k RPM up to 6TB DD 6GB/s 7.2k RPM up to 1TB FIPS D 6GB/s up to 1TB ory PCIe NVMe 32GB Me SSD up to 2TB 5 supported			
I RST SATA RAID I RSTe PCIe			
Burner			
owing 0000 92%			
n (6.7"") Depth: 315.35mm (12.4"") Height: 376mm			
ation: 9.4kg (20.7lb)		USB 3.0 + 1x Video port, USB-C	
	WLAN + Bluetooth	Intel AX201 11ax, 2x2 + BT5.1	
	SECURITY & PRIVACY		
RGY STAR 8.0, 80 Plus Platinum (500W, 300W PSU)	Chassis Intrusion Switch		

Chassis Intrusion Switch Cable Lock E-Lock Kensington lock slot Padlock slot Cable lock Hardware TPM 2.0

MANAGEABILITY

Intel vPro with AMT 14. DASH Standard Manageability

ISV CERTIFICATIONS

ANSYS, Altair HyperWorks, Autodesk Alias, Autodesk AutoCAD, Autodesk Inventor, Autodesk Revit, Autodesk VRED, Avid Media Composer, BarcoMedical Monitors, Bentley MicroStation V8i, CONNECT Edition, LumenRT, DS (CATIA, DELMIA, ENOVIA), DS SOLIDWORKS, McKesson / Change Healthcare Enterprise Medical Imaging, PTC Creo, Siemens NX, TcVis, Tecnomatix, Siemens Solid Edge, Vectorworks

Information presented here may represent the maximum possible configurations for this product, but it does not necessarily reflect what is available in your region. Please ask your rep or check the specifications for specific Part Numbers in your region. © 2020 Lenovo. Products are available while supplies last. Lenovo is not responsible for photographic or typographic errors. Lenovo, the Lenovo logo, ThinkPad, ThinkCentre, ThinkBook, ThinkStation and ThinkVision are trademarks or registered trademarks of Lenovo. 3rd party product and service names may be trademarks of others. Depending on factors such as the processing capability of peripheral devices, file attributes, system configuration and operating environments, the actual data transfer rate of USB connectors will vary and is typically slower than published standards.

Recommended for this device



ThinkVision T32h-20

31.5" QHD (2560x1440) near-borderless monitor with 99% sRGB colour gamut

1x HDMI, 1x DisplayPort, 1x USB-C (data, video & data), 4x USB3.1, audio out

Lift, Tilt, Pivot, Swivel stand for viewing comfort. Integrated smartphone holder in base.



ThinkVision T34w-20

34" WQHD display with 1500R curvature, ultra-wide 21:9 aspect ratio, 3000:1 contrast ratio, 99% sRGB colour gamut

1x HDMI, 1x DisplayPort. Integrated USB hub (1x USB-C. 4x USB3.1). Audio out.

Lift, Tilt, Pivot, Swivel stand for viewing comfort. Integrated smartphone holder in base.



Technician Installed Customer Replaceable Unit

Add-on service for On-Site Warranty Upgrades and Premier Support

If a faulty device requires a Customer Replaceable Unit (CRU) part we will send a technician to your premises