Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name	or	trade	mark:	Wiz	
------------	------	----	-------	-------	-----	--

Supplier's address: WiZ, WiZ I.B.R.S. / C.C.R.I. Number 10461, 5600VB Eindhoven, NL

Model identifier:	9290023839AW
-------------------	--------------

_	•			
Type	Λt	liont	COLL	rca.
IVDE	VI.	HEIL	SOU	ıcc.

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	E27		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Daramatar		Value	Daramatar	Value
Parameter		Value	Parameter	Value
		General product p	arameters:	
0,	mption in on- 100 h), rounded st integer	11	Energy efficiency class	F
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	22006500	
On-mode pexpressed in W	oower (P _{on}),	11,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	0,50
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		0,50	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer	Height	139	Spectral power	See image
dimensions	Width	95	distribution in the	in last page

without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	95	range 250 nm to 800 nm, at full-load		
Claim of equivale	ent power ^(a)	Yes	If yes, equivalent power (W)	75	
			Chromaticity	0,458	
			coordinates (x and y)	0,410	
Parameters for L	ED and OLED lig	ht sources:			
R9 colour render	R9 colour rendering index value		Survival factor	0,90	
the lumen maintenance factor		0,96			
Parameters for LED and OLED mains light sources:					
displacement fac	ctor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6	
Claims that a source replaces light source with ballast of a partic	nout integrated	_(b)	If yes then replacement claim (W)	-	
Flicker metric (Ps	st LM)	1,0	Stroboscopic effect metric (SVM)	0,4	

(a)'-': not applicable; (b)'-': not applicable;

