## IdeaPad Flex 3 CB 11IGL05 Intel Platform Specifications

| Processor                        | Intel® Celeron® Processor  | Dimensions  | WxDxH: 11.41" x 8.18" x 0.70"; 290mm x 207.8mm x 17.8mm 1.2 kg / 2.64 lb Abyss Blue or Almond Display cover: Aluminum Bottom: PC/ABS plastic  HD720p, fixed focus HD Audio, Maxim Integrated™ MAX98357A codec / stereo speakers, 2W x 2 / mono microphone, 3.5mm (0.14inch) combo audio / microphone jack (CTIA) |
|----------------------------------|--|---|--|
|                                  | Processor # of Number Cores Threads Frequency Cache Memory Types Processor Graphics  Cel N4000 2 2.6 GHz Intel UHD   | Case color<br>Case material   |  |
|                                  | Cel N4000         2         2         1.1 GHz         2.6 GHz<br>2.8 GHz         4MB         LPDDR4-2400         Intel UHD<br>Graphics 600   |   |  |
|                                  | Intel UHD Graphics 600 in processor; supports external digital monitor via USB Type-C;   | Audio support F<br>n<br>Keyboard 6  |  |
|                                  | supports three independent displays;<br>Max resolution: 4096x2160@60Hz (USB Type-C)  |   | 6-row<br>Buttonless Mylar® (BoPET) surface multi-touch touchpad  |
| Chipset<br>Memory                | Intel SoC (System on Chip) platform 8GB max offering / 2400MHz LPDDR4, soldered to systemboard, no sockets   | Security<br>Security chip   | Security keyhole<br>Google Security Chip H1  |
| Display                          | 11.6" (294mm) HD (1366x768), WVA, glossy, glass, LED backlight, 250 nits,  | Fingerprint reader None   |  |
| Multi-touch<br>Multi-mode<br>Pen | 16:9 aspect ratio, 50% NTSC gamut<br>Supports 10-finger gesture<br>4 modes: notebook, tablet, stand and tent; 360° hinge<br>None   | Battery<br>Max battery life<br>AC adapter   | Integrated Li-Polymer 42Wh battery Google power load test® 2014: 10 hrs * Battery life varies significantly with hardware configurations, settings, usage, & other factors 45W USB-C AC adapter  |
| Storage                          | eMMC 5.1 (embedded Multi Media Card) flash memory on board   | Preload   | Google Chrome OS™  |
| Optical                          | None   | Limited warranty  | 5  |
| Ethernet                         | None   | 1-year depot repair service     1-year depot with 2-year system board repair service     2-year/1-yr battery depot repair service |  |
| WLAN<br>Bluetooth™               | WiFi 5 (802.11ac), 2x2 Wi-Fi + Bluetooth 4.2, M.2 Card<br>Bluetooth 4.2 wireless, integrated in Wi-Fi + Bluetooth combo adapter  |   |  |
| Media reader<br>Ports            | MicroSD™ Card Two USB 3.1 Type-A Gen 1, MicroSD card reader, Two USB 3.1 Gen 1 Type-C™ (with the function of power delivery, data transfer and DisplayPort 1.1a), 3.5mm (0.14inch) headphone / microphone combo jack (CTIA)  * Depending on many factors, actual data transfer speed may be lower than theoretical speed | Environment   | ENERGY STAR® 8.0; ErP lot3; RoHS-compliant   |

Note: The specifications above may not be available in all regions and might change by regions.