# HP Stitch S1000 126-in Printer

### Take your application range to the next level with 126-inch (3.2-m) dye-sub production printing



*Product image may differ from actual product					
<ul> <li>Produce high-quality jobs, gain high versatility</li> <li>With a single device, print on both transfer paper and direct-to-fabric with great results.</li> <li>Enhance your backlit saturation performance on direct-to-fabric thanks to the contact heater.<sup>1</sup></li> <li>Get deep blacks, vivid colors, and high-resolution with 1200 native dpi printheads and the Drop &amp; Dry system.</li> <li>Reliable image quality at speed with a Smart Nozzle Compensation system and Optical Media Advance Sensor Plus.</li> </ul>	<ul> <li>Meet your deadlines with high productivity</li> <li>Fast turnaround production with very short start-up times<sup>2</sup> and speeds up to 2370 ft<sup>2</sup>/hr (220 m<sup>2</sup>/hr).<sup>3</sup></li> <li>Help increase your uptime with user-replaceable printheads and HP preventive maintenance support.<sup>4</sup></li> <li>Confidently print unattended with spreader rollers, 10-liter ink supplies, and rolls up to 600 lb (300 kg).</li> <li>Double throughput on substrates up to 63 in (1.6 m) with the dual roll option.</li> </ul>	<ul> <li>Save time with easy operation</li> <li>In 40% less time, a single operator can easily load both transfer and textile rolls.<sup>2</sup></li> <li>Distribute jobs over the fleet, get color consistency with built-in spectrophotometer/HP Configuration Center.</li> <li>Control your print operations virtually anytime, anywhere and make data-driven decisions with HP PrintOS.<sup>5</sup></li> </ul>			

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

#### **Messaging Footnotes**

<sup>1</sup>Applicable to the backlit media included in the HP Media Solutions Locator, see http://www.hp.com/go/mediasolutionslocator. <sup>2</sup> Very short start up times compared to alternative 126-inch dye-sublimation based textile printers under \$250,000 USD available as of July, 2020. Preparation time including 40% less loading time, printhead cleaning, and warm up time. This is based on internal HP testing in July, 2020 and features including automatic media tension adjustment and easy, simple media path, automatic and optimized printhead cleaning, and warm up in parallel with loading. Testing was performed measuring the time from starting the printer loading process until the printer starts printing, and measuring time with a chronometer. <sup>3</sup> Production-Economy print mode, 2-pass, 50%, for certain patterns of curtains and upholstery for interior décor applications. Based on internal HP testing in February, 2019 on transfer paper (Coldenhove Jet X 57 grams, 102 to 102

126-in/3.2-m width).

<sup>4</sup> Individual services may be provided by HP or an HP-authorized partner. Some services depend on printer, service contract, and region availability.
<sup>5</sup> HP PrintOS is available in both web and mobile app view and needs the printer to be connected to the Internet. The HP PrintOS Mobile Application is compatible with Android<sup>™</sup> 4.0 or later and iPhone mobile devices running iOS 8 or later.

For more information, please visit http://www.hp.com/go/stitchs1000



## **Technical specifications**

Print		Dimensions (W x D x H	)
Print speed	350 m²/hr - Max Speed (1-pass); 220 m²/hr - Production Economy (2-pass); 160 m²/hr - Production Fast (3-pass); 130 m²/hr - Production Quality (4-pass); 100 m²/hr - High Quality (6- pass);	Product	574 x 138 x 167 cm;
		Shipping	586 x 181 x 191 cm;
		Operating area	8.74 x 4.38 m;
Print resolution	Up to 1200 x 600 dpi	Weight	
Technology	HP Dye Sub Printing Technologies	Product	1370 kg;
Ink types	HP Dye Sub Inks	Shipping	2015 kg;
Print Cartridges/Bottle, Number	4 (cyan, magenta, yellow, black)	Included What's in the box	
Print cartridge/bottle volume	10 L	What's in the box	HP Stitch S1000 126-in Printer, printheads, printhead cleaning kit, 126-in spindles (x2), spreader rollers, ink collector, set of ink collector foams and filters, aerosol extractor channel, HP Internal Print Server and monitor, documentation software, user manual, media edge holders (x4), cleaning supplies, pneumatic gun, beacon
Ink drop	12 pl		
Printheads	4 HP Thermal Inkjet (2 cyan/black, 2 magenta/yellow)		
Long-term print-to-print	Average ≤ 1 dE2000, 95% of colors ≤ 1.5 dE2000 <sup>1</sup>	Environmental ranges	
repeatability		Operating temperature	15 to 30°C;
Media		Operating humidity	20 to 70% RH (non-condensing)
Applications	Banners; Billboards; Displays; Exhibition and event graphics;	Acoustics	
Handling	Exterior signage; Interior decoration; POP/POS; Textile	Sound pressure	Printing: <68 dB(A) (operating), <58 dB(A) (idle)
· ·	Roll-to-roll, ink collector	Power	
Media rolls	1	Consumption	5.5 kW (typical) transfer paper; 6.5 kW (typical) direct-to-fabric
Roll size	635 to 3200 mm;	Certification	
Maximum roll weight	300 kg;	Safety	IEC 60950-1+A1+A2 and IEC 62368-1, 2nd Ed. compliant; United States and Canada (CSA listed); EU (LVD and MD compliant, EN60950-1, EN 62368-1, EN12100-1, EN60204-1, and EN1010); Russia, Belarus and Kazakhstan (EAC)
Maximum roll diameter	35 cm;		
Maximum media width	3.2 m;		
Thickness	Up to 0.5mm;	Electromagnetic	Compliant with Class A requirements, including: USA (FCC
Stretchability	Winding direction up to 5%; Cross winding direction up to 10%; Diagonal up to 10%		rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM)
Media types	Sublimation transfer papers, sublimation polyester fabrics	Environmental	WEEE; China RoHS; EAEU RoHS; EU RoHS; REACH; CE marking compliant
Connectivity		Warranty	One-year limited hardware warranty
Interfaces	Gigabit Ethernet (1000Base-T)		
Ordering inform	ation		
Product			0-liter Black Stitch Dye Sublimation Ink Cartridge
1D3A8A HP Stite	h S1000 126-in Printer	4UV64A HP 638 1	0-liter Cyan Stitch Dye Sublimation Ink Cartridge

Product		4UV63A HP 638 10-liter Black Stitch Dye Sublimation Ink Cartridge	
1D3A8A	HP Stitch S1000 126-in Printer	4UV64A HP 638 10-liter Cyan Stitch Dye Sublimation Ink Cartridge	
		4UV65A HP 638 10-liter Magenta Stitch Dye Sublimation Ink Cartridge	
Accessories 4J0X0A 4R4W4A 4R4W7A 4TA09A 7JC63A D9Z41B G1K80B L5E74C	HP 126-in Dual Roll Kit HP 126-in Spindle HP 126-in Diverter Roller HP Stitch S1000 Ink Collector Foam Kit HP Ergosoft Pro RIP S1000 Color Edition HP Large Format Onyx Thrive RIP Software HP 126-in Dual Roll Spindle HP Large Format Caldera Grand RIP Software	4UV66A         HP 638 10-liter Yellow Stitch Dye Sublimation Ink Cartridge           4UV67A         HP 618 Magenta and Yellow Stitch Dye Sublimation Printhead           4UV68A         HP 618 Black and Cyan Stitch Stitch Dye Sublimation Printhead           4UV69A         HP 618 stitch Dye Sublimation Printhead           40v69A         HP 618 stitch Dye Sublimation Printhead           40v7         HP 618 stitch Dye Sublimation Printhead<	
Original HP printing supplies		for full HP warranty protection. For more information, visit	
		https://hp.com/go/OriginalHPinks	

HP Support Services offer installation and extended support services (e.g. 2, 3, 4, and 5 years). For more information, please visit http://www.hp.com/go/cpc

#### **Specification Footnotes**

<sup>1</sup> The color variation inside a printed job has been measured at 4-pass mode on transfer media and also in direct-to-fabric situations within this limit: maximum color difference (95% of colors) < 1.5 dE2000. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 1.5 dE2000. Backlit substrates measured in transmission mode may yield different results. Results are dependent on sublimation process variability.

© Copyright 2025 HP Development Company, LP. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

March 2025 th-en

