



Philips
Digital satellite diplexer

SDW5004GN



Combine and separate satellite and antenna signals

Consolidate satellite and antenna signals into a single path. Use a second to separate the signals. For use with quad shield cable. For indoor or outdoor use.

Enjoy a better, brighter picture

- Minimum signal loss

Enjoy extended durability

- Corrosion-resistant connections

PHILIPS
sense and simplicity

Specifications

Packaging

- EAN/UPC/GTIN: 6 09585 11882 9
- Quantity: 1
- Gross Weight: 0.27 kg
- Tare Weight: 0.04 kg
- Net Weight: 0.23 kg
- Length: 19.7 cm
- Width: 10.8 cm
- Height: 4.40 cm

Inner Carton

- EAN/UPC/GTIN: 1 06 09585 11882 6
- Quantity: 6
- Gross Weight: 1.64 kg
- Tare Weight: 0.22 kg

- Net Weight: 1.42 kg
- Length (cm): 20.3 cm
- Width (cm): 10.8 cm
- Height (cm): 15.9 cm

Outer Carton

- EAN/UPC/GTIN: 2 06 09585 11882 3
- Quantity: 72
- Gross Weight: 19.64 kg
- Tare Weight: 2.62 kg
- Net Weight: 17.02 kg
- Length (cm): 41.9 cm
- Width (cm): 32.4 cm
- Height (cm): 34.3 cm

Product highlights

Corrosion-resistant connection

24K gold-electroplated connectors create secure and extremely durable connections that optimize signal quality and deliver the best picture and data transfer.

Minimum signal loss

Signal information is inevitably lost going from any digital source to any TV. Minimum signal loss means you only lose the least amount of that signal information.



Issue date 2007-12-08

Version: 2.2.8

12 NC: 9082 100 09585
UPC: 6 09585 11882 9

© 2007 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com