



Philips
3x4 multi-switch

SDW5034



Expand the capability of your satellite system

Connect up to four satellite TV receivers and enjoy uncompromised signal quality to each of the four receivers. Watch four different programs from one dual LNB satellite dish.

Enjoy a better, brighter picture

- Minimum signal loss

No external power required

- Self-powered

Enjoy extended durability

- Corrosion-resistant connections

PHILIPS
sense and simplicity

Specifications

Packaging Data

- Quantity: 1
- EAN/UPC/GTIN: 6 09585 11808 9
- Gross weight: .52 kg
- Tare weight: .06 kg
- Net weight: .46 kg
- Length: 223 mm
- Width: 196 mm
- Height: 37 mm

Outer Carton

- EAN/UPC/GTIN: 1 06 09585 11808 6
- Quantity: 4
- Gross weight: 2.4 kg
- Tare weight: .4 kg
- Net weight: 2. kg
- Length: 240 mm
- Width: 190 mm
- Height: 220 mm

Product highlights

Corrosion-resistant connection

24K gold-electroplated connectors create secure and extremely durable connections that optimize signal quality and deliver the best picture and data transfer.

Minimum signal loss

Signal information is inevitably lost going from any digital source to any TV. Minimum signal loss means you only lose the least amount of that signal information.

Self-powered

Provides its own power so no external power source is necessary.



Issue date 2008-11-15

Version: 3.0.7

I2 NC: 9082 100 09437
UPC: 6 09585 11808 9

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.

Specifications are subject to change without notice.
Trademarks are the property of Koninklijke Philips
Electronics N.V. or their respective owners.

www.philips.com