

6-Outlet Surge Protector Tower, 3x USB-A, 1x USB-C, 8 ft. Cord, 5-15P Plug, 1800 Joules, Black

MODEL NUMBER: TLP606UCTOWER



Surge protection tower with USB charging safeguards your electronics against dangerous surges, spikes and line noise.

Features

6-Outlet Surge Protection Tower Safeguards Your Sensitive Electronics

Ideal for your home or office workstation, this Protect It!® six-outlet tower features a surge suppression rating of 1800 joules to defend your sensitive electronic components against even the strongest power surges and spikes. Because residential power outlets have three wires—hot line (H), neutral (N) and ground (G)—the TLP606UCTOWER protects all three, covering the two protection modes: full normal mode (H-N) and common mode (N-G/H-G).

6 NEMA 5-15R Outlets Accept a Wide Range of Electronic Devices

Plug your laptop, external hard drive, desk lamp and other home/office devices into the NEMA 5-15R outlets to protect them against dangerous surges, spikes and line noise. The outlets are split between three sides of the tower and spread apart to allow easy connection of bulky transformers without blocking adjacent outlets.

USB Ports Share 6 Amps of Charging Power

Three USB-A ports, as well as one USB-C port, are available for charging your smartphone, tablet and other USB mobile devices. They share 6A for charging multiple devices at the same time.

Premium Protection from EMI/RFI Line Noise Helps Your Equipment Perform Better

Various electromagnetic and radio sources found in virtually every home and business can cause disruptive interference on the AC line. Known as EMI (electromagnetic interference) and RFI (radio frequency interference), this line noise is a common cause of performance problems. This surge protector filters out disruptive line noise that can disturb your electronics and inflict hardware damage or data loss. This EMI/RFI filtering also helps your connected components perform better and last longer.

Includes the Latest Safety Features to Maintain Your Equipment's Well-Being

An on/off switch allows you easy one-touch control over all connected equipment. The green LED confirms at a glance that your plugged-in devices are protected.

Versatile Tower Design Gives You Plenty of Options for Installation and Use

The TLP606UCTOWER fits easily into your home or office workspace, conference table or classroom, providing power and USB charging at your fingertips. The braided eight-foot power cord and space-saving right-angle NEMA 5-15P plug allows connection in tight spaces, such as behind furniture.

Highlights

- Ideal for conference tables, home offices and other areas with multiple mobile devices
- 6 NEMA 5-15R outlets spaced widely apart to accommodate bulky transformers
- 1800 joules protect your valuable electronics against dangerous surges and spikes
- USB-C and USB-A ports provide fast charging of phones, tablets and other mobile devices
- Right-angle NEMA 5-15P plug with braided 8 ft. cord allows connection in tight spaces

Applications

- Ensure critical devices, such as laptops and tablets, stay fully powered and charged during important conferences and meetings
- Filter potentially damaging line noise to improve connected equipment's performance and lifespan
- Safeguard valuable data against damage stemming from unexpected surges
- Charge a smartphone and tablet via USB without taking up available AC outlets

Package Includes

- TLP606UCTOWER 6-Outlet Surge Protector Tower, Black
- Owner's manual



Specifications

OVERVIEW	
UPC Code	037332260307
Device Compatibility	Phone; Tablet
INPUT	
Nominal Input Voltage(s) Supported	120V AC
Input Plug Type	NEMA 5-15P
Input Cord Length (ft.)	8
Right-Angle Plug	No
Input Cord Length (m)	2.44
Integrated Cord Clip	No
OUTPUT	
Frequency Compatibility	60 Hz
Output (Watts)	1800
Output Receptacles	(6) 5-15R
Circuit Breaker (amps)	15
Overload Protection	Yes
Transformer Accommodation	Yes
Right-Angle Outlets	No
USER INTERFACE, ALERTS & CONTROLS	
Diagnostic LED(s)	Yes
Diagnostic LED Details	Yes
SURGE / NOISE SUPPRESSION	
AC Suppression Joule Rating	1800
AC Suppression Response Time	< 1ns
Protection Modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line suppression
UL1449 Let Through Rating	L-N, L-G, N-G 800,800,800
EMI / RFI Filtering	Yes
Immunity	Conforms to IEE 587/ANSI C62.41
Automatic Shut-Off	No
CHARGING	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Charging Ports / Amps	(3) 3.1A; (1) 3A
Number of Charging Ports	4
Charging Method	USB
Charging Port Type	(3) USB A (FEMALE); (1) USB C (FEMALE)
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	No
Cable (Coax) Protection	No
Network (Ethernet) Protection	No
PHYSICAL	
Antimicrobial Coating	No
Color	Black; Gray
Color (AC Line Cord)	Black and Gray Braided
Housing Color	Black
Integrated Keyhole Mounting Slots	No
Material of Construction	Plastic
Receptacle Color	Gray
Unit Dimensions (hwd / cm)	19.8 x 14.9 x 10.6
Unit Dimensions (hwd / in.)	7.8 x 5.9 x 4
Unit Weight (kg)	1.04
Unit Weight (lbs.)	2.3
SPECIAL FEATURES	
Rotatable Outlets	No
STANDARDS & COMPLIANCE	
Canada	CAN/CSA-22.2 No. 269.3:2007(3rd Ed.);CAN/CSA-C22.2 No.308-14
Approvals	RoHS
UL1449 3rd Edition (AC Suppression)	UL1449:2014 (4thEd) R8.18
UL1363 (Power Tap)	UL1363:2018 5th Edition
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$10,000 Ultimate Lifetime Insurance



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:
<https://www.tripplite.com/products/product-certification-agencies>