SHARP/NEC

NEC LED-FA015i2-137 Indoor LED 1.5 mm 137" FullHD Bundle

Datasheet





Nothing less than magnificent

For premium large surface visualization, Sharp/NEC's fine pitch LED FA series bundles provide standard resolution, direct view LED screens for applications in meeting spaces and exclusive signage. With a depth of just 5cm, plus complete internal cabling, the FA series presents a sleek profile for a bezel-free viewing experience. With excellent viewing angles, consistent vibrant colours and superb brightness; the FA series delivers content that gets noticed. Native HD, FHD, UHD and QHD resolutions are achieved through configuration of multiple 16:9 cabinets which are bundled with a power bar, framing, mounting and controller. Designed with high quality components and maintenance access from the front, the FA Series provides a display solution with longevity and good return on investment. The prime solution for boardrooms, auditoria, luxury retail environments and control rooms.

Benefits

Care-free installation – with bundled solutions that deliver all you need to get your LED video wall up and running.

Large scale for perfectly detailed imagery – completely bezel-less design with high contrast rates deliver an unhindered viewing experience.

Secure performance for demanding applications – with high-end components and redundant module design with additional power supply and data cards to ensure ongoing operations with a minimal loss of brightness levels.

Superb readability in bright light environments – high brightness levels of up to 800 cd/m², along with wide viewing angles deliver clear messages to your audience even under varying and demanding ambient conditions.

Slim design – with a flush rear profile, LED modules can be integrated very close to the wall with minimal gap necessary due to very low heat emission.

Product Information

Product Name	NEC LED-FA015i2-137
Product Group	Indoor LED 1.5 mm 137" FullHD Bundle
Order Code	81000173

Display

Pixel Configuration	3-in-1 SMD (Black)
LED type	SMD (1010)
Screen Size [inch/cm]	137 / 348
Aspect Ratio	16:9
Pixel Pitch [mm]	1.5
Brightness (max.) [cd/ m²]	800
Lifetime	100000 hrs (50% brightness)
Contrast Ratio (typ.)	5000:1
Viewing Angle [°]	170 horizontal / 170 vertical
Dimming Capability	256 levels
Colour Processing	16 bit
Colours [Trill.]	281
LED Driving Method	1/27 dynamic scan
Frame Rate [Hz]	50/60
Refresh Rate [Hz]	≤ 3840
Colour Temperature [K]	3000 - 9500

Screen Resolution

Resolution	1920 x 1080
Resolution per m ²	398892
Number of Pixel per module [dot]	384 x 216
Number of Pixel per card [dot]	96 × 108

Connectivity

Input Video Digital	1 x 3G SDI; 1 x DVI-D; 1 x HDMI
Input Control	1 x GenLock; 1 x LAN

Electrical

Total Power	1425 typ. / 3125 max.
Consumption [W]	

Power Consumption typ. [W]	275 per m ² (normal use)
Power Consumption max. [W]	600 per m²

Environmental Conditions

Operating Temperature [°C]	-20 to 40
Operating Humidity [%]	10 to 80

Mechanical

Dimensions (W x H x D) [mm] per module	608 x 342 x 49
Dimensions (W x H x D) [mm]	3,080 x 1,831.5 x 81
Weight [kg]	279

Additional Features

Shipping Content	2x LED Controller; LED Modules (25 Cabinets, 200 Pixel Cards); Overframe Kit (5x5); Pixel Card Removal Tool; Power Bar; Spare Parts Kit; Wall mount (5x5)
Special Characteristics	Cableless Connector for Data and Power; Flush Surface SMD Design; Humidity-proof SMD Design; Redundant Data Receiving Cards; Redundant Power Supplies
Manufacturer	NEC
Serviceability	Front Service
IP Level	IP20
Certifications	CE; ETL; FCC Class A; RoHS
Warranty	3 years
Material	Aluminum Cabinet

* 137 inch

This document is $\,$ © 2025 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 13.02.2025