

Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 1 of 30

BESTWAY (HONGKONG) INTERNATIONAL LTD.

SUITE 713, 7/FLOOR, EAST WING, TSIM SHA TSUI CENTRE, 66 MODY ROAD, KOWLOON, HONGKONG

Sample Description : AIR MAT Style/ Item No. : 43414

Sample Receiving Date : MAR. 09, 2020

Testing Period : MAR. 09, 2020 TO MAR. 27, 2020

Testing Location : 3RD BUILDING, LANE 3999, XIUPU RD., PUDONG

DISTRICT, SHANGHAI, CHINA

Test Performed : SELECTED TEST(S) AS REQUESTED BY APPLICANT
Test Requested : 1. EN ISO 25649-1:2017 FLOATING LEISURE ARTICLES

FOR USE ON AND IN THE WATER PART 1:

CLASSIFICATION, MATERIALS, GENERAL REQUIREMENTS AND TEST METHODS

2. EN ISO 25649-2:2017 FLOATING LEISURE ARTICLES FOR USE ON AND IN THE WATER PART 2: CONSUMER

INFORMATION

3. EN ISO 25649-3:2017 FLOATING LEISURE ARTICLES

FOR USE ON AND IN THE WATER PART 3:

ADDITIONAL SPECIFIC SAFETY REQUIREMENTS AND

TEST METHODS FOR CLASS A DEVICES



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service prints overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format document overleaf, available on request or the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits client's instructions, if any. The Company's sole responsibility is to its Client and this document does not expense responsibility is to its Client and this document does not expense parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content appearance of this document is unlawful and effonders may be procedured to the fullest extent of the Issue, Unless otherwise stated the results shown in this test report refer only to the sample(s) lested and such sample(s) are retained for 30 days only.



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 2 of 30

Test Result(s) : FOR FURTHER DETAILS, PLEASE REFER TO THE

FOLLOWING PAGE(S)

Conclusion : THE SUBMITTED SAMPLE MET THE TEST

REQUIREMENT.

Signed for and on behalf of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd.

Yomoro Gu Authorized Signatory





Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 3 of 30

Test Conducted:

- 1. EN ISO 25649-1:2017 Floating leisure articles for use on and in the water Part 1: Classification, materials, general requirements and test methods
- 2. EN ISO 25649-2:2017 Floating leisure articles for use on and in the water Part 2: Consumer information
- 3. EN ISO 25649-3:2017 Floating leisure articles for use on and in the water Part 3: Additional specific safety requirements and test methods for Class A devices

Device Classification: Class A, Case D

Sample size: 2 pieces

Clause	Test Method/Requirement	Result	Rating
1. EN ISO 2564	9-1:2017		
5 General safety	requirements and test methods related to all classes		
5.1 General	Floating leisure articles for use on and in the water shall be designed in a way that they are safe und usable for persons of a minimum age of 36 months and above, also in deep water where the user is out of its standing depth. Via adequate labelling, it shall be made clear to the consumer and user that these articles are intended for swimmers only, that they do not provide protection against drowning and that they are in no case PPE (Personal Protective Equipment). These basic requirements are deemed to be met if a product complies with the relevant parts of this series of standards. ISO 25649-3 to ISO 25649-7 may include deviations and exclusions from the above.		Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.gapx and, for electronic Focuments at http://www.sgs.com/en/Terms-and-Conditions/en/Terms-e-Document.aspx.
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its invervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawful and offendore may be procedured to the fullest extent of the law. Unlose otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: Onesch the autherfield of testing insepection report & certificate, please contact us at telephone: (86-755) 8307 1443, Attention: Onesch the autherfield of testing insepection report & certificate, please contact us at telephone: (86-755) 8307 1443,



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 4 of 30

Clause	Test Method/Requirement	Result	Rating		
5.2 Body entrapm	5.2 Body entrapment				
5.2.1 General					
5.2.1.1 Introduction	Floating leisure articles shall not have accessible design features that may cause body entrapment. This requirement is deemed to be met if the following requirements are met and the specified test procedures prove that body entrapment does not occur.		Pass		
	Design features i.e. gaps, openings, slots etc. are categorised in design types A to E as shown in Annex A and Annex B. They include features providing fixed interior spaces and such with flexible interior components/spaces and thus variable dimensions. Design features likely to cause entrapment may be arranged in the plane but also in 3-dimensional structures providing considerable height as e.g. ladder structures, labyrinths or body enclosing structures. Testing should be undertaken according to the instructions laid out in this document.				
5.2.1.2 Accessibility	Design features accessible to the test person in any stable floating position the product can take on the water.	/	Pass		
5.2.1.3 Product categorization regarding age	Products shall be labelled with regard to their intended user groups according to ISO 25649-2. With regard to body entrapment floating leisure articles are to be distinguished in two sizes only: child use and adult use: Child use includes	Adult use only Age group: 14+	Pass		
group and body weight of user/test persons/torso templates	age group 3 years to 10 years of age/body weight 18 kg to 45 kg respectively. Products for combined child /adult use or adult use only include all other user groups. According to these user groups the relevant foot and torso probes or the test persons shall be applied for testing.	Body weight: Max. 90 kg			



4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661

t (86) 400 960 9661 f (86-21) 6115 6899 f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Page: 5 of 30 Date: MAR. 27, 2020

Clause	Test Method/Requirement	Result	Rating
5.2.2 Requirements on body entrapment	All design features of a floating leisure article as e.g. gaps, openings, slots etc. which allow the initial ingress of the foot probe according to 5.2.1.4.1 shall prove that they subsequently allow the free passage of either the appropriate (see 5.2.1.3) test probe (adult/child) according to 5.2.1.4.2 or the relevant test subject according to 5.2.1.4.3. For design features likely to cause body entrapment see categorization of types of openings in Annex B.	Not allow the initial ingress of the foot probe	N/A
	a) Dimensions of probe b) Application of probe		
	Figure 1 — Foot probe		
	Dimensions in millimetres		
	342		
	a) Dimensions of probe b) Application of probe		
	Figure 2 — Adult torso probe		
	Dimensions in millimetres		
	225		
	a) Dimensions of probe b) Application of probe		
	Figure 3 — Child torso probe, 10 years of age		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be proceduted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661

t (86) 400 960 9661 f (86-21) 6115 6899 f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 6 of 30

Clause	Test Method/Requirement	Result	Rating
5.2.4	Openings, gaps, slots etc. are considered as not causing	For adult use	Pass
Depths of gaps	body entrapment if they have a restriction in depth which	only:	
and openings	prevents the user from getting too deep into it. This depth	Depth: 0 mm	
	shall not allow an entry of the foot probe according to		
	5.2.1.4.1 of more than 30 cm for products intended for adult		
	use only and not more as 20 cm for products intended for		
	child use or combined adult and child use.		
5.3 Torso entrapn	nent on safety line with regard to children		
5.3.1	The child torso probe shall pass through the opening	No safety line	N/A
Requirements	between safety line and the hull of the device at any position	·	
	under the force of its own weight.		
	Dimensions in millimetres		
	155 200 Key		
	1 child's torso probe, 3 years of age		
	Figure 4 — Child torso probe		
5.4 Accessible pre	otruding parts causing entanglement		
5.4.1	To prevent the user from entanglement when unintentionally	/	Pass
Requirements	sliding out or from a device, there shall be no hazardous		
	protrusions.		
	The test rope shall slip of any part of the device that		
	protrudes in the area where the user intentionally and		
	foreseeably interacts with the product.		
	It shall be checked whether the test rope disengages under		
	any circumstances, such as capsize, slip off, protruding part		
	breakage, etc.		



4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661

t (86) 400 960 9661 f (86-21) 6115 6899 f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 7 of 30

Clause	Test Method/Requirement	Result	Rating
5.5 Human subje			
5.5.2 Test panel	Test subject 1 shall always be one time in the total number of adult male test subjects. If more than one test subject shall act, the rest shall be a mix of sex in accordance with Table 2.	Max. load of the product (kg): 90 Number of	/
	Table 2 — Test panel	users: Adult: 1	
	Test subjects Sex Age years kg cm Number of subjects Sex Age years cm Number of subjects Child/adult equivalence	Child: 0	
	Subject 1 male >18 ≥90 ≥180 according to manufacturer's 1 time Subject 2 male >18 70 - 80 ≥170 according to manufacturer's 50/50 2 children Subject 3 female >18 40 - 45 <150		
	a Test subject.4 represents a child. In order to avoid involvement of children in testing, the child subject is substituted by the statistically smallest adult women (5th percentile). b If a device is classified for an unequal number of adult users, subject 1 shall constitute the majority.		
	a) Posture 1 b) Posture 1.1 c) Posture 2 d) Posture 3 e) Posture 4 Figure 6 — Basic test postures of human test subjects		
5.6 Design working	g pressure	-	1
5.6.1 Requirements	The recommended working pressures (if applicable) shall be specified by the manufacturer for each main buoyancy chamber of the fully inflated device. These pressures shall be indicated on the device and in the operator's instruction manual (see ISO 25649-2). If for any reason working pressure is not given, inflate until full shape and functionality is achieved. Where relevant, the sequence of inflation shall be numbered next to the chamber's inflation valves. In order that the user may ascertain that the specified working pressure has been reached, the manufacturer shall provide appropriate equipment or a pressure gauge for this purpose. Alternatively, instructions shall be included in the operator's instruction booklet, which will enable a sufficiently close estimate to be made. The working pressure shall be consistently expressed in bars.	Recommended working pressure: 0.03 bar	Pass



4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661 f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 8 of 30

Clause	Test Method/Requirement	Result	Rating
5.7 Load bearing	components		
5.7.1 Requirements	If not otherwise stated in the specific parts all load bearing fittings, e.g. lifting and carrying handles, fittings for safety ropes, etc. shall be compatible with the material of the hull itself and shall not break or result in any impairment in air tightness or water integrity when apply a load of 500 N, maintain for 1 min.	/	N/A
5.8 Towing device		Ι,	
5.8.1 Requirements	If not otherwise stated in the specific parts, floating articles shall be equipped with means to attach a towing rope in case of an emergency. This means shall withstand a horizontal pulling force of 1 kN in any direction loaded progressively and maintained for 15 min, without any damage to the fitting and the entire structure.		N/A
	Not applicable if the device is marked with safety information symbol "pool use only" according to ISO 25649-2.		
5.9 Valves and va			
5.9.1 Requirements	Inflating and/or deflating valves shall be made of corrosion- resistant materials, shall be compatible with the material of the hull and shall not be capable of damaging the device. EN 16051-1 gives examples how to achieve compatibility valves and inflating devices geometry. They should meet the requirements specified in EN 16051-1. In general, valves shall a) not inconvenience the persons in the device in their predetermined seating positions, b) not interfere with the operation of the device, and c) not be damaged or torn off by moveable components of the device construction. All valves shall enable airtight sealing by manual operation, independent of their sealing or non-return valve. For the buoyancy system, valves with a non-return device in accordance with EN 16051-1 should be used. NOTE A specific European Standard dealing with compatibility of valves and valve adapters is currently under development. Each filling valve shall enable a controlled pressure reduction.	See Remark 1	Pass
5.9.3 Numbering of air chambers	If the sequence of air chamber inflation is relevant for function or safety of the product, the correct inflation sequence shall be indicated by numbers in close proximity to the valves.	/	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be proceduted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661

f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 9 of 30

Clause	Test Method/Requirement	Result	Rating		
5.10 Edges, corne	5.10 Edges, corners and points				
5.10.1 Requirements	All devices shall be of a design such that they cannot cause harm to the user. Edges and corners of hard and rigid materials shall be chamfered or rounded. Round edges or corners shall have a minimum radius of 1 mm and where a chamfer is part of the design, it shall be of (45°±5) mm and at least 1 mm in width. There shall be no barbs or other sharp points or features.		Pass		
5.11 Shearing and		No obsering or	N/A		
5.11.1 Requirements	Floating articles not specifically excluding the use by children shall meet the requirements regarding parts moving against each other as specified in EN 71-1:2005, 4.10.1 d) and 4.10.2.	No shearing or crushing points	N/A		
	【Folding and sliding mechanisms, clause 4.10.1 d): The space between moving elements shall also allow a 12mm diameter rod to be inserted if it allows a 5mm diameter rod to be inserted.				
	Driving mechanisms, clause 4.10.2: Driving mechanisms shall be enclosed in such a way that they do not expose accessible hazardous sharp edges or hazardous sharp points or otherwise present a hazard of crushing the fingers or other parts of body				
	Floating articles for adult use only shall have no accessible shearing and/or crushing points. Shearing and crushing points exist if the distance between two rigid movable parts is less than 25 mm. If access to shearing and crushing points is prevented by covers, none of the remaining openings shall allow a 5 mm cylindric probe to be inserted. Not applicable for oars and oar-locks.				
5.12 Strength of t	he hull and test conditions	•			
5.12.1 Requirements	If applicable, the device shall remain airtight after each of the tests below (see 5.12.2 to 5.12.5). All tests shall be performed at a temperature of (20 \pm 3) °C, unless specified otherwise.	/	Pass		



4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661

t (86) 400 960 9661 f (86-21) 6115 6899 f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 10 of 30

Clause	Test Method/Requirement	Result	Rating
5.12.2 Pressure t	est		
5.12.2 Pressure to 5.12.2.1 Combined cycle pressure/static load test for devices manufactured from unsupported material	Inflate all chambers of the device to the design working pressure as instructed by the manufacturer on the product or in the instructions but not less than 0,03 bar or, if no working pressure is given for test purposes a pressure of 0,06 bar is valid and keep the device inflated for 12 h. This test procedure shall be applied alternately to at least two adjoining inflated chambers (chamber 1, chamber 2) in turn as required in Figure 7 and shall comprise 50 inflation/deflation cycles. a) Inflate chamber 1 to a pressure of 1,1 times the design working pressure and keep it for the specified time. b) Deflate chamber 1 to zero pressure and inflate chamber 2 to 1,1 times of the design working pressure and keep it for the specified time. c) Repeat this process for 75 times (pressure tolerance: +10% to -0% of applied test pressure) Test the air tightness of all inflated air chambers in accordance with paper strip test in 5.12.4. Y X Key X time, min Y pressure, bar 1 chamber 1 2 chamber 2 3 design working pressure Figure 7 - Cyclic pressure test for buoyancy chambers (unsupported materials) In direct succession to this cyclic pressure test the product shall be put on an even rigid floor and loaded statically with the weight of the designated user(s) for the duration of 20	Design working pressure: 0.03 bar Test load: 90 kg	Pass



4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661

f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 11 of 30

Clause	Test Method/Requirement	Result	Rating
5.12.2.2 Overpressure test for inflatables made from reinforced or fabric covered material	Inflate each compartment of the device to 1,5 times the manufacturer's design working pressure for 30 min. If no design working pressure is given, a pressure of 0,06 bar is valid. For Class D devices, a pressure of only 1,2 times the design pressure applies. No damage or rupture shall occur and the device shall be tested for air tightness as described in 5.12.5. NOTE Flocked film materials do not fall under the category of being "reinforced".		N/A
5.12.3 Heat test (not applicable to Class D devices)	Assemble the device in accordance with the manufacturer's instructions and inflate it to a pressure of 1,1 times the design working pressure. If no working pressure is given, a pressure of 0,06 bar shall be used. When assembled, place the device in a heat chamber, set at (60 ± 2) °C, f or a period of 6 h. On completion of the test period, remove the device from the heat chamber and allow to cool down to ambient temperature. Test the air tightness of the device in accordance with the relevant test specified in 5.12.5 for devices manufactured from reinforced material or 5.12.4 for devices manufactured from unsupported material.	Design working pressure: 0.03 bar	Pass
5.12.4 Air tightness test for inflatables made from unsupported material	The air tightness is measured indirectly as shrinkage of the material. Test all chambers for buoyancy individually with all adjacent chambers deflated. Inflate the chamber to be tested for buoyancy to a pressure of 1,1 times the manufacturer's design working pressure. If no working pressure is given, a pressure of 0,06 bar is valid. Immediately stick a strip of paper, approximately 100 mm long, at its ends onto the outer surface of the air chamber in a circumferential direction. Cut the strip in half horizontally. Following a test period of 2 h, there shall be no overlapping of the two cut ends.	No overlapping	Pass



4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661

f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 12 of 30

Clause	Test Method/Requirement	Result	Rating
5.12.5 Air	Support or insulate the device from the floor and do not	1	N/A
tightness test	expose it to any air currant and direct sunlight.		
for inflatables	Inflate the device (all air chambers) for 30 min to a pressure		
made from	that is 20 % in excess of the manufacturer's design working		
reinforced or	pressure if indicated in order to pre-stretch the device. Then		
fabric covered	reset the pressures to the design working pressure for a		
material	further period of 30 min in order to stabilize conditions.		
	Reset the pressures to the design working pressure and		
	record the ambient temperature and atmospheric pressure.		
	Following a test period of 24 h, the pressure drop shall not		
	be greater than 20 % in any air chamber. Record the final		
	ambient temperature and atmospheric pressure.		
	The temperature difference between the start of the test and		
	the end of the test shall not exceed ±3 °C.		
	The atmospheric pressure difference between the start of		
	the test and the test readings shall not exceed ±1 %.		
	For each rise or fall by 1 °C in ambient temperature, an		
	allowance of 0,004 bar may be respectively subtracted from,		
	or added to, the recorded device pressure.		
5.13 Buckles and			T
5.13.1	If buckles or other detachable fastening devices are used as	/	N/A
Requirements	parts of the entire device in order to attach or connect		
	functional parts or components, they shall require at least		
	two simultaneous actions for their release or opening in		
	order to prevent unintended opening.		
	Where one of the two sequences of buckle opening relies		
	on pressure, it shall be necessary to apply a force of at least		
6 Material requi	50 N on this release mechanism. rements and test methods		
6.1 General	ements and test methods		
6.1.1	All materials used in floating leisure articles shall be visually	/	Pass
Requirements	clean and free from contamination.		
'	They shall be selected by the manufacturer according to the		
	stresses that are resulting from the intended service		
	conditions and the requirements set out for shape,		
	dimension, maximum load, etc.		
	The use under normal conditions shall not materially impair		
	their performance and they shall meet all the requirements		
	specified in Clause 6 and Clause 7.		
	To avoid rotting, all fibre materials shall not be made from		
	natural fibres like cotton.		
	For conditioning, the test procedure related to immersion in		
	chlorinated salt water (see 6.2.2) and storage in cold and		
	hot conditions (see 6.3) shall be carried out prior to all other		
	tests.		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be proceduted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661

f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 13 of 30

Clause	Test Method/Requirement	Result	Rating		
6.2 Chemical requ	6.2 Chemical requirements for materials making up the hull, unsupported or reinforced				
6.2.1 General	In house or outside test confirmation may be allowed to	/	Pass		
	verify compliance.				
6.2.2 Resistance	to mineral oil				
6.2.2.1	After the contact during a period of (22 ± 0.25) h the change	Change of mass	Pass		
Requirements	in mass per unit area shall not exceed 100 g/m ² .	(g/m ²): -17.21			
	to chlorinated salt water				
6.2.3.1 Water	After the contact during a period of minimum 36 h the	Change of mass	Pass		
absorption	change in mass per unit area shall not exceed 100 g/m ² .	(g/m ²): 10.08			
6.3 Physical requ	irements				
6.3.1 Resistance	to cold				
6.3.1.1	After an exposure for 4 h and the treatment, there shall be	No cracking	Pass		
Requirements	no signs of cracking when the test sample is examined				
	under a magnification of ×10.				
6.3.2 Resistance					
6.3.2.1	The test sample shall give neither evidence of blocking nor	No blocking nor	Pass		
Requirements	show damages of the surface after unfolding when the	damage			
	sample is examined under a magnification of x5.				
	equirements of unsupported hull materials				
6.4.1 General	Unless otherwise specified, the standard environmental	/	/		
	conditions for the tests shall be a temperature of (20 \pm 2) $^{\circ}$				
	and a relative humidity of (65 ± 5) %.				
	NOTE See specific requirements in ISO 25649-3 to ISO				
	25649-7.				
6.4.2 Resistance		Ι.	_		
6.4.2.1	Air filled buoyancy chambers shall remain air tight after	/	Pass		
Requirements	resistance to puncturing test.				
	equirements for reinforced hull materials				
	coatings (if applicable)	1	1		
6.5.2.1	Where the hull of a floating leisure article consists of coated	/	N/A		
Requirements	reinforcing materials (e.g. cloths), the adhesion between the				
	coating and the substrate (base cloth) shall be sufficiently				
	strong, so as to exclude any unintentional separation of the				
	coating from the substrate during the intended use of the				
	floating leisure article.				
	The separating force between the coating and the				
	reinforcing material shall be at least 20 N/cm ² .				



4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661

f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Page: 14 of 30 Date: MAR. 27, 2020

Clause	Test Method/Requirement	Result	Rating
6.6 Other materia	ls		
6.6.1 Wood			
6.6.1.1 Requirements	The exposed types of timber and plywood used shall be suitable for the application and the marine environment and shall be given weatherproof protection, such as paint, varnish or preservative, when exposed to the marine environment. All plywood used shall incorporate hardwoods for both internal and external veneers and the bonding adhesive shall be waterproof and boil-proof. The timber used shall be seasoned and free from sapwood, decay, insect attack, splits and other imperfections likely to adversely affect the performance of the material. The timber shall be generally free from knots but an occasional sound intergrown knot is acceptable. Adjoining edges and/or surfaces, including any end-grain, shall be effectively sealed. The legal regulations of the country or region of application shall be met. For the European region the selection of preservatives, relevant regulations shall be considered. Restrictions on the marketing and use of certain dangerous substances and	No wood	N/A
	preparations are addressed in the European Directive		
	76/769/EEC and its amendments, e.g. the restriction of organostannic compounds for crafts.		
6.6.2 Metal and s	ynthetic material parts	<u> </u>	
6.6.2.1	Materials used shall be of a type, strength and finish,	/	Pass
Requirements	suitable for the intended purpose of the components and compatible with the marine environment.		
6.7 Threads			
6.7.1	To sew load bearing components, only threads	No thread	N/A
Requirements	manufactured from synthetic materials whose properties		
7 Dunck!!!ter of	correspond to polyester or polyamide fibres shall be used.		
	arnings and markings		
7.1 Resistance to		Coo Booult 1	Door
7.1.1 Requirements	The change in colour of the warnings and markings shall be 3 or better on the grey scale.	See Result 1	Pass
	chlorinated salt water	<u> </u>	
7.2.1 Colour	The change in colour of the warnings and markings shall be	See Result 1	Pass
fastness	3 or better on the grey scale according to EN 20105-A03.		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-and-Condit

4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661 f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 15 of 30

Clause	Test Method/Requirement	Result	Rating
7.3 Adhesion of m	narkings		
7.3.1	The markings shall not be damaged and shall remain legible	See Result 1	Pass
Requirements	in all details when assessed by the assessment panel.		
	The requirements do not apply where the warnings or		
	markings are embossed onto or moulded into the device.		
7.4 Provision of	Each floating leisure article shall be supplied with a repair	/	Pass
repair means	kit, together with instructions for use, suitable for repairing		
0 FN ICO 0504	small punctures of limited extent.		
2. EN ISO 2564			
4 Consumer info		1 /	D
4.1 General	Floatable leisure articles shall be accompanied by adequate	/	Pass
	product information. This information shall serve the		
	purpose of:	1	Dana
	— information before buying (point of sale information);	1	Pass
	— information for preparing the product for use;	1	Pass
	— information relating to the use of the product;	/	Pass
	— information concerning maintenance, storage and repair.	/	Pass
	Supplementary safety information symbols and safety signs as given in Clause 6 may be used to substitute the text and	'	Pass
	to inform the user about all relevant information related to		
	safety, use, sizing, etc.		
	The supplementary safety information symbol related to	/	Pass
	fatal risks shall be presented in a combination of this symbol	'	1 033
	and explanatory text.		
	This applies for the symbol "No protection against drowning"		
	(see Figure 1).		
	Figure 1 — No protection against drowning		
4.2 Consumer info	ormation at point of sale (information before buying)	ı	
4.2.1 General	Information at point of sale shall be given on the packaging	/	Pass
	or in a way that it can be noticed by the consumer, e.g.		
	through a transparent cover.		
	It shall include all data relevant for matching consumer	/	Pass
	needs with the performance characteristics of the product,		
	in particular those related to the rough shape (appearance)		
	and dimensions of the product, user specifications (age		
	groups, body weight, etc. if applicable), load capacity, place		
	of use, performance and relevant safety information.		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be proceduted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661

f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 16 of 30

Clause	Test Method/Requirement	Result	Rating
	As means of conveying this information in a unified and comprehensible way, the supplementary safety information symbol and safety sign as specified in Clause 6 shall be applied.	/	Pass
	When necessary, supplementary safety information symbol and safety sign shall be supplemented by plain text.	/	Pass
	The order of supplementary safety information symbols shall follow a coherent approach following the logic of buying and use.	/	Pass
	The supplementary safety information symbols and the safety sign shall be grouped together as specified in 6.2.	/	Pass
4.2.2 General	The general information is the following:	/	Pass
information to	Name and address of supplier;	/	Pass
be provided	— Type of device, designation;	/	Pass
	Picture or diagram showing the rough shape of the inflatable and its main dimensions;	/	Pass
	— Number of this document.	/	Pass
4.3 Information related to preparation for use	Information for installation and preparing for use shall be given in the instructions for use. In cases of simple design and use, it may be printed on the product.	/	Pass
4.4 Information related to maintenance, repair and storage	Information on maintenance, repair and storage shall be given in the instructions for use.	/	Pass
5 Requirements	related to printing		
5.1 General	Printing containing information shall be in contrast to its background.	/	Pass
	Supplementary safety information symbols and general safety signs shall be printed as shown in Clause 6.	/	Pass
5.2 Durability of printings on the product	Printings of all information on the product shall comply with the durability requirements given in ISO 25649-1:2017, Clause 7.	See Result 1	Pass
5.3 Language and	d letter size for plain text information on the product		
5.3.1 Requirements	Markings shall be printed or embossed in upper case, letter size not less than 5 mm in height for the word "WARNING" and not less than 3 mm in height lower case for the remaining text.	/	Pass
	Colour may vary but shall always be in contrast or relief to the background and be legible.	/	Pass
	Plain text information shall be given in the language of the country of sale.	/	Pass





Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 17 of 30

Clause	Test Method/Requirement	Result	Rating
6 Product safety		•	
6.1 General	Supplementary safety information symbols and general safety signs on the product or in the accompanying information material shall be in accordance with the layout as presented in Figure 1 to Figure 37.	/	Pass
6.2 Supplementar	ry safety information symbol		
6.2.1 Supplementary safety information symbols related to warnings	The supplementary safety information symbols below (allocation of the supplementary safety information symbol, see 6.7) shall be headed by the warning action sign in Figure 35.	/	Pass
6.2.2 Supplementary safety information symbols related to prohibition	The supplementary safety information symbols below (allocation of the supplementary safety information symbol see 6.7) shall be headed by the prohibition sign in Figure 37.	/	Pass
6.2.3 Supplementary safety information symbols related to mandatory instruction	The supplementary safety information symbols below (for allocation of the supplementary safety information symbol, see 6.7) shall be preceded by the mandatory action sign in Figure 36.	/	Pass
6.3 Safety sign	Figure 35 — General warning sign Figure 36 — General mandatory action sign Figure 37 — General prohibition sign	/	Pass
6.4 Position of supplementary safety	Supplementary safety information symbols expressing warnings shall be arrayed in a separate group and shall be visible during use of the product.	/	Pass
information symbol and safety sign	Graphical symbols or other means of consumer information are deemed visible during use if they are positioned on the top or sides of the product that are above the water surface during use and can therefore be seen when the product is placed in/on the water for intended use. This includes visibility during setup and/or boarding of the product.	/	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic Documents a thittp://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlikefully and offondors may be procedured to the fullest extent of the law. Unless otherwise attent the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please conta

4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661 f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 18 of 30

Clause	Test Method/Requirement	Result	Rating
	For those floating leisure articles providing more than one position of use (e.g. air mattresses), the graphical symbols or other means of consumer information shall be placed on the intended upper side of use.	/	N/A
	This group of supplementary safety information symbol and safety sign should be arranged as shown in Annex A.	/	Pass
	The supplementary safety information symbol shall be placed below or beside the safety sign.	/	Pass
	Figure 1 and Figure 20 shall be placed separately on the product. If relevant, number the sequences of chamber inflation by 1 or 2 times. Figure 1 — No protection against drowning Figure 20 — Swimmers only	/	Pass
6.5 Colour of supplementary	Colour of safety signs (see 6.3) shall be in accordance with ISO 3864-2.	/	Pass
safety information	The supplementary safety information symbols shall be in black and white.	1	Pass
symbols and safety sign	Supplementary safety information symbols and safety sign for foam products may be embossed.	/	N/A
6.6 Size of supplementary safety information symbol and safety sign	The size of supplementary safety information symbols and safety signs on the product shall be at least 30 mm × 30 mm minimum (for supplementary safety information symbol see Figure 38).	/	Pass
	Figure 38 — Sizing of supplementary safety information symbol	,	_
	The size of the supplementary safety information symbols and safety signs shall however correlate to the size of the product.	/	Pass
	For the graphical symbol in the supplementary safety information symbol, all available space shall be used.	/	Pass



4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661

t (86) 400 960 9661 f (86-21) 6115 6899 f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 19 of 30

Clause	Test Method/Requirement	Result	Rating
6.7 Allocation of	The safety sign (see Figures 35, 36 and 37) categorize the	/	Pass
the	supplementary safety information symbols in "warnings		
supplementary	symbols" "mandatory instruction symbols" and "prohibition		
safety	symbols".		
information	The general safety signs in Figures 35, 36 and 37 shall		
symbols	always be used in combination with following relevant supplementary safety information symbol (see Table 1 to		
	12).		
	NOTE Examples are given in Annex A.		
	The messages specified in Table 1 to 12 represent the		
	mandated safety information with which a floating leisure		
	article and/or the packaging shall be labelled.		
	Additional safety information shall be given if needed. It	/	Pass
	shall be visible and legible on the packaging and/or product.	,	
7 Instructions			
7.1 General	Instructions shall be supplied in (a) suitable language(s) and	/	Pass
	in simple terms, sufficient to enable the user to correctly		
	assemble, inflate and prepare the device for use afloat.		
	If relevant, guidance shall also be given on drying, storage	/	Pass
	and servicing of the inflatable.		
7.2 Safety	All safety information shall be provided in the instructions.	1	Pass
information	Full explanations related to the supplementary safety	/	Pass
	information symbol and general safety signs shall be given.		
	There shall be explanations emphasizing the dangers of not	/	Pass
	following the operator's instructions.	,	_
	A safety warning shall be included regarding the dangers	/	Pass
0.14: 1.1.11:	associated with uneven distribution of persons or loads.	,	_
8 Mislabelling	Safety warning and other information contained in this	/	Pass
	document shall anticipate the foreseeable misuse of the		
	relevant product.		
	If for example a product is clearly recognizable for use in open water requirements related to this application shall not		
	be bypassed by mislabelling it "Pool use only" (see Figure		
	32).		
	<i>S2).</i>		
	Figure 32 — Pool use only		



4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661

f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 20 of 30

Clause	Test Method/Requirement	Result	Rating
3. EN ISO 2564	9-3:2017		
	ments and test methods		
4.1 General	Construction of a floating leisure article shall be such that it corresponds in terms of design, dimensions, safety, strength and durability for its intended use. The requirements set out in this standard were chosen to ensure compliance with these considerations. If inflatable floating leisure articles shall provide buoyancy in several components then requirements apply to all components. Floating leisure articles shall provide residual buoyancy if one air chamber fails. This residual buoyancy shall maintain the safety of the device even if its function is lost. The following safety requirements are therefore related to: — design; — sizing; — materials; — strength; — performance; — information. In individual cases, due to the unpredictability, valency and indeterminability of existing and future concrete products, a corresponding choice shall be made. Design and appearance of floating leisure articles shall not change the intended primary function of these floating leisure articles nor introduce a toy play value.		Pass
	, admissible number of users and maximum load capacity	1	
4.2.1 General	Devices shall be marked according to their size and/or number of permitted users and maximum load capacity.	/	Pass
4.2.2 Sizing		T	
4.2.2.1 Requirements	If a specific size/body weight correlation between user and device is relevant, the marking shall be in accordance with the range of body weights.	/	N/A
	The size/body weights of the user shall be indicated on the product by completing the relevant boxes of the appropriate safety information symbol "User's body weight range" as specified in ISO 25649-2.	/	N/A
	, space per person and admissible number of users		
4.2.3.1 Requirements	A1-products shall be labelled with regard to the intended posture — lying/sitting — of the user(s) and the maximum permissible number of users.	A2 product	N/A



4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661

t (86) 400 960 9661 f (86-21) 6115 6899 f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 21 of 30

Clause	Test Method/Requirement	Result	Rating
	The minimum space for a user in lying posture shall correspond to a flexible template (adult/child) the dimensions of which are specified in ISO 25649-1:2017, A.1.1.	A2 product	N/A
	The minimum space for a sitting user shall correspond to the template (adult/child) as specified in ISO 25649-1:2017, A.1.2.	A2 product	N/A
	The angle between centre line of the template and tangential of a possible back rest, board wall, etc. shall be greater than 60° (see Figure 1).	A2 product	N/A
	a) At Themself 280 min dispusion (48 m m 28 m		
	a) A1, "Big raft": 3,8 m in diameter/4,8 m × 2,8 m		
	b) A1, "Small raft": 2,5 m in diameter/3 m × 2 m Key 1 template space per person, adult 2 template Space per person, child Figure 1 — Available space per person, determination of number of users		
	The total amount of users determined by the templates shall not contradict to the load capacity and floating stability of the device. Space requirement using templates is not applicable for ride-on devices where distinct upright seats and/or seating positions are imposed by the device.	A2 product	N/A
4.2.4 A2-products	s, space per person and admissible number of users		
4.2.4.1 Requirements	A-2 products shall provide distinct seat(s) or sitting areas or recognizable space where the user is to be positioned in the intended posture.	/	Pass
	Seats, etc. of ride-on devices shall be equipped with at least one grab handle for each permissible user.	/	N/A
	If the device implies sitting in line of more than one user, the sitting space for each user shall be at least a length of:	For one adult only	N/A
	— Child = 30 cm if the legs hang down;	For one adult only	N/A
	— Child = 60 cm if the thighs follow the seat surface.	For one adult only	N/A



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be proceduted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661

f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 22 of 30

Clause	Test Method/Requirement	Result	Rating
	Adult = 35 cm if the legs hang down;	For one adult	N/A
		only	
	Adult = 70 cm if the thighs follow the seat surface.	For one adult	N/A
		only	
4.3 In water perfo			
	puoyancy and stable floating position	1,	
4.3.1.1	All devices (A1, A2) shall provide sufficient buoyancy and	/	Pass
Requirements	adequate buoyancy distribution to bear the weight of the intended number of users.		
	Floating devices shall float stable with all test subjects	/	Pass
	placed	'	1 433
	on the intended position and posture on the device.		
	The design supporting area shall not be flooded, not	/	Pass
	applicable if the product is designed to provide a supporting		
	area which is intentionally under water.		
	Floating leisure articles claiming to provide floating stability	A2 product	N/A
	(A1) shall additionally meet the test as specified in 4.3.2.2.2.		
	When loaded with the maximum/minimum number of	A2 product	N/A
	passengers, the device shall maintain the stable floating		
	position as defined in ISO 25649-1:2017, 3.13.	,	
	The capability of stable floating performance or the need for	/	Pass
	balancing shall be marked on the packaging via the relevant		
	pair-safety information symbol "Device provides floating stability" and "Device requires balancing" as specified in ISO		
	25649-2.		
4 3 2 Residual bu	loyancy of devices claiming floating stability (CASES A, B)		
4.3.2.1 General	Where buoyancy is not provided by inherently buoyant	Case D	N/A
	material, the device shall have a minimum of two separate		
	air chambers distributing the buoyancy so that the		
	requirements in 4.3.2.2 are met.		
4.3.2.2 CASE A,	residual buoyancy and stable floating after failure of one air cha	amber	
4.3.2.2.1	A1-devices having a lying/seating area (cockpit) fully or	Case D	N/A
Requirements	partly surrounded by circumferential inflated chambers		
	(walls) regardless of their shape or form which provide an		
	inner wall height of at least 15 cm when measured from top		
	of the inflated bottom to the top of the inflated wall:		
	a) shall not collapse in a way that the permissible number of		
	users or a single user falls or slides into the water if the air		
	chamber most likely to cause failure is fully deflated; b) shall allow the permissible number of users to stay safely	Case D	N/A
	on the device for at least 10 min;	Case D	IN/A
	c) shall retain their function to stay on the device as far as	Case D	N/A
	there is an initial function which is relevant with regard to	J 300 D	13//3
	safety (e.g. propulsion to reach the shore).		
	If the device is made up by several independent	Case D	N/A
	components, these requirements apply for each of them.		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be proceduted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661

f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 23 of 30

Clause	Test Method/Requirement	Result	Rating
4.3.2.3 CASE B, r	esidual buoyancy and distinct means to hold on after failure of	one air chamber	
4.3.2.3.1 Requirements	A1-devices without distinct circumferential air chambers (walls) higher than the available area, CASE B-designs: a) shall at least provide a residual buoyancy which is sufficient to keep all permissible users somehow afloat on the device regardless of their posture on or in the water when holding onto the device;	Case D	N/A
	NOTE Persons are considered to be still on the device even if parts of the available area onto which they can remain is partly flooded, respectively the device takes a crucial floating angle so that these persons get partly into the water.		
	b) the achievable floating position shall enable the users to keep their airways above water level without exercising swimming strokes or any other active movements to keep them afloat except holding to the device;	Case D	N/A
	c) there shall be means on the device to grab on for each permissible user;	Case D	N/A
	d) these means shall be available and reachable for each permissible user after immersion.	Case D	N/A
	If the device is made up by several independent components these requirements apply for each of them.	Case D	N/A
4.3.3 Residual bud	oyancy of floating leisure articles not claiming floating stability	(CASES C, D)	
4.3.3.1 CASE C, r			
4.3.3.1.1 Requirements	A2-products of floating articles for single and collective use, CASE C-designs: a) shall at least provide a residual buoyancy which is sufficient to keep all permissible users afloat when holding onto it;	Case D	N/A
	b) the achievable floating position shall enable the users to keep their airways above water without exercising swimming strokes or any other active movements to keep them afloat except holding to the device;	Case D	N/A
	c) there shall be means on the device to grab on for each permissible user;	Case D	N/A
-	d) these means shall be available and reachable for each permissible user after immersion.	Case D	N/A
-	If the device is made up by several independent components, this requirement applies for each of them.	Case D	N/A
4.3.3.2 CASE D, r		•	
4.3.3.2.1 Requirements	A2-products of floating articles for single use only, CASE D designs: a) shall at least provide a residual buoyancy which is sufficient to keep the user when holding on to it after immersion;	/	Pass
ı	b) it shall be shown that the user is able to grab at least the	1	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be proceduted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

4th Building, No. 889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661 f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 24 of 30

Clause	Test Method/Requirement	Result	Rating
	entire remaining buoyant structure or parts of it in a way		
	enabling him to stay safely afloat with the airways above		
	water level without exercising swimming strokes or any		
	other active movements to keep them afloat except holding		
	onto the device.		
	If the device is made up by several independent	/	Pass
	components, this requirement applies for each of them.		
4.3.4 Capsizing a			
4.3.4.1 Escape	In normal foreseeable use and during incidents of sudden	/	Pass
from the device	capsize none of the users shall become entrapped,		
(body	entangled or otherwise hindered from complete separation		
entrapment,	from the device.		
leg/foot	For this purpose, the standard is focusing on the following		
entanglement)	known major entrapment risks:		
	— foot/leg entrapment;		
	— head/neck entrapment;		
	— torso entrapment;		
	entanglement due to protruding parts.		
	There shall be no entrapment/entanglement of the test		
	devices/test probes if they are applied on the product in its		
	normal working position.		
	es and safety lines (not applicable to air mattresses)	1	
4.3.5.1	Floating leisure articles of CASES A, B and C in 4.3.2.2;	Case D	N/A
Requirements	4.3.2.3 and 4.3.3.1 shall be fitted with means of holding		
	(grab handles, safety lines, etc.) for each permissible user		
	which are reachable from an on- board position and/or also		
	for persons in the water.		
	Safety lines shall be arranged in a way that they	Case D	N/A
	can be grabbed from an in-water position and shall not		
	cause entrapment (see 4.3.2.2).		
	The means of holding shall be provided regardless of the	Case D	N/A
	floating stability of the device and shall be reachable also in		
	capsized condition of the device.	<u> </u>	
	ation from the water in normal use and failure of one air chamb		
4.3.6.1	Floating devices shall be so designed that a normal user	A2 product	N/A
Requirements	(test subject) is able to re-embark on the device.		
	Not applicable to A.2 products or borderline products falling		
	under A.2.		
	h super structure (wind, drift)	1	
4.3.7.1	Floating articles of Class A having a superstructure which	/	N/A
Requirements	exceeds 100 cm above water level shall be restricted to		
	pool use by marking them with the safety information		
	symbol "Pool use only" according to ISO 25649-2.		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx.and, for electronic Documents a thittp://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlikefully and offondors may be procedured to the fullest extent of the law. Unless otherwise attent the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or small: CN. Doccheck@sqs.com 90 testing /inspection report & certificate, please conta

4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661 f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 25 of 30

Clause	Test Method/Requirement	Result	Rating
4.3.8 Anchorage			
4.3.8.1 Requirements	If a floating leisure article is equipped with an anchoring device, it shall be capable to hold the device in place up to a pulling force of 500 N.	No anchoring device	N/A
	with bottom, strength of entire device		
4.3.9.1 General	No part or component of the body holding system or its attachment to the buoyant structure (welding seams) shall break or show any deficiency compromising safety.	/	N/A
5 Consumer info			
5.1 General	Consumer information (on the packaging, on the product and by means of written instructions for use) shall be in accordance with ISO 25649-2.	/	Pass
5.2 Consumer information on the packaging	Information on the packaging of Class A products shall — show a picture or dimensional correct drawing of the floating article inside,	/	Pass
(point of sale information)	disclose via the appropriate safety information symbols any warning and restriction related to use and application, and	/	Pass
	disclose via the appropriate safety information symbols the maximum number of users and the maximum load capacity.	/	Pass
5.3 Consumer information on the product (information	Consumer information on the product shall — show via the appropriate safety information symbols all warnings and obligatory instructions related to the safe use of the product.	/	Pass
related to safe use)	Safety information symbols related to very serious risks shall be accompanied by the plain text version as specified in ISO 25649-2.	/	Pass
	Very serious risks for Class A products are: — Attention! No protection against drowning! — Swimmers only!	/	Pass
5.4 Consumer info	ormation by instructions for use (separate written information)		
5.4.1 General	Instructions of use shall be in accordance with ISO 25649-2.	/	Pass
5.4.2 Safety and product information	Instruction for use shall contain all information provided in 5.1, 5.2 and 5.3. Warnings, obligatory instructions and all restrictions in use shall be explained in a way that they can be understood and perceived by the user.	/	Pass
	Safety information symbols shall be explained by their plain text version.	/	Pass
5.4.3 Assembly (if applicable)	Instructions shall enable the user to assemble the floating article correctly and ready for safe use.	1	Pass
5.4.4 Maintenance and repair (if applicable)	Instructions shall enable the user to maintain store and repair the floating article correctly.	/	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.aspx and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forger or falsification of the content or appearance of this document is unlawful and offenders may be proceduted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing inspection report & certificate, please contact us at telephone: (86-755) 8307 1443,

4th Building, No.889, Yishan Road, Xuhui District Shanghai, China 200233 中国・上海・徐汇区宜山路889号4号楼 邮编: 200233

t (86) 400 960 9661 f (86-21) 6115 6899 t (86) 400 960 9661

f (86-21) 6115 6899



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 26 of 30

Remark:

- 1. The dimension of the valve is different from the standard, but the function test result is positive.
- 2. N/A = Not applicable.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service prints overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.spx.nd, for lectronic format document subject to Terms and Conditions for Electronic Document as the <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forger yor falsification of the content approarance of this document is unlawful and offenders may be prococuted to the fullcate extent of the law. Unloss otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 27 of 30

Result 1:

Clause 7.1 Resistance to Perspiration (ISO 105 E04-2013)

Acidic

Change in shade 4-5

<u>Alkaline</u>

Change in shade 4-5

Requirement:

The change in colour of the warnings and markings according to EN 20105-A02 and shall be 3 or better

on the grey scale.

Remarks: Grey Scale Rating is based on the 5-step scale of 1 to 5, where 1 is bad and 5 is good.

Clause 7.2 Resistance to Chlorinated Salt Water

Change in shade 4-5

Requirement:

The change in colour of the warnings and markings according to EN 20105-A02 and shall be 3 or

on the grey scale.

Remarks: Grey Scale Rating is based on the 5-step scale of 1 to 5, where 1 is bad and 5 is good.

Clause7.3 Adhesion of markings (ISO 105 X12-2016, 100 cycles)

Dry - Assessment: No damaged and remain legible in all details

when assessed by the assessment panel

Wet - Assessment: No damaged and remain legible in all details

when assessed by the assessment panel

Requirement: The markings shall not be damaged and shall remain legible in all details when assessed by the assessment panel.





Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 28 of 30



Since the data and / or information above division line of front page is provided by the applicant, the relevant results or conclusions of this report are only made for these data and / or information, SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion. Testing results only apply to the sample as received.

The declaration of conformity is only based on the actual value of laboratory activity, measurement uncertainty of the results not take into account.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service prints overleaf, available on request or accessible at http://www.sgs.com/en/Terms-and-Conditions.spx.nd, for lectronic format document subject to Terms and Conditions for Electronic Document as at <a href="http://www.sgs.com/en/Terms-end-Conditions/Terms-e-Document.aspx.Attention is drawn to the limitation of liability, indemnification and jurisdiction issues define therein. Any holder of this document advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduce except in full, without prior written approval of the Company. Any unauthorized alteration, forger or fallsification of the content approarance of this document cannot be reproduced to the fullow of the content of the low. Unloss otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only to the sample(s) tested and such sample(s) are retained for 30 days only the sample(s) tested and such sample(s) are retained for 30 days only the sample(s) tested and such sample(s) are retained for 30 days only the sample(s) tested and such sample(s) are retained for 30 days only the sample(s) tested and such sample(s) are retained for 30 days only the sample(s) tested and such sample(s) are retained for 30 days only the sample(s) tested and such sample(s) are retained for 30 days only the sample(s) tested and such sample(s) are retained for 30 days only the sample(s) tested and such sample(s) are retained for 30 days only the sample(s) tested and such sample(s) are retained for 30 da



Test Report No.: SHHL2003505229IF Date: MAR. 27, 2020 Page: 29 of 30

Sample Photo:

Test sample



Marking on product



Marking on product



Artwork of instruction manual





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com/en/Terms.and-Conditions.apx and, for electronic Documents at http://www.sgs.com/en/Terms.and-Conditions/Terms-e-Document.aspx. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document annot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or apporance of this document is unlawful and offonders may be prococuted to the fullost extent of the faw. Unloca otherwise stated the results shown in this test report refer only to the sample(s) are responsed for 50 days only.




Test Report

No.: SHHL2003505229IF

Date: MAR. 27, 2020

Page: 30 of 30

Repair patch



SGS authenticate the photo on original report only

End of Report

