

Fujitsu recommends Windows 11 Pro.

Data Sheet

FUJITSU Workstation CELSIUS M7010

Bring Your Ideas To Life

Looking for a true workhorse to speed up your creative and engineering workflows? The CELSIUS M7010 is designed to help power users achieve next level of performance and reliability by enabling them design products, build complex 3D models, run simulations, create & visualize digital content. It is a highly expandable VR ready workstation optimized for demanding CAD, CAE and media & entertainment applications.

Performance you can count on

Spectrum of performance due to a wide range of professional grade features

- Powerful Intel® Xeon® Processor W Family
- Support of Windows 10 Pro for Workstations
- Support of up to 512 GB DDR4 2,933 memory
- Fujitsu SSD PCIe card (up to 2 x 2 TB)

Dual GPU, VR ready workstation

Enjoy a fully immersive and real-time virtual reality experience with low latency at high frame rates

- Intel® vPro® processors with up to 4.6 GHz frequency
- Professional graphics cards up to NVIDIA RTX™ A6000 and AMD Radeon™ Pro WX 3200
- Support for NVIDIA® NVLink™ technology – inter-GPU communication protocol, which makes it perfect for scientific and high-end renderings



Ultimate reliability, usability and innovative design

Quality you can trust

- Built for 24/7 operations with reliable top-quality components
- Intelligent tri-channel thermal management
- Cable-free design and green touchpoints
- Cold-plug technology: Storage accessible via a front disk tray

Robust security

Human centric innovation meets security

- Optional security lock (side door and front access)
- Intrusion detector sensor integrated into the power supply
- USB keyboard with integrated PalmSecure™: Easy log-on with the help of your palm veins frame rates



Components

| | CELSIUS M7010 (S26361-K1507-V165) | CELSIUS M7010power (S26361-K1507-V265) |
|--------------------------------|--|---|
| Processor | Intel® Xeon® processor W-2295 (18 cores, 3.00 GHz, up to 4.6 GHz) Intel® Xeon® processor W-2275 (14 Cores, 3.30 GHz, up to 4.6 GHz) Intel® Xeon® processor W-2265 (12 Cores, 3.50 GHz, up to 4.6 GHz) Intel® Xeon® processor W-2255 (10 Cores, 3.70 GHz, up to 4.5 GHz) Intel® Xeon® processor W-2245 (8 Cores, 3.90 GHz, up to 4.5 GHz) Intel® Xeon® processor W-2235 (6 Cores, 3.80 GHz, up to 4.6 GHz) Intel® Xeon® processor W-2225 (4 Cores, 4.10 GHz, up to 4.6 GHz) Intel® Xeon® processor W-2223 (4 Cores, 3.60 GHz, up to 3.9 GHz) Intel vPro® technology | |
| Operating systems | | |
| Operating system pre-installed | Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 10 Pro | |
| Operating system compatible | FREE Upgrade to Windows 11* *Upgrade timing may vary by device. Features and app availability may vary by region. Certain features require specific hardware (see aka.ms/windows11-spec). | |
| Operating system notes | Certified for Red Hat® Enterprise Linux Certified for SUSE Enterprise Desktop Certified for SUSE Enterprise Server After the end of the product life Fujitsu will continue to test and support all upcoming Windows releases for a period of maximum 5 years, depending on the available extension of hardware services through Fujitsu Warranty top ups. For details please see "Fujitsu Service Statement for Windows General Availability Channel" at https://support.ts.fujitsu.com/IndexProdSupport.asp?lng=com&OpenTab= | |
| | CELSIUS M7010 (S26361-K1507-V165) | CELSIUS M7010power (S26361-K1507-V265) |
| Memory modules | 8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,933 MT/s 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s 32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s 64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s | 8 GB (1 module(s) 8 GB) DDR4, registered, ECC, 2,933 MT/s 16 GB (1 module(s) 16 GB) DDR4, registered, ECC, 2,933 MT/s 32 GB (1 module(s) 32 GB) DDR4, registered, ECC, 2,933 MT/s 64 GB (1 module(s) 64 GB) DDR4, registered, ECC, 2,933 MT/s |
| Graphics | High-end 3D: NVIDIA® Quadro® RTX 4000, 8 GB, PCIe x16, 3 x DisplayPort, 1 x Virtual Link Midrange 3D: NVIDIA RTX™ A2000, 6 GB, PCIe x16, 4 x DisplayPort Midrange 3D: NVIDIA RTX™ A2000, 6 GB, PCIe x16, 4 x DisplayPort Entry 3D: NVIDIA® T600, 4 GB, PCIe x16, 4 x miniDP Entry 3D: NVIDIA® T400, 2 GB, PCIe x16, 3 x miniDP Entry 3D: NVIDIA® T1000, 4 GB, PCIe x16, 4 x miniDP Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4 x miniDP Entry 3D: AMD Radeon™ Pro WX 3200, 4 GB, PCIe x16, 4 x miniDP Remote Graphics: CELSIUS RemoteAccess Quad Card, PCIe x1, 4 x miniDP, PCoIP Remote Graphics: CELSIUS RemoteAccess Dual Card, PCIe x1, 2 x miniDP, PCoIP Others: MiniDP to DP Adapter Cable Others: DP to DVI-D (single link) Adapter Cable | Ultra-high-end 3D: NVIDIA® Quadro® RTX 6000, 24 GB, PCIe x16, 4 x DisplayPort, 1 x Virtual Link Ultra-high-end 3D: NVIDIA® Quadro® RTX 5000, 16 GB, PCIe x16, 4 x DisplayPort, 1 x Virtual Link Ultra-high-end 3D: NVIDIA® Quadro® P6000, 24 GB, PCIe x16, 1 x Dual Link DVI-D, 4 x DisplayPort High-end 3D: NVIDIA® Quadro® RTX 4000, 8 GB, PCIe x16, 3 x DisplayPort, 1 x Virtual Link Midrange 3D: NVIDIA RTX™ A2000, 6 GB, PCIe x16, 4 x DisplayPort Midrange 3D: NVIDIA RTX™ A2000, 6 GB, PCIe x16, 4 x DisplayPort Entry 3D: NVIDIA® T600, 4 GB, PCIe x16, 4 x miniDP Entry 3D: NVIDIA® T400, 2 GB, PCIe x16, 3 x miniDP Entry 3D: NVIDIA® T1000, 4 GB, PCIe x16, 4 x miniDP Entry 3D: NVIDIA® Quadro® P1000, 4 GB, PCIe x16, 4 x miniDP Entry 3D: AMD Radeon™ Pro WX 3200, 4 GB, PCIe x16, 4 x miniDP Remote Graphics: CELSIUS RemoteAccess Quad Card, PCIe x1, 4 x miniDP, PCoIP Remote Graphics: CELSIUS RemoteAccess Dual Card, PCIe x1, 2 x miniDP, PCoIP Others: MiniDP to DP Adapter Cable Others: DP to DVI-D (single link) Adapter Cable |

| CELSIUS M7010 (S26361-K1507-V165) | CELSIUS M7010power (S26361-K1507-V265) |
|---|--|
| Hard disk drive | CELSIUS M7010 (S26361-K1507-V165) |
| | HDD SAS, 10,000 rpm, 1200 GB, 2.5-inch |
| | HDD SAS, 10,000 rpm, 1800 GB, 2.5-inch |
| | HDD SAS, 10,000 rpm, 2400 GB, 2.5-inch |
| | HDD SAS, 10,000 rpm, 600 GB, 2.5-inch |
| | HDD SATA III, 7,200 rpm, 1,000 GB, 2.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch |
| | HDD SATA III, 7,200 rpm, 1,000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 2,000 GB, 2.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch |
| | HDD SATA III, 7,200 rpm, 2,000 GB, 3.5-inch, business critical |
| | HDD SATA III, 7,200 rpm, 4,000 GB, 3.5-inch, business critical |
| | SSD PCIe, 1024 GB M.2 NVMe Highend module |
| | SSD PCIe, 1x 2048 GB M.2 NVMe Highend card |
| | SSD PCIe, 1x 512 GB M.2 NVMe Highend card |
| | SSD PCIe, 1x1024 GB M.2 NVMe Highend card |
| | SSD PCIe, 2048 GB M.2 NVMe Highend module |
| | SSD PCIe, 256 GB M.2 NVMe Highend module |
| | SSD PCIe, 2x 1024 GB M.2 NVMe Highend card |
| | SSD PCIe, 2x 2048 GB M.2 NVMe Highend card |
| | SSD PCIe, 2x 512 GB M.2 NVMe Highend card |
| | SSD PCIe, 512 GB M.2 NVMe Highend module |
| | SSD SATA III, 1024 GB, 2.5-inch |
| | SSD SATA III, 240 GB High Endurance, 1DWDP, 2.5-inch |
| | SSD SATA III, 256 GB, 2.5-inch |
| | SSD SATA III, 480 GB High Endurance, 1.5DWDP, 2.5-inch |
| | SSD SATA III, 512 GB, 2.5-inch |
| | SSD SATA III, 960 GB High Endurance, 1.5DWDP, 2.5-inch |
| Mass storage 3.5 inch size | HDD SATA III, 7,200 rpm, 8000 GB, 3.5-inch, business critical |
| Hard disk notes | HDD SATA III, 7,200 rpm, 8000 GB, 3.5-inch, business critical |
| | One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. |
| | 24/7 ready (Business Critical HDDs or SAS HDDs or High Endurance SSDs required) |
| | Up to 20 GB of HDD space is reserved for system recovery |
| | SED (Self-Encrypting Drive) |
| | SSD (Solid State Disk) |
| Optical drive | CELSIUS M7010 (S26361-K1507-V165) |
| | MultiCard Reader 24in1 USB 2.0 3.5", USB 2.0 |
| | DVD-ROM |
| | DVD Super Multi, SATA |
| | DVD Super Multi ultra slim (tray), SATA |
| | BD Triple Writer SATA ultra slim (tray), SATA |
| SCSI / SAS Controller | CELSIUS M7010 (S26361-K1507-V165) |
| | LSI RAID Ctrl SAS 1GB (D3216) RAID 5/6 Ctrl. 12 Gbit/s 8 ports int. |
| | LSI RAID Ctrl SAS (D3327) RAID 0/1 Ctrl. 12 Gbit/s 8 ports int. |
| | Intel VROC HW key Standard M.2 |
| Interfaces add on cards / components | CELSIUS M7010 (S26361-K1507-V165) |
| | WLAN 802.11ac (2x2) PCIe x1 and BT 5, SRD 5.8GHz (dedicated regions only) |
| | PLAN EP X550-T2 2x10GBASE-T |
| | Intel 2x1Gb Ethernet Adapter I350-T2 |
| | Dual serial card PCIe x1 |
| | Dual 10 Gigabit Ethernet PCIe x8 |
| | CELSIUS M7010 (S26361-K1507-V165) |
| | CELSIUS M7010power (S26361-K1507-V265) |

Base unit

| Base unit | CELSIUS M7010 (S26361-K1507-V165) | CELSIUS M7010power (S26361-K1507-V265) |
|------------|-----------------------------------|--|
| Page 3 / 8 | | www.fujitsu.com/emeia/CELSIUS |

Mainboard

| | |
|-------------------------------|---|
| Mainboard type | D3498-A2 |
| Formfactor | extended ATX |
| Chipset | Intel® C422 |
| Processor socket | Socket R4 |
| Processor quantity maximum | 1 |
| Supported capacity RAM (max.) | 512 GB |
| Memory slots | 8 DIMM (DDR4) ECC |
| Memory frequency | 2,933 MT/s |
| Memory notes | 4 memory channels supporting up to 2 DIMMs per channel. For quad channel, a minimum of 4 memory modules have to be ordered and the capacity per channel has to be the same. DDR4 2,933MHz may be clocked down to 2,666 or 2,400 or 2,133 depending on the processor. |

LAN

10/100/1,000 MBit/s Intel® I219LM

BIOS version

AMI Aptio V

BIOS featuresBIOS Flash EPROM update by software
Recovery BIOS
Unified Extensible Firmware Interface (UEFI)**Audio type**

On board

Audio codec

Realtek ALC671

Audio features

High Definition Audio

I/O controller on board

| | |
|----------------------|---|
| Serial ATA total | 8 |
| thereof SATA III | 8 |
| thereof eSATA | |
| Controller functions | Serial ATA III (6 Gbit) NCQ AHCI RAID 0/1/5/10 |

Interfaces

| | |
|------------------------------|---|
| Audio: in (rear) | 1 |
| Audio: out (rear) | 1 |
| Audio: in | 1 |
| Audio: out | 1 |
| Internal speakers | 1 |
| USB 2.0 total | 2 optional via front panel |
| USB 3.1 Gen1 (USB 3.0) total | 6 |
| USB 3.1 Gen2 total | 2 optional via front panel |
| USB front | 2x USB 2.0; 2x USB 3.1 (Gen1); optional: 2x USB 3.1 Type-C (Gen2) instead of 2x USB 2.0 |
| USB rear | 6 |
| USB internal | 3, thereof 1 type A |
| Ethernet (RJ-45) | 1 |
| eSATA | 1 (optional) |
| Interface Module notes | Anytime USB charge functionality |

Drive bays

| | |
|-------------------------|---|
| Drive bays total | 7 |
| 2.5-inch internal bays | 4 |
| 3.5-inch internal bays | 4 |
| 3.5-inch external bays | 1 |
| 5.25-inch external bays | 1 |
| Drive bay notes | Total 4x 3.5-inch/2.5-inch Disk Tray front accessible (with Cold-plug access) |
| M.2-2280 | 1 x on mainboard (for PCIe SSD modules) |

Slots

| | |
|--------------------|---------------------------------------|
| PCI-Express 3.0 x1 | 2 x (340 mm / 13.39 inch) Full height |
|--------------------|---------------------------------------|

| Slots | | |
|--|--|--|
| PCI-Express 3.0 x4 | 2 x (340 mm / 13.39 inch) Full height | |
| PCI-Express 3.0 x8 | 1 x (200 mm) Full height | |
| PCI-Express 3.0 x16 | 2 x (340 mm / 13.39 inch) Full height | |
| Base unit | CELSIUS M7010 (S26361-K1507-V165) | CELSIUS M7010power (S26361-K1507-V265) |
| Electrical values | | |
| Power consumption note | 225 W depending on configuration | 400 W depending on configuration |
| Rated voltage range | 100 V - 240 V | 100 V - 240 V |
| Rated frequency range | 50 Hz - 60 Hz | 50 Hz - 60 Hz |
| Operating voltage range | 90 V - 264 V | 90 V - 264 V |
| Operating line frequency range | 47 Hz - 63 Hz | 47 Hz - 63 Hz |
| Max. output of single power supply | 450 W up to 90% efficiency | Continuous main output power - 800 W (up to 90% efficiency) Peak main output power - 1080 W for max. duration of 10ms |
| Power factor correction/active power | active | active |
| Power supply output | 2 graphics power rails (on Mainboard) | 2 graphics power rails (on Mainboard) |
| Base unit | CELSIUS M7010 (S26361-K1507-V165) | CELSIUS M7010power (S26361-K1507-V265) |
| Noise for standard configuration (HDD, ODD) | | |
| Related Processors for noise | 140W Thermal Design Power (TDP) Processor | 140W Thermal Design Power (TDP) Processor |
| Standard noise emission | According to ISO 7779:2010, ECMA-74 | According to ISO 7779:2010, ECMA-74 |
| Standard noise notes / description | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) | A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A)) |
| Standard noise operation mode: CPU 50% load | 3.6 B / 20 dB(A) Bystander position | 3.6 B / 20 dB(A) Bystander position |
| Standard noise operation mode: CPU 90% load | 3.7 B / 20 dB(A) Bystander position | 3.7 B / 20 dB(A) Bystander position |
| Standard noise operation mode: HDD load | 3.5 B / 19 dB(A) Bystander position | 3.5 B / 19 dB(A) Bystander position |
| Standard noise operation mode: Idle mode | 3.5 B / 19 dB(A) Bystander position | 3.5 B / 19 dB(A) Bystander position |
| Standard noise operation mode: ODD load | 4.5 B / 28 dB(A) Bystander position | 4.5 B / 28 dB(A) Bystander position |
| Standard noise operation mode: Office applications 2.0 | 3.7 B / 21 dB(A) Bystander position | 3.7 B / 21 dB(A) Bystander position |
| Dimensions / Weight / Environmental | | |
| Dimensions (W x D x H) | 176 x 500 x 433 mm 6.9 x 19.7 x 17.1 inch | |
| Operating position | Vertical / horizontal | |
| Weight | approx. 18 kg | |
| Weight (lbs) | approx. 39.67 lbs | |
| Weight notes | Actual weight may vary depending on configuration | |
| Operating ambient temperature | 10 - 35 °C (50 - 95 °F) | |
| Operating relative humidity | 5 - 85 % (relative humidity) | |
| Compliance | | |
| Product | CELSIUS M7010 | CELSIUS M7010power |
| Model | CM17 | |
| Germany | GS depending on configuration | |
| Europe | CE | |
| USA/Canada | FCC Class B cCSAus | |

Compliance

| | |
|------------------|---|
| Global | RoHS (EU & China) Microsoft Operating Systems (HCT / HCL entry / WHQL) WEEE (Waste electrical and electronic equipment) ENERGY STAR® 7.0 compliant |
| China | CCC (depending on configuration) TPM 2.0 for China (optional) |
| Compliance notes | Product Name maybe followed by suffixes |
| Compliance link | https://sp.ts.fujitsu.com/sites/certificates |

Additional Software

| | |
|------------------------------------|---|
| Additional software (preinstalled) | McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre-installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.) |
| Additional software (optional) | Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL |

| | | |
|-----------|-----------------------------------|--|
| Base unit | CELSIUS M7010 (S26361-K1507-V165) | CELSIUS M7010power (S26361-K1507-V265) |
|-----------|-----------------------------------|--|

| | | |
|--------------------------|---|---|
| Physical Security | Kensington Lock support Eye for padlock Intrusion switch Integrated cabinet lock (optional) | Kensington Lock support Eye for padlock Intrusion switch Integrated cabinet lock (optional) |
| System and BIOS Security | Embedded security (TPM 2.0) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces | Embedded security (TPM 2.0) Boot sector virus protection Write protect option for the Flash EPROM Control of all USB interfaces External USB ports can be disabled separately Control of external interfaces |
| User Security | User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution) | User and supervisor BIOS password Hard disk password Access protection via external SmartCard reader (optional) Access protection via internal SmartCard reader (optional) Workplace Protect (secure authentication solution) |
| Workplace Embedded Tools | Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional) | Auto BIOS Update via Fujitsu Server Auto BIOS Update via customer server (optional) Easy PC Protection (optional) |

Manageability

| | |
|--------------------------|--|
| Manageability technology | DeskUpdate Driver management iAMT 11.6 (depending on processor) PXE 2.1 Boot code Wake up from S5 (off mode) Intrusion switch (optional) WoL (Wake on LAN) |
| Manageability software | DeskView Client DeskView Instant BIOS Management |
| DeskView components | Inventory Management BIOS Management Driver Management Security Management Alarm Management |
| Supported standards | WMI (Windows Management Instrumentation) PXE (Preboot Execution Environment) DMI (Desktop Management Interface) SMBIOS (System Management BIOS) WBEM (Web Based Enterprise Management) CIM (Common Information Model) |
| Manageability link | http://www.fujitsu.com/fts/manageability |

Miscellaneous

| | | |
|-------------------------|---------------------|---------------------|
| | Rack mountable (4U) | Rack mountable (4U) |
| Spare part availability | 5 years | 5 years |

Packaging information

| | | |
|-----------------|---|---|
| Packaging notes | printed user documentation is bleached in chlorine free process | printed user documentation is bleached in chlorine free process |
|-----------------|---|---|

Warranty

| | |
|-----------------------------|--|
| Warranty type | Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations) |
| Warranty Terms & Conditions | http://www.fujitsu.com/warranty |
| Digital bug fixes | Subject to availability and following their generic release for the product, bug fixes and function-preserving patches for product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/ free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer. |

Product Support Services - the perfect extension

| | |
|-----------------|---|
| Service Weblink | http://www.fujitsu.com/emeia/products/product-support-services/ |
|-----------------|---|

Recommended Accessories

SpaceMouse Pro



Using the SpaceMouse™ Pro 3D mouse to navigate 3D models or environments is as simple as holding them in your hand. A slight movement of the controller cap delivers easy and precise control. SpaceMouse™ Pro is a companion to the traditional mouse and is operated with the free hand. Your traditional mouse hand is free to select, create and edit.

Order Code:
S26381-K459-L100

Keyboard KB950 Phone



The KB950 Phone is a modern and slim line USB keyboard with integrated Skype for business features. This extremely reliable, high-speed input device is the perfect way to manage incoming and outgoing calls, even when the system is locked. Three additional keys make it easy to accept and end calls and mute your microphone during a call. Easy number dialing is assured with the numpad. The integrated 61 x 12 mm display shows the time and date, the user status and shows incoming call data in the form of the calling number and caller ID.

S26381-F950-L4** (**:
Country specific variation)

More information

Fujitsu products, solutions & services

In addition to the FUJITSU Workstation CELSIUS M7010, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about the FUJITSU Workstation CELSIUS M7010, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/CELSIUS

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT.

Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>

Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH

Website: www.fujitsu.com

2022-04-01 EM-EN

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see <http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html>

Copyright 2020 Fujitsu Technology Solutions GmbH