Fujitsu recommends Windows 10 Pro for business.



Data Sheet FUJITSU Desktop ESPRIMO Q7010

Mini PC with excellent performance and integration capabilities

The FUJITSU ESPRIMO Q7010 is an elegant mini PC which provides excellent performance with high energy efficiency. This mini-PC can be used for various purposes apart from the standard office usage like for embedded applications, can be VESA mounted for attaching the PC to displays, stands or walls. The FUJITSU ESPRIMO Q7010 provides an experience of a cleaner, quieter workplace with Zero Noise PC function thus helping to boost office ergonomics and productivity.

An elegant mini PC with great performance

Eye-catching exclusive modern design

- Fully equipped PC with a volume of ~2.0 liters based on standard desktop technology
- 10th generation Intel® Core[™] processor family
- Features multi-bay concept (DVD option/ Smartcard reader option)

Zero Noise PC

Pleasant working environment due to completely quiet system

■ Fan stop in standard operations

Ultimate usability

Various use case scenarios including for special purpose applications

- Can be used for horizontal or vertical operations and easy upgrade of major components
- VESA mount for attaching the PC to displays, stands or walls
- Embedded usage like PoS systems and optional Windows 10 IoT operating system

Feature-rich and highly energy-efficient

Do a lot more with this mini-PC and also get significantly reduced energy bill

- Integrated power supply leads to less than 5 watts power consumption in idle-mode
- Ready for future needs with double max. memory size, improved graphics

State-of-the-art security features

Keep your most valuable assets safe - your data

- Integrated Smartcard reader and security front bezel to prevent misuse
- Embedded security (TPM 2.0), Fujitsu Authconductor software, Kensington Lock support





Components

Operating systems	
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business. Windows 10 Home
Operating system notes	Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support.ts.fujitsu.com.
Processor	Intel® Core™ i7-10700T processor (8 Cores / 16 Threads, 2.00 GHz, 16 MB, Intel® UHD Graphics 630) **
	Intel® Core™ i5-10600T processor (6 Cores / 12 Threads, 2.40 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i5-10500T processor (6 Cores / 12 Threads, 2.30 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i5-10400T processor (6 Cores / 12 Threads, 2.00 GHz, 12 MB, Intel® UHD Graphics 630) *
	Intel® Core™ i3-10100 processor (4 Cores / 8 Threads, 3.60 GHz, 6 MB, Intel® UHD Graphics 630) *
	Intel® Celeron® processor G5905 (2 Cores / 2 Threads, 3.50 GHz, 4 MB, Intel® UHD Graphics 610)
	Intel® Pentium® Gold G6400 (2 Cores / 4 Threads, 4.00 GHz, 4 MB, Intel® UHD Graphics 610)
	*with Intel® Turbo Boost Technology 2.0 (clock speed and performance will vary depending on workload and other variables)
Ethernet (RJ-45)1	
Memory modules	4 GB (1 module(s) 4 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, SO DIMM
	8 GB (1 module(s) 8 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, SO DIMM
	16 GB (1 module(s) 16 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, SO DIMM
	32 GB (1 module(s) 32 GB) DDR4, unbuffered, non-ECC, 2,933 MT/s, SO DIMM
Mass storage 2.5 inch size	SSD SATA III, 512 GB, 2.5-inch
•	SSD SATA III, 256 GB, 2.5-inch
Mass Storage M.2 technology	SSD PCIe, 1024 GB M.2 NVMe module, SED
	SSD PCIe, 1024 GB M.2 NVMe module
	SSD PCIe, 512 GB M.2 NVMe module, SED
	SSD PCIe, 512 GB M.2 NVMe module
	SSD PCIe, 256 GB M.2 NVMe module, SED
	SSD PCIe, 256 GB M.2 NVMe module
	SSD PCIe, 128 GB M.2 NVMe module
Mass storage 2.5 inch size	HDD SATA III, 5,400 rpm, 2000 GB, 2.5-inch
	HDD SATA III, 5,400 rpm, 1000 GB, 2.5-inch
	HDD SATA III, 5,400 rpm, 500 GB, 2.5-inch
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. SSD (Solid State Disk)
	SED (Self-Encrypting Drive) 2.5-inch bay for devices with 7mm height
Drives (optional)	BD Triple Writer SATA ultra slim (tray)
	DVD Super Multi ultra slim (tray)
Interface add on cards/components (optional)	
	Intal® WI-FL6 AY200 and Rhietooth 5.1 (dedicated regions only)

Intel® WI-FI 6 AX200 and Bluetooth 5.1 (dedicated regions only)

Base unit

Base unit	ESPRIMO Q7010
Mainboard	ESI NIMO 07010
	D3813
Mainboard type Formfactor	
	proprietary Intel® H470
Chipset Processor socket	LGA 1200
	1
Processor quantity maximum	64 GB
Supported capacity RAM (max.)	
Memory slots	2 DIMM (DDR4)
Memory frequency	2,933 MT/s
Memory notes	Dual channel support For dual channel performance, 2 memory modules have to be ordered. Capacity per channel has to be the same. 2933 MHz may be clocked down to 2400MHz depending on processor and memory configuration
LAN	10/100/1,000 MBit/s Realtek RTL8111H
Integrated WLAN	1 (optional with Bluetooth together)
BIOS version	AMI Aptio V UEFI Specification 2.6
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)
Audio type	On board
Audio codec	Realtek ALC623
Audio features	Internal speaker supports audio playback (optional), High Definition audio
I/O controller on board	
Serial ATA total	2
thereof SATA III	2
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI
Interfaces	
Audio: line-out	1
Front audio: headset	1
USB 2.0 total	4
USB 3.2 Gen 1 (5 Gbps) total	4
USB 3.2 Gen 2 (10 Gbps) total	3
USB front	2x Type-A USB 3.2 Gen 2; 1x Type-C USB 3.2 Gen 2; supports up to 15W)
USB rear	2x Type-A USB 2.0; 4x Type-A USB 3.2 Gen 1; 1x optional USB 2.0 Type-C (supports DisplayPort 1.4), 1x optional Type-A USB 2.0
VGA	optional
DisplayPort	2
Serial (RS-232)	optional: serial port (9pin, 16 byte FIFO, 16550 compatible)
Ethernet (RJ-45)	1
Interface Module notes	Anytime USB charge functionality
Kensington Lock support	1
Input device / components	
Input devices (optional)	Keyboard Mouse
Drive bays	
Drive bays total	2
2.5-inch internal bays	1
5.25-inch external bays	1

Drive bays	
Drive bay notes	5.25" bay: for slim optical disc drive only
M.2-2280	1 x on mainboard for SSD NVMe (PCle 3.0 x4; up to 32Gbit/s)
	i λ on mambuaid iui ככם invinie (rcie σ.υ λ4, up to σεαυίνδ)
Mini PCI slots	
M.2-2230	on mainboard for WLAN module
Graphics on board	
Graphics brand name	Intel® HD Graphics 610, Intel® HD Graphics 630
Shared video memory	Up to half size of total system memory
TFT resolution (VGA)	Up to 1,920 x 1,080 pixel
TFT resolution (DVI)	up to 1,920 x 1,200 pixel
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel
TFT resolution (HDMI)	Up to 4,096 x 2,160 pixel (30 Hz)
Graphics features	Support for up to three independent displays DirectX® 12 HDCP support OpenCL™ 2.1 OpenGL® 4.5 DisplayPort interface supports Ver. 1.4 incl. Multi-Stream Digital audio formats are supported, including Dolby Digital Plus (7.1 channels) DVI-D interface supports audio output if connected to the HDMI interface of a display via suitable adapter cables (not included) Additional I/O connectors configurable, choice of DVI-D HDMI™ VGA USB Type-C™ (supports DisplayPort™ 1.4 and power delivery (PD) up to 15W)
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz
Electrical values	
Power efficiency note	power supply efficiency (at 230V; 2 Watt/ 10% / 20% / 50% / 100% load) : > 85%/ 90% / 90% / 92% / 92%
Rated voltage range	100 V - 240 V
Rated frequency range	50 Hz - 60 Hz
Operating voltage range	90 V - 264 V
Operating line frequency range	47 Hz - 63 Hz
Max. output of single power supply	65 W (integrated in system)
Power factor correction/active power	No (meets input harmonic current according EN61000-3-2)
Power consumption	
Power consumption note	See white paper Energy Consumption
Heat dissipation	1 1 2/ 1
Heat dissipation notes	See white paper Energy Consumption
<u> </u>	see white paper Energy consumption
Noise emission Related Processors for noise	Intol® Coro™ i5, 10600T processor
Standard noise emission	Intel® Core™ i5-10600T processor 8GB, no ODD, Windows 10
אניםוומקות ווהואה הוווואאוהוו	According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	3.0 B / 17 dB(A) Bystander; 17 dB(A) Operator position (SSD M.2)
Standard noise operation mode: HDD load	3.0 B / 17 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)
Standard noise operation mode: Idle mode	2.9 B / 16 dB(A) Bystander; 16 dB(A) Operator position (SSD M.2)

Naisa amissian	
Noise emission Shandard paics appraise modes ODD	4.6 B / 32 dB(A) Bystander; 36 dB(A) Operator position (SSD M.2)
Standard noise operation mode: ODD load	4.0 b / 32 db(A) bystalider, 30 db(A) Operator position (330 M.2)
Standard noise operation mode: Office applications 2.0	3.0 B / 16 dB(A) Bystander; 16 dB(A) Operator position (SSD M.2)
Dimensions / Weight / Environmental	
Dimensions (W x D x H)	185 x 190 x 54 mm; with VESA cover: 185 x 190 x 56.2 mm
	7.29 x 7.49 x 2.13 inch
Operating position	Vertical / horizontal (no feet needed)
/ESA mount	optional VESA cover (100 mm & 75 mm) e.g. to mount the system at the rear side of a display
Weight	1.6 kg
Weight (lbs)	3.53 lbs
Weight notes	Actual weight may vary depending on configuration
Operating ambient temperature	10 - 35 °C (50 - 95 °F)
Operating relative humidity	5 - 85 % (relative humidity)
Compliance	
Product	ESPRIMO Q7010
Model	MPC4
Germany	CS
Еигоре	CE
JSA/Canada	FCC Class B cTUVus
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® in progress EPEAT® in progress (dedicated regions) TCO Certified 8.0 in progress
Compliance notes	This product is free of polyvinyl chloride (PVC) when ordered with the optional PVC free power cord
Compliance link	https://sp.ts.fujitsu.com/sites/certificates
Additional Software	
Additional software (preinstalled)	Adobe® Reader® (pdf reader) McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial preinstalled) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2019 Microsoft® Office Home and Business 2019 (A Microsoft Account is required to activate each copy of these products. For purchase and activation only in the region in which it was acquired.)
Manageability	
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)
Manageability software	DeskView Client DeskView Instant BIOS Management
DeskView components	BIOS Management incl. Security Inventory Management Driver Management Alarm Management

nore system RAM and SSD
ex.html
.pdf
90mm / (19.69 x
let = 56; printed user

Warranty	
Warranty period	1 year
Warranty type	Bring-In / Onsite Service (depending on country)
Warranty Terms & Conditions Product Support Services - the performance	http://www.fujitsu.com/warranty ect extension
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

Recommended Accessories

Blue LED Mouse M960



The Blue LED Mouse M960 comes in a slim design with proven Fujitsu engineering quality. The track on glass Blue LED sensor enables ultra precise switchable resolution at 1,000, 1,600 and 2,000 dpi. Blue LED Mouse M960 makes your life easier because it's tailor-made for right handed users. It just feels great in your hand.

Order Code: S26381-K470-L100

Keyboard KB955



The KB955 is a very flat keyboard with extra low keys and spill-resistant protection. The elegant design and top-quality construction makes the KB955 the ideal input device for any PC or Notebook user. If you accidently spill some water or coffee onto the keyboard, this special construction helps the liquid to flow away.

S26381-K955-L4** (**: Country specific variation)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO Q7010, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO Q7010, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html

Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2020-09-02 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2020 Fujitsu Technology Solutions GmbH