# HP Color LaserJet Enterprise M856dn

٠

# Maintain maximum productivity while printing exceptional colour.

Print phenomenal colour while maximising uptime – now with original HP JetIntelligence toner technology. Expect consistently fast output, brilliant prints, and the world's strongest security.<sup>1</sup>





This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block • Get professional quality and performance with Original HP Toner cartridges with JetIntelligence and drums. cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused,

remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

# Highlights

- World's most secure printing
- JetIntelligence technology
- Exceptional colour performance
- Minimal interruptions, maximum productivity



## Work stands out with exceptional colour performance

- Special print mode for a wider colour range and extra vividness for documents and marketing materials.
- Look professional with vibrant, high-guality colour prints that can stand the test of time.
- Produce full-bleed A3 marketing materials by printing on SRA 3 paper and trimming down to size.

## The world's most secure printing<sup>1</sup>

- Each printer in your fleet checks its operating code and repairs itself from attacks.
  - Your printer's outgoing network connections are inspected to stop suspicious requests and thwart malware. Memory activity is monitored to continually detect and stop attacks
- Firmware is automatically checked during startup to determine if it's authentic code digitally signed by HP.

## Minimal interruptions, maximum productivity

- Change the toner and drum in seconds. Both are easily accessible and come already installed out of the box.
- . Avoid interruptions with an HP LaserJet printer designed for maximum productivity.
- Tailor this printer to help you meet the needs of your business with a wide range of paper-handling accessories.
- Grab pages and go. This HP Laser Jet wakes up quickly and prints fast up to 56 ppm(A4).<sup>2</sup>

## Built with the environment in mind

- Benefit from reduced energy consumption and increased sustainability, up to 78% over predecessors.<sup>3</sup>
- Help save paper right out of the box. The duplex print setting is set at default paper savings mode.<sup>4</sup>

## Product walkaround

#### HP Color LaserJet Enterprise M856dn shown

- 1. 10.9 cm (4.3 inch) colour graphics display with touchscreen
- 2.500 sheet output bin
- 3. Front door (access to JetIntelligence toner cartridges and imaging drums)
- 4. Automatic two-sided printing
- 5. 550 sheet tray 2 supports media sizes up to 297 x 432 mm (11.7 x 17 inches)
- 6. Hardware Integration Pocket
- 7. Easy-access USB port
- 8. Upper-right door (access to print path)
- 9. Right door (access to the fuser and print path)
- 10. 100 sheet multipurpose tray 1 supports media sizes up to 305 x 457 mm (12 x 18  $\,$
- inches) and SRA3
- 11. 2 Hi-Speed USB 2.0 Host ports
- 12. Gigabit/Fast Ethernet 10/100/1000Base-TX network port
- 13. Hi-Speed USB 2.0 device port



# Accessories, Supplies and Support

Supplies	W2004A HP 660A Original Laser Jet Imaging Drum (65,000 standard pages in accordance with ISO/IEC 19752)
	W2010A HP 659A Black Original Laser Jet Toner Cartridge (~16,000 pages)
	W2010X HP 659X High Yield Black Original LaserJet Toner Cartridge (~34,000 pages)
	W2011A HP 659A Cyan Original LaserJet Toner Cartridge (13,000 pages)
	W2011X HP 659X High Yield Cyan Original Laser Jet Toner Cartridge (29,000 pages)
	W2012A HP 659A Yellow Original Laser Jet Toner Cartridge (13,000 pages)
	W2012X HP 659X High Yield Yellow Original Laser Jet Toner Cartridge (29,000 pages)
	W2013A HP 659A Magenta Original LaserJet Toner Cartridge (13,000 pages)
	W2013X HP 659X High Yield Magenta Original LaserJet Toner Cartridge (29,000 pages)
Accessories	2MU47A HP Accessibility Assistant
	2NR09A HP 2GB 144-Pin DDR3 TAA Version DIMM
	3JN69A HP Jetdirect 3100w BLE/NFC/Wireless Accessory
	4QL32A HP Legic Secure USB Reader
	5EL03A HP Secure Hard Disk Drive with FIPS Validation (TAA Compliant)
	B5L28A HP Internal USB Ports
	B5L29A HP High-Performance Secure Hard Disk
	B5L31A HP Foreign Interface Harness
	E5K48A HP 1 GB x32 144-pin (800 MHz)DDR3 SODIMM
	E5K49A HP 2 GB x32 144-pin (800 MHz) DDR3 SODIMM
	J8031A HP Jetdirect 2900nw Print Server
	T3V27A HP LaserJet 550-sheet Paper Tray
	T3V28A HP LaserJet Printer Stand
	T3V29A HP Color Laser Jet 2x550-sheet Feeder and Stand
	T3V30A HP LaserJet 2700-sheet High Capacity Paper Tray and Stand
	X3D03A HP USB Universal Card Reader
	Y7C05A HP HIP2 Keystroke Reader
Service and Support	UC2U9E HP 3 year Next Business Day with Defective Media Retention for Color LaserJet Enterprise M856 service UC2V0E HP 4 year Next Business Day with Defective Media Retention for Color LaserJet Enterprise M856 service UC2V1E HP 5 year Next Business Day with Defective Media Retention for Color LaserJet Enterprise M856 service UC2W1PE HP 1 year Post Warranty Next Business Day with Defective Media Retention for Color LaserJet M856 service UC2W2PE HP 2 year Post Warranty Next Business Day with Defective Media Retention for Color LaserJet M856 service US2W2PE HP 2 year Post Warranty Next Business Day with Defective Media Retention for Color LaserJet M856 service US2W3PE HP Instant service with Department Printer

# Technical specifications

Model	HP Color Laser Jet Enterprise M856dn
Product number	T3USTA
Functions	Print
Control panel	10.92 cm (4.3 in) Infrared touch panel with home button
Print	
Print technology	Laser
Print speed <sup>1</sup>	Black (A4, normal): Up to 56 ppm Colour (A4, normal): Up to 56 ppm : Black (A4, duplex): Up to 56 ipm Colour (A4, duplex): Up to 56 ipm Colour (A4, normal): Up to 56 ppm Colour (A4, normal): Up to 56 ipm Colour (A4, normal): Up to 56 ppm Colour
First page out <sup>2</sup>	Black (A4, ready): As fast as 5.9 sec Colour (A4, ready): As fast as 6.3 sec; Black (A4, sleep): As fast as 11.6 sec Colour (A4, sleep): As fast as 11.8 sec
Print resolution	Black (best): Up to 1200 x 1200 dpi Colour (best): Up to 1200 x 1200 dpi ; Technology: HP ImageREI 4800, Enhanced (600 × 600 dpi), Fine Lines (1200 x 1200 dpi), Quickview (300 x 300 dpi), Pantone Calibrated
Monthly duty cycle <sup>3</sup>	Up to 250,000 pages A4, Recommended monthly page volume <sup>6</sup> . Up to 50,000
Printer smart software features	Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB, HP EasyColor
Standard print languages	HP PCL 5, HP PCL 5 driver available from the Web only), HP postscript level 3 emulation, native PDF printing (v 1.7), Apple AirPrint®, Google Cloud Print
Fonts and typefaces	105 internal TrueType fonts scalable in HP PCL; Barcode font variants (Code 39, I2 of 5, UPC/ENA, Code 128, OCR-A/OCR-B); 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 internal Windows Vista 8 Fonts (Calbri, Cambria); Additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPOS Emulation available at http://www.hp.com/go/laserJetfonts
Print area	Print margins Top: 5 mm, Bottom: 5 mm, Left: 5 mm, Right: 5 mm, Maximum print area : 316 x 453 mm
Duplex printing	Automatic (standard)
Processor speed	1.2 GHz
Connectivity	•
Standard	1 Hi-Speed Device USB 2.0, 2 Hi-Speed USB 2.0, rear-host ports; 1 walkup USB 2.0 host port; 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network port; 1 Hardware Integration Pocket 2nd generation (HIP2)
Optional	HP Jetdirect 2900nw Print Server JB031A, HP Jetdirect 3100w BLE/NFC/Wireless Accessory 3JN69A
Mobile printing capability <sup>5</sup>	HP ePrint; Apple AirPint <sup>tes</sup> ; Google Cloud Print <sup>tes</sup> ; Mopris <sup>194</sup> Certified
Supported network protocols	Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, IPP 2:0, Apple Air/Print/M, HP ePrint, FTP Print, Google Cloud Print; Discovery; SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutolP, Manual, TFTP Config, ARP-Ang), IPv6 (Stateless Link-Local and via Router; Stateful via DHCPv6); Management: SNMPv2/v3, HTTP/HTTPs, Tener, TFTP Config, Syslog; Security: SNMPv3, SSL Cert Management, IPSec/Firevall, ACL, 802.1x
Network capabilities	Yes, via HP Jetdirect Ethernet embedded print server (standard) which supports: 108ase-Ti, 1008ase-Ti, 8002.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard), 802.11a/b(g/n wireless networking (optional), second Ethernet port (optional)
Hard disk	Optional 500 GB available hard disk space: HP Secure High Performance Hard Disk drive 500 GB BSL29A; HP TAA Version Secure Hard Disk Drive SEL03A
Memory	Standard 1.5.68;Maximum: <sup>6</sup> 3.5.68
Media handling	•
Number of paper trays	Standard 2 Maximum: 6
Media types	Paper (plain, heavy, extra heavy, glossy, light, recycle, tough), envelopes, labels, glossy film, cardstock, transparencies
Media size	Custom (metric): 100 sheet multipurpose Tray 1: 64 x 127 to 320 x 457.2 mm; 550 sheet input Tray 2: 148 x 148 to 297 x 431.8 mm; Optional 1 x 550 and 2 x 550 tray and stand: 148 x 148 to 320 x 457.2 mm; Optional 2.700 sheet HCI paper tray and stand: 279.4 x 210 mm to 297 x 215.9 Supported (metric): 100 sheet multipurpose Tray 1: 64 x 4, A4.e, A5, A6, A3, SRA3, RA4, SRA4, A64 U(S), B5 (U(S), Obtio 21 5 x 340, BK (270 x 390), BK (260 x 360), BK (270 x 390), BK (195 x 270), 16K (197 x 273), Postcard U(S), Envelopes: B5, C5, C6, DL; 550 sheet input Tray 2: A3, A4, A4-R, A5, RA4, SRA4, B4 (U(S), B5 (U(S), Obtio 21 5 x 340, BK (270 x 390), BK (270 x 39
Media handling	Standard input: 100 sheet multipurpose tray, 550 sheet input tray Standard output: 500 sheet output: bin Optional input: Add up to two: 1 x 550 sheet paper tray, Add up to one: 2 x 550 sheet paper tray and stand; 2,700 (1,600 + 1,100) sheet HQ paper tray and stand
Media weight	100 sheet multipurpose Tray 1:60 to 300 g/m <sup>2</sup> ; 550 sheet input Tray 2:60 to 256 g/m <sup>2</sup> ; Optional 1 x 550 and 2 x 550 tray and stand: 60 to 256 g/m <sup>2</sup> ; Optional 2,700 sheet HQ paper tray and stand: 60 to 256 g/m <sup>2</sup>
Input capacity	Tray 1: Sheets: 100 sheet multi-purpose tray 1 (80 g/m²); Transparencies: 50: Envelopes: 10: Labels: 50 Tray 2: Sheets: 550 (80 g/m²); Transparencies: 200; Labels: 200 Tray 3: Optional 1 x 550 and 2 x 550 tray and stand - Sheets: 550 (80 g/m²); Transparencies: 200; Labels: 200; Diptional 2,700 sheet HCI paper tray and stand - Sheets: 1.100 + 1,600 (80 g/m²); Maximum: Up to 4,450 sheets (80 g/m² paper)
Output capacity	Standard: Up to 500 sheets Envelopes: Up to 50 envelopes Transparencies: Up to 50 sheets Maximum: Up to 500 sheets
Compatible operating systems	Windows Client OS (32/64-bit): Win10, Win8.1, Win7 Starter Edition SP1, UPD Win7 Ultimate; Mobile OS: IOS, Android; Apple <sup>®</sup> macOS High Sierra v10.13, Apple <sup>®</sup> macOS Mojave v10.14, Mac: Apple <sup>®</sup> macOS Latalina v10.15; Discrete PCL6 Printer Driver: For more information on the supported operating systems go to http://www.support.hp.com, Enter your product name and search (Lick on User Guides and enter your product Name) User Guide, Search for ryour (Product Name) User Guide, Search for the Supported operating systems section; UPD PCL6 / PS inter Driver: For more information on the supported operating systems and enter your product name and search. (Lick on User Guides and enter your product name and search for User Guide, Search for your (Product Name) User Guide, Search for your (Product Name) User Guide, Search for User Guide, Search for User Guide, Search for User Guide, Search for your (Product Name) User Guide, Search for your (Product Name) User Guide, Search for your Product Name) User Guide, Search for User Guide, Search for User Guide, Search for User Guide, Search for your (Product Name) User Guide, Search for your
Compatible network operating systems	Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 64-bit, Windows Server 2016 64-bit, Windows Server 2019 64-bit, Fallover Cluster 2008 R2; Fallover Cluster 2012 R2; Terminal server 2008 R2; Renote Desktop Date (SP1), Windows Server 2012 R2; Cltrix Server 2016 R2; Fallover Cluster 2008 R2; Fallover Cluster 2012 R2; Terminal server 2008 R2; Renote Desktop Date (SP1), Windows Server 2012 R2; Cltrix Server 7.11 for more information see http://www.thready.cltrix.com; Linux-For more information thready.cltrix.com; Linux-For more information see http://www.thready.cltrix.com; Linux-Fo
Minimum system requirements	Windows: 2 GB available hard disk space, Internet connection, USB port, Internet browser. For additional OS hardware requirements see http://www.microsoft.com Mac 2 GB available hard drive space, Internet connection or USB port. For OS hardware requirements see http://www.apple.com
Software included	No wife was not allowed with the Proceedings between the sector was a sector of the sector was
	No software solutions are included in the Box only on http://www.hp.com, http://www.123.hp.com
Security management	No software solutions are included in the six only of inttp://www.lg.um, ntup://www.lg.um, ntup://ww Retworks.www.lg.um, ntup://www.lg.um, ntup://wwww.lg.um
Security management Printer management	Management security: SNMPv3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAP, EAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, and
	Management security: SNMPv3, Web Services over port 7627, SSL/TLS 11.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAP, EAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, Support Tor VWA-10 Psec Configuration using Psec Rug-in Retheros Authentication; Support Tor VWA-10 Psec Configuration using Psec Rug-in HP Printer Advantant; HD Pevic Configuration Utility; Driver Deployment Utility; Manager, HP SNP Proxy Agent; PM SP Pro Proxy Agent; Printer Administrator Resource KI for HP Universal Print Driver Configuration Utility; Driver Deployment Utility; Managed
Printer management	Management security: SNMPv3, Web Services over port 7627, SSL/TLS 11.0 1:1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, B02.1X authentication (EAP-PEAP, EAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, Support To VWA-10 Psec, Configuration using Psec Rug-in Retheros Authentication; Support To VWA-10 Psec, Configuration using Psec Rug-in HP Printer Asstant; HP Device Configuration Utility, Driver Deployment Utility; Manager, HP SNP Proxy Agent; Pmter Administrator Resource Kt for HP Universal Print Driver Configuration Utility; Driver Deployment Utility; Managed
Printer management Dimensions and weight	Management security: SNMPv3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAP, EAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, Support for VIA-10 Psec Configuration using Psec Pug-in HP Printer Assistant; HP Device Toolbox; HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SIMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility; Driver Deployment Utility; Managed Printing Administrator)
Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>7</sup>	Management security: SNMPv3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAP, EAP-TLS), IPsec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for WIA-10 IPsec Configuration using IPsec Plug-in HP Printer Assistant; HP Device Toolbox HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SIMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility; Driver Deployment Utility; Managed Printing Administrator MInimum S56 x 610 x 520 mm; Maximum: 921 x 610 x 598 mm
Printer management Dimensions and weight Printer dimensions (W × D × H) <sup>7</sup> Printer weight <sup>®</sup>	Management security: SNMPv3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAP, EAP-TLS), IPsec/Frewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for VIA-10 Psec Configuration using IPsec Plug-in HP Printer Assistant; HP Device Toolbox HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility; Driver Deployment Utility; Managed Printing Administrator)  Minimum 556 x 610 x 520 mm; Maximum: 921 x 610 x 598 mm 52.3 kg
Printer management Dimensions and weight Printer dimensions (W × D × H0 <sup>7</sup> Printer weight <sup>®</sup> Operating environment	Management security: SNMPv3, Web Services over port 7627, SSL/TLS 11.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAP, EAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication; Support for VIIA-10 Psec Configuration using Psec Plug-in HP Printer Assistant; HP Device Toolbox HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility; Driver Deployment Utility; Managed Printing Administrator) HD Printing Assistant; HD Cevice Toolbox HP Web JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility; Driver Deployment Utility; Managed Printing Administrator) HD Printing Assistant; HD Cevice Toolbox HP Web JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility; Driver Deployment Utility; Managed Printing S6x 610 x 520 mm; Maximum; 921 x 610 x 598 mm Sca 31 ag Temperature: 10 to 32.5°C Humidity: 30 to 70% RH
Printer management Dimensions and weight Printer dimensions (W × D × H) <sup>2</sup> Printer weight <sup>8</sup> Operating environment Storage conditions	Management security: SNMIV3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAP EAP-TLS), Psec/Frewall with Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAP EAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, and Previous Authentication (Support for VIA)-10 Psec. Configuration using Psec Rug-in         HP Printer Advantages Security Device Toolbox HP Web JetAdmin Software, HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver Configuration Utility; Driver Deployment Utility; Managed         Wininum S56 x 610 x 520 mm; Maximum 921 x 610 x 598 mm         52.3 kg         Temperature: 10 to 32.5°C HumidBy. 30 to 70% RH         Temperature: 10 to 32.5°C HumidBy. 30 to 70% RH         Requirements 6.8 B(A) Acoustic pressure emissions: 53 dB(A)         Requirements for vision of 6.8 B(A) Acoustic pressure emissions: 53 dB(A)         Requirements (DP): Place Advantage Security Avaits (Auto-Off), 0.08 watts (Auto-Off), 0.08 watts (Off); Typical Electric(DP): Bus Anage 2.56 KMW/Week; for Star Auto-Off), 0.08 watts (Auto-Off), 0.08 watts (Off); Typical Electric(DP): Bus Anage 2.56 KMW/Week; for Star Auto-Off), 0.08 watts (Off); Typical Electric(DP): Bus Anage 2.56 KMW/Week; For Star Auto-Off), 0.08 watts (Auto-Off), 0.08 watts (Auto-Off)
Printer management Dimensions and weight Printer weights W K D x HV <sup>2</sup> Printer weight <sup>8</sup> Operating environment Storage conditions Acoustics <sup>9</sup> Power <sup>10</sup>	Management security:SNMV3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAP EAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication, Support for VIA-10 Psec Configuration using Psec Rug-in         HP Printer Asstant; HD Device Toobox HP Web JetAdmin Software, HP JetAdwantage Security Manager; HP SNNP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver Configuration Utility, Driver Deployment Utility, Managed         V       Minimum 556 x 610 x 520 mm; Maximum: 921 x 610 x 598 mm         52.3 kg       Temperature: 10 to 32.5°C Humidity: 30 to 70% RH         Temperature: -20 to 40°C       Acoustic power emissions: 53 dB(A)         Acoustic power emissions: 53 dB(A)       Commind (4/-10%), 50 - 60 Hz normal (4/-3 Hz), 6 A; Commind (4/-3 Hz), 6 A; Power Supply
Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>7</sup> Printer weight <sup>®</sup> Operating environment Storage conditions Acoustics <sup>9</sup>	Management security: SNMV3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP- PEAP EAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, Support for VWA-10 Psec. Configuration using Pisec Paug-in         HP Printer Asstant; HD Queice Tootbox; HP Web JetAdmin Software; HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver (Driver Configuration Utility, Driver Deployment Utility, Managed Printing Administrator)         Minimum 556 x 610 x 520 mm; Maximum: 921 x 610 x 598 mm         52.3 kg         Temperature: 10 to 32.5°C Humidity: 30 to 70% RH         Temperature: 20 to 40°C         Accusitic power emissions: 6.8 B(A) Acoustic pressure emissions: 53 dB(A)         Requirements: Input voltage: 220 to 240 to rominal (+/- 3Hz), 6.4; Consumption TRy voltas (240, 7) volts (540, 6), 0.00 watts (Auto-0ff), 0.08 watts (Auto-0ff), 0.08 watts (0ff); Typical Electricity Consumption TEC1 <sup>(1)</sup> : Bitus Angel: 2.665 KM/Week; Energy Star 3.0: 0.725 KM/Week; Prevy Star 3.0:
Printer management Dimensions and weight Printer dimensions (W × D × H0 <sup>7</sup> Printer weight <sup>®</sup> Operating environment Storage conditions Acoustics <sup>9</sup> Power <sup>10</sup>	Management security:SNMV3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAP, EAP-TLS), Psec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication, Support for VIA-10 Psec Configuration using Psec Rug-in         HP Printer Asstant; HD Device Toobox; HP Web JetAdmin Software, HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver Configuration Utility, Driver Deployment Utility, Manager         V       Minimum 556 x 610 x 520 mm; Maximum: 921 x 610 x 598 mm       52.3 kg         Temperature: 10 to 32.5°C Humidity: 30 to 70% RH       Temperature: -20 to 40°C       Acoustic power emissions: 53 dB(A)         Acoustic power emissions: 53 dB(A)       Commindi (4/-10%), 50 - 60 Hz normal (4/-3 Hz), 6.4;       Commindi (4/-3 Hz), 6.0;         Origo Electricity Community Commindi (-1/-3) Hz), 6.4;       Commended (-1/-3) Hz), 6.0;       Coll (-1/-3), 0.0;         Printing Administrator       Statis (Diff);       Statis (Diff);       Statis (Diff);         Yub Device Tool (-2/-2/-2/-2/-2/-2/-2/-2/-2/-2/-2/-2/-2/-
Printer management Dimensions and weight Printer dimensions (W x D x H) <sup>7</sup> Printer weight <sup>8</sup> Operating anvironment Storage conditions Acoustics <sup>9</sup> Power <sup>10</sup> Energy savings feature technology	Management security:SNMV3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAPEAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, and Kentens Authentication (SAP-PEAPEAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, and Psec Toug-in         HP Printer Adaministrator       Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAPEAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, and Key Authentication (SAP-PEAPEAP).         HP Printer Adaministrator       Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAPEAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, and Key Authentication (SAP-PEAPEAP).         HP Printer Adaministrator       Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FPS 140-2, Certificate Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver Configuration Utility, Driver Deployment Utility, Managed         Horinum S56 x 610 x 520 mm; Maximum; 921 x 610 x 598 mm       S2.3 kg         Secure 10 to 32.5°C HumidBy: 30 to 70% RH       Temperature: 10 to 32.5°C HumidBy: 30 to 70% RH         Temperature: 10 to 32.5°C HumidBy: 30 to 70% RH       Regurements 6.8 R/A Aoustic preserve emissions: 53 dIA)         Regurements for board (printing) 77 watts (Februard Confi, Configuration On), O.08 watts (Auto-Off), O.08 watts (Off); Typical Electring(Sec SMM) Veek; Energy Star 3.0: 0.7 25 kM/N
Printer management Dimensions and weight Printer weight Operating environment Storage conditions Acoustics <sup>9</sup> Power <sup>10</sup> Energy savings feature technology Certifications <sup>12</sup>	Management security:SNMV3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAPEAP-TLS), Psec/Frewall with Certificate, Pre-Shared Key Authentication, Support for VWA-10 Deac Configuration using Pase Paug-in         He Printer Sature Status FIP Device Toobox FIP Web JetAdmin Software, HP JetAdvantage Security Manager, HP SNMP Proxy Agent, HP WS Pro Proxy Agent, Printer Administrator Resource Kit for HP Universal Print Driver Configuration Utility, Driver Deployment Utility, Managed         S2.3 kg       Temperature: 10 to 32.5°C Humidity: 30 to 70% RH         Temperature: 20 to 40°C       Acoustic power emissions: 53 dB(A)         Requirements Roy 10 to 32.5°C Humidity: 30 to 70% RH       Temperature: 20 to 40°C         Acoustic power emissions: 6.8 RA Acoustic pressure emissions: 53 dB(A)       Requirements: Imput voltage: 220 V Pauls: S1.0.0, Twaits (Beap), D.7 waits (Beap), D.7 wai
Printer management Dimensions and weight Printer dimensions (W × D × H) <sup>2</sup> Printer weight <sup>®</sup> Operating environment Storage conditions Acoustics <sup>®</sup> Power <sup>10</sup> Energy savings feature technology Certifications <sup>12</sup> Sustainable impact specifications	Management security: SNMV3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAP, EAP-TLS), Psec/Firewall with Certificate, Pre-Shared Key Authentication, and Kerberos Authentication, Support for VWA-10 Psec. Configuration using Psec Rug-in         HP Printer Asstant; HD Device Tootbox; HP Web JetAdmin Software, HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver Configuration Utility, Driver Deployment Utility, Managed         # Printer Asstant; HD Device Tootbox; HP Web JetAdmin Software, HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver Configuration Utility, Driver Deployment Utility, Managed         # Sta 3kg       Temperature: 10 to 32.5°C Humidity: 30 to 70% RH         Temperature: -20 to 40°C       Acoustic pressure emissions: 5.8 B(A)         Acoustic pressure emissions: 5.8 B(A)       Acoustic pressure emissions: 5.3 B(A)         Requirements: Input: voltage: 220 V to 240 V nominal (+/-194;); 6.4; Consumption TS, Vants Tieded), 0.7 vants HP Auto-OffAuto Onl, 0.08 watts (Auto-Off), 0.08 watts (Auto-Off), 0.08 watts (Off); Typical Electricity Consumption TECH Vises, Lengry Star 3.0: 0.725 kWh/ Veek; Energy Star 3.0: 0.725 kWh/ Veek; Energy Star 3.0: 0.725 kWh/ Veek; Pro-Wer Supply De Built-11 115 V. 2014; De Acto: 0.725 kWh Veek; Energy Star 3.0: 0.725 kWh Veek; Pro-Wer Supply De Built-11 15 V. 2014; Due Tothology.         Electrongenetic emission standard: CSPR 22:2008 (International) - Class A, EN 55032:2012 (EU) - Class A, EN 61000-3-3:2013, EN 55024:2010, EMC Directive 2014/30/E
Printer management Dimensions and weight Printer dimensions (W × D × H <sup>2</sup> Printer weight <sup>®</sup> Operating environment Storage conditions Acoustics <sup>9</sup> Power <sup>10</sup> Energy savings feature technology Certifications <sup>12</sup> Sustainable impact specifications Country of origin	Management security:SNMV3, Web Services over port 7627, SSL/TLS TLS 1.0/1.1/1.2, FIPS 140-2, Certificate Management, Embedded Web Server, WPA2-Enterprise, 802.1X authentication (EAP-PEAR, EAP-TLS), Pace/Firewall with Certificate, Pre-Shared Key Authentication, and Kerbens Authentication, Support for VIA-10 Pace Configuration using Pace Rug-in         HP Printer Sacation, FIP Device Toobox, HP Web JetAdmin Software, HP JetAdvantage Security Manager, HP SNMP Proxy Agent; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver Configuration Utility, Driver Deployment Utility, Manager         Minimum S56 x 610 x 520 mm; Maximum; 921 x 610 x 598 mm         52.3 3g         Temperature: 10 to 32.5°C Humidity: 30 to 70% RH         Temperature: 20 to 40°C         Accountic power emissions: 6.8 RIA Acoustic pressure emissions: 5.3 RIA)         Requirements (service): 10 valids (service), 0.7 valids (service), 0.7 valids (service), 0.0 valids (service), 0.0 valids (service), 0.1 valids (service), 0.2 valids (service), 0.1 vali

#### Footnotes

<sup>1</sup> Based on HP review of 2019 published security features of competitive in-class printers. Only HP offers a combination of security features that can monitor to detect and automatically stop an attack then self-validate software integrity in a rebot. For a list of printers, visit http://www.hp.com/go/PrintersThatProtect. For more information: http://www.hp.com/go/printerscurityclaims.
<sup>2</sup> Measured using ISO/IEC 24734, excludes first set of test documents. For more information, see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and

document complexity.

<sup>3</sup> Based on HP Internal testing using normalised TEC Value, 2019.

<sup>4</sup> Dependent upon country setup specifications.

<sup>5</sup> An FCC Class A emissions compliant device meets the less stringent (higher) levels of emissions allowed by the FCC for a product operation in a commercial environment. An FCC class A device cannot be marketed for use in a residential environment and an FCC class A device should not be purchased for use in a residential environment due to the increased risk of interference to radio communications.

#### Technical specifications disclaimers

<sup>1</sup> Measured using ISO/IEC 24734 excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims, Exact speed varies depending on the system configuration software application driver and document complexity

<sup>2</sup> Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration software application driver and document complexity. <sup>3</sup> Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP Laser Jet or HP Color Laser Jet devices, and enables appropriate

deployment of printers and MFPs to satisfy the demands of connected individuals or groups.

<sup>4</sup> HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.

<sup>5</sup> To enable HP Roam, some devices may require firmware to be upgraded and an optional accessory to add Bluetooth® Low Energy (BLE) beaconing capabilities. Subscription may be required. For more information, visit

http://www.hp.com/go/roam.  $^6$  The Configuration Pages will report maximum memory at 2 GB after 1 GB DIMM installed. This is an expected behavior of this product.

<sup>7</sup> With no accessories and multi-purpose tray closed.

<sup>8</sup> With print cartridges.

<sup>9</sup> Acoustic values are subject to change. For current information see http://www.hp.com/support, Configuration tested: base model, simplex printing. A4 paper at an average of 56 ppm. <sup>10</sup> Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Power consumption values typically based on

measurement of 115V device. <sup>11</sup> BA TEC is equal to Best TEC. Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star Version 3.0 TEC is not comparable to Energy Star Version 2.0 TEC values or BA TEC values. BA uses Energy Star Version 2.0 TEC. Energy Star value typically based on measurement of 115V device.

<sup>12</sup> EPEAT® registered where applicable. EPEAT registration varies by country. See http://www.epeat.net for registration status by country.

<sup>13</sup> Standard cartridges included; yields 16,000 black and 13,000 colour composite (C/M/Y) pages. Average black and colour composite (C/M/Y) declared toner yields based on ISO/IEC 19798 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/qo/learnaboutsupplies.



#### http://www.hp.com/uk

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ie-en October 2023

