

Immersive all play, every play.

Play longer, comfier, and with amazing accuracy on our suite of sweet curved gaming monitors. We've redefined high definition gaming with VA Panel Technology, 165Hz refresh rate, 1ms response time¹, and AMD² FreeSync[™] Premium³.



*Product image may differ from actual product



Believing is Seeing

Find more room to play on these VA 1500R curved monitors in Full HD (1920x1080)⁴. Immerse yourself in even more colors and catch all the action with ultra-wide viewing angles.



Game in comfort

A curved panel that reduces eye strain and has HP Eye Ease with Eyesafe[®] certification that keeps high-energy bad blue light out and the color accuracy in. Customize your comfort with the adjustable base.



Smooth Moves

Live in the flow of 165Hz with a super fast 1ms response time¹ with MPRT and keep your gameplay smooth-as-silk with AMD² FreeSync[™] Premium³.



A Display of Responsibility

Packaging is sustainably sourced and recyclable⁵. Doing good never looked so good.

Featuring

Eyesafe[®] Certified Display

Eyesafe® certified displays meet TÜV low blue light requirements and Eyesafe® standards for protecting your eyes from harmful blue light without distorting colors to reduce eyestrain when working for long periods of time.

Adjust your view

Adjust your screen for comfortable viewing with tilt capability.

Sustainably Sourced Packaging

HP is innovating new ways to reduce the amount of materials in our packaging and to use more recycled materials in the design.^{5,7}

VA panel

Get wide, 178-degree viewing angles and better black levels for deep, rich contrast.

1,500R curved display

A dramatic curve delivers an incredibly realistic and immersive gaming experience.

165Hz refresh rate

Crisp action and incredibly responsive gameplay with virtually no artifacting or screen tearing.¹

AMD FreeSync[™] Premium Technology

Game confidently with a high refresh rate, low framerate compensation, and low latency with AMD FreeSync™ Premium Technology.⁷

Console compatibility

Easily connects with your favorite current and next gen gaming consoles - just plug and play.

1-millisecond response time with Overdrive

Eliminates motion blur for crisp, fluid gameplay no matter what's happening on-screen.¹

Moving Picture Response Time

Greatly reduces motion blur for a more fluid visual experience.

OMEN Gaming Hub

OMEN Gaming Hub is your one place for everything to make your gaming experience better. From software enhancements to hardware control, and live services, OGH elevates play in easy and simple way.

FHD display / 1080p display

Brilliant visuals and unforgettable quality from a stunning FHD display.⁴

Highly accurate color

97% sRGB color space for ideal color reproduction.¹

Off the desk and on the wall

VESA mounts for easy mounting on a wall or arm.⁸

Three-sided micro-edge display

See more of your screen with a three-sided micro-edge display that maximizes your viewing area.







Bit waseModel Statistication (Unit Statistication and Statistication		
Bayes44-0000Bayes45-0000Bayes30-11-00000Bayes30-11-00000Bayes30-11-00000Bayes30-11-00000Bayes30-11-00000Bayes30-11-000000Bayes30-11-000000Bayes30-11-000000Bayes30-11-0000000Bayes30-10-000000000000000000000000000000000	Product number	32G13AA#ABB;; #A2N; #ABT; #ABU; #ABU; #ABU; #ACQ; #UUG; #UUZ
Section Isia Term provide Isia Hadden Isia Hadden Isia Hadden Isia Hadden Isia Marcen file	UPC number	(A2N) 195697574443; (A8B) 195697574450; (ABT) 195697574467; (ABU) 195697574474; (ABV) 195697574481; (ABV) 195697574488; (ACQ) 195697574504; (UUG) 195697574528; (UUZ) 195697574535
Behysical814Behysical1000Store2000Behysical2000Store2000S	Display size	68.6 cm (27')
Page fam3114 mm. 3114 mm. 3144	Aspect ratio	169
Important Important Status 2000.1 Endpance 2000.0 Endpance 1000.00 Endpance 1000.00 Endpance 1000.00 Endpance 978.40 Endpance 979.40 Endpance	Display type	VA1
BedresBooksBedresBooksConstantionBooksBedres	Pixel pitch	0.3114 mm x 0.3114 mm
Generation1000000000000000000000000000000000000	Response time	1ms MPRT (with overdrive) ¹
Design constrained legand1000000000000000000000000000000000000	Brightness	350 nits ¹
Partner in #isi Diagly Odd Form System System Bankbarn instanting Profit/NV-11880-015.150 Bankbarn instanting Gott State 7.124 and 2001 (DC, 124 and 128 and 2001 (DC,	Contrast ratio	3000:1
Depletion Projection Read. Kork May Control Projection Projection Read. Kork May Control Projection Projection Read. Kork May Control Projection Projection Depletion Projection Projection Projection Depletion Projection	Display contrast ratio (dynamic)	1000000:1
Beckborinstrum Not10829 (1000 (0168 Hg) Beckborinstrum OH (1082) (1000 (0168 + 706 (128) + 706 (128) + 100 (100) + 10	Product color	Black
Resultans segmend 648 x 400 720 x 400 000 x 000 x 700 x 720 x 200 x 200 x 1000 x 1000 x 1000 x 1000 x 1000 x 1000 Dickly scan freesend by octamal 3x 2 10 6 L Dickly scan freesend by octamal 3x 2 10 6 L Dickly scan freesend by octamal 10 16 18 2 Dickly scan freesend by octamal 10 16 18 2 Dickly scan freesend by octamal 2x 30 10 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Display Color Gamut	97% sRGB
Decky scan frequency Deckad 45:200.502 Dicky scan frequency Deckad 55:505 Dicky scan frequency Deckad 55:505 Dicky scan frequency Deckad 10:001 20	Resolution (maximum)	FHD (1920 x 1080 @ 165 Hz)
Disply scan frequenty bertial 60: 10312 Disply scan frequenty bertial Low Statu light methy their given to Statu light methy film statuter, Weight algutabler, MO Frequent ^{em} Permiture, Garring Grande Carrena Mate Disply Scan frequenty Enviro Scan Scan Scan Scan Scan Scan Scan Scan	Resolutions supported	640 × 480; 720 × 400; 800 × 600; 1024 × 768; 1280 × 720; 1280 × 800; 1280 × 1024; 1440 × 900; 1600 × 900; 1680 × 1050; 1920 × 1080
Dipply features Low blue light node, Arti-glave, 15000 concursure, ling to adjustable, MRD Freeyner," Permane, Gamed, Campabbe Dipply features 16000 2 concil, the glave plane," 14.6 km/h the file adjustable, MRD Freeyner, "Permane, Gamed, Campabbe Dipply features Beney efficiency class, Con-mode power consumption, SD W finanianus, Menual energ, campane, CD IV Standay, SD W Barabab, Power consumption, SD W finanianus, Menual energ, campane, CD IV Dipply features Ext. Hommator, Hanagement, Power consumption, SD W finanianus, Menual energ, campane, CD IV Dipply features Ext. Hommator, Hanagement, Power consumption, SD W finanianus, Menual energ, campane, CD IV Dipply features Ext. Hommator, Hanagement, Power consumption, SD W finanianus, Menual energ, campane, CD IV Dipply features Ext. Hommator, Hanagement, Power consumption, SD W finanianus, Menual energ, campane, CD IV Dipply features Ext. Hommator, Hanagement, Power consumption, SD W finanianus, Menual energ, campane, CD IV Dipply features Ext. Hommator, Hanagement, Power consumption, SD W finanianus, Menual energ, campane, CD IV Dipply features Ext. Hommator, Hanagement, Power consumption, SD W finanianus, Menual energ, campane, CD IV Dipply features Ext. Hommator, Hanagement, Power consumption, SD W finanianus, Menual energ, campane, CD IV Dipply features Ext. Hommator, Hanagement, Power consumpton, SD W finanianus, Menual energ, campane, CD IV <th>Display scan frequency (horizontal)</th> <th>30-210 KHz</th>	Display scan frequency (horizontal)	30-210 KHz
Decky rput Type 1160H22 drafth IECP suproft.1 Dispting/Part*1.4 He Intell IECP support] Phycical social functions Security User instal Bingry officery officery Security User instal Decky User Control Options SecUrity User instal Bingry officery officery SecUrity User instal Decky User Control Options SecUrity User instal Decky User Control Optinstal SecUrity User instal	Display scan frequency (vertical)	60-165 Hz
Physical security features Security leaves Barge Millongy Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leaves Ency Millongy Leaves Barge Millongy Leaves Ency Millongy Leave	Display features	Low blue light mode; Anti-glare; 1500R curvature; Height adjustable; AMD Freesync™ Premium; Garning Console Compatible
Physica scarbin basesSocial ScarbinghoutBrack starbinghoutSocial Scarbingh	Display Input Type	1 HDMI 2.0 (with HDCP support); 1 DisplayPort™ 1.4-in (with HDCP support)
Design efficiency Every efficiency data E. De-mode baser consumption: S10 W insummunit. Annual energy: consumption: S1 W Stradbyll, Power consumption Ed. W Beginder Diskly Micron Design Micro Basel Diskly Micron Bits Information: Nanagement, Power control, Uput control, Kenu control, Caming, Image, Cabir Diskly Micron Bits Information: Nanagement, Power control, Venu control, Caming, Image, Cabir Diskly Micron Bits Information: Nanagement, Power control, Venu control, Caming, Image, Cabir Diskly Micron Bits Information: Nanagement, Power control, Venu control, Caming, Image, Cabir Diskly Micron Bits Information: Nanagement, Power control, Venu control, Caming, Image, Cabir Diskly Micron Bits Information: Nanagement, Power control, Venu control, Caming, Image, Cabir Diskly Micron Bits Information: Nanagement, Power control, Venu control, Caming, Image, Cabir Diskly Micron Bits Information: Nanagement, Power control, Venu control, Caming, Image, Cabir Diskly Micron Diskly Micron Control Diskly Micron Diskly Micron Diskly Micron Diskly Micron Diskly Micron Diskly Micron Bits Micron Diskly Micron Diskly Micron Diskly Micron Bits Micron Diskly Micron		
Balay Loot and young the second is part control is part contro	Energy efficiency	Energy efficiency class: E; On-mode power consumption: 50 W (maximum); Annual energy consumption: 21 kWh; Standby: 0.5 W (standby); Power consumption (on-mode): 50 W (maximum); Power consumption (off
Webcan No integrated cancer Generating importantie range 518 S°C Operating importantie range 618 SS°C Operating importantie range 218 SDN non-condensing Operating importantie range 208 SDN non-condensing Operating importantie range 208 SDN non-condensing Standard 100 - 240 VK SDOND h VESA mort	Display User Control Options	
Operating temperature range 515 33C Operating temperature range 415 555 Operating temperature range 2015 030%-non-condensing Excluders CEL Gode 1: Power spaph 100 74000 KS0060 kz VESAmourt 100 mm broader not excluded Cond-wolded Not text-texted Power spaph 202 a VESAmourt 828 a Cond-wolded Not text-texted Power spaph 100 7400 KS0060 kz VESAmourt 828 a Power spaph 828 a VESAmourt 828 a Power spaph 100 mm broader not excluded VESAmourt 828 a VESAmourt 828 a VESAmourt 100 mm broader not excluded VESAmourt 105 VESAmourt 100 mm VESAmourt No work Read No work Read No work Read concetter No work Read concetter No work Read concetter No work Rea		
Operating temperature range41 to 95%Operating temperature range20 to 800 non-condensingOperating temperature range20 to 800 non-condensingOperating temperature20 to 800 non-condensingParet supply20 to 240 WK 50K50 HzParet supply100 non-todixet entircludedTodi-nonloidNot todi-nonloidParet supply82 pcplParet supply92 pcplParet supply92 pcpl <t< th=""><th></th><th></th></t<>		
Operating humidity range 20 to 80%, non-condensing Exclusions CEL Gade 1; Power suppy 100 - 240 VLC S0/60 FJz Exclusions 000 rm % 100 mm backet not included Exclusions 000 rm % 100 mm backet not included Exclusions 82 ps/ Exclusions 82 ps/ Exclusions 82 ps/ Exclusions 82 ps/ Exclusions 83 ps/ Exclusions 93 ps/ Exclusions 93 ps/ Exclusions 93 ps/ Exclusions 93 ps/ Exclusions 94 ps/		
Cotababs CLL Gade 1; Poorer supply 100 - 740 VMC 50160 Hz VESA mount 100 mm x 100 mm bracket not included Toch-enabled Nat toch-enabled Pooler supply 82 ppl Toch-enabled Nat toch-enabled Pooler supply 82 ppl Pooler supply 82 ppl Pooler supply 1797 Formetht depth 8 bit Pooler supply 1797 Formetht depth 9-sided micro-edge Pooler supply 9-sided micro-edge Tit -5 to -20° Sweld No sweld Pooler		
Power supply 100 - 240 WA S0160 Hz VESA mouth 100 mm krotewine included VESA mouth 100 mm krotewine included Power supply Not touch-wabled Not touch-wabled Power Supply Not touch-wabled Rest watch of pol Rest per included Power Supply Dist per included Rest per included Rest per included Rest per included Power Supply 178 * Rest per included Rest per included<	<u> </u>	
VEX.nout 100 mm kr 00 mm kr 00 mm kradet net includedi Toch-enabled Notoch-enabled Panels per incluppi 82 ppi Panels treget 81 mm Panels treget 81 mm Vertical viewing angle 178* Bezet 3-sided mino-odype Bezet 3-sided mino-odype Bezet 3-sided mino-odype Strike 3-sided mino-odype Bezet 3-sided mino-odype Strike 3-sided mino-odype Strike 3-sided mino-odype Strike No survet Poot No poot Hadget adjustment range 100 mm Nord 3-diad mino-odype Streem treatment And-gare Korker No Streem treatment No Nord No. Streem treatment No Notagement software No Notagement software Notageset (Contreatment) Notageset (Contreatment) Notageset (Contreatment) Notageset (Contreatment) Notageset (Co		
Touch-enabled Nat touch-enabled Parles per inch (pp) 82 ppi Parles tou (ppi) 82 ppi Parles tou (ppi) 178* Parles tou (ppi) 100 mm Parles tou (ppi) 100		
Pakes per inch (pp) 82 pi Panel bit depth 8bit Panel bit depth 8bit Vertical Weing angle 176° Vertical Weing angle 178° Bezel 3sided micro-edge Bezel 3sided micro-edge Tit -510 - 20° Sweid Nosweid Pool Nosweid Bejch adjustment ange 100 mm Heidh adjustment ange 100 mm Storeen treatment No-Bace Integrated phoce/filter No Storeen treatment No-Bace Integrated phoce/filter No Roberts Spesafe* Cettled Roberts Nospole************************************		
Panel bit depth 8 bit Vertical viewing angle 178* Horizont Livewing angle 178* Bezel 3-sided micro-edge Bezel 3-sided micro-edge Till -5 to -20* Swikel No swikel Proto No pivot Height adjustment range 100 mm DO mm -5 to -20* Swikel No pivot Height adjustment range 100 mm DO mm -5 to -20* Statistment range 00 mm Horizontal Arti-glare Integrated privacy filter No Ricker-free Ves Low blue light Ves_ Eyesafer® Certified Port and Connectors 1 Holl 2:0: 10 toglay@ort** 1:4:1:3.5 mm Audio Jack (Audio Out; Nr. No HDP Ves_ DisplayPort** and Holl Warranty 1 yee limited warranty. Certificatios and compliances Micro CCC ESC EXC, ESC Mark: Kin 9 241-307: KC/KCC; KOM, ESE, Velagenting EEG0950-1; VCQ, WEEE; California Energy Commission (ECC); Mexico Energy: Ww applicator; KE; Warts in the box Montor, DisplayPort** cable, Wouranty card; Product		
Vertical Verving angle 178* Horizontal viewing angle 178* Bezel 3-sided micro-edge Tit -5 to ~20* Swikel No swikel Poot No pikot Height adjustment range 100 mm Hordenses 3H Screen treatment Anti-glare Integrated privacy filter No No by Subject Ves Low bull light Ves. Spesafe® Certified Port and Cornectors 1HDML 20, 1 DisplayPort™ 14, 1 x 3.5 mm Audio Jack (Audio Dut); Nc; No HOCP Ves. DisplayPort™ 14, 1 x 3.5 mm Audio Jack (Audio Dut); Nc; No HOCP Ves. DisplayPort™ 14, 1 x 3.5 mm Audio Jack (Audio Dut); Nc; No HOCP Ves. DisplayPort™ 14, 1 x 3.5 mm Audio Jack (Audio Dut); Nc; No HOCP Ves. DisplayPort™ 14, 1 x 3.5 mm Audio Jack (Audio Dut); Nc; No Warranty Uest Initied warranty. Certifications and compliances Mice Certificates, NICS of South Africe, 9EEE, Belaus, Energy, Elyesafe® Certified Wats in the box Monitor: DisplayPort™ 20, FEE, Elee, Belaus, Energy, Elyesafe® Certified Wats in the box Monitor: DisplayPort™ 20, South Africe, 9		
Horizontal Wewing angle 178 ⁺ Bezel 3-sided micro-edge Titk -5 to -20 ⁺ Swikel No swikel Poot No swikel Poot No polo Height adjustment range 100 mm Hardness 3H Screen treatment Anti-glare Integrated privacy filter No No bub L Yes Low bub light Yes, Sussamment of the Su		
Bezel 3-sided micro-edge Tilt -5 to +20° Swikel No swikel Pixed No pixot Height adgustment range 100 mm Stream teatment Anti-gare Integrated prixosy filter No No No Ficker-free Ves Dot add Connectors 1HDM2.0; 1 DisplayPort**14;1 x 3.5 mm Audo Jack (Audo Out); No; No HOP Ves, DisplayPort**14;1 x 3.5 mm Audo Jack (Audo Out); No; No HOP Ves, DisplayPort**14;1 x 3.5 mm Audo Jack (Audo Out); No; No HOP Ves, DisplayPort***14;1 x 3.5 mm Audo Jack (Audo Out); No; No HOP Ves, DisplayPort****14;1 x 3.5 mm Audo Jack (Audo Out); No; No HOP Ves, DisplayPort************************************		
Titk -5 to +20* Swhel No swiel Piot No joiot Height adjustment range 100 mm Hardness 3H Screen treatment Anti-glare Integrated privacy filter No Ricker-free Ves Low blue light Ves, Elysafe* Certified Port and Connectors 11 HDM 2.0; 10 lipslayPort** 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Ves, DisplayPort** 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Ves, DisplayPort** 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Ves, DisplayPort** 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Ves, DisplayPort** 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Ves, DisplayPort** 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Ves, DisplayPort** 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Ves, DisplayPort** 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Ves, DisplayPort** 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No Waranty User Initited waranty. Certifications and compliances Bis SBM; CB; CCC; CE; CECP; CE; CTUVus; EA; FCC; ISC Mark; ISO 9241-307; KC, KCC; NOM; PSB; TUV-S (Argentina) IEC60950-1; VCC; WEEE; California Energy Commission (CEC); Mexico Energy; WW application; KE; UMA; Ni the box What's in the box Monito; DisplayPort** adale; War		
Swivel No swivel Pivot No pivot Height adjustment range 100 mm Hardness 3H Screen treatment Anti-glare Integrated privacy filter No Ricker-Free Ves Up blue light Ves, Eyesafe® Certified Port and Connectors 1 HDBL 20; 1 DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HDCP Ves, DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No Mangement software OMEN Gaming Hub Waranty 1 year limited waranty. Certifications and compliances BIS; SSMI: ER; CC; CE: CEEP; CE; CT Mus; EAC; FCC; ISC Mark; ISO 9241-307; KC/KCC; NOM; PSB; TUV-S (Argentina) IEC60950-1; VCC; WEEE; California Energy Commission (CEC); Mexico Energy; WW application; ICE; Musici So South Africa; PSE EAC; Belarus Energy; Eyesafe® Certified Waranty 1 year limited waranty. Certifications and compliances BIS; SSMI: ER; CC; CE: CEEP; CE; CT Mus; EAC; FCC; ISC Mark; ISO 9241-307; KC/KCC; NOM; PSB; TUV-S (Argentina) IEC60950-1; VCC; WEEE; California Energy Commission (CEC); Mexico Energy; WW application; ICE; Musici So Subt Africa; PSE EAC; Belarus Energy; Eyesafe® Certified Waranty 1 year limited waranty. Certified So Subt Africa; PSE EAC; Belarus Energy; Eyesafe® Certified <th< th=""><th></th><th></th></th<>		
Pivid No pivot Height adjustment range 100 mm Hardness 3H Screen treatment Anti-glare Integrated privacy filter No Ricker-free Ves Low blue light Ves. Eyesafe [®] Certified Port and Connectors 1HDMI 2.0; 1 DisplayPort ^{1m} 14; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Ves. Eyesafe [®] Certified Waranty Ves. Eyesafe [®] Certified Management software OMEN Gaming Hub Waranty 1 year limited waranty. Certifications and compliances BIS BSMU: GCCC CE: CECP: CEL: CT.UNUS EAC; FCC; IS Mark; IS 9241-307; KC/KCC; NOM; PSB; TUV-S (Argentina) EEG0950-1; VCC; WEEE; California Energy, Commission (CEC); Mexico Energy; WW application; ICE; What's in the box Monitor. DisplayPort ^{1m} and; Price SPE EAC; Belarus Energy; Eyesafe [®] Certified Warts in the box Monitor. DisplayPort ^{1m} and; Price SPE EAC; Belarus Energy; Eyesafe [®] Certified Warts in the box Monitor. DisplayPort ^{1m} and; Price Arg Price Arg Port and Energy. Eyesafe [®] Certified Warts in the box Monitor. DisplayPort ^{1m} and; Price Arg Port and Energy. Eyesafe [®] Certified Warts in the box Monitor. DisplayPort ^{1m} and; Price Arg Port and Port and		
Height adjustment range100 mmHardness3HScreen treatmentAnti-glareIntegrated privacy filterNoRicker-freeVesUow blue lightVes, Eyesafe® CertifiedPort and Connectors1HDM12.0; 1 DisplayPort™ 14; 1 x 3.5 mm Audio Jack (Audio Out); No; NoHOCPVes, DisplayPort™ 14; 1 x 3.5 mm Audio Jack (Audio Out); No; NoHOCPVes, DisplayPort™ 14; 1 x 3.5 mm Audio Jack (Audio Out); No; NoHOCPVes, DisplayPort™ 14; 1 x 3.5 mm Audio Jack (Audio Out); No; NoHOCPVes, DisplayPort™ 14; 1 x 3.5 mm Audio Jack (Audio Out); No; NoHOCPVes, DisplayPort™ 14; 1 x 3.5 mm Audio Jack (Audio Out); No; NoHOCPVes, DisplayPort™ 14; 1 x 3.5 mm Audio Jack (Audio Out); No; NoManagement softwareOMEN Gaming HubWaranty1 year limited waranty.Certifications and compliancesBis; BSM1; EB; CCC; CEC; CEC; CEC; CEC; CT; CT; SC Mark; ISO 9241-307; KC/,KCC; NOM; PSB; TUV-5G (argentina) IEC60950-1; VCC; WEEE; California Energy Commission (CEC); Mexico Energy; WW applicator; KCE;What's in the boxMonitor; DisplayPort™ cable; Warranty card; Product notice; AC power cordDimensions (Lx W x H)6.113 x 8.53 x 36.76 cm (Without stand.)Weight6.6 kg (Wth stand.)Package Dimensions (Lx W x H)6.88 x 22.5 x 44 cm		
Hardness 3H Screen treatment Anti-glare Integrated privacy filter No Filcker-free Ves Low blue light Ves, Eyesafe® Certified Port and Connectors 1 HDMI 2.0; 1 DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Ves, DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Ves, DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No Management software OMEN Gaming Hub Waranty 1 year limited waranty. Certifications and compliances BIS; BSMI; CB; CCC; CE; CEP; CEL; CTUVus; EAC; FCC; ISC Mark; ISO 9241-307; KC/KCC; NOM; PSB; TUV-5 (Argentina) IEC60950-1; VCC); WEEE; California Energy, CW applicator; ICEC); Mexico Energy; WW applicator; ICEC) What's in the box Monitor; DisplayPort™ cable; Warranty card; Product notice; AC power cord Dimensions (L x W x H) 64.13 x 8.53 x 36.76 cm (Without stand.) Weight 6.6 kg (With stand.) Package Dimensions (L x W x H) 68.8 x 22.5 x 44 cm		
Screen treatmentAnti-glareIntegrated privacy filterNoFicker-freeYesLow blue lightYes, Eyesafe® CertifiedPort and Connectors1 HDM12.0; 1 DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; NoHDCPYes, DisplayPort™ and HDMIManagement softwareOMEG Gaming HubVarranty1 year limited warranty.Certifications and compliancesBB; BSM; (ES; CCC; CEC; CEC; CSC, SCC, Mark; ISO 9241-307; KC/KCC; NOM; PSB; TUV-S (Argentina) IECG0950-1; VCCI; WEEE; California Energy Commission (CEC); Mexico Energy; WW application; ICE; UAE; TUV-GS; Ukraine certificates; NRCS of South Africa; PSE EAC; Belarus Energy; Eyesafe® CertifiedWarts In the boxMontor: DisplayPort™ cable; Warranty card: Product notice; AC power cordDimensions (Lx Wx H)6.13 x 8.53 x 36.76 cm (Without stand.)Bedge Dimensions (Lx Wx HX)6.88 x 22.5 x 44 cm		
Integrated privacy filter No Ricker-free Ves Low blue light Ves, Eyesafe® Certified Port and Connectors 1 HDM12.0; 1 DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HDCP Ves, DisplayPort™ and HDMI Management software 0MEN Gaming Hub Varranty 1 year limited warranty. Certifications and compliances BiS; BSM; (G; CC; CE; CECP; CEL; cTUVus; EAC; FCC; ISC Mark; ISO 9241-307; KC/KC; NOM; PSB; TUV-S (Argentina) IEG60950-1; VCCI; WEEE; california Energy Commission (CEC); Mexico Energy; WW application; ICE; WAS in the box Wontor, DisplayPort™ ache; Warranty card; Product notice; AC power cord Dimensions (Lx Wx H) 6.13 x 8.53 x 3.67.6 cm (Without stand.) Weight 6.kg (With stand.) Package Dimensions (Lx Wx H) 68.8 x 22.5 x 44 cm		
Fildeer-free Yes Eldeer-free Yes Low blue light Yes, Eyesafe® Certified Port and Connectors 1 HDM12.0; 1 DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HOCP Yes, DisplayPort™ and HDMI Management software OMEG Gaming Hub Variantly 1 year limited warranty. Certifications and compliances BIS; BSM; (G; CC; CE; CECP; CEL; cTUVus; EAC; FCC; ISC Mark; ISO 9241-307; KC/KCC; NOM; PSB; TUV-S (Argentina) IEG60950-1; VCCI; WEEE; California Energy Commission (CEC); Mexico Energy; WW application; ICE; UAS's IM-S of South Africa; PSE EAC; Belarus Energy; Eyesafe® Certified Wars in the box Montor; DisplayPort™ cale); Warranty card; Product notice; AC power cord Dimensions (Lx Wx H) 6.13 x 8.53 x 3.67.6 cm (Without stand.) Weight 6.8g (With stand.) Package Dimensions (Lx Wx H) 68.8 x 22.5 x 44 cm		
Low blue light Yes, Eyesafe® Certified Port and Connectors 1 HDM12.0; 1 DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HDCP Yes, DisplayPort™ and HDMI Management software 0MEN Gaming Hub Warranty 1 year limited warranty. Certifications and compliances BIS; BSM; (Sc; CC; CE; CECP; CEL; cTUVus; EAC; FCC; ISC Mark; ISO 9241-307; KC/KCC; NOM; PSB; TUV-S (Argentina) IEC60950-1; VCCI; WEEE; California Energy Commission (CEC); Mexico Energy; WW application; ICE; UAFs in the box Monitor, DisplayPort™ cable; Warranty card; Product notice; AC power cord Dimensions (Lx Wx H) GestgeDimensions (Lx Wx H) 6.8 g X22.5 x 44 cm		
Pot and Connectors 1 HDMI 2.0; 1 DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HDCP Ves, DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No HDCP Ves, DisplayPort™ 1.4; 1 x 3.5 mm Audio Jack (Audio Out); No; No Management software OMEN Gaming Hub Waranty 1 year limited waranty. Certifications and compliances BIS; BSM; CB; CCC; CE; CECP; CLL; cTUVus; EAC; FCC; ISC Mark; ISO 9241-307; KC/KCC; NOM; PSB; TUV-S (Argentina) IEC60950-1; VCCI; WEEE; California Energy Commission (CEC); Mexico Energy; WW application; ICE; UAE; TUV-GS; Ukraine certificates; NRCS of South Africa; PSE EAC; Belarus Energy; Eyesafe® Certified Whats in the box Monitor; DisplayPort™ cable; Warranty card; Product notice; AC power cord Dimensions (Lx Wx H) 6.13 x 8.53 x 3.67.6 cm (Without stand.) Weight 6.8 gu(With stand.) Package Dimensions (Lx Wx H) 6.8 x 22.5 x 44 cm		
HDCP Yes, DisplayPort™ and HDMI Management software OMEN Gaming Hub Waranty 1 year limited waranty. Certifications and compliances BIS; BSM; CB; CCC; CEC, CEC, CTUVus; EAC, FCC; ISC Mark; ISO 9241-307; KC/KCC; NOM; PSB; TUV-S (Argentina) IEG0950-1; VCCI; WEEE; California Energy Commission (CEC); Mexico Energy; WW application; ICE; UAE; TUV-GS; Ukraine certificates; NRCS of South Africa; PSE EAC, Belarus Energy; Eyesafe® Certified Whats in the box Monitor; DisplayPort™ cable; Warranty card; Product notice; AC power cord Dimensions (Lx Wx H) 6.13 x 8.53 x 3.67.6 rm (Without stand.) Weight 6.8 g(With stand.) Package Dimensions (Lx Wx H) 68.8 x 22.5 x 44 cm		
Management software OMEN Gaming Hub Waranty 1 year limited warranty. Certifications and compliances BIS; BSM; CB; CC; CE; CECP; CEL; cTUVus; EAC; FCC; ISC Mark; ISO 9241-307; KC/KCC; NOM; PSB; TUV-S (Argentina) IEC60950-1; VCCI; WEEE; California Energy Commission (CEC); Mexico Energy; WW application; ICE; UAE; TUV-GS; Ukraine certificates; NRCS of South Africa; PSE EAC; Belarus Energy; Eyesafe® Certified What in the box Monitor; DisplayPort™ cable; Warranty card; Product notice; AC power cord Dimensions (Lx Wx H) 6.13 x 8.53 x 3.67.6 cm (Without stand.) Weight 6.8g (With stand.) Package Dimensions (Lx Wx H) 6.88 x 22.5 x 44 cm		
Waranty 1 year limited waranty. Certifications and compliances BIS; BSM; CB; CCC; CE; CECP; CL; cTUUus; EAC; FCC; ISC Mark; ISO 9241-307; KC/KCC; NOM; PSB; TUV-S (Argentina) IEC60950-1; VCC; WEEE; California Energy Commission (CEC); Mexico Energy; WW application; ICE; UArs in the box What's in the box Monitor; DisplayPort [™] cable; Warranty card; Product notice; AC power cord Dimensions (L x W x H) 61.13 x 8.53 x 36.76 cm (Without stand.) Begglithensions (L x W x H) 68.8 x 22.5 x 44 cm		
Certifications and compliances BS; BSM; CB; CCC; CE; CECP; CLL; cTUVus; EAC; FCC; ISC Mark; ISO 9241-307; KC/KCC; NOM; PSB; TUV-S (Argentina) IEC60950-1; VCCI; WEEE; California Energy Commission (CEC); Mexico Energy; WW application; ICE; UAE; TUV-GS; Ukraine certificates; NRCS of South Africa; PSE EAC; Belarus Energy; Eyesafe® Certified What's in the box Monitor; DisplayPort [™] cable; Warranty card; Product notice; AC power cord Dimensions (L x W x H) 61.13 x 8.53 x 36.76 cm (Without stand.) Weight 6.6 kg (With stand.) Package Dimensions (L x W x H) 68.8 x 22.5 x 44 cm		
Certification and on planted UAE; TUV-GS; Ukraine certificates; NRCS of South Africa; PSE EAC; Belarus Energy; Eyesafe® Certified What's In the box Monitor; DisplayPort™ cable; Warranty card; Product notice; AC power cord Dimensions (Lx Wx H) 61.13 x 8.53 x 36.76 cm (Without stand.) Weight 6.6 kg (With stand.) Package Dimensions (Lx Wx H) 68.8 x 22.5 x 44 cm		
Dimensions (L x W x H) 61.13 x 8.53 x 36.76 cm (Without stand.) Weight 6.6 kg (With stand.) Package Dimensions (L x W x H) 68.8 x 22.5 x 44 cm		UAE; TUV-GS; Ukraine certificates; NRCS of South Africa; PSE EAC; Belarus Energy; Eyesafe® Certified
Weight 6.6 kg (With stand.) Package Dimensions (L x W x H) 68.8 x 22.5 x 44 cm		
Package Dimensions (L x W x H) 68.8 x 22.5 x 44 cm		
	-	и и
Package weight 10.5 kg	Package Dimensions (L x W x H)	68.8 x 22.5 x 44 cm
	Package weight	10.5 kg

Messaging Footnotes

¹ All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower. Results may vary based on quality of the original picture/photo/video and difference between the previous monitor settings compared to the HP Enhance + mode.

Universitive version of the previous monitor settings compared to the HP Enhance + mode. ² FreeSync[™] Premium is only available when it is connected on Display Port or HDMI. FreeSync is an AMD® technology enabled on FHD or QHD displays and is designed to eliminate stuttering and/or tearing in games and videos by locking a display's refresh rate to the frame rate of the graphics card. Mandatory low framerate compensation and at least 120Hz refresh rate, AMD Radeon Graphics and/or AMD A-Series APU-compliant monitors with DisplayPort/HDMI Adaptive-Sync required. AMD 15.11 Crimson driver (or newer) required to support FreeSync over HDMI. Adaptive refresh rates vary by monitor. More information is available at www.amd.com/freesync. ³ Supports Adaptive-sync with NVIDIA® GeForce® graphics cards and AMD Radeon graphics cards. FreeSync[™] certified. Compatible with NVIDIA® GeForce® GTX 10 series, GTX 16 series and newer graphics cards. ⁴ Full high-definition (FHD) content required to view FHD images.

Full high-dennition (FHD) Content required to view FHD images.
Fibit high-dennition (FHD) Content required to view FHD images.
Fiber cushions made from 100% recycled visions made from sustainably sourced certified and recycled fibers. Plastic cushions are made from >90% recycled plastic.
Fiber cushions made from 100% recycled wood fiber and organic material.
Requires a monitor and AMD Radeon[®] graphics, both with FreeSync[®] Premium support. AMD FreeSync[®] Premium requires mandatory low framerate compensation and at least 120 Hz refresh rate at minimum FHD. See www.amd.com/freesync for complete details. Confirm capability with your system manufacturer before purchase. GD-161.
VESA mounting arm or wall mounting assembly sold separately.

Technical Specifications Footnotes

¹ All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower

© Copyright 2023 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editional errors or omissions contained herein. All performance specifications are provided by the component manufacturers. Performance specifications represent the higher store over. March 2023

