HP Z40c G3 WUHD Curved Displays



Your Window to Your World.

Stay focused and productive by immersing yourself in the brilliant, expansive views of the HP Z40c G3 Curved Display. Experience extraordinary, true-to-life color and see all of your projects at once, in stunning detail, on an Ultrawide display with 5K:2K resolution. Look and sound like you do in real life on calls with an integrated 4K webcam and high fidelity speakers.



*Product image may differ from actual product

Multitask with ease for higher productivity with a 101.6 cm (40-inch) diagonal 5K:2K-resolution Ultrawide screen that can be segmented into the equivalent of four 50.8 cm (20-inch) monitors for maximum viewing and minimal toggling.

• With a 101.6 cm (40-inch) diagonal 5K:2K-resolution screen, size versus resolution trade offs are over. Multitask with ease and improve productivity with an Ultrawide screen that can be segmented into the equivalent of four 50.8 cm (20-inch) monitors so users can view all of their projects, more lines of code, and bigger spreadsheets with minimal toggling and scrolling.

1.07 Billion Colors Realistically Displayed².

Remove the barriers between you and your screen with vivid, life-like and always accurate colors and details. Factory-calibrated for color accuracy out-of-the-box, this monitor delivers 100% sRGB and 98% DCI-P3 wide color gamuts¹ so colors like firetruck red match what you see in real life².

A Lifelike Conferencing Experience

• The Zoom Certified Z40c Monitor blurs the line between virtual conference calls and reality. Look and sound true-to-life on video with an integrated pop up and tiltable 4K webcam that puts your face in focus and delivers a clear image in any lighting, while built-in dual noise cancelling microphones and room filling speakers make any space your own private office.

Total Control. Totally Connected.

Streamline your work by connecting and viewing content from two PCs with superfast Thunderbolt™ 3 connections that also deliver up to 165W of power—enough to charge two PCs at once.
 Integrated HP Device Bridge 2.0 lets you control two Windows® and/or Mac® devices from the same keyboard and mouse while maintaining network security with controlled file sharing³.

Featuring

- Every HP Z Display undergoes factory color calibration and testing to achieve a Delta E of less than 2, making color differences virtually indistinguishable to the human eye.
- Because HP met or exceeded all Zoom quality benchmarks, you can be sure our hardware works seamlessly with Zoom's software to deliver an unmatched conferencing experience every time
- Control two devices copy, paste, drag and drop files or data between them with one keyboard and mouse. View their images side by side or one at a time.³
- The integrated webcam pops up when needed and can be pushed down which acts as a kill switch for the camera and mic for worry-free privacy
- Integrated webcam features an improved discrete IR sensor so using your face as a password with Windows® Hello has never been more hassle-free.
- Built-in mics and speakers that pick up and deliver crystal-clear audio.
- Customize your webcam and audio settings using simple controls in HP Display Center. Crop in and adjust brightness, exposure, volume using simple sliders. 5
- HP is helping conserve natural resources, reduce waste sent to landfills, and lower energy consumption by using 80% recycled plastics in the plastics of Z G3 Monitors. 6,7
- HP is committed to reducing plastic in landfills by using 100% recyclable packaging that meets recycling requirements, so it stays out of the landfill.^{8,9}
- HP Eye Ease is an always-on, low-blue light filter that helps keep your eyes comfortable throughout the day by reducing blue light without impacting color accuracy or adding a yellow color shift.
- Work effortlessly with 3-way ergonomics that help keep your neck, shoulders, and back comfortable throughout the day. Customize tilt, 150mm height adjust, and swivel settings to fit you, your desk, and your needs.
- More ports means more capabilities. With a USB-C®, HDMI, DisplayPort™, four USB-A 3.0 ports and a USB-B port, you can connect multiple devices like a keyboard and mouse.
- Customize your display with easy, intuitive HP Display Center software that lets you tailor your settings, partition screens, and even dim the screen—all through the host PC.
- HP Display Manager makes remote management of the monitor easy. Simplify deployment, asset tracking, and remotely control monitor settings, like turning the power off.
- Feel confident in your connection with a monitor that connects directly to Ethernet via RJ-45 port for stable internet connection and remote IT manageability.
- With these monitors, not only do you get full-conferencing ability, but also peace of mind, with the standard 3-year limited warranty.

HP Z40c G3 WUHD Curved Displays Specifications Table





*Product	image	may differ	from	actual	product

*Product image may differ from actual product	
Display type	IPS ¹
Brightness	300 nits ¹
Contrast ratio	1000:11
Response Ratio	14 ms gray to gray ¹
Product colour	Black and Silver
Aspect ratio	21.9
Native resolution	WUHD (5120×2160) ^{1,3}
Resolutions supported	640 x 480; 720 x 400; 800 x 600; 1024 x 768; 1280 x 800; 1280 x 1024; 1440 x 900; 1600 x 900; 1600 x 1200; 1680 x 1050; 1920 x 1080; 1920 x 1200; 2560 x 1440; 2560 x 1600; 3840 x 2160; 4096 x 2160; 5120 x 2160
Display features	Anti-glare; Height adjustable; Integrated speakers; Curved display; Webcam; HP Eye Ease; Integrated microphone
User controls	Exit; Information; Language; Management; Power control; Input control; Menu control; Brightness*; Image; Color; Picture-by-Picture
Display size (diagonal, metric)	100.8 cm (39.7")
Ports and Connectors	USB Type-C® video input: 2 Thunderbolt™ 3 (40Gbps signaling rate) with SuperSpeed USB Type-C® 5Gbps signaling rate (Up to 100W USB Power Delivery, Alt Mode DisplayPort™ 1.4); HDCP: Yes, DisplayPort™ and HDMl; 1 HDMl 2.0; 1 DisplayPort™ 1.4; 4 SuperSpeed USB Type-A 5Gbps signaling rate; 1 RJ-45
Camera	Yes, 13MP
Multimedia	Integrated speakers
Environmental	Operating temperature: 5 to 35°C; Operating humidity: 20 to 80% non-condensing;
Power	100 - 240 VAC 50/60 Hz
Power consumption	310 W (maximum), 72 W (typical), 0.5 W (standby)
Dimensions	94.74 x 14.195 x 44.71 cm (Without stand.)
Weight	14.3 kg (With stand)
Physical security features	Security lock-ready ²
Ecolabels	EPEAT® registered ⁴
Energy star certified (series fixed)	ENERGY STAR® certified
Certification and compliance	BIS; BSMI; CB; CCC; CE; CECP; CEL; CEL Grade 1; CTUVus; EAC; ENERGY STAR®; E-standby; FCC; GS Mark; ISO 9241-307; KC/KCC; NOM; PSB; SEPA; TCO Certified; TUV-S; VCCI; WEEE; ISC; Low blue light; South Africa Energy; UAE; Ukraine certificates; Zoom Certified; Windows Hello
Sustainable impact specifications	85% (TE-derived closed loop plastic; Low Halogen; Outside box and corrugated cushions are 100% sustainably sourced and recyclable; Designed with recycled metals; Contains Ocean-Bound plastic ^{5,6,7,8,9}
What's in the box	Monitor; DisplayPort™ cable; HDMI cable; VESA Mount adapter; Warranty card; QSP; AC power cord; Color calibration report; Thunderbolt™ cable¹0
Pixels per inch (ppi)	139 ррі
Pixels per inch (ppi) Panel bit depth	10 bit (8 bit + FRC)
Pixels per inch (ppi) Panel bit depth Vertical viewing angle	10 bit (8 bit + FRC) 178*
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle	10 bit (8 bit + FRC) 176* 178*
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel	10 bit (8 bit + FRC) 178° 178° 3-sided micro-edge
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel	10 bit (8 bit + FRC) 178° 178° 3-sided micro-edge ±30°
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel	10 bit (8 bit + FRC) 178° 178° 3-sided micro-edge ±30° -5 to +20°
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tit Pivot	10 bit (8 bit + FRC) 178* 3-sided micro-edge 230* -5 to +20* No pivot
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pivot Height adjustment range	10 bit (8 bit + FRC) 178° 178° 3-sided micro-edge ±30° -5 to +20° No pivot 150 mm
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pixot Height adjustment range VESA mounting	10 bit (8 bit + FRC) 178° 178° 3-sided micro-edge ±30° >5 to +20° No pivot 150 mm 100 mm x 100 mm (bracket included)
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pivot Height adjustment range VESA mounting Hardness	10 bit (8 bit + FRC) 178" 178" 3-sided micro-edge ±30" -5 to +20" No pivot 150 mm 100 mm x 100 mm (bracket included) 3H
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pixot Height adjustment range VESA mounting Hardness Screen treatment	10 bit (8 bit + FRC) 178* 178* 3-sided mitor-edge ±30* -5 to +20* No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tit Pixot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled	10 bit (8 bit + FRC) 178* 3-sided micro-edge ±30° -5 to +20° No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pivot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter	10 bit (8 bit + FRC) 178* 3-sided micro-edge ±30* -5 to +20* No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pivot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Flicker-free	10 bit (8 bit + FRC) 178° 178° 3-sided micro-edge ±30° -5 to +20° No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not buch-enabled No Yes
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pivot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Flicker-free Low blue light modes	10 bit (8 bit + FRC) 178" 178" 3-sided micro-edge ±30" -5 to +20" No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No Yes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified)
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pixot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Filicker-free Low blue light modes Energy efficiency class	10 bit (8 bit + FRC) 178* 3-sided mitro-edge ±30° -5 to +20° No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No Yes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) G
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pixot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Flicker-free Low blue light modes Energy efficiency class Display scan frequency (horizontal)	10 bit (8 bit + FRC) 178* 3-sided micro-edge 3-0° -5 to +20° No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No Yes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) 6 15-134 kHz
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pixot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Flicker-free Low blue light modes Energy efficiency class Display scan frequency (horizontal) Display scan frequency (horizontal)	10 bit (8 bit + FRC) 178* 3-sided mitro-edge ±30° -5 to +20° No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No Yes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) G
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pivot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Flicker-free Low blue light modes Energy efficiency class Display scan frequency (horizontal) Display scan frequency (vertical) Pixel pitch	10 bit (8 bit + FRC) 178* 3-sided micro-edge 3-0° -5 to +20° No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No Yes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) G 15-134 kHz 29-71 Hz
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pixot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Flicker-free Low blue light modes Energy efficiency class Display scan frequency (horizontal) Display scan frequency (horizontal)	10 bit (8 bit + FRC) 178* 3-sided micro-edge ±30° -5 to +20° No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No Yes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) G 15-134 kt/z 29-71 Hz 0.181 mm x 0.181 mm
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pivot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Flicker-free Low blue light modes Energy efficiency class Display scan frequency (horizontal) Display scan frequency (vertical) Pixel pitch Display Scan frequency (vertical) Pixel pitch Display Scan frequency (vertical)	10 bit (8 bit + FRC) 178° 178° 3-sided micro-edge ±30° -5 to +20° No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not buch-enabled No Yes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) G 15-134 kHz 29-71 ltz 0.181 mm x 0.181 mm 100% sRGG; 98% DCL-P3; 100% BT.709
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pixot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Filcker-free Low blue light modes Energy efficiency class Display scan frequency (horizontal) Display scan frequency (vertical) Pixel pitch Display Color Gamut Microphone	10 bit (8 bit + FRC) 178" 3-sided mitro-edge ±30" -5 to +20" No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No Yes Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) G 15-134 kHz 29-71 Hz 0.181 mm x 0.181 mm 100% sRGG: 98% DCI-P3; 100% BT.709 Yes (noise cancelling)
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pixot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Flicker-free Low blue light modes Energy efficiency class Display scan frequency (horizontal) Display scan frequency (vertical) Pixel pitch Display Clor Gamut Microphone Windows Hello compatible	10 bit (8 bit + FRC) 178" 3-sided micro-edge 3-0" -5 to +20" No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No Yes 159 Tese (TÜV Low Blue Light Hardware Solution certified) G 15-134 kHz 29-71 hz 0.181 mm x 0.181 mm 100% sRGS; 98% DCI-P3; 100% B17.799 Yes (Roise ancelling) Yes Yes (Roise ancelling)
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tit Pixot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Flicker-free Low blue light modes Energy efficiency class Display scan frequency (horizontal) Display scan frequency (vertical) Pixel pitch Display Color Gamut Microphone Windows Helio compatible Speakers	10 bit (8 bit + FRC) 178" 178" 178" 3-sided micro-edge 330" -5 to +20" No pivot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No Ves Yes, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) G 15-134 kHz 29-71 Hz 0.181 mm x 0.181 mm 100% sRGB; 98% (CLP3; 100% BT.709 Yes (ves cancelling) Yes (ves cancelling)
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pivot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Flicker-free Low blue light modes Energy efficiency class Display scan frequency (horizontal) Display scan frequency (vertical) Pixel pitch Microphone Mirdows Hello compatible Speakers Speakers output power	10 bit (8 bit + FRC) 178* 178* 178* 3-sided micro-edge 3-30* -5 to +20* No pixot 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No Ves Ves, HP Eye Ease (TÜV Low Blue Light Hardware Solution certified) 6 15-134 kHz 29-71 Hz 0.181 mm x 0.181 mm 100% sRGR; 98% DCL-P3; 100% BT.709 Ves fives earcelling) Ves
Pixels per inch (ppi) Panel bit depth Vertical viewing angle Horizontal viewing angle Bezel Swivel Tilt Pivot Height adjustment range VESA mounting Hardness Screen treatment Touch-enabled Integrated privacy filter Flicker-free Low blue light modes Energy efficiency class Display scan frequency (horizontal) Display scan frequency (vertical) Pixel pitch Microphone Windows Hello compatible Speakers Certified collaboration software	10 bit (8 bit + FRC) 178* 178* 178* 3-3idel miror-edge ±30" -5 to +20" No pixet 150 mm 100 mm x 100 mm (bracket included) 3H Anti-glare Not touch-enabled No Yes Ves, HE bye Ease (TÜV Low Blue Light Hardware Solution certified) G 15-134 bitz 29-71 Hz 0.181 mm x 0.181 mm 100% sRGR 98% DCL-P3: 100% BT.709 Ves (roise cancelling) Ves (roise cancelling) Ves (roise cancelling) Ves (roise cancelling)

HP Z40c G3 WUHD Curved Displays

Accessories and services (not included)

HP Business PC Security Lock v3 Kit



Help prevent chassis tampering and secure your PC and display in workspaces and public areas with the affordable HP Business PC Security Lock v3 Kit.

Product number: 3XJ17AA

HP B600 Z Display PC Mounting



Product number: 529H3AA

HP Quick Release Bracket 2



Use the HP Quick Release Bracket 2 to attach your HP Desktop Mini to an HP display¹ and a variety of stands, arms or wall mounts.² The failsafe "Sure-Lock" mechanism snaps the PC securely in place, and can be further secured with a theft-deterrent security screw. **Product number: 6KD15AA**



HP Z40c G3 WUHD Curved Displays

Messaging Footnotes

- 1 All performance specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.
 2 Number of colors available through A-FRC technology.
 3 HP Device Bridge 2.0 works with two computers and is compatible with Windows 10 and higher, MacOS M1 platforms, and up to Ubuntu 18.04 devices.
 4 Windows Hello requires Windows 10 or higher. Internet connection required for online logins and sold separately.

- Host PC requires Windows 10 or higher. HP Display Center is available on the Microsoft store.

- HP Sustainability Report 2020.

 **Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 EPEAT standard.

 **https://www.greenmatters.com/p/what-percent-recycling-actually-gets-recycled.

 **Own outer box/corrugate cushion packaging made from sustainably sourced certified and recycled fibers. Fiber cushions made from 100% recycled wood fiber and organic material. Any plastic cushions are made from >90% recycled plastic. Excludes plastic bags and plastic foam sheeting.

 10 Comes with Power Cord and USB-C Cable, all other cables sold separately.
- 11 HP Display Manager software agent must be running on a web server and host PC. Some limitations may apply to legacy monitors.

Technical Specifications Footnotes

- ¹ All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower
- ² Lock sold separately.

 ³ DisplayPort™ 1.4 or HDMI 2.0 required to drive panel at its native resolution. The video card of the connected PC must be capable of supporting 5120 x 2160 at 60 Hz with 10-bit color using one DisplayPort™, HDMI, or USB Type C® (Alt Mode DisplayPort™).

 ⁴ EPEAT® registered where applicable. EPEAT registration varies by country. See www.epeat.net for registration status by country. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. Status varies by country. "EPEAI" registered where applicable. EPEAI registration varies by country. See www.epeat.net for registration status by country. Based on US EPEAI" registration.

 ITE Derived Closed Loop Plastic percentage is based on the definition set in the IEEE 1680.1-2018 standard.

 External power supplies, WWAN modules, power cords, cables and peripherals excluded. Service parts obtained after purchase may not be Low Halogen.

 7 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers.

 8 Percent of recycled metal varies by product.

 9 Percentage of ocean-bound plastic contained in each component varies by product.

- ¹⁰ Included cables may vary by country.
 ¹¹ Host PC requires Windows 10 or higher. HP Display Center is available on the Microsoft store.

Sign up for updates hp.com/go/getupdated

© Copyright 2022 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

