HP Latex R2000 Plus Printer

Unprecedented quality and colours² on rigid up to 2.49 m, for sustained production environments





Achieve amazing colours and media look and feel

- Help increase profitability with higher value rigid and flexible applications with vibrant HP Latex gamut.
- Gain versatility with HP Latex Ink—from indoor/outdoor signage to thermoforming and high-quality decoration.
- Win more jobs with UL ECOLOGO® Certified, water-based HP Latex Inks that produce odorless prints.³

Expand your offering with the glossiest white $^{1} \ensuremath{\mathsf{^1}}$

- Expand your portfolio into a wide range of applications with glossiest white that resists yellowing.¹
- No waste between white jobs⁴ with removable HP Thermal Inkjet printheads stored in offline rotating chamber.
- You're always ready to print white—automatic recirculation and printhead cleaning eliminate manual purging.

Increase your productivity with smart printing

- Meet production peaks—get high-speed quality up to 28 outdoor boards/hr⁵ with belt system, smart vacuum.
- Drive high productivity with multi-board printing, assisted loading, and advanced queuing.
- Maximise uptime with automatic maintenance and smart service tools for fast diagnosis and issue resolution.
- Maintain control of your production and costs with the help of HP PrintOS software tools.

For more information, please visit http://www.hp.com/go/LatexR2000

Join the community, find tools, and talk to experts. Visit the HP Latex Knowledge Center at https://hplatexknowledgecenter.com/

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: http://www.hp.com/learn/ds

¹ Glossiest white based on internal HP testing in January, 2018 compared to the HP Scitex FB750/FB550 Printer using UV-curable ink technology. White ink measured for the level of gloss at 60 degrees on a rigid material (acrylic). Tested using Glossmeter BYK micro-TRI-gloss (20°, 60°, 85°), compatible with ISO 2813 and ASTM D523 relative to glossiness measure. High opacity and resists yellowing over time based on internal HP WeatherOmeter testing October, 2017 with 1 dot-per-pixel HP Latex Overcoat, on a range of rigid and flexible unlaminated substrates. Yellowing based on L* and B* of white underflood samples.
 ² Most vibrant colours based on internal HP testing, January 2018 compared to leading competitive printers under \$350,000 USD. Tested in High Quality print mode on rigid (white acrylic 12-pass, 6-colour, 120%). Internal HP testing with HP GamutViewer, Alpha Shapes=50000.
 ³ HP Latex Inks are UL ECOLOGO® Certified, UL ECOLOGO® Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental

³ HP Latex Inks are UL ECOLOGO[®] Certified. UL ECOLOGO[®] Certification to UL 2801 demonstrates that an ink meets a range of multi-attribute, lifecycle based criteria related to human health and environmental considerations (see http://www.ul.com/EL). There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print. ⁴ When HP 886 White Latex Printheads are placed in the storage cassettes, no white ink is used for servicing when printheads are not in use.

⁵ Outdoor mode 3-pass, 70%. On 1.2 x 2.4 m boards.

Technical specifications

Printing modes	22 m²/hr - Indoor High Quality (12p 120%) 43 m²/hr - Indoor Production (6p 110%) 86 m²/hr - Outdoor (3p 70%) 36 m²/hr - White Spot (100%) 16 m²/hr - White Overfload/Underfload (100%) 5.2 m²/hr - 3 layers day & night ¹	
Print resolution	Up to 1200 x 1200 dpi	
Ink types	Water-based HP Latex Inks	
Ink cartridges	9 (cyan, magenta, yellow, black, light cyan, light magenta, HP Latex Optimizer, HP Latex Overcoat, white)	
Cartridge size	5 L (colours, HP Latex Optimizer, HP Latex Overcoat); 3 L (white)	
Printheads	8 (cyan/black, magenta/yellow, light cyan/light magenta, HP Latex Overcoat, 2 HP Latex Optimizer, 2 white)	
Long-term print-to-print repeatability	Average ≤ 1.0 dE2000, 95% of colours ≤ 2 dE2000 ²	
Media		
Handling	Flatbed, sheet feed, roll feed, vacuum belt media drive for easy loading and accurate media advance	
Media types	Rigid substrates: paper foamboard, plastic foamboard, PVC foam, plastic corrugated, acrylic, polycarbonate, polystyrene, compressed cardboard, corrugated board, honeycomb board, aluminum composite panel, wood, glass, ceramic; Roll substrates: PVC boarne; self-adhesue vorul, coated paper, polypropylene, polystyrene, polycarbonate, polyester, textile (non porous), canvas, leather	
Rigid media size	297 x 420 mm to 2489 x 1220 mm (up to 2489 x 3050 mm with two sets of optional extension tables)	
Roll size	60.9 cm to 2.49 m	
Roll weight	Up to 100 kg	
Roll diameter	Up to 25 cm	
Thickness	Up to 50.8 mm	
Applications	Signage: indoor, flat, backlit, thermoformed; Decoration: wall coverings, window decoration; Vehicle decoration: fleet graphics, wraps, decals; Textile: soft signage, frontlit, backlit; POS and Packaging: corrugated displays, short-run customised packaging, prototyping	
Connectivity		
Interfaces	Gigabit Ethernet (1000Base-T)	
Dimensions (w x d	x h)	
Printer	5.10 x 2.04 x 1.75 m (printer); 5.10 x 3.64 x 1.75 m (including standard input and output tables)	
Shipping	5.32 x 2.24 x 2.15 m	
Operating area	8.7 x 7.23 x 3 m	
Weight		
Printer	1600 kg	
Shipping	2800 kg	
What's in the box	HP Latex R2000 Printer; HP Latex R Series White Upgrade Accessory Kit; HP Latex R2000 Roll Printing Accessory Kit with 98-in spindles (x2) and pneumatic gun adapter and table top roll holders (x2); HP 886 Latex Printheads; HP Latex Printhead (Leaning Kit; standard input and output tables; foot switch; HP Internal Print Server and displays (x2); printer maintenance kit; warranty and intro docs	
Environmental ran	ges	
Operating temperature	15 to 30°C	
Operating humidity	20 to 70% RH (non-condensing)	
Power		
Consumption	10 to 12 kW (typical)	
Certification		
Safety	IEC 60950-1+A1+A2 compliant; United States and Canada (CSA listed); EU (LVD and MD compliant; EN60950-1, EN12100-1, EN ISO13849-1, EN60204-1, and EN1010-1); Russia, Belarus and Kazakhstan (EAC); Australia, New Zealand (RCM)	
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM)	
Environmental	WEEE; ROHS (EU, China, Korea, Singapore, Turkey, Ukraine); India Waste Management Rules; REACH; CA 65 Prop; ErP Ecodesign Directive	
Warranty	180-day limited hardware warranty. Warranty may vary by country as required by law. Go to http://www.hp.com/support to learn about HP service and support options in your region.	

Ordering information

Product

KOQ46C	HP Latex R2000 Plus Printer		
Accessories			
T7V23A Y6V16A	HP Latex R2000 Extension Tables HP Latex R Series Edge Holders Kit		
Original HP printing supplies			
G0Z21A G0Z22A	HP 886 White Latex Printhead HP 886 Ontimizer Latex Printhead		

GUZZZA	HP 886 Optimizer Latex Printneau		
GOZ24A	HP 886 Latex Printhead		
GOZOOA	HP 886 Latex Printhead Cleaning Kit		
G0Z09A	HP 886 3-liter White Latex Ink Cartridge		
G0Z10A	HP 882 5-liter Cyan Latex Ink Cartridge		
GOZ11A	HP 882 5-liter Magenta Latex Ink Cartridge		
GOZ12A	HP 882 5-liter Yellow Latex Ink Cartridge		
GOZ13A	HP 882 5-liter Black Latex Ink Cartridge		
GOZ14A	HP 882 5-liter Light Cyan Latex Ink Cartridge		
G0Z15A	HP 882 5-liter Light Magenta Latex Ink Cartridge		
G0Z16A	HP 882 5-liter Optimizer Latex Ink Cartridge		
GOZ17A	HP 882 5-liter Overcoat Latex Ink Cartridge		
Original HP large format printing materials			
Unginal ne large iunnal philling Malendls			

HP Premium Removable Gloss Adhesive Vinyl HP Permanent Gloss Adhesive Vinyl HP Durable Backlit Fabric (Take-back program)³ HP Backlit Polyester Film (Take-back program)³

For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.

Service and Support

If you want to extend the support beyond what's included: HOHXARC HP Standard Service, Maintenance and Support extension contract HORIAC HP Enhanced Service, Maintenance and Support extension contract UASWOS HP Latex R series Level 3 Train to repair and maintain – 5 days training at HP U27S3E 3 Yaes Next Businases Day with Defective Media Retention for HP Latex R2000 Plus K0Q45-67269 HP Latex R series Expert spare parts uptime kit

ECO highlights

- Better for print operations—no hazard warning labels or HAPs, no special ventilation needed¹
 Better for the environment—HP designs end-to-end sustainability into large-format printing
 Water-based inks produce odorless prints²
 HP Latex Inks are UL ECOLOGO® and UL GREENGUARD GOLD Certified³

Please recycle large-format printing hardware and printing supplies. Find out how at our website: http://www.hp.com/ecosolutions

¹ Contains no Hazardous Air Pollutants according to EPA Method 311. Special ventilation equipment (air filtration) is not required to meet U.S. OSHA requirements. Special ventilation equipment installation is at the discretion of the customer—see the Site Preparation Guide for details. Customers should consult state and local requirements and regulations. Contains no Hazardous Air Pollutants according to EPA Method 311.
² There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.
³ ULECOLGO® (CECOLGO® Contains no Hazardous Air Pollutants according to EPA Method 31.
⁴ There is a broad set of media with very different odor profiles. Some of the media can affect the odor performance of the final print.
³ ULECOLGO® (CECOLGO® Contains on Hazardous Air Pollutants according the therm of the media can affect the odor criteria related to human health and environmental considerations (see http://www.ul.com/EL). UL GREENGUARD GOLD Certification to UL 2818 demonstrates that print of the ULS GREENGUARD Standards for low chemical emissions into indoor air during product usage. For more information, visit http://www.ul.com/gg or http://www.ul.com/gg or

¹ Print speed may vary due to the adaptive printing mechanism to avoid image quality defects.
² Reflective measurements on a 943 colour target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard D5 014–6/E:2012. Backlit substrates measured in transmission moder may yield different results.
³ Recyclable HP papers can be recycled through commonly available recycling programs, or according to region-specific parcial take-back program. Programs may not exist in your area. See http://www.HPLFMedia.com/hp/ecosolutions for details.



