HP LaserJet Tank MFP 2604sdw Printer



Business capabilities with up to 5,000 pages of pre-filled toner and the lowest cost per page.¹

Discover business-ready capabilities and savings with HP LaserJet Tank MFP 2604sdw All-in-One Printer prefilled with up to 5,000 pages of Original HP Toner.¹



Get high-quality printing with the lowest cost per page

- Engineered for high-volume printing pre-filled with 5,000 pages of toner in the tank.¹
- Help to save on refills with ultra high yield HP Toner Reload Kit.
- Deliver exceptional quality with sharp text and bold blacks, page after page.

Easy toner refill in 15 sec with Original HP Toner²

- Easily refill Original HP Toner in 15 seconds.²
- Less downtime with 2,500 and 5,000 page HP Toner refill options.¹
- The Original HP Toner Reload Kit has an unique design, made with over 75% less plastic.³

Full features for powerful productivity.

- Speed through multipage documents with automatic two-sided printing.
- Increase productivity with 40-page automatic document feeder
- Print, scan, and share anytime, anywhere with HP Smart app.⁴
- Low maintenance with long-life up to 50,000 page imaging drum. $^{\rm 5}$

Product walkaround

LaserJet Tank MFP 2604sdw shown

- 1. 40-sheet auto document feeder
- 2. Sharp text and consistent printing
- 3. Automatic two-sided printing
- 4. HP Smart Advance
- 5. Pre-filled with up to 5000 pages of Original HP Toner
- 6. Up to 50,000 pages Imaging Drum
- 7. Dual-band Wi-Fi® with self reset & Bluetooth LE
- 8. Built-in Fast Ethernet
- 9. Print speed up to 22 ppm (A4)
- 10. HP WOLF Security Essential
- 11. 250-sheet input tray
- 12. Smart-guided buttons



Accessories, Supplies and Support

Supplies	W1530A HP 153A Black Original LaserJet Tank Toner Reload Kit (~2,500 pages)
	W1530X HP 153X Black Original Laser Jet Tank Toner Reload Kit (~5,000 pages)
Service and Support	U04TNE 3 years Standard Exchange (available in All EMEA countries Except Adriatic, Africa, CIS, EEM, Israel, Middle East, Russia, South Africa, Turkey) U04TKE 3 years Next Business Day Exchange (available in Austria, Belgium, Czech Rep, Denmark, Finland, France, Germany, Greece, Ireland, Italy, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Spain, Sweden, Switzerland, UK)

Technical specifications

Model	HP LaserJet Tank MFP 2604sdw Printer
Product number	381VIA
Control panel	Icon LCD; 2 lights (Media, Lid open); 10 buttons (WiFi, Down, Menu, Up, Copy, ID copy, Info, Resume, Cancel, Power)
Print	
Print technology	Laser
Print speed ¹	Black (A4, normal): Up to 22 ppm; Black (A4, duplex): Up to 14 ipm
First page out ²	Black (A4, ready): As fast as 8 sec; Black (A4, sleep): As fast as 8.4 sec
Print resolution	Black (best): Up to 600 × 600 dpi ; Technology, 600 × 600 dpi; 600 × 400 dpi
Monthly duty cycle	Up to 25,000 pages A4; Recommended monthly page volume: 250-2500
Printer smart software features ^{3,4}	Automatic duplex printing, HP Auto-On/Auto-Off, HP Smart App
Standard print languages	PCLmS; URF; PWG
Print area	Print margins Top: 2 mm, Bottom: 2 mm, Left: 2 mm, Right: 2 mm, Maximum print area : 215.9 x 355.6 mm
Duplex printing	Automatic
Сору	
Copy speed	Black (A4): DM-EMEA: Up to 14 cpm; DM-NA/AP: Up to 22 cpm
Scan	
Scan speed ⁵	Normal (A4): Up to 19 ppm (b&w), up to 10 ppm (color)
Scan file format	Normal ways of period and ways of the comparison
	PEG. NAVIGARY, TWG. (IV, FOR
Scanner specifications	dpi
Recommended monthly scan volume	
Scannable area	Maximum media size (flatbed): 216 x 297 mm; Minimum media size (ADF): 148 x 210 mm Maximum media size (ADF): 216 x 356 mm
Bit depth/ Grey scale levels	24-bit/255
Processor speed	500 MHz
Connectivity	
Standard	Hi-Speed USB (compatible with USB 2.0 specifications; Ethernet 10/100 Base-TX; 802.11a/b/g/n (2.4/5 GHz) Wi-Fi radio
Mobile printing capabilityApple AirPrint™; HP Smart App; Mopria™ Certified	HP Smart App; Apple AirPrint™; Mopria™ Certified; Wi-Fi® Direct Printing
Supported network protocols	TCP/IP: IPv4; IPv6; LPD; SLP; Bonjour; WS-Discovery; BOOTP/DHCP/AutoIP; SNMP v 1/2/3;HTTP/HTTPS; UDP; IPP
Network capabilities	Ethernet 10/100Base-TX; built-in WiFi 802.11b/g/n (2.4/5GHz)
Memory	Standard: 64 MB ; Maximum: 64 MB SDRAM
Media handling	-
Number of paper trays	Standard: 1:Maximum: 1 Input Tray
Media types	Plain paper, Heavy paper, Bond paper, Label, Light paper, Envelope
Media size	Custom (metric): 102 x 152 to 215.9 x 355.6 mm Supported (metric): A6; A5; A4; No. 10 Env; C5 Env; DL Env; B5 Env; B5 [UIS]; 216mm x 340mm; Custom ADF: A4, Letter, Legal
Media handling	Standard input: 250-sheet input tray Optional input: Not applicable
Media weight	60 to 163 g/m²
Input capacity	Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADF: Standard, 40 sheets
Input capacity Output capacity	Tray 1: Sheets: 250; Envelopes: 10 Maximum: Up to 250 sheets ADP: Standard, 40 sheets Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets
Output capacity	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets
	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linux-
Output capacity Compatible operating systems	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linux- imaging-and-printing) Windows Wincrosoft® Windows® 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge.
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Sarver 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linux- imaging-and-printing) Windows: Microsoft® Windows® 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur, macOS v12 Monterey; 2 GB HD; Internet required
Output capacity Compatible operating systems Compatible network operating systems	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Cataline; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linus- imaging-and-printing) Windows: Microsoft® Windows* 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur; macOS v12 Monterey; C GB HD; Internet required No CD in box; Downloadable Software from http://123.hp.com Secure Boat, Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPV1,
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; macO5 10.15 Catalina; macO5 11 Big Sur; macO5 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linux- imaging-and-printing) Windows Microsoft® Windows [®] 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac. Apple® macOS V10.15 Catalina, macOS V12 Monterey; 2 GB HD; Internet required No CD in box; Downloadable Software from http://U2.hp.com Secure Bonx; Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure Drowsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SMMPv2, and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, Active FW update, Admin password by default; Cipher & TLS selection; Account lockout; Secure Wi-Fi setup
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Cataline; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linus- imaging-and-printing) Windows: Microsoft® Windows* 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur; macOS v12 Monterey; C GB HD; Internet required No CD in box; Downloadable Software from http://123.hp.com Secure Boat, Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPV1,
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linux- imaging-and-printing) Windows functors oft® Windows [®] 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur; macOS v12 Monterey; 2 GB HD; Internet required No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.com Secure Biort, Secure Firmware Integrity, Runtime Code Integrity, password hoped: Secure 2015 edata at rest, Active FW update, Admin password by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPV1, SNMPV2, and SMINPV3, Gommunity password Ange: Secure Version 4.active FW update, Admin password by default; Secure Wi-Fi setup HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac)
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W × D × H)	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum; Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SPI), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linux- imaging-and-printing) Windows Microsoft® Windows® 11, 10, 2 6d available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® macOS v10.15 Catalina; macOS v11 Big Sur; macOS v12 Monterey; 2 6d HD; Internet Explorer or Edge. Mac Apple® macOS v10.15 Catalina; macOS v10 Big Sur; macOS v12 Monterey; 2 6d HD; Internet required No CD In box; Downloadabile Software from http://123.hp.com Secure Biot, Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2, TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, Active FW update, Admin password by default; Open & TLS selection; Account lockout; Secure Wi-Fi setup HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 418 x 345 x 311.4 mm; Maximum: 418 x 398.5 x 311.4 mm
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W x D x H) Printer weight	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linus- imaging-and-printing) Windows Microsoft® Windows [®] 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur; macOS v12 Monterey; 2 GB HD, Internet required No CD in box; Downloadable Software from http://ww.hp.com or http://123.hp.com Secure Biox; Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, and SNMPv2, community password change; Secure defaults, Encrypted data at rest, Active FW update, Admin password by default; Cipher & TLS selection; Account lockout; Secure Wi-Fi setup HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Max)
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer mensions (W × D × H) Printer weight Printer weight Operating environment	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum; Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Cataline; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linus- imaging-and-printing) Windows Microsoft® Windows® 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® macOS v10.15 Catalina, macOS v11 Big Sur; macOS v12 Monterey; 2 GB HD, Internet required No CD in box; Downloadable Software from http://wwh.pc.com or http://123.hp.com Secure Box; Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.2; TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPV1, SNMPv2, and SNMPv2, community password change; Secure defaults, Encrypted data at rest, Active FW update, Admin password by default, Cipher & TLS selection; Account lockout; Secure Wi-Fi setup HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 418 x 345 x 311.4 mm; Maximum; 418 x 398.5 x 311.4 mm 9.5 kg Temperature: 15 to 32.5*C Humidity: 30 to 70% RH
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer weight Operating environment Storage conditions	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; mac05 10.15 Catalina; mac05 11 Big Sur; mac05 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linus- imaging-and-printing) Windows, Microsoft® Windows® 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® mac05 v10.15 Catalina, mac05 v11 Big Sur; mac05 v12 Monterey; 2 GB HD; Internet required No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.com Secure Box; Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, Active FW update, Admin password by default, Cipher & TLS selection; Account lockout; Secure Wi-Fi setup HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 418 x 345 x 311.4 mm; 9.5 kg Temperature: 15 to 32.5°C Humidity: 30 to 70% RH Temperature: -20 to 60°C
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer mensions (W × D × H) Printer weight Printer weight Operating environment	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; mac05 10.15 Catalina; mac05 11 Big Sur; mac05 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linux- imaging-and-printing) Windows Microsoft® Windows® 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® macOS V10.15 Catalina, macOS V12 Monterey; 2 GB HD; Internet required No CD in box; Downloadable Software from http://Www.hp.com or http://12.hp.com Secure Borx; Secure Finware Integrity, Runtime Coel Integrity, Baxowd protected EWS, secure EWW secure Finware Integrity, Runtime Coel Integrity, Baxowd protected EWS, secure EWW secure Finware Integrity, Runtime Coel Integrity, Baxowd protected EWS, secure EWW secure EWW, secure EWW, secure EWW, secure Wi-Fi setup HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 418 x 345 x 311.4 mm; Maximum: 418 x 398.5 x 311.4 mm 9.5 kg Temperature: 15 to 60°C Acoustic power emissions: 6.3 B(A) Acoustic pressure emissions: 49 dB(A)
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; mac05 10.15 Catalina; mac05 11 Big Sur; mac05 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linus- imaging-and-printing) Windows, Microsoft® Windows® 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® mac05 v10.15 Catalina, mac05 v11 Big Sur; mac05 v12 Monterey; 2 GB HD; Internet required No CD in box; Downloadable Software from http://www.hp.com or http://123.hp.com Secure Box; Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, and SNMPv3, Community password change; Secure defaults, Encrypted data at rest, Active FW update, Admin password by default, Cipher & TLS selection; Account lockout; Secure Wi-Fi setup HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 418 x 345 x 311.4 mm; 9.5 kg Temperature: 15 to 32.5°C Humidity: 30 to 70% RH Temperature: -20 to 60°C
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Cataline; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linus- imaging-and-printing) Windows Microsoft® Windows® 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® macOS v10.15 Cataline, macOS v11 Big Sur; macOS v12 Monterey; 2 GB HD, Internet required No CD in box; Downloadable Software from http://wwh.pc.com or http://123.hp.com Secure Box; Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.2; TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, and SNMPv2, Community password change; Secure defaults, Encrypted data at rest, Active FW update, Admin password by default, Cipher & TLS selection; Account lockout; Secure Wi-Fi setup HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Minimum 418 x 345 x 311.4 mm; Maximum: 418 x 398.5 x 311.4 mm 9.5 kg Temperature: -10 to 60°C Acoustic power emissions: 6.3 B(A) Acoustic pressure emissions: 49 dB(A) Requirements: IUV -1277 vnominal @ +/-10% (min 990; max 1400); 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz); 220V - 240V nominal @ +/-10% (min 198V, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz); 220V - 240V nominal @ +/-10% (min 198V, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz); 200V - 240V nominal @ +/-10% (min 198V, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz); 220V - 240V nominal @ +/-10% (min 198V, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz); 220V - 240V nominal @ +/-10% (min 198V, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz); 220V - 240V nominal @ +/-
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer mensions (W × D × H) Printer dimensions (W × D × H) Printer weight Operating environment Storage conditions Acoustics Power ⁷	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum: Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Cataline; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linus- marging-and-printing) Windows Microsoft® Windows [®] 11, 10, 2 GB available hard disk space, Internet connection, Microsoft® Internet Explorer or Edge. Mac Apple® macOS v10.15 Catalina, macOS v12 Monterey; 2 GB HD, Internet required No CD in box; Downloadsbib Software from http://nz3.hp.com Secure Box, Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPV1, SNMPv2, and SNMPv2, community password change; Secure defaults, Encrypted data at rest, Active FW update, Admin password by default, Cipher & TLS selection; Account lockout; Secure Wi-Fi setup HP Printer Assistant (UDC); HP Device Toolbox; HP Utility (Mac) Network 114 wm; Maximum; 418 x 398.5 x 311.4 mm 3.5 kg Temperature: 15 to 32.5°C Humidity: 30 to 70% RH Temperature: 20 to 60°C Account Cover emissions: 6.3 B(A) Accountic pressure emissions: 49 dB(A) Requirements: 10.10, 12.10, 12.10, 12.2, 12.2, 20.2, -240V nominal @ +/-10% (min 198V, Max Z64V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz; Torypscal Editory Consumption (TDC): Forsy Stars: 0.194.Wh/veek; Blue Angel: 0.203.Wh/Veek; Power supply type Internal (Built-in) power supply)
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer mensions (W × D × H) Printer dimensions (W × D × H) Porating environment Storage conditions Acoustics Power ⁷ Energy savings feature technology	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency Maximum : Up to 100 sheets Windows 11; Windows 10; macOS 10.15 Catalina; macOS 11 Big Sur; macOS 12 Monterey; Linux Windows Server 2008 R2 64-bit, Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 64-bit, Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linux- imaging-and-printing) Windows Microsoft* Windows 51, 11, 10, 26 Baveliable hard disk space, Internet connection, Microsoft* Internet Explorer or Edge. Mac Apple* macOS v10.15 Catalina, macOS v11 Big Sur; macOS v12 Monterey; 2 GB HD; Internet required No CD In box; Downloadable Software from http://www.hp.com or http://123.1p.com Secure Biot, Secure Firmware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2; TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, and SNMPv3, Community password change. Secure defaults, Encrypted data at rest, Active FW update, Admin password by default; Open & TLS selection; Account lociout; Secure Wi-Fisetup HP Printer Assistant (UDC): HP Device Toolbox; HP Utility (Mac) Minimum 418 x 345 x 311.4 mm; Maximum; 418 x 398.5 x 311.4 mm 9.5 kg Temperature: 15 to 32.5°C Humidity: 30 to 70% RH Temperature: -20 to 60°C Account Dover emissions: 6.3 B(A) Acounts pressure emissions: 49 dB(A) Requirements: T10V -1271 nominal (# -110% (min 1991, max 100%), 50 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 220V - 240V nominal (# -110% (min 1980, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 220V - 240V nominal (# -110% (min 1980, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 220V - 240V nominal (# -110% (min 1980, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 220V - 240V nominal (# -110% (min 1980, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 220V - 240V nominal (# -110% (min 1980, Max 264V), 50 - 60Hz nomi
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W × D × H) Printer dimensions (M × D × H) Printer dimensions Acoustics Power ⁷ Energy savings feature technology Certifications	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency. Max/mum: Up to 100 sheets Windows 11; Windows 10; maxC5 10.15 Catallan; maxC5 11B (SurmacC5 12 Monterey; Linux Windows Server 2008 R2 64-bit; Windows Server 2008 R2 64-bit (SP1), Windows Server 2012 R2 64-bit; Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linux- maging-and-grinting) Windows Vincosoft* Windows* 11, 10, 2 GB available hard disk space, Internet connection, Microsoft* Internet Explorer or Edge. Mac Apple* maxC5 V10.15 Catallan; maxC5 V1 Bug, transC5 V1 2 Monterey; 2 GB H2, Internet connection, Microsoft* Internet Explorer or Edge. Mac Apple* maxC5 V10.15 Catallan; maxC5 V1 Bug, transC5 V1 2 Monterey; 2 GB H2, Internet explorer or Edge. Mac Apple* maxC5 V10.15 Catallan; maxC5 V1 Bug, transC5 V1 2 Monterey; 2 GB H2, Internet explorer or Edge. Mac Apple* maxC5 V10.15 Catallan; maxC5 V1 Bug, transC5 V1 2 Monterey; 2 GB H2, Internet explorer or Edge. Mac Apple* maxC5 V10.15 Catallan; maxC5 V1 Bug, transC5 V1 2 Monterey; 2 GB H2, Internet explorer or Edge. Mac Apple* maxC5 V10.15 Catallan; password hange; Secure Boxin, secure Stranspace M2, Secure Brimware Integrity, Runtime Code Integrity, password protected EWS, secure browsing via SSL/TLS 1.0, TLS 1.1, TLS 1.2, TLS 1.0/1.1 disabled by default; OpenSSL version 1.1.1; Enable/disable Network ports; SNMPv1, SNMPv2, and SNMPX3, Community Bay, Sava S11.4 mm 9 Sis Ig Temperature 15 to 32.5 °C Hunidity 30 to 70% RH Temperature - 20 to 60°C Acoustic power emissions: 6.3 B(A) Acoustic pressure emissions: 49 dB(A) Requirements 110 v-127V moninal @ +/10% (min 198V, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 220V - 240V nominal @ +/-10% (min 198V, Max 264V), 50 - 60Hz nominal +/- 3Hz (min 47Hz, max 63Hz), 220V -
Output capacity Compatible operating systems Compatible network operating systems Minimum system requirements Software included Security management Printer management Dimensions and weight Printer dimensions (W × D × H) Power ⁷ Energy savings feature technology Certifications Sustainable impact specifications ^{22, 27}	Standard: Up to 100 sheets Envelopes: Up to 10 envelope Transparencies: Does not support transparency. Maximum: Up to 100 sheets Windows 11; Windows 10; maxC5 111 Stataling; maxC5 111 Big Sur; maxC5 12 Monterey; Linux Windows Server 2008 R2 64-bit; Windows Server 2008 R2 64-bit; SP1), Windows Server 2012 R2 64-bit, Windows Server 2016 64-bit; Linux (For more information see http://developers.hp.com/hp-linux- mapping-and-printing) Windows: Microsoft* Windows* 11, 10, 2 GB available hard dak space. Internet connection, Microsoft* Internet Explorer or Edge. Max Apple* maxC5 V110 Stataling; maxC5 V11 Big Stataling; ma

Footnotes

¹ Actual yield varies considerably based on content of printed pages and other factors. Average based on ISO/IEC 19752 and continuous printing. Additional printed pages require toner reload. For details see

www.hp.com/go/learnaboutsupplies. ² When used in accordance with instructions. Average reload time based on HP internal testing.

³ Over 75% plastic reduction is calculated by comparing the weight of the plastic in HP Neverstop Laser 103/143 A/AD and HP Laser NS 108 A/AD Toner Reload Kit and its packaging.

⁴ Requires the HP Smart app download. For details on local printing requirements see http://www.hp.com/go/mobileprinting. Certain features/software are available in English language only and differ between desktop and mobile applications. Subscription may be required; subscription may not be available in all countries. See details at HPSmart.com. Internet access required and must be purchased separately. HP account required for full functionality. List of supported operating systems available in app stores.

⁵ The yield of imaging drum is approximately 50,000 single-sided pages (letter or A4 size paper). There are many factors that determine the actual drum useful life, such as temperature, humidity, type of paper, type of toner used and other variables. The imaging drum unit is replaceable through authorized service provider

⁶ Toner Reload Kit is not included with the printer; please purchase separately.

Technical specifications disclaimers

¹ Measured using ISO/IEC 24734, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity

² Measured using ISO/IEC 17629. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application, driver, and document complexity.

³ HP Auto-On/Auto-Off Technology capabilities subject to printer and settings; May require a firmware upgrade.
⁴ Requires the HP Smart app download. For details on local printing requirements see http://www.hp.com/go/mobileprinting. Certain features/software are available in English language only and differ between desktop and mobile applications. Subscription may be required; Subscription may not be available in all countries. See details at: HPSmart.com; Internet access required and must be purchased separately. HP account required for full functionality. List

of supported operating systems available in app stores. ⁵ Scan speeds measured from ADF. Actual processing speeds may vary depending on scan resolution, network conditions, computer performance, and application software.

⁶ Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device.

⁷ Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty. Energy Star value typically based on measurement of 115V device.

⁸ HP Black Original Laser Jet Tank Imaging Drum (introductory ~5,000 page black toner yield provided). For yield information included with your printer, see http://www.hp.com/go/toneryield. Yield values measured in accordance with ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. ⁹ Declared yields based on ISO/IEC 19752 and continuous printing. Actual yields vary considerably based on images printed and other factors. For details see http://www.hp.com/go/toneryield

¹⁰ Measured using ISO/IEC 24734 Feature Performance Test, excludes first set of test documents. For more information see http://www.hp.com/go/printerclaims. Exact speed varies depending on the system configuration,

software application, driver, and document complexity.

© Copyright 2025 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein. ie-en February 2025

