

OVERVIEW





1. Thunderbolt 4	5. Pen slot
2. Thunderbolt 4	6. Headphone / microphone combo jack (3.5mm)
3. USB 3.2 Gen 1	7. USB 3.2 Gen 1 (Always On)
4. HDMI 2.0	8. Kensington Nano Security Slot

Notes:

• Optional nano-SIM card slot on the right side (not shown on the sample product above)



PERFORMANCE

Processor

Processor Family

11th Generation Intel® Core™ i5 / i7 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Core i5-1135G7	4	8	2.4GHz	4.2GHz	8MB	LPDDR4x-4266	Intel Iris® Xe Graphics
Core i5-1145G7	4	8	2.6GHz	4.4GHz	8MB	LPDDR4x-4266	Intel Iris Xe Graphics
Core i7-1165G7	4	8	2.8GHz	4.7GHz	12MB	LPDDR4x-4266	Intel Iris Xe Graphics
Core i7-1185G7	4	8	3.0GHz	4.8GHz	12MB	LPDDR4x-4266	Intel Iris Xe Graphics

Operating System

Operating System**

- Windows® 11 Pro 64
- Windows 11 Home 64
- Windows 11 DG Windows 10 Pro 64
- Windows 10 Pro 64
- Windows 10 Home 64
- Linux
- Ubuntu Linux
- · No operating system

Graphics

Graphics

Graphics	Туре	Memory	Key Features	
Intel Iris Xe Graphics	Integrated	Shared	DirectX® 12	

Monitor Support

Monitor Support[1]

Supports up to 4 independent displays (native display and 3 external monitors via Thunderbolt™ and HDMI®)

- Thunderbolt supports up to 5K@60Hz
- HDMI supports up to 4K@60Hz

Notes

1. Refresh rates >60hz also supported, however max resolution will be limited.

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory^[1]

- 8GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable
- 32GB soldered memory, not upgradable

Memory Slots

Memory soldered to systemboard, no slots, 8-channel

Memory Type

LPDDR4x-4266

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.



Storage

Storage Support

One drive, up to 2TB M.2 2280 SSD

Storage Slot

One M.2 2280 PCIe[®] Gen 4x4 slot, supports M.2 2280 SSD

Storage Type**

Disk Type	Interface	Offering	Security
M.2 2280 SSD	PCIe NVMe®, PCIe x4	-	Opal2
M.2 2280 SSD	PCIe NVMe, PCIe 4.0 x4 Performance	-	Opal2

Removable Storage

Optical

None

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3306 codec

Speakers

Stereo speakers, 2W x2 and 0.8W x2, Dolby® Atmos®

Microphone

Four array microphones, 360° far-field, Dolby Voice

Camera**

- 720p, with privacy shutter, fixed focus
- IR & 720p hybrid, with privacy shutter, fixed focus

Sensor

Sensors

- · Accelerometer (G) sensor
- · Proximity (P) sensor

Battery

Battery

Integrated Li-Polymer 57Wh battery, supports Rapid Charge (charge up to 80% in 1hr) with 65W AC adapter

Max Battery Life[1]

MobileMark® 2014: 21.0 hr MobileMark 2018: 16.1 hr JEITA 2.0: 23.9 hr

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**

- 45W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 45W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C slim (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz



• 65W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz

DESIGN

Display

Display**[1]

Size	Resolution	Touch	Туре	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
14.0"	WUXGA (1920x1200)	Multi- touch	IPS	400 nits	Anti-glare	16:10	1000:1	100% sRGB	170°	Low power, low blue light
14.0"	WUXGA (1920x1200)	Multi- touch	IPS	400 nits	Anti- reflection, Anti-smudge	16:10	1000:1	100% sRGB	170°	Low power, low blue light
14.0"	WUXGA (1920x1200)	Multi- touch	IPS	500 nits	Anti-glare	16:10	1000:1	100% sRGB	170°	Low power, ThinkPad® Privacy Guard
14.0"	WQUXGA (3840x2400)	Multi- touch	IPS	500 nits	Anti- reflection, Anti-smudge	16:10	1500:1	100% DCI-P3	170°	Low blue light, HDR 400

Touchscreen

Capacitive-type on-cell multi-touch, supports 10-point touch

Notes:

1. California Electronic Waste Recycling Fee

In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product. For more information, go to https://www.calrecycle.ca.gov/Electronics/Consumer

Multi-mode

Multi-mode

Laptop, tent, stand, and tablet modes supported by 360° hinge

Input Device

. ...

ThinkPad Pen Pro - 10 for X1 Yoga® Gen 6, with built-in rechargeable battery, 4096 levels of pressure sensitivity, on-board garaged and rechargeable

Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

Keyboard Backlight

LED backlight

UltraNav™

TrackPoint® pointing device and glass surface multi-touch touchpad

Mechanical

Dimensions (WxDxH)

	Models	Dimensions
1	All models	314.4 x 223 x 14.99 mm (12.38 x 8.78 x 0.59 inches)

Weight

Models	Weight				
All models	1.399 kg (3 lbs)				

Case Color

Storm grey

Case Material



Aluminium (top), aluminium (bottom)

Notes:

1. The system weight varies depending on configurations.

CONNECTIVITY

Network

Onboard Ethernet

Ethernet support via optional Lenovo USB-C to Ethernet Adapter

WLAN + Bluetooth®[1]

Intel Wi-Fi® 6 AX201, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2

WWAN**

- Integrated Mobile Broadband 4G LTE, Quectel EM120R-GL, M.2 card, with embedded eSIM functionality
- Qualcomm® Snapdragon™ X55 5G Modem M.2 card RF System with embedded eSIM functionality
- · No support

SIM Card

No SIM card inbox

NFC

- Near Field Communication
- No support

Notes:

1. Intel Wi-Fi 6 full features might be limited by country level restrictions. Bluetooth 5.2 is supported with driver version 22.30 and later.

Ports⁽¹⁾

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 2x Thunderbolt 4 / USB4[™] 40Gbps (support data transfer, Power Delivery 3.0 and DisplayPort[™] 1.4a)
- 1x HDMI 2.0
- 1x Headphone / microphone combo jack (3.5mm)

Optional Ports

1x Nano-SIM card slot (WWAN model)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

Thunderbolt 3: 40 Gbit/s; FireWire 400: 400 Mbit/s:

FireWire 800: 800 Mbit/s

Docking

Docking

Various docking solutions supported via Thunderbolt.

For more compatible docking solutions, please visit Docking for ThinkPad X1 Yoga Gen 6

Monitor Cable

Monitor Cable

- Lenovo HDMI to VGA Monitor Adapter
- No monitor cable

SECURITY & PRIVACY



Security

Security Chip**

- · Discrete TPM 2.0, TCG certified
- Firmware TPM 2.0 integrated in chipset
- Disabled (in some regions)

Physical Locks

Kensington® Nano Security Slot

Smart Card Reader

No smart card reader

Fingerprint Reader

Touch style fingerprint reader on power button, match-on-chip

BIOS Security

- · Power-on password
- · Supervisor password
- NVMe password
- Self-healing BIOS

Other Security

- · Camera privacy shutter
- (Optional) IR camera for Windows Hello
- (Optional) Privacy Guard with Privacy Alert
- (Optional) Human Presence Detection

MANAGEABILITY

System Management

System Management

- · Intel vPro Technology, DASH
- None

SERVICE

Warranty

Base Warranty**[2]

- 1-year depot service
- 1-year depot with 2-year system board service
- 1-year limited onsite service
- 1-year + 2-year depot service
- 1-year + 2-year limited onsite service
- 3-year (1-yr battery) depot service
- 3-year (1-yr battery) limited onsite service
- · No base warranty

Notes:

- 1. More information of warranty policy, please access https://pcsupport.lenovo.com/warranty
- 2. No base warranty is for special bid only.

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Humidity

ThinkPad X1 Yoga Gen 6



- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10° C (50° F).

ACCESSORIES

Bundled Accessories

Bundled Accessories

- Lenovo USB-C to Ethernet Adapter
- None

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Gold
- ENERGY STAR® 8.0
- TCO Certified
- · RoHS compliant

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

Other Certifications

- (Optional) Intel Evo™ Platform
- (Optional) TÜV Rheinland® Low Blue Light
- TÜV Rheinland Dynamic Privacy Filter (DPF) Certification
- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.



