

## Key **Features**

- Lifelike True Beauty: International color standard Pantone validated and 100% sRGB wide color gamut
- Precise Color: ColorPro Verified with prefactory calibration for overwhelmed Delta E <</li>
   2 color accuracy
- Multimedia Devices: Support USB-C with 60W high-speed charging, plus HDMI 1.4, DisplayPort 1.2a, USB3.2
- Unlimited Flexibility: Auto Pivot &
   Ergonomic Stand with tilt, swivel, pivot, and
   height adjustments
- The Visible Difference: 4K UHD(3840\* 2160) resolution IPS panel with 32" frameless design



## Product **Description**

Designed with creative professionals in mind, the ViewSonic VP3256-4K delivers stunning true-to-life colors on screen. Pantone validated 100% sRGB coverage provides precise color reproduction, ensuring your work looks how it should, every time. A USB-C port that easily connects with your devices for easy charging and data transfer. Ergonomic engineering gives you the flexibility to do more without injury, while Auto Pivot lets shift between horizontal and vertical orientations effortlessly, letting your work be viewed how it's supposed to be.

Visit Us www.viewsonic.com

DISPLAY  Display Size (in.):	32	WALL MOUNT VESA Compatible:	100 x 100 mm
Viewable Area (in.):	31.5	INPUT SIGNAL	100 X 100 IIIII
Panel Type:	IPS Technology	Frequency Horizontal:	15 ~ 136KHz
Resolution:	3840 x 2160	Frequency Vertical:	24 ~ 75Hz
	UHD	VIDEO INPUT	2
Resolution Type:		VIDEO IIII OT	TMDS - HDMI (v2.0), PCI-E -
Static Contrast Ratio:	1,000:1 (typ)	Digital Sync:	DisplayPort (v1.4), Micro-Packet - Type C
Dynamic Contrast Ratio:	20M:1	ERGONOMICS	1,466.0
Light Source:	LED	Height Adjust (mm):	130
Brightness:	350 cd/m² (typ)	Swivel:	120°
Colors:	1.07B	Tilt (Forward/Back):	-5° / 21°
Color Space Support:	10 bit (8 bit + A-FRC)	Pivot (Right/Left):	90° / 90°
Aspect Ratio:	16:9	WEIGHT (IMPERIAL)	90 7 90
Response Time (Typical GTG):	5ms	Net (lbs):	24
Response Time (GTG w/OD):	5ms	Net Without Stand (lbs):	15.8
Viewing Angles:	178º horizontal, 178º vertical		33.7
Backlight Life (Hours):	30000 Hrs (Min)	Gross (lbs): WEIGHT (METRIC)	33.7
Curvature:	Flat	` '	10.9
Refresh Rate (Hz):	60	Net (kg):	7.2
Adaptive Sync:	Yes	Net Without Stand (kg):	
Blue Light Filter:	Yes	Gross (kg):	15.3
Flicker-Free:	Yes	DIMENSIONS (IMPERIAL) (	•
	Adobe RGB: 95% size / 82%	Packaging (in.):	33.1 x 20.5 x 12.8
Color Gamut:	coverage (Typ)DCI-P3: 95% size / 90% coverage (Typ)EBU: 127% size / 100% coverage (Typ)REC709: 128% size / 100% coverage (Typ)SMPTE-C: 139% size / 100% coverage (Typ)NTSC: 91% size (Typ)SRGB:	Physical (in.):	28.2 x 20.23~25.35 x 10.4
		Physical Without Stand (in.):	28.2 x 16.7 x 2.6
		DIMENSIONS (METRIC) (W	·
	128% size / 100% coverage (Typ)	Packaging (mm):	840 x 520 x 326
Pixel Size:	0.182 mm (H) x 0.182 mm (V)	Physical (mm):	715 x 513.8~643.8 x 265
Surface Treatment:	Anti-Glare, Hard Coating (3H)	Physical Without Stand (mm):	715 x 423 x 66
COMPATIBILITY		GENERAL	
PC Resolution (max):	3840x2160	Regulations:	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy, CE, CE EMC, CB, RoHS, ErP, REACH, WEEE, EAC, UKrSEPRO, UKCA, CCC, China
Mac® Resolution (max):  PC Operating System:	3840x2160 Windows 7/8/8.1/10 certified; macOS		
To Operating dystem.	tested		RoHS, China Energy Label
Mac® Resolution (min):	3840x2160		VP3256-4K x1, 3-pin Plug (IEC C13 CEE22) x1, HDMI Cable (v2.0; Male
CONNECTOR		PACKAGE CONTENTS:	Male) x1, DisplayPort Cable (v1.2; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start
USB 3.2 Type A Down Stream:	2		
USB 3.2 Type B Up Stream:	1		Guide x1
USB 3.2 Type C Up Stream; DisplayPort Alt mode :	1	Recycle/Disposal:	Please dispose of in accordance wit local, state or federal laws.
HDMI 2.0 (with HDCP 2.2):	2	Warranty:	*Warranty offered may differ from market to market
DisplayPort:	1	Power Management:	Energy Star standards, EPEAT
Power in:	3-pin Socket (IEC C14 / CEE22)	r oner management.	znongy otal otaliaanao, zn znin
AUDIO			
Internal Speakers:	3Watts x2		
POWER			
Eco Mode (Conserve):	32W		
Eco Mode (optimized):	39W		
Consumption (typical):	46W		
Consumption (max):	50W		
Voltage:	AC 100-240V		
Stand-by:	0.5W		
Power Supply:	Internal Power Supply		
ADDITIONAL HARDWARE			
Kensington Lock Slot:	1		
Cable Organization:	Yes		
CONTROLS			
Physical Controls:	Key 1, Key 2, Key 3, Key 4, Key 5, Key 6 (power)		
On Screen Display:	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu		
OPERATING CONDITIONS			
Temperature:	32°F to 104°F (0°C to 40°C)		
Humidity (non-condensing):	20% to 90%		

Copyright © ViewSonic Corporation 2000-2021. All rights reserved.

Humidity (non-condensing):

20% to 90%