Fujitsu recommends Windows 11 Pro.



Data Sheet FUJITSU Desktop ESPRIMO G5011

Mini, Mighty | Takes up your challenges, not your space

The FUJITSU ESPRIMO G5011 is a stylish mini PC which offers desktop functionality in an ultracompact, space-saving design. Latest Intel chipset along with 10th or the latest 11th Gen Intel® Core™ processors provides the performance for daily office needs. It supports flexible mounting options - attach to displays, wall mount, under table mount. Its compact size and wide range of interfaces make it an ideal device where space saving is critical for the business.

A stylish mini PC with ultra-compact design

Small footprint; energy and space-saving device for clean, clutter-free desk

- Fully equipped PC with a volume of only ~0.86 liters
- Impressive performance/volume ratio and is easy to set up in minutes

Ultimate usability

Flexible mounting options and wide range of usage scenarios

- Can be used for horizontal or vertical operations and easy upgrade of major components
- VESA mount for attaching the PC to displays, stands or walls

Small yet grand

High performance in a small mini PC design

- Latest Intel chipset technology along with 10th or the latest 11th generation Intel® Core™ processor family
- Legacy support for standard mini PC interfaces DisplayPort, HDMI

Perfect fit for modern offices and workplaces of tomorrow

The PC which can transform your workplace for the next generation

- Supports new workplace scenarios with a single Type-C connection
- Type-C docking port for future workplace and AiO-like usage

Feature-rich and energy-efficient

Do a lot more with this mini-PC and also get lesser energy bill

- Improved energy efficiency
- Next generation INTEL integrated graphics
- Type-C connector with convenient front access to support modern peripherals like Type-C USB sticks or headsets















Components

	ESPRIMO G5011	ESPRIMO G5011 ESTAR
Processor	Intel® Core™ i7-11700T processor (8 Cores / 16 Threads, 1.40 GHz, 16 MB, Intel® UHD Graphics 750) ** Intel® Core™ i7-10700T processor (8 Cores / 16 Threads, 2.00 GHz, 16 MB, Intel® UHD Graphics 630) ** Intel® Core™ i5-11500T processor (6 Cores / 12 Threads, 1.50 GHz, 12 MB, Intel® UHD Graphics 750) * Intel® Core™ i5-10600T processor (6 Cores / 12 Threads, 2.40 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-10500T processor (6 Cores / 12 Threads, 2.30 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-10400T processor (6 Cores / 12 Threads, 2.00 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i3-10105 processor (4 Cores / 8 Threads, 3.70 GHz, 6 MB, Intel® UHD Graphics 630) * Intel® Pentium® Gold G6400 (2 Cores / 4 Threads, 4.00 GHz, 4 MB, Intel® UHD Graphics 610) *with Intel® Turbo Boost Technology 2.0 (clock speed and	Intel® Core™ i7-11700T processor (8 Cores / 16 Threads, 1.40 GHz, 16 MB, Intel® UHD Graphics 750) ** Intel® Core™ i7-10700T processor (8 Cores / 16 Threads, 2.00 GHz, 16 MB, Intel® UHD Graphics 630) ** Intel® Core™ i5-11500T processor (6 Cores / 12 Threads, 1.50 GHz, 12 MB, Intel® UHD Graphics 750) * Intel® Core™ i5-10600T processor (6 Cores / 12 Threads, 2.40 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-10500T processor (6 Cores / 12 Threads, 2.30 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i5-10400T processor (6 Cores / 12 Threads, 2.00 GHz, 12 MB, Intel® UHD Graphics 630) * Intel® Core™ i3-10105 processor (4 Cores / 8 Threads, 3.70 GHz, 6 MB, Intel® UHD Graphics 630) *
	variables) **with Intel® Turbo Boost Max Technology 3.0 (clock speed other variables)	
Operating systems		
Operating system pre-installed	Windows 11 Pro. Fujitsu recommends Windows 11 Pro for business. Windows 11 Home Windows 10 Pro	
Operating system compatible	FREE Upgrade to Windows 11* *Upgrade timing may vary by device. Features and app availability may vary by region. Certain features require specif hardware (see aka.ms/windows11-spec).	
Operating system notes	After the end of the product life Fujitsu will continue to test and support all upcoming Windows releases for a period of maximum 5 years, depending on the available extension of hardware services through Fujitsu Warranty top ups. F details please see "Fujitsu Service Statement for Windows General Availability Channel" at https://support.ts.fujitsu.com/IndexProdSupport.asp?Ing=com&OpenTab=	
	ESPRIMO G5011	ESPRIMO G5011 ESTAR
Memory modules	32 GB (module(s) 32 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 16 GB (module(s) 16 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 8 GB (module(s) 8 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 4 GB (module(s) 4 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM	32 GB (module(s) 32 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 16 GB (module(s) 16 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 8 GB (module(s) 8 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM 4 GB (module(s) 4 GB) DDR4, unbuffered, non-ECC, 3,200 MT/s, SO DIMM
	ESPRIMO G5011	ESPRIMO G5011 ESTAR
Graphics		
	ESPRIMO G5011	ESPRIMO G5011 ESTAR
Mass storage 2.5 inch size	HDD SATA III, 5,400 rpm, 2000 GB, 2.5-inch	HDD SATA III, 5,400 rpm, 2000 GB, 2.5-inch
Mass Storage M.2 technology	SSD PCIe, 1024 GB M.2 NVMe module (Gen4), SED SSD PCIe, 128 GB M.2 NVMe module (Value) SSD PCIe, 256 GB M.2 NVMe module (Gen4), SED SSD PCIe, 256 GB M.2 NVMe module (Value) SSD PCIe, 512 GB M.2 NVMe module (Gen4), SED SSD PCIe, 512 GB M.2 NVMe module (Value)	SSD PCle, 1024 GB M.2 NVMe module (Gen4), SED SSD PCle, 128 GB M.2 NVMe module (Value) SSD PCle, 256 GB M.2 NVMe module (Gen4), SED SSD PCle, 256 GB M.2 NVMe module (Value) SSD PCle, 512 GB M.2 NVMe module (Gen4), SED SSD PCle, 512 GB M.2 NVMe module (Value)
Hard disk notes	One Gigabyte equals one billion bytes, when referring to h SSD (Solid State Disk) SED (Self-Encrypting Drive) 2.5-inch bay for devices with 7mm height	nard disk drive capacity.

	ESPRIMO G5011	ESPRIMO G5011 ESTAR
Optical drive		
	ESPRIMO G5011	ESPRIMO G5011 ESTAR
Interfaces add on cards / components	Intel® WI-FI 6 AX210 and Bluetooth 5.2 vPro, SRD 5.8GHz (dedicated regions only)	Intel® WI-FI 6 AX210 and Bluetooth 5.2 vPro, SRD 5.8GHz (dedicated regions only)
	ESPRIMO G5011	ESPRIMO G5011 ESTAR
Component notes	The listed product components and optional functions are not available in all region/countries	The listed product components and optional functions are not available in all region/countries; Energy Star certification only with Windows operating system base unit for TCO Certified generation 9

Base unit

Base unit	ESPRIMO G5011	ESPRIMO G5011 ESTAR
Mainboard		
Mainboard type	D3904	
Formfactor	proprietary	
Chipset	Intel® H510	
Processor socket	LGA 1200	
Processor quantity maximum	1	
Supported capacity RAM (max.)	64 GB	
Memory slots	2 DIMM (DDR4)	
Memory frequency	3,200 MT/s	
Memory notes		ory modules have to be ordered. Capacity per channel has to be the same. 33/2400MHz depending on processor and memory configuration
LAN	10/100/1,000 MBit/s Realtek RTL8111H	
Integrated WLAN	optional; WLAN 802.11ax/Wi-Fi 6 and B	luetooth 5.2
BIOS version	AMI Aptio V UEFI Specification 2.6	
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (I	UEFI)
Audio type	On board	
Audio codec	Realtek ALC623	
Audio features	Internal speaker supports audio playba	ack, High Definition audio
I/O controller on board		
Serial ATA total	1	
thereof SATA III	1	
Controller functions	Serial ATA III (6 Gbit) NCQ AHCI	
Interfaces		
Front audio: headset	1	
USB 2.0 total	3	
USB 3.2 Gen1 (5 Gbps) total	4	
USB front	1x USB 3.2 Gen 1 1x USB 3.2 Gen 1 Type-C (provides up to	o 15W)

Interfaces			
USB rear	3x USB 2.0		
	1x USB 3.2 Gen 1		
	1x USB 3.2 Gen 1 Type-C (supports DisplayPort 1.4 and inc	cl. 60W power delivery sink support e.g. from a display)	
VGA	optional: via external active adapter cable		
DisplayPort	1		
HDMI	1		
Ethernet (RJ-45)	1		
Interface Module notes	Anytime USB charge functionality, HDMI Ver. 1.4 (with 11t	h generation CPUs: Ver. 2.0)	
Kensington Lock support	1		
Input device / components			
Input devices (optional)	Keyboard Mouse		
Drive bays			
Drive bays total	1		
2.5-inch internal bays	1		
M.2-2280	1 x on mainboard for SSD NVMe (PCle 3.0 x4; up to 32Gbit	t/s)	
Mini PCI slots			
M.2-2230	on mainboard for WLAN module		
Graphics on board		IIID Carabias (10 Intel® IIIID Carabias (20	
Graphics brand name	Intel® UHD Graphics 730, Intel® UHD Graphics 750, Intel® UHD Graphics 610, Intel® UHD Graphics 630		
Shared video memory		Up to half size of total system memory	
TFT resolution (DisplayPort)	Up to 4,096 x 2,304 pixel		
TFT resolution (HDMI) Graphics features	up to 4,096 x 2,160 Dual display support		
	DirectX® 12 HDCP support OpenCL™ 2.1 OpenGL® 4.5 DisplayPort interface supports Ver. 1.4 incl. Multi-Stream Digital audio formats are supported, including Dolby Digit USB Type-C™ (supports DisplayPort™ 1.4 and power deliver.)		
Graphics notes	up to 1 GB dedicated video memory (main memory owned and locked for graphics use) Tested resolutions, depending on display type additional resolutions and frequencies possible Shared memory depending on main memory size and operating system Resolution (color depth up to 32 Bit/pixel) For TFT we recommend using 60Hz		
Base unit	ESPRIMO G5011	ESPRIMO G5011 ESTAR	
Electrical values			
Power efficiency note	nower supply efficiency at 115/230V/ 80% average efficien	ncv	
Rated voltage range	power supply efficiency at 115/230V: 89% average efficiency 100 V - 240 V		
Rated frequency range	50 Hz - 60 Hz		
Operating voltage range	90 V - 264 V		
	90 V - 204 V 47 Hz - 63 Hz		
Operating line frequency range Max. output of single power supply	47 HZ - 63 HZ 65 W		
max. output of single power supply	۷۷ دن		
Base unit	ESPRIMO G5011	ESPRIMO G5011 ESTAR	
Power consumption			
	ESPRIMO G5011 See white paper Energy Consumption	ESPRIMO G5011 ESTAR See white paper Energy Consumption	
Power consumption Power consumption note			
Power consumption	See white paper Energy Consumption https://docs.ts.fujitsu.com/dl.aspx?id=9a164a82-6707-		

Noise emission		
Noise emission Standard noise emission	According to ISO 7779:2010, ECMA-74	According to ISO 7779:2010, ECMA-74
Standard noise notes / description	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))	A-weighted sound power level Lwad (in B) / Workplace related A-weighted sound pressure level LpAm (in dB(A))
Standard noise operation mode: CPU 50% load	- · · · · · · · · · · · · · · · · · · ·	3.1 B / 18 dB(A) Bystander; 20 dB(A) Operator position (SSD M.2)
Standard noise operation mode: HDD load	3.2 B / 20 dB(A) Bystander; 21 dB(A) Operator position (SSD M.2)	3.2 B / 20 dB(A) Bystander; 21 dB(A) Operator position (SSD M.2)
Standard noise operation mode: Idle mode	3.0 B / 17 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)	3.0 B / 17 dB(A) Bystander; 18 dB(A) Operator position (SSD M.2)
Standard noise operation mode: Office applications 2.0	3.0 B / 18 dB(A) Bystander; 19 dB(A) Operator position (SSD M.2)	3.0 B / 18 dB(A) Bystander; 19 dB(A) Operator position (SSD M.2)
Dimensions / Weight / Environmental		
Dimensions (W x D x H)	146.9 x 164.5 x 36 mm	
	5.78 x 6.48 x 1.42 inch	
Operating position	Vertical / horizontal (feet included)	
VESA mount	optional mounting kit	
Weight	0.8 kg	
Weight (lbs)	1.76 lbs	
Weight notes	Actual weight may vary depending on configuration	
Operating ambient temperature	10 - 35 °C (50 - 95 °F)	
Operating relative humidity	5 - 85 % (relative humidity)	
Compliance		
Product	ESPRIMO G5011	ESPRIMO G5011 ESTAR
Model	TCS5	
Germany	GS TÜV NRTL	
Europe	CE	
Global	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)	RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL) ENERGY STAR® 8.0 EPEAT® Silver (dedicated regions) TCO Certified 9.0
Compliance link	https://sp.ts.fujitsu.com/sites/certificates	
Additional Software		
Additional software (preinstalled)	McAfee® LiveSafe™ (provides award-winning antivirus protection for your PC and much more. 30 days trial pre- installed) Microsoft Office (1 month trial for new Microsoft® Office 365 customers. Buy Microsoft Office.)	
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) CyberLink PowerDVD BD (playback software for Blu-ray Disc™) CyberLink PowerDVD DVD (playback software for DVD) Nero Essentials XL Microsoft® Office Professional 2021 Microsoft® Office Home and Business 2021 (Need to buy license to activate the pre-installed Microsoft Office. Purchase and activation only in the region in which it was acquired.)	
Base unit	ESPRIMO G5011	ESPRIMO G5011 ESTAR
Security		
Physical Security	Kensington Lock support	Kensington Lock support

Page 5 / 9 www.fujitsu.com/emeia/ESPRIMO

Security	5 1 11 1 · · · · · (TDM 2 0)	5 1 11 1 3 (TDM 2.0)
System and BIOS Security	Embedded security (TPM 2.0) EraseDisk	Embedded security (TPM 2.0) EraseDisk
	Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby ready (for configurations with Gen4 NVMe SSD and w/o PCIe cards)	Credential Guard Ready and Device Guard Capable (requires 8 GB or more system RAM and SSD PCIe NVME) Modern Standby ready (for configurations with Gen4 NVMe SSD and w/o PCIe cards)
	Write protect option for the Flash EPROM	Write protect option for the Flash EPROM
	Control of all USB interfaces	Control of all USB interfaces
	External USB ports can be disabled separately Control of external interfaces	External USB ports can be disabled separately Control of external interfaces
User Security	User and supervisor BIOS password	User and supervisor BIOS password
,	Hard disk password	Hard disk password
	Access protection via external SmartCard reader (optional)	
	AuthConductor Client Basic (secure authentication solution)	AuthConductor Client Basic (secure authentication solution)
Manageability		·
Manageability technology	DeskUpdate Driver management	
	PXE 2.1 Boot code Wake up from S5 (off mode)	
	WoL (Wake on LAN)	
Manageability software	DeskView Client	
DeskView components	DeskView Instant BIOS Management BIOS Management incl. Security	
Deskview components	Inventory Management	
	Driver Management	
	Alarm Management	
Supported standards	DMI (Desktop Management Interface)	
	SMBIOS (System Management BIOS) PXE (Preboot Execution Environment)	
	WMI (Windows Management Instrumentation)	
	WBEM (Web Based Enterprise Management)	
	CIM (Common Information Model)	
Manageability link	http://www.fujitsu.com/fts/manageability	
Miscellaneous		
	Keyboard on (Special Fujitsu keyboard required) Keyboard on with one key (KBPX Eco, KB521) Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special	Keyboard on (Special Fujitsu keyboard required) Keyboard on with one key (KBPX Eco, KB521) Keyboard on with 2 keys (CTRL+CTRL) with PS2 or special
	USB keyboards	USB keyboards
	Keyboard on with any key (USB)	Keyboard on with any key (USB)
	Thermal management	Thermal management
	Extended lifetime	Extended lifetime
Accessories information	Further helpful options	Further helpful options
	Desktop Accessories:	Desktop Accessories:
	http://www.fujitsu.com/global/products/computing/	http://www.fujitsu.com/global/products/computing/
	peripheral/accessories/desktop/ http://www.fujitsu.com/global/products/computing/	peripheral/accessories/desktop/ http://www.fujitsu.com/global/products/computing/
	peripheral/accessories/connectivity/	peripheral/accessories/connectivity/
	Stands and Mounting kits:	Stands and Mounting kits:
	http://www.fujitsu.com/global/products/computing/	http://www.fujitsu.com/global/products/computing/
	peripheral/accessories/desktop/ums/index.html	peripheral/accessories/desktop/ums/index.html
	Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/ Publications/public/pos-connectivity.pdf	Available Adapters: http://globalsp.ts.fujitsu.com/dmsp/ Publications/public/pos-connectivity.pdf
Packaging information		
Packaging dimension (mm)	395 x 197 x 288 mm	395 x 197 x 288 mm
Packaging dimension (inch)	15.55 x 7.76 x 11.34 inch	15.55 x 7.76 x 11.34 inch
Max. quantity / pallet	72	72
Material - Weight (g) Carton	650 g	650 g

Packaging information		
Material - Weight (lbs) Carton	1.43 lbs	1.43 lbs
Material - Weight (g) PE	80 g	80 g
Material - Weight (lbs) PE	0.18 lbs	0.18 lbs
Packaging notes	If keyboard is included in packaging: 1.)packaging dimension is increasing to: 497 x 206 x 293mm / (19.6 x 8.11 x 11.5 inch); 2.) material weight of carton will increase to 850g; 3.) max. quantity/pallet = 42; printed user documentation is bleached in chlorin free process; Bulk packaging for projects (optional)	If keyboard is included in packaging: 1.)packaging dimension is increasing to: 497 x 206 x 293mm / (19.6 x 8.11 x 11.5 inch); 2.) material weight of carton will increase to 850g; 3.) max. quantity/pallet = 42; printed user documentation is bleached in chlorin free process; Bulk packaging for projects (optional)
Warranty		
Warranty period	1 year	
Warranty type	Bring-In / Onsite Service (depending on country)	
Warranty Terms & Conditions	http://www.fujitsu.com/warranty	
Digital bug fixes	Subject to availability and following their generic release for the product, bug fixes and function-preserving patches fo product-related software (firmware) can be downloaded from the technical support at: https://support.ts.fujitsu.com/free of charge by entering the respective product serial number. For application software supplied together with the product, please directly refer to the support websites of the respective software manufacturer.	
Product Support Services - the perfe	ect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day	
Spare Parts availability	5 years	
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-	services/

Recommended Accessories

DisplayPort to DisplayPort 1.4 Cable



The Fujitsu DisplayPort to DisplayPort Cable connects your system with your display offering you an ultra high resolution graphics connection up to (8K UHD (7.680 × 4.320 Pixel) @ 60 Hz).

Order Code: S26391-F6055-L219

HDMI to HDMI Cable



The Fujitsu HDMI to HDMI Cable connects your display with your system or Order Code: Port Replicator.

S26391-F6055-L230

USB Type-C to USB Type-A Adapter



The FUJITSU USB Type-C to USB Type-A Adapter allows you to connect Accessories with an USB Type-A interface with your system.

Order Code: S26391-F6058-L100

USB-C Cable 5A Gen2



The FUJITSU USB-C Cable 5A Gen2 allows you to connect Accessories with Order Code: an USB Type-C interface with your system.

S26391-F6058-L101

USB-C to HDMI2.0 Adapter



The FUJITSU USB-C to HDMI2.0 Adapter enables the connection of HDMI displays to systems providing an alternate mode based USB-C interface.

Order Code: S26391-F6058-L130 USB Type-C to DisplayPort Adapter



The FUJITSU USB Type-C to DP Adapter offers a fast and easy way to connect a DisplayPort-display to your mobile system, or desktop PC, using S26391-F6058-L201 the USB Type-C port via plug-and-play functionality

Order Code:

USB Type-C to VGA Adapter



The FUJITSU USB Type-C to VGA Adapter offers a fast and easy way to connect an analog VGA-display or projector to your mobile system, or desktop PC, using the USB Type-C port via plug-and-play functionality Order Code: S26391-F6058-L203

Wireless Keyboard Set LX410



The Wireless Keyboard Set LX410 is an excellent desktop solution for users with ambition. This durable keyboard set is equipped with 2.4 GHz technology and plug and play technology. The elegant mouse with new silent keys works on many surfaces due to its precise 1600 dpi sensor. It offers fabulous features and an ultra slim, portable design.

S26381-K410-L4** (**: country specific variation)

More information

Fujitsu products, solutions & services

In addition to FUJITSU Desktop ESPRIMO G5011, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/computing/

Software www.fujitsu.com/software/

More information

Learn more about FUJITSU Desktop ESPRIMO G5011, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/ESPRIMO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.

Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2022-04-01 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2020 Fujitsu Technology Solutions GmbH