

Product datasheet

Specifications



NetShelter SX 48U 1200mm Deep Split Feed Through Side Panels Black Qty 2

AR7314

EAN Code: 0731304287971

Main

Provided equipment	Brush strips Installation guide Key(s) Slam latches
Product or component type	Side panel

Physical

Colour	Black
Height	966 mm
Width	1097 mm
Depth	14 mm
Product weight	25 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable
Marking	18 gauge side panels

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	104.8 cm
Package 1 Width	17.2 cm
Package 1 Length	117.8 cm
Package 1 Weight	29 kg

Logistical informations

Country of origin	CN
-------------------	----

Contractual warranty

Warranty (in months)	24
----------------------	----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	102 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	97 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	95
End of life manual availability	No need of specific recycling operations
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins