

## SYSTEM

### XPC all-in-one

# P9200PA Black

P92U, 8 GB RAM, 250 GB SSD, with OS

### 19.5" ALL-IN-ONE PC FOR POS, POI AND KIOSK APPLICATIONS

The Shuttle XPC all-in-one P9200PA is a fully configured All-in-One PC with Windows 10 and capacitive 19.5" touchscreen. An Intel Ultra-Low-Voltage (ULV) processor makes for high computing power while it keeps energy consumption at a low level. Thanks to its passive cooling, the system is virtually noiseless, maintenance-free and approved for 24/7 nonstop operation. Particularly suitable for vertical applications is the arrangement of connectors at the bottom and the IP54 compliant front panel which is dust-protected and protected from splashing of water.



#### COMMON FEATURES

- IP54 compliant front panel ■ Dimensions: 487 x 321 x 44 mm (WHD)
- Supports 24/7 Nonstop Operation ■ 100 mm VESA mount capable
- Operating temperature: 0~40 °C ■ Fanless heatpipe cooling system

#### DISPLAY & GRAPHICS

- 49.5 cm (19.5") LC Display, 1600 x 900 pixel ■ Capacitive 10-point multi-touch ■ Integrated Intel UHD 610 graphics ■ HDMI 1.4 & VGA

#### OPERATING SYSTEM

- Windows 10 IoT Enterprise Entry (64-bit)

#### PROCESSOR

- Intel Celeron 5205U "Comet Lake-U" Dual Core, TDP: 15W

#### STORAGE

- 8 GB DDR4 SO-DIMM ■ 250 GB M.2-2280 SSD (PCIe/NVMe)
- Supports one 2.5" SATA hard disk / SSD
- Supports internal USB stick (USB 2.0, type A)

#### CONNECTIVITY

- HDMI 1.4 ■ D-Sub/VGA ■ 4x USB 3.2 Gen 1 ■ 2x USB 2.0 ■ internal: 1x USB 2.0 (Type A) ■ 2x Audio (Mic & headphones) ■ Gigabit LAN (Intel)

#### BUILT-IN

- SD card reader ■ 2.0 Megapixel FHD webcam ■ 2x 2 W speakers
- Electret Condenser Microphone ■ Wireless LAN 802.11ac, BT 4.2

#### POWER SUPPLY

- External 65W / 19V power adapter

#### OPTIONAL ACCESSORIES

- PCL71: 2x COM, 1x LPT
- POS01: 4x COM (2x D-Sub, 2x RJ45), LPT, RJ11



#### FIXED CONFIGURATIONS OF THE P92U SERIES

Product	Type	Intel ULV CPU	RAM	M.2 SSD	Accessory	OS	Bar Code
<b>P92U</b>	Barebone	Celeron 5205U	-	-	-	-	Black: 887993003191 (UPC) White: 887993003764 (UPC)
<b>P9200XA</b>	System without OS	Celeron 5205U	8 GB	500 GB NVMe	-	-	Black: 4046047103713 (EAN)
<b>P9200PA</b>	System with OS	Celeron 5205U	8 GB	250 GB NVMe	-	Win 10 IoT	Black: 4046047103706 (EAN)
<b>POS P920</b>	System without OS	Celeron 5205U	4 GB	128 GB NVMe	PCL71 (2x COM, LPT)	-	Black: 4046047103720 (EAN)

## PRODUCT FEATURES



### All applications at your fingertips - 10-point multi-touch

The innovative touchscreen technology delivers the simplest operation possible and makes the screen the centre of action. Its high-quality design gives you access to all capabilities of the PC - by just touching the screen.



### Optimised Cable Management

Most of the connectors are now located at the back panel facing down. This leads to an effective cable management making for a clean, tidy appearance on the desk. On the left side sit those connectors which need to be accessed from the front: the card reader and two USB ports.



### 24/7 nonstop operation

The Shuttle XPC all-in-one P9200PA is officially approved for 24/7 permanent operation. Thanks to its low power consumption and completely passive cooling, this PC runs highly reliable making it perfectly suitable for digital signage and POI/POS applications.



### Connects to two external Full HD displays

The Shuttle XPC all-in-one P9200PA features two video outputs: One analog D-Sub/VGA connector and one HDMI connector. Two separate Full HD displays can be connected in extended mode. Now add the built-in display of the P9200PA and there are three displays showing different content.



### Fanless and quiet

The Shuttle XPC all-in-one P9200PA uses a passive thermal module to lead heat out of the case quickly and evenly. The unique fanless design makes it perfect to be used in noise-sensitive environments. As an additional benefit, fanless cases rarely gather dust on the inside and stay cleaner than others. So it's not only quiet and low in energy use, but also virtually maintenance-free.



### Hidden Power Button

The power button can be deactivated to prevent unauthorised use. To do so, disconnect the appropriate connection (SW2302) inside the chassis. Still, it can be used with a straightened paper clip as shown on the left (see photo).



### Protection Class IP54

The front panel of the Shuttle XPC all-in-one P9200PA is dust-protected and protected from splashing of water according to IP protection class 54. Consequently, this All-in-One PC can be used for those indoor applications, where the touchscreen may be exposed to humidity and occasional splashing of water. This is particularly welcome in restaurants, laboratories, production or other places.



### VESA mount \*)

The stand on the rear can easily be removed to unveil four VESA mounting screw holes that can be used for mounting arms and other mounting devices from a variety of manufacturers.

\*) VESA mount is not included

## Front and Back Panel



- |  |                                  |                                     |
|--|----------------------------------|-------------------------------------|
| 1. Stand                               | 8. SD card reader                | 18. 2x RJ45 COM port (optional)     |
| (a) Stand mounting plate               | 9. 4x USB 3.2 Gen 1 (5 Gbps)     | 19. RJ11 for cash drawer (optional) |
| (b) VESA cover                         | 10. Power LED                    | 20. DC-input for power adapter      |
| (c) 100 x 100 mm VESA mount            | 11. Hard disk LED                | 21. 2x USB 2.0                      |
| 2. Full HD Webcam                      | 12. 2x speakers (stereo)         | 22. RJ45 Gigabit LAN port           |
| 3. Microphone                          | 13. Name plate (rating label)    | 23. HDMI video output               |
| 4. Touchscreen LCD display             | 14. Hole for Kensington lock     | 24. Audio Line-out (headphones)     |
| 5. Power button                        | 15. D-Sub/VGA video output       | 25. Microphone input                |
| 6. 2x Perforation for external antenna | 16. LPT Parallel Port (optional) | 26. Openings for ventilation        |
| 7. Hole for hidden power button        | 17. 2x D-Sub COM port (optional) |                                     |

## SHUTTLE XPC all-in-one P9200PA – SPECIFICATIONS

<b>FANLESS AND SILENT</b>	<p>Passive heatpipe cooling, absolutely no fan noise</p> <p>Perfect for noise-sensitive environments</p> <p>Fanless, dust-free and thus virtually maintenance-free</p>
<b>24/7 NONSTOP OPERATION</b>	<p>This device is approved for 24/7 permanent operation. Requirements:</p> <ul style="list-style-type: none"> <li>- Free circulation of air amongst the PC must be guaranteed.</li> <li>- Ventilation holes must be kept clear.</li> <li>- If a hard disk is installed, this must also be approved for permanent operation by its manufacturer.</li> </ul>
<b>IP54 PROTECTED</b>	<p>The front panel is dust-protected and protected from splashing of water according to protection class IP54.</p>
<b>CHASSIS</b>	<p>Colour: black</p> <p>Dimensions: 487 x 321 x 44 mm (W x H x D)</p> <p>100 mm VESA mountable</p> <p>Hole for Kensington lock</p> <p>Weight: 4.29 kg net, 5.62 kg gross</p>
<b>OPERATING SYSTEM</b>	<p>Windows 10 IoT Enterprise Entry (64-bit)</p>
<b>TOUCHSCREEN</b>	<p>Touchscreen function supports fingertip input</p> <p>Capacitive Touch Panel with 10-point multi-touch</p> <p>Supports input with gloves (PVC, cotton, cotton/linen)</p> <p>Stylus pen not supported</p>
<b>19.5" DISPLAY</b>	<p>49.5 cm / 19.5" LCD display</p> <p>Ratio: 16:9 wide-screen panel</p> <p>Resolution: 1600 x 900 = 1.44 Megapixel (WSXGA/HD+)</p>
<b>PROCESSOR</b>	<p>Model: Intel Celeron 5205U (ULV)</p> <p>System-on-a-chip architecture (SoC): no chipset required</p> <p>FCBGA1528 package - directly soldered onto the mainboard</p> <p>Code name: Comet Lake-U (10th Generation Intel Core)</p> <p>Cores / Threads: 2 / 2</p> <p>Clock rate: 1.9 GHz</p> <p>L1/L2/L3 Cache: 256 kB / 1 MB / 2 MB</p> <p>Memory controller: DDR4-2400 Dual Channel (1.2 V)</p> <p>TDP wattage: 15 W maximum</p> <p>Manufacturing process: 14 nm</p> <p>Maximum Tjunction Temperature: 100 °C</p> <p>Supports 64-bit, VT-x (EPT), VT-d, Enhanced SpeedStep, NX bit, AES-NI, SSE 4.1/4.2</p>
<b>INTEGRATED GRAPHICS</b>	<p>Intel UHD Graphics 610</p> <p>GPU clock frequency: 300~900 MHz</p> <p>Execution Units (EUs): 12</p> <p>Supports DirectX 12</p> <p>Supports full H264, H265 8/10 bit, VP8/9, VC-1, AVC hardware decoding</p> <p>Supports Quick Sync Video and Clear Video HD technology</p>
<b>SUPPORTS TRIPLE DISPLAY</b>	<p>Two video ports support two additional independent screens:</p> <ol style="list-style-type: none"> <li>1) HDMI 1.4b supports 1920 x 1080 @ 60 Hz or 3840 x 2160 @ 30 Hz</li> <li>2) VGA / D-Sub analog video supports 1920 x 1080 @ 60 Hz</li> </ol> <p>Multi-Monitoring modes as follow:</p> <p>Clone mode: All displays show the same content at 1600 x 900.</p> <p>Extended mode: all displays show different content.</p>
<b>BIOS</b>	<p>AMI BIOS in 8 MByte EEPROM with SPI interface</p> <p>Supports Power-on-after-power-fail / always on</p> <p>Supports Wake-on-LAN (WOL) from S3, S4, S5 ACPI states</p> <p>Supports hardware monitoring and Watchdog function</p> <p>Supports Firmware TPM v2.0 function</p>
<b>MEMORY</b>	<p>8 GB DDR4 SO-DIMM memory</p> <p>Supports a maximum of 32 GB per DIMM, maximum total size: 64 GB</p>
<b>2.5" BAY FOR HDD/SSD</b>	<p>Supports one SATA hard disk or one SATA SSD drive in 6.35 cm / 2.5" format</p> <p>The SATA 3.0 interface supports up to 600 MB/s of data transfer speed (6 Gbit/s)</p> <p>Supports one drive with up to 12.5 mm in height</p> <p>SATA cable pre-installed</p>

<b>M.2-2280M SSD SLOT</b>	250 GB SSD module in M.2-2280 format Supports PCIe interface and NVMe mode
<b>CARD READER</b>	Integrated card reader supports SD, SDHC and SDXC memory flash cards
<b>WEBCAM</b>	Integrated Full HD webcam (1920 x 1080 pixels)
<b>MICROPHONE AND SPEAKERS</b>	Front panel with integrated Electret Condenser Microphone and 2x 2 W speakers
<b>INTEGRATED AUDIO</b>	C-Media CM6542 (USB) or Realtek ALC269 (HD Audio) Two analog audio connectors (3.5 mm) on the bottom side: 1) Line-out (head-phones) 2) Microphone input Digital Audio is supported via HDMI.
<b>WIRED NETWORK</b>	Intel i211 Ethernet Controller with MAC, PHY and PCIe interface Supports 10 / 100 / 1.000 MBit/s operation Supports WAKE ON LAN (WOL) from S3, S4 modes Supports network boot by Preboot eXecution Environment (PXE)
<b>WIRELESS NETWORK (WLAN)</b>	Chipset: Realtek RTL8821CE-CG M.2-2230 (NGFF) extension card Connected with two internal antennas (via IPEX4) Supports WiFi IEEE 802.11b/g/n/ac in the 2.4/5 GHz band, 1T1R Max. 72.2 / 150 Mbps using 20 / 40 MHz bandwidth in n-mode Max. 433.3 Mbps using 80 MHz bandwidth in ac-mode Supports Bluetooth 4.2 in the 2.4 GHz band
<b>FRONT LEDs</b>	Power LED (blue) Hard disk LED (orange)
<b>CONNECTORS LEFT SIDE</b>	Power button 2x USB 3.2 Gen 1 (max. 5 Gbps) SD card reader Hole with power button Perforation for optional WLAN/LTE antenna (diameter: 7 mm)
<b>CONNECTORS BOTTOM SIDE</b>	HDMI 1.4b (supports digital video and digital audio) 2x USB 3.2 Gen 1 (max. 5 Gbps) 2x USB 2.0 Gigabit Network (LAN, RJ45) Audio Line-out / head-phones (3.5 mm jack) Microphone input (3.5 mm jack) DC input for external power adapter (5.5 / 2.5 mm) Perforation for optional WLAN/LTE antenna (diameter: 7 mm) Optional: 2x COM/serial (RJ45), DIO (RJ11) for cash drawer (accessory POS01)
<b>CONNECTORS REAR SIDE</b>	VGA connector (D-Sub 15 pol., analog video) Optional: 2x COM/serial (D-Sub), 1x LPT/parallel (accessory: PCL71 or POS01)
<b>CONNECTORS ONBOARD</b>	Internal USB 2.0 type A connector for a USB stick (Overall length of the USB stick: 100 mm) Serial ATA (6 Gbps) Serial ATA power connector 3x USB 2.0 header (all occupied) eDP connector (Embedded DisplayPort) - occupied by the display Connector for optional COM/LPT adapter POS01 or PCL71
<b>OPTIONAL ANTENNAS</b>	The chassis features two perforated 7 mm holes for optional antennas mounted with an (RP-)SMA connector for wireless network such as WLAN or WWAN (e.g. LTE)
<b>POWER ADAPTER</b>	External 65 W power adapter (fanless) Input: 100~240 V AC, 50/60 Hz, max. 1.6 A Output: 19 V DC, max. 3.42 A, max. 65 W
<b>DC INPUT CONNECTOR</b>	DC Input Connector: 5.5 / 2.5 mm (outer/inner diameter) The DC-input of the computer supports an external power source with either 12V ±5 % or 19V ± 5%.

<b>SUPPLIED ACCESSORIES</b>	Quick Guide Driver DVD External Power Adapter (65W / 19V) Power cord Screws
<b>OPTIONAL ACCESSORIES</b>	<p><b>PCL71:</b> COM / LPT / RJ11 adapter:</p> <ul style="list-style-type: none"> <li>- 1x Parallel (25p D-Sub)</li> <li>- 2x Serial RS232 (9p D-Sub) supports 0 / 5 / 12V</li> </ul> <p><b>POS01:</b> COM / LPT / RJ11 adapter:</p> <ul style="list-style-type: none"> <li>- 1x Parallel (25p D-Sub)</li> <li>- 2x Serial RS232 (9p D-Sub) supports 0 / 5 / 12V</li> <li>- 2x Serial RS232 (8p RJ45)</li> <li>- 1x DIO/RJ11 connector for cash drawer supports 12 / 24V</li> </ul> <p><b>PNFC03:</b> NFC module (supports Windows 10 only, no Linux and transaction support)</p> <ul style="list-style-type: none"> <li>- Note: PNFC03 is only available on request</li> </ul>
<b>ENVIRONMENTAL SPECIFICATIONS</b>	Operating temperature: 0~40 °C Humidity: 10~90 %
<b>CERTIFICATIONS / COMPLIANCE</b>	EMI: CE, RED, FCC, RCM, VCCI Safety: CB, ETL Other compliances: RoHS, ErP Lot3, Energy Star v7.0
<b>CONFORMITY</b>	This device is classed as a technical information equipment (ITE) in class B and is intended for use in living room and office. The CE-mark approves the conformity by the EU directives: <ol style="list-style-type: none"> <li>(1) 2014/30/EU relating to electromagnetic compatibility (EMC),</li> <li>(2) 2014/35/EU relating to Electrical Equipment designed for use within certain voltage limits (LVD),</li> <li>(3) 2009/125/EU relating to ecodesign requirements for energy-related products (ErP),</li> <li>(4) 2014/53/EU related to Radio and Telecommunications Terminal Equipment (RED)</li> </ol>