

OVERVIEW



1. USB 3.2 Gen 1 (Always On)	6. HDMI 1.4b
2. USB 3.2 Gen 1	7. USB-C 3.2 Gen 1
3. Card reader	8. Headphone / microphone combo jack (3.5mm)
4. Power button	9. NOVO button hole
5. Power connector	

Notes:

- If a USB-C adapter is shipped with your computer, connect the adapter to USB-C 3.2 Gen 1 for charging

PERFORMANCE

Processor

Processor Family

Intel® Pentium® or 11th Generation Intel Core™ i3 / i5 / i7 Processor

Processor**

Processor Name	Cores	Threads	Base Frequency	Max Frequency	Cache	Memory Support	Processor Graphics
Pentium Gold 7505	2	4	2.0GHz	3.5GHz	4MB	DDR4-3200	Intel UHD Graphics
Core i3-1115G4	2	4	3.0GHz	4.1GHz	6MB	DDR4-3200	Intel UHD Graphics
Core i5-1135G7	4	8	2.4GHz	4.2GHz	8MB	DDR4-3200	Intel Iris® Xe Graphics
Core i7-1165G7	4	8	2.8GHz	4.7GHz	12MB	DDR4-3200	Intel Iris Xe Graphics

Operating System

Operating System**

- Windows® 11 Pro 64
- Windows 11 Home 64
- Windows 11 Home in S mode
- Windows 10 Pro 64
- Windows 10 Home 64
- Windows 10 Home in S mode

Graphics

Graphics**

Graphics	Type	Memory	Key Features
Intel UHD Graphics	Integrated	Shared	DirectX® 12
Intel Iris Xe Graphics	Integrated	Shared	DirectX 12
NVIDIA® GeForce® MX450	Discrete	2GB GDDR6	DirectX 12

Monitor Support

Monitor Support

Supports up to 2 independent displays via native display and 1 external monitor; supports external monitor via HDMI® (up to 4096x2160@30Hz)

Chipset

Chipset

Intel SoC (System on Chip) platform

Memory

Max Memory^[1]

- 4GB soldered memory, not upgradable
- 8GB soldered memory, not upgradable
- 12GB soldered memory, not upgradable
- 16GB soldered memory, not upgradable

Memory Slots**

- Memory soldered to systemboard, no slots (4GB model)
- Memory soldered to systemboard, no slots, dual-channel (8GB, 12GB, or 16GB model)

Memory Type

DDR4-3200

Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support

One drive, up to 512GB M.2 2242 SSD or 512GB M.2 2280 SSD

Storage Slot

One M.2 2280 PCIe® Gen 3x4 slot, supports M.2 2242/2280 SSD

Storage Type**

Disk Type	Interface	RPM	Offering	Security
M.2 2242 SSD	PCIe NVMe®, PCIe 3.0 x4	-	128GB / 256GB / 512GB	-
M.2 2280 SSD	PCIe NVMe, PCIe 3.0 x4	-	512GB	-

Removable Storage

Optical

None

Card Reader

4-in-1 card reader (SD, SDHC, SDXC, MMC)

Multi-Media

Audio Chip

High Definition (HD) Audio

Speakers

Stereo speakers, 2W x2, Dolby® Audio™

Microphone

Dual array microphone

Camera

720p, with privacy shutter, fixed focus

Sensor

Sensors

Accelerometer (G) sensor

Battery

Battery

Integrated Li-Polymer 52.5Wh battery, supports Quick Charge (charge up to 80% in 1hr) and Smart Charge (get 2 hours of runtime with a 15-minute charge)

Max Battery Life^[1]

- Local video (1080p) playback: 11 hr
- MobileMark® 2014: 10 hr

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**

- 65W USB-C (3-pin) AC adapter
- 65W round tip (3-pin) AC adapter
- 65W round tip (2-pin, wall-mount) AC adapter

DESIGN

Display

Display**^[1]

Size	Resolution	Touch	Type	Brightness	Surface	Aspect Ratio	Contrast Ratio	Color Gamut	Viewing Angle	Key Features
14.0"	FHD (1920x1080)	Multi-touch	TN	220 nits	Glossy	16:9	-	45% NTSC	-	-
14.0"	FHD (1920x1080)	Multi-touch	IPS	250 nits	Glossy	16:9	-	45% NTSC	-	-

Touchscreen

OGS (One Glass Solution) multi-touch, supports 10-point touch

Multi-mode

Laptop, tent, stand and tablet modes supported by 360° hinge

Notes:

1. California Electronic Waste Recycling Fee
- In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.
- For more information, go to <https://www.calrecycle.ca.gov/Electronics/Consumer>

Input Device

Pen**

- Lenovo Digital Pen with replaceable AAAA alkaline battery, 4096 levels of pressure sensitivity
- Lenovo Digital Pen without replaceable AAAA alkaline battery, 4096 levels of pressure sensitivity
- No pen (pen sold separately)

Keyboard

6-row, multimedia Fn keys

Keyboard Backlight^[1]

- LED backlight
- No support

Touchpad

Buttonless Mylar® surface multi-touch touchpad

Notes:

1. Optional 2-level LED backlight

Mechanical

Dimensions (WxDxH)

Models	Dimensions
Metal models	321.5 x 217.5 x 17.9-20.4 mm (12.65 x 8.56 x 0.70-0.80 inches)
Plastic models	321.5 x 217.5 x 17.9-20.9 mm (12.65 x 8.56 x 0.70-0.82 inches)

Weight^[1]

Models	Weight
All models	1.5 kg (3.3 lbs)

Case Color**

- Abyss blue
- Graphite grey
- Platinum grey

Surface Treatment**

- Aluminium anodizing stamping
- Metallic painting

Case Material**

- Aluminium (top), PC + GF (bottom)
- PC + ABS (top), PC + GF (bottom)

Notes:

1. The system weight varies depending on configurations.

CONNECTIVITY

Network

WLAN + Bluetooth^{**}

- 802.11ac 2x2 Wi-Fi® + Bluetooth 5.0, M.2 card
- Wi-Fi 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.0, M.2 card

Ports^[1]

Standard Ports

- 1x USB 3.2 Gen 1
- 1x USB 3.2 Gen 1 (Always On)
- 1x USB-C 3.2 Gen 1 (support data transfer and Power Delivery)
- 1x HDMI 1.4b
- 1x Card reader
- 1x Headphone / microphone combo jack (3.5mm)
- 1x Power connector

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed.
 - USB 2.0: 480 Mbit/s;
 - USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;
 - USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;
 - USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;
 - Thunderbolt™ 3: 40 Gbit/s;
 - FireWire 400: 400 Mbit/s;
 - FireWire 800: 800 Mbit/s

SECURITY & PRIVACY

Security

Security Chip

Firmware TPM 2.0 integrated in chipset

Fingerprint Reader

- Touch style fingerprint reader on palm rest
- No fingerprint reader

BIOS Security

- Administrator password
- User password
- Master hard disk password
- User hard disk password

Other Security

Camera privacy shutter

SERVICE

Warranty

Base Warranty^{**}

- 1-year depot service
- 1-year depot with 2-year system board service
- 2-year (1-yr battery) depot service
- 3-year (1-yr battery) depot service

ENVIRONMENTAL

Operating Environment

Temperature^[1]

- At altitudes up to 2438 m (8,000 ft)
 - Operating: 5°C to 35°C (41°F to 95°F)
 - Storage: 5°C to 43°C (41°F to 109°F)
- At altitudes above 2438 m (8,000 ft)
 - Maximum temperature when operating under the unpressurized condition: 31.3°C (88°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitude

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10°C (50°F).

CERTIFICATIONS

Green Certifications

Green Certifications

- ENERGY STAR® 8.0
- ErP Lot 3
- RoHS compliant

- Feature with ** means that only one offering listed under the feature is configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS," WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.

