

OVERVIEW



| 1. USB-C 3.2 Gen 1 | 5. Headphone / microphone combo jack (3.5mm) |
|------------------------------|--|
| 2. Charging light | 6. USB 2.0 |
| 3. USB 3.2 Gen 1 (Always On) | 7. Ethernet (RJ-45) |
| 4. HDMI 1.4b | 8. Kensington Security Slot |



PERFORMANCE

Processor

Processor Family

AMD Ryzen™ 3 / 5 / 7 Processor

Processor**[1]

| Processor Name | Cores | Threads | Base Frequency | Max Frequency | Cache | Memory Support | Processor Graphics |
|--------------------------|-------|---------|-------------------|------------------|--------------------|-------------------|-------------------------|
| AMD Ryzen 3 4300U | 4 | 4 | 2.7GHz | 3.7GHz | 2MB L2 / 4MB L3 | DDR4-3200 | AMD Radeon™ Graphics |
| AMD Ryzen 5 4500U | 6 | 6 | 2.3GHz | 4.0GHz | 3MB L2 / 8MB L3 | DDR4-3200 | AMD Radeon Graphics |
| AMD Ryzen 5 4600U | 6 | 12 | 2.1GHz | 4.0GHz | 3MB L2 / 8MB L3 | DDR4-3200 | AMD Radeon Graphics |
| AMD Ryzen 5 PRO 4650U | 6 | 12 | 2.1GHz | 4.0GHz | 3MB L2 / 8MB L3 | DDR4-3200 | AMD Radeon Graphics |
| AMD Ryzen 7 4700U | 8 | 8 | 2.0GHz | 4.1GHz | 4MB L2 / 8MB L3 | DDR4-3200 | AMD Radeon Graphics |
| AMD Ryzen 7 4800U | 8 | 16 | 1.8GHz | 4.2GHz | 4MB L2 / 8MB L3 | DDR4-3200 | AMD Radeon Graphics |

Notes:

Operating System

Operating System**

- Windows® 10 Pro 64
- Windows 10 Home 64
- No operating system

Graphics

Graphics

| Graphics | Туре | Memory | Key Features |
|---------------------|------------|--------|--------------|
| AMD Radeon Graphics | Integrated | Shared | DirectX® 12 |

Monitor Support

Monitor Support

Supports up to 3 independent displays (native display and 2 external monitors via HDMI® and USB-C)

- HDMI supports up to 3840x2160@30Hz
- USB-C supports up to 3840x2160@60Hz

Chipset

Chipset

AMD SoC (System on Chip) platform

Memory

Max Memory[1]

- Up to 20GB (4GB soldered + 16GB SO-DIMM) DDR4-3200
- Up to 24GB (8GB soldered + 16GB SO-DIMM) DDR4-3200

Memory Slots

One memory soldered to systemboard, one DDR4 SO-DIMM slot, dual-channel capable

Memory Type

DDR4-3200

^{1.} Ryzen 5 4600U, Ryzen 5 PRO 4650U and Ryzen 7 4800U are NOT available in EMEA



Notes:

1. The max memory is based on the test results with current Lenovo® memory offerings. The system may support more memory as the technology develops.

Storage

Storage Support

Up to two drives, 2x M.2 SSD

- M.2 2242 SSD up to 512GB
- M.2 2280 SSD up to 1TB

Storage Type***

| Disk Type | Interface | RPM | Security |
|--------------|--------------------------|-----|----------|
| M.2 2242 SSD | PCIe® NVMe®, PCIe 3.0 x4 | - | - |
| M.2 2280 SSD | PCIe NVMe, PCIe 3.0 x4 | - | - |

Removable Storage

Optical

None

Card Reader

No card reader

Multi-Media

Audio Chip

High Definition (HD) Audio, Realtek® ALC3287 codec

Speakers

Stereo speakers, 2W x2, Dolby® Audio™, Harman Speakers

Microphone

Dual array microphone

Camera**

- 720p, with privacy shutter, fixed focus
- IR & 720p hybrid, with privacy shutter, fixed focus

Battery

Battery

Integrated Li-Polymer 45Wh battery, supports Rapid Charge (charge up to 80% in 1hr)

Max Battery Life[1]

MobileMark® 2014: 13 hr MobileMark 2018: 10.7 hr

Notes:

1. All battery life claims are approximate maximum and based on results using the MobileMark 2014, MobileMark 2018, JEITA 2.0, continuous 1080p video playback (with 150nits brightness and default volume level) or Google Power Load Test (PLT) battery-life benchmark tests. Actual battery life will vary and depends on many factors such as product configuration and usage, software use, wireless functionality, power management settings, and screen brightness. The maximum capacity of the battery will decrease with time and use.

Power Adapter

Power Adapter**[1]

- 65W USB-C (2-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- 65W USB-C (3-pin) AC adapter, supports PD 3.0, 100-240V, 50-60Hz
- No power adapter

Notes:

1. No power adapter is for special bid only.

DESIGN



Display

Display**[1]

| Size | Resolution | Touch | Туре | Brightness | Surface | Aspect Ratio | Contrast Ratio | Color Gamut | Viewing Angle | Key Features |
|-------|--------------------|-------|------|------------|----------------|-----------------|-------------------|----------------|------------------|-----------------|
| 14.0" | FHD (1920x1080) | None | TN | 220 nits | Anti- glare | 16:9 | 400:1 | - | 90° | - |
| 14.0" | FHD (1920x1080) | None | IPS | 250 nits | Anti- glare | 16:9 | 700:1 | - | 170° | - |

Touchscreen

Non-touch

Notes:

Input Device

Keyboard

6-row, spill-resistant, multimedia Fn keys with Unified Communications controls

Keyboard Backlight

- · LED backlight
- No support

UltraNav™

TrackPoint® pointing device and Mylar® surface multi-touch touchpad

Mechanical

Dimensions (WxDxH)

| Models | Dimensions |
|--|--|
| Aluminium (top), aluminium (bottom) models | 324 x 220 x 17.9 mm (12.76 x 8.66 x 0.7 inches) |
| Aluminium (top), PC + ABS (bottom) models | 324 x 220 x 18.9 mm (12.76 x 8.66 x 0.74 inches) |
| PC + ABS (top), PC + ABS (bottom) models | 324 x 220 x 20.5 mm (12.76 x 8.66 x 0.81 inches) |

Weight[1]

| Models | Weight |
|--|--------------------|
| Aluminium (top), aluminium (bottom) models | 1.64 kg (3.62 lbs) |
| Aluminium (top), PC + ABS (bottom) models | 1.59 kg (3.51 lbs) |
| PC + ABS (Top), PC + ABS (Bottom) models | 1.69 kg (3.73 lbs) |

Case Color

Black

Case Material**

- Aluminium (top), aluminium (bottom)
- Aluminium (top), PC + ABS (bottom)
- PC + ABS (top), PC + ABS (bottom)

Notes:

1. The system weight varies depending on configurations.

CONNECTIVITY

Network

Onboard Ethernet

^{1.} California Electronic Waste Recycling Fee
In California, per state law, Lenovo charges an electronic waste recycling fee on this covered device at the time of sale of the product.
For more information, go to https://www.calrecycle.ca.gov/Electronics/Consumer



Gigabit Ethernet, Realtek RTL8111GUS, 1x RJ-45, supports Wake-on-LAN

WLAN + Bluetooth®**[1]

- Wi-Fi® 6, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 card
- Mediatek Wi-Fi 6 MT7921, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 Card
- Realtek RTL8822CE, 802.11ac Dual Band 2x2 Wi-Fi + Bluetooth 5.0, M.2 card
- Realtek RTL8852AE, Wi-Fi 6, 802.11ax Dual Band 2x2 Wi-Fi + Bluetooth 5.2, M.2 card
- Intel® Wi-Fi 6 AX200, 802.11ax 2x2 Wi-Fi + Bluetooth 5.2, M.2 card

WWAN

No support

SIM Card

No SIM card inbox

NFC

No support

Notes:

1. Realtek RTL8822CE is NOT available in EMEA Intel Wi-Fi 6 full features might be limited by country level restrictions Bluetooth 5.2 is supported with driver version 22.30 and later

Ports^[1]

Standard Ports

- 1x USB 2.0
- 1x USB 3.2 Gen 1 (Always On)
- 1x USB-C 3.2 Gen 1 (support data transfer, Power Delivery and DisplayPort™ 1.2)
- 1x HDMI 1.4b
- 1x Ethernet (RJ-45)
- 1x Headphone / microphone combo jack (3.5mm)

Notes:

1. The transfer speed of following ports will vary and, depending on many factors, such as the processing speed of the host device, file attributes and other factors related to system configuration and your operating environment, will be slower than theoretical speed. USB 2.0: 480 Mbit/s;

USB 3.2 Gen 1 (SuperSpeed USB 5Gbps, formerly USB 3.0 / USB 3.1 Gen 1): 5 Gbit/s;

USB 3.2 Gen 2 (SuperSpeed USB 10Gbps, formerly USB 3.1 Gen 2): 10 Gbit/s;

USB 3.2 Gen 2x2 (SuperSpeed USB 20Gbps): 20 Gbit/s;

Thunderbolt™ 3: 40 Gbit/s;

FireWire 400: 400 Mbit/s;

FireWire 800: 800 Mbit/s

Docking

Docking

Various docking solutions supported via USB-C.

For more compatible docking solutions, please visit Docking for ThinkPad® E14 Gen 2 (AMD)

SECURITY & PRIVACY

Security

Security Chip**

- Discrete TPM 2.0, TCG certified
- Firmware TPM 2.0 integrated in chipset

Physical Locks

Kensington® Security Slot

Smart Card Reader

No smart card reader

Fingerprint reader

- Touch style fingerprint reader on power button
- No fingerprint reader

BIOS Security

ThinkPad E14 Gen 2 (AMD)



- Power-on password
- · Supervisor password
- · Hard disk password
- Self-healing BIOS

Other Security

- · Camera privacy shutter
- (Optional) IR camera for Windows Hello

SERVICE

Warranty

Base Warranty**[1]

- 1-year mail-in service
- 1-year depot service
- 1-year depot with 2-year system board service
- 1-year limited onsite service
- · No base warranty

Notes:

1. More information of warranty policy, please access https://pcsupport.lenovo.com/warranty

ENVIRONMENTAL

Operating Environment

Temperature[1]

- Operating: 5°C (41°F) to 35°C (95°F)
- Storage and transportation in original shipping package: -20°C (-4°F) to 60°C (140°F)
- Storage without package: 5°C (41°F) to 43°C (109°F)

Humidity

- Operating: 8% to 95% at wet-bulb temperature 23°C (73°F)
- Storage and transportation: 5% to 95% at wet-bulb temperature 27°C (81°F)

Altitudo

Maximum altitude (without pressurization): 3048 m (10,000 ft)

Notes:

1. When you charge the battery, its temperature must be no lower than 10 $^{\circ}\text{C}$ (50 $^{\circ}\text{F}$).

CERTIFICATIONS

Green Certifications

Green Certifications

- EPEAT™ Gold
- ENERGY STAR® 8.0
- ErP Lot 3
- TCO Certified
- · RoHS compliant

Other Certifications

Mil-Spec Test

MIL-STD-810H military test passed

• Feature with ** means that only one offering listed under the feature is configured on selected models.

ThinkPad E14 Gen 2 (AMD)



- Feature with *** means that one or more offerings listed under the feature could be configured on selected models.
- Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not
 responsible for photographic or typographical errors. LENOVO PROVIDES THIS PUBLICATION "AS IS,"
 WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES
 OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Some jurisdictions do not allow
 disclaimer of express or implied warranties in certain transactions, therefore this disclaimer may not apply to
 you.
- The specifications on this page may not be available in all regions, and may be changed or updated without notice.







AMD**∄**





дама дама



AMD∄



LDMA